Privacy by Design

What is stored, what is hashed, what never leaves the server — and why.

Exposure-Check-OSINT v1.6.0 · Apache-2.0 · self-hosted · keyless · no AI · github.com/RanaKhan77/Exposure-Check-OSINT

This page is the honest, complete list. If it is not listed here, it does not happen.

What is stored locally (and only locally)

Data	Where	Form
Check history	exposure_checks table (SQLite on your machine)	Type + salted SHA-256 hash of the identifier + masked display form (j***n@gmail.com) + aggregated results. The raw identifier is never stored.
Password checks	nothing	Password checks store no result rows at all — matching happens in your browser
Settings, license state	local tables	Quotas, toggles, license key
Platform logos cache	storage/app/osint-logos	Public favicons, cache only, purgeable

Delete any record from the History page, or Purge all — one click, gone.

What leaves the server, and to whom

- The identifier you type (email/username/phone/IP) — sent over HTTPS to the keyless OSINT sources listed in SOURCES.md, because that is literally what a lookup is. Each source sees only what it needs.
- For password checks: only the first 5 hex chars of the SHA-1 (k-anonymity). Not the password. Not the full hash. See CHECKS.md.
- License network calls — ONLY when you explicitly activate, refresh or deactivate a free key on the license page (payload: key, random install ID, domain, version — to 2mny.com). This powers the voluntary install counter and free update notifications. It carries no check data and no identifiers. There is no scheduled heartbeat by default (v2, Oct 2026): the daily heartbeat cron was removed; operators who want to appear on the public install map can opt in with LICENSE_HEARTBEAT=on. The whole license client is ~300 readable lines: app/Services/CommunityLicenseService.php.

What is deliberately NOT collected

- No analytics, no tracking pixels, no third-party JavaScript
- No raw identifiers in any log (audit rows store hashes + masked forms only)
- No credential material in the database (credential_lines are stripped before storage)
- No telemetry beyond the explicit license actions above (and none at all unless you activate a key; the heartbeat is opt-in only)

Threat-model honesty

- The OSINT sources themselves learn that someone at your IP checked a given identifier — that is inherent to any lookup tool, hosted or self-hosted. Running this yourself means the results never touch anyone else's server.
- The result cache (30 min default, configurable) is keyed by a SHA-1 of type + identifier and stored in your local cache store only.