DOCUMENTATIONPACK·3OF6

The 21 Sources & Attribution

Every data source, its endpoint, its limits, and the deliberate exclusions.

Exposure-Check-OSINT v1.3.1 · Apache-2.0 · self-hosted · keyless · no AI · github.com/RanaKhan77/Exposure-Check-OSINT

Every source below is **free, keyless (no API key, no account), read-only, and queried over HTTPS**. Per-source enable/disable lives on the Settings page. Attribution and limits are listed honestly — if a source is down, its card shows `unavailable` and the check continues (per-source isolation).

#	Source	Category	Checks	Endpoint / data	Notes
1	HudsonRock	stealer	email	`cavalier.hudsonrock.com` infostealer corpus	Stealer-log infections linked to the email (counts + machine info only; no raw cookies)
2	XposedOrNot	breach	email	`api.xposedornot.com/v1/breach-analytics`	Which breaches contain the email (names, dates, record counts)
3	ProxyNova COMB	breach	email, phone	`api.proxynova.com/comb`	11B+ credential-pair COMB corpus association (masked, credential lines never stored)
4	HIBP Pwned Passwords	breach	password	`api.pwnedpasswords.com/range/{5-hex}`	k-anonymity: only the 5-char SHA-1 prefix leaves this server; suffix matching happens in YOUR browser
5	Mailcheck	email	email	`mailcheck.ai/domain/`	Domain deliverability + disposable classification
6	Gravatar	profile	email	`gravatar.com`	Public avatar + profile existence
7	Disposable Email Domains list	email	email	`disposable-email-domains` blocklist (GitHub)	One-time/temp provider domain flag
8	Disify	email	email	`disify.com/api/email/`	Disposable/validity signal
9	Kickbox Open	email	email	`open.kickbox.com/v1/disposable/`	Disposable signal (open endpoint)
10	FachaTemp	email	email	`api.facha.dev/v1/temporary-email/`	Temp-provider domain signal
11	Presend	email, phone	email, phone	`presend.pages.dev/api/`	Deliverability + phone lookups
12	GitHub public search	profile	email, username	`api.github.com` (unauthenticated)	Public code/profile associations

#	Source	Category	Checks	Endpoint / data	Notes
13	Maigret corpus (150 sites)	profile	username	Local `storage/app/maigret/sites.json` + live site probes	Username registered on N of 150 popular platforms — rendered as the platform logo grid. Corpus: maigret (MIT) + WhatsMyName (CC BY-SA 4.0), differential-verified
14	Bluesky (AT Protocol)	profile	username	`public.api.bsky.app`	Handle/profile existence
15	Hacker News (Firebase)	profile	username	`hacker-news.firebaseio.com`	Public HN account existence + karma
16	PhoneValidity	infra	phone	E.164 parsing (libphonenumber semantics, in-process)	Country, line type, validity — no external call
17	Shodan InternetDB	infra	ip	`internetdb.shodan.io` (keyless)	Open ports + services on the IP
18	ipapi.is	infra	ip	`api.ipapi.is` (keyless)	VPN/proxy/hosting classification
19	Bot-CIDR attribution	infra	ip	offline crawler-network ranges (CrawlerScope-inspired)	Is the IP a known crawler/bot network — offline, no external call
20	crt.sh — Certificate Transparency	infra	domain	`crt.sh/?q=%.{domain}` (keyless)	Historical subdomains that ever obtained a TLS certificate — counts + first 40 names
21	RDAP — Domain Registration Records	infra	domain	`rdap.org/domain/{domain}` (keyless)	Registrar, registration/expiry dates, status — registration age as a fraud/trust signal

Display images

Platform favicons and Gravatar avatars are fetched once per platform by the in-repo `OsintLogoService` (24h negative cache, 5s budget per fetch) and served from `/osint-logo/{key}` and `/osint-avatar/gravatar/{hash}`. A missing image falls back to a letter tile — never blocks a result.

Deliberately NOT in the Community Edition

- **GrayHatWarfare** — bucket search (the hosted 2mny.com version uses an owner API key; the CE stays 100% keyless)
- **Domain / website checks** — that is the job of the

Website Vulnerability Scanner CE (200 modules). Domain intelligence lives in the main scanner engine instead: the hosted platform's `org_breach_history` module reports an organization's documented data-breach history from the **LeakLens registry** — leaklens.org, free for non-commercial use, attribution required and given. The CE stays personal-identifiers-only.

- **holehe binary** — the hosted product runs it internally (GPLv3, run-not-redistributed); the CE stays license-clean without it
- **The ~120-platform linked-account probe** — v1.1 roadmap: it needs a companion headless-browser microservice (the same one the hosted product runs); ships as an optional Docker add-on, never as a hard dependency
- **Telegram / WhatsApp lookups** — require bot keys and risk account bans (fail the keyless + safe-to-operate bar)

Adding a source

Implement `App\Modules\Osint\Sources\OsintSource` (two methods: `requests()` + `parse()`), register the class in `OsintCheckService::SOURCES`, add a row here. The contract is documented inline in `app/Modules/Osint/Sources/OsintSource.php` — including the non-negotiable ethical rules (never return plaintext credentials, never return third-party personal data, always degrade to `unavailable` on failure).