DOCUMENTATIONPACK·4OF6

Privacy by Design

What is stored, what is hashed, what never leaves the server — and why.

Exposure-Check-OSINT v1.3.1 · Apache-2.0 · self-hosted · keyless · no AI · github.com/RanaKhan77/Exposure-Check-OSINT

This page is the honest, complete list. If it is not listed here, it does not happen.

What is stored locally (and only locally)

Data	Where	Form
Check history	`exposure_checks` table (SQLite on your machine)	Type + **salted SHA-256 hash** of the identifier + masked display form (`j***n@gmail.com`) + aggregated results. The raw identifier is **never** stored.
Password checks	nothing	Password checks store **no result rows at all** — matching happens in your browser
Settings, license state	local tables	Quotas, toggles, license key
Platform logos cache	`storage/app/osint-logos`	Public favicons, cache only, purgeable

Delete any record from the History page, or **Purge all** — one click, gone.

What leaves the server, and to whom

- **The identifier you type** (email/username/phone/IP) — sent over HTTPS to the

keyless OSINT sources listed in SOURCES.md, because that is literally what a lookup is. Each source sees only what it needs.

- **For password checks: only the first 5 hex chars of the SHA-1** (k-anonymity).

Not the password. Not the full hash. See CHECKS.md.

- **License heartbeat** (daily, if you activate a free key): install ID, status,

version, PHP version — to `2mny.com`. This powers the public install counter and free update notifications. It carries **no check data and no identifiers**. The whole license client is ~300 readable lines: `app/Services/CommunityLicenseService.php`.

What is deliberately NOT collected

- No analytics, no tracking pixels, no third-party JavaScript
- No raw identifiers in any log (audit rows store hashes + masked forms only)
- No credential material in the database (`credential_lines` are stripped before storage)
- No telemetry beyond the license heartbeat above

Threat-model honesty

- The OSINT sources themselves learn that *someone at your IP* checked a given

identifier — that is inherent to any lookup tool, hosted or self-hosted. Running this yourself means the *results* never touch anyone else's server.

- The result cache (30 min default, configurable) is keyed by a SHA-1 of

type + identifier and stored in your local cache store only.