Implementation of Zermelo's work of 1908 in Lestrade: Part III, opening of Zermelo well-ordering theorem argument

M. Randall Holmes
January 5, 2022

1 Introduction

This document was originally titled as an essay on the proposition that mathematics is what can be done in Automath (as opposed to what can be done in ZFC, for example). Such an essay is still in in my mind, but this particular document has transformed itself into the large project of implementing Zermelo's two important set theory papers of 1908 in Lestrade, with the further purpose of exploring the actual capabilities of Zermelo's system of 1908 as a mathematical foundation, which we think are perhaps underrated.

This is a new version of this document in modules, designed to make it possible to work more efficiently without repeated execution of slow log files when they do not need to be revisited.

The new version in March 2020 is designed for the new release of Lestrade.

2 Zermelo's 1908 proof of the well-ordering theorem

I am now going to carry out or at least attempt a significant piece of mathematics in Lestrade. I shall attempt to directly translate Zermelo's 1908 proof of the well-ordering theorem (which was published at about the same time as the axiomatization implemented above: they are intimately connected) into a Lestrade proof.

Zermelo starts by stating prerequisites which are found in the axiomatization. Point I: he requires the axiom of Separation, stated above. He points out as an important corollary the existence of relative complements.

As point II he requires the existence of power sets, provided by us in the axiomatization above.

As point III, he notes that Separation implies the existence of intersections of (nonempty) sets.

In earlier versions, declarations of the above points appeared here, but we have moved them back into the second file, which implements the axiomatics paper.

Zermelo states the following Theorem, the central result in his argument (the well ordering theorem follows immediately from this theorem and the axiom of choice, as we will verify below).

Theorem: If with every nonempty subset of a set M an element of the subset is associated by some law as "distinguished element", then $\mathcal{P}(x)$, the set of all subsets of M, possesses one and only one subset \mathbf{M} such that to every arbitrary subset P of M there always corresponds one and only one element P_0 of M that includes P as a subset and contains an element of P as its distinguished element. The set M is well-ordered by \mathbf{M} .

The apparent second-order quality of this theorem is dispelled by the proof in Lestrade, in which we see how we can introduce the "law" referred to as a hypothetical without in fact allowing quantification over such laws (and nonetheless successfully carry out the proof of the corollary).

We declare the hypotheses of the theorem, the set M and the unspecified law that, given a subset S of M, allows us to select a distinguished element of S.

```
begin Lestrade execution

>>> comment load whatismath2

{move 1}

>>> clearcurrent
```

```
{move 1}
   >>> declare M obj
  M : obj
   {move 1}
   >>> declare Misset that Isset M
  Misset : that Isset (M)
   {move 1}
   >>> open
      {move 2}
      >>> declare S obj
     S : obj
      {move 2}
      >>> declare x obj
     x : obj
      {move 2}
      >>> declare subsetev that S <<= M
      subsetev : that S <<= M
      {move 2}
     >>> declare inev that Exists [x => \
             x E S]
```

```
inev : that Exists ([(x_2 : obj) =>
          ({def} x_2 E S : prop)])
      {move 2}
      >>> postulate thelaw S : obj
      thelaw : [(S_1 : obj) => (--- : obj)]
      {move 1}
      >>> postulate thelawchooses subsetev \
          inev : that (thelaw S) E S
      thelawchooses : [(.S_1 : obj), (subsetev_1
          : that .S_1 <<= M), (inev_1 : that
          Exists ([(x_3 : obj) =>
             ({def} x_3 E .S_1 : prop)])) =>
          (---: that thelaw (.S_1) E .S_1)
      {move 1}
      >>> close
   {move 1}
end Lestrade execution
```

It appears for direct implementation of Zermelo's argument that the choice of a distinguished element should return something arbitrary when the argument is empty, and further it is convenient for the choice to work for any set (or indeed atom) at all, formally, though we make no assumptions about the result. Otherwise we need axioms handling proof indifference and there are other embarrassments.

This seems to be a general fact: operations taking sets to sets (or more generally, sets and atoms to sets and atoms) should be universal, or we end up stumbling over the Lestrade type system.

```
begin Lestrade execution
   >>> open
      {move 2}
      >>> declare S obj
      S : obj
      {move 2}
      >>> declare subsetev that S <<= M
      subsetev : that S <<= M
      {move 2}
      >>> define prime1 S : Complement (S, Usc \setminus
          (thelaw S))
      prime1 : [(S_1 : obj) => (--- : obj)]
      {move 1}
      >>> save
      {move 2}
      >>> close
   {move 1}
   >>> declare S1 obj
   S1 : obj
   {move 1}
```

```
>>> define prime2 thelaw, S1 : prime1 \
       S1
   prime2 : [(thelaw_1 : [(S_2 : obj) =>
          (--- : obj)]), (S1_1 : obj) =>
       ({def} S1_1 Complement Usc (thelaw_1
       (S1_1)) : obj)
   prime2 : [(thelaw_1 : [(S_2 : obj) =>
          (--- : obj)]), (S1_1 : obj) =>
       (--- : obj)]
   {move 0}
   >>> open
      {move 2}
      >>> define prime S : prime2 thelaw, S
      prime : [(S_1 : obj) => (--- : obj)]
      {move 1}
end Lestrade execution
```

An important operation in Zermelo's argument takes each subset A of M to the subset $A' = A \setminus \{a\}$, where a is the distinguished element of A if A is nonempty. This is defined above. Below, we prove its natural comprehension axiom.

```
begin Lestrade execution
>>> open
```

{move 3}

```
>>> declare u obj
u : obj
{move 3}
>>> open
   {move 4}
   >>> declare hyp1 that u E prime \
   hyp1 : that u E prime (S)
   {move 4}
   >>> declare hyp2 that (u E S) & ~ (u = thelaw \setminus
   hyp2 : that (u E S) & \tilde{} (u = thelaw
    (S))
   {move 4}
   >>> define line1 hyp1 : Iff1 \
       (hyp1, Ui (u, Compax (S, Usc \
       (thelaw S))))
   line1 : [(hyp1_1 : that u E prime
       (S)) \Rightarrow (--- : that (u E S) & ~ (u E Usc
       (thelaw (S))))]
   {move 3}
   >>> define line2 hyp1 : Simp2 \
       (line1 hyp1)
```

```
line2 : [(hyp1_1 : that u E prime
    (S)) \Rightarrow (--- : that ~(u E Usc
    (thelaw (S))))]
{move 3}
>>> open
   {move 5}
   >>> declare hyp3 that u = thelaw \
       S
   hyp3 : that u = thelaw (S)
   {move 5}
   >>> define line3 : Inusc2 \
       (thelaw S)
   line3: that thelaw (S) E thelaw
    (S); thelaw (S)
   {move 4}
   >>> declare v obj
   v : obj
   {move 5}
   >>> define line4 hyp3 : Subs \
       (Eqsymm hyp3, [v \Rightarrow v E (Usc \setminus
           (thelaw S))], line3)
   line4 : [(hyp3_1 : that
       u = thelaw(S)) \Rightarrow (---
       : that u E Usc (thelaw
```

```
(S)))]
   {move 4}
   >>> define line5 hyp3 : line4 \
       hyp3 Mp line2 hyp1
   line5 : [(hyp3_1 : that
       u = thelaw(S)) \Rightarrow (---
       : that ??)]
   {move 4}
   >>> close
{move 4}
>>> define line6 hyp1 : Conj \
    (Simp1 line1 hyp1, Negintro \
    line5)
line6 : [(hyp1_1 : that u E prime
    (S)) \Rightarrow (--- : that (u E S) & ~ (u = thelaw
    (S)))]
{move 3}
>>> open
   {move 5}
   >>> declare hyp4 that u E Usc \setminus
       (thelaw S)
   hyp4 : that u E Usc (thelaw
    (S))
   {move 5}
```

```
>>> define line8 hyp4 : Mp \
          (Inusc1 hyp4, Simp2 hyp2)
      line8 : [(hyp4_1 : that
          u E Usc (thelaw (S))) =>
          (--- : that ??)]
      {move 4}
      >>> close
   {move 4}
   >>> define line9 hyp2 : Conj \
       (Simp1 hyp2, Negintro line8)
   line9 : [(hyp2_1 : that (u E S) & ~ (u = thelaw)]
       (S))) \Rightarrow (--- : that
       (u E S) & \tilde{} (u E Usc (thelaw
       (S))))]
   {move 3}
   >>> define line10 hyp2 : Iff2 \
       (line9 hyp2, Ui (u, Compax \
       (S, Usc (thelaw S))))
   line10 : [(hyp2_1 : that (u E S) \& ~ (u = thelaw)]
       (S))) => (--- : that
       u E S Complement Usc (thelaw
       (S)))]
   {move 3}
   >>> close
{move 3}
```

```
>>> define bothways u : Dediff line6, line10
         bothways : [(u_1 : obj) \Rightarrow (---
             : that (u_1 E prime (S)) ==
             (u_1 E S) & (u_1 = thelaw)
             (S)))]
         {move 2}
         >>> close
      {move 2}
      >>> define primeax subsetev : Ug bothways
      primeax : [(.S_1 : obj), (subsetev_1
          : that .S_1 <<= M) => (--- : that
          Forall ([(x'_2 : obj) =>
             ({def} (x'_2 E prime (.S_1)) ==
             (x'_2 E .S_1) & (x'_2 = thelaw)
             (.S_1)) : prop)]))]
      {move 1}
      >>> close
   {move 1}
end Lestrade execution
```

Now we are ready to define the central concept of this central argument, the idea of a Θ -chain. The definition of a Θ -chain has four clauses, and there are a tiresome number of occurrences in this document of proofs of the four statements required to show that a particular set is a Θ -chain.

begin Lestrade execution

```
>>> declare C11 obj
C11 : obj
{move 1}
>>> declare D11 obj
D11 : obj
{move 1}
>>> declare F11 obj
F11 : obj
{move 1}
>>> define thetachain1 M thelaw, C11 \
    : (M E C11) & (C11 <<= Sc (M)) & Forall \setminus
    [D11 => (D11 E C11) -> (prime D11) E C11] & Forall \setminus
    [D11 => Forall [F11 => ((D11 <<= C11) & (F11 \setminus
          E D11)) -> (Intersection D11 \
          F11) E C11]]
thetachain1 : [(M_1 : obj), (thelaw_1
    : [(S_2 : obj) => (--- : obj)]), (C11_1)
    : obj) =>
    ({def} (M_1 E C11_1) & (C11_1 <<=
    Sc (M_1)) & Forall ([(D11_5 : obj) =>
       ({def}) (D11_5 E C11_1) \rightarrow prime2
       (thelaw_1, D11_5) E C11_1 : prop)]) & Forall
    ([(D11_5 : obj) =>
       ({def} Forall ([(F11_6 : obj) =>
          ({def}) ((D11_5 <<= C11_1) \& F11_6
          E D11_5) -> (D11_5 Intersection
          F11_6) E C11_1 : prop)]) : prop)]) : prop)]
```

```
\label{eq:thetachain1} \ : \ \texttt{[(M\_1 : obj), (thelaw\_1)}
    : [(S_2 : obj) => (--- : obj)]), (C11_1)
    : obj) => (--- : prop)]
{move 0}
>>> open
   {move 2}
   >>> declare C obj
   C : obj
   {move 2}
   >>> declare D obj
   D : obj
   {move 2}
   >>> declare F obj
   F : obj
   {move 2}
   >>> define thetachain C : thetachain1 \setminus
        M thelaw, C
   \texttt{thetachain} \; : \; \texttt{[(C_1 : obj) => (---}
        : prop)]
   {move 1}
   >>> declare thetaev that thetachain \
```

```
thetaev : that thetachain (C)
   {move 2}
   >>> declare G obj
   G : obj
   {move 2}
   >>> declare ginev that G E C
   ginev : that G E C
   {move 2}
   >>> define Setsinchains1 thetaev ginev \
       : Simp1 (Simp2 (Iff1 (Mp (ginev, Ui \setminus
       (G, Simp1 (Simp1 (Simp2 thetaev)))), Ui \
       G Scthm M)))
   Setsinchains1 : [(.C_1 : obj), (thetaev_1
       : that thetachain (.C_1)), (.G_1
       : obj), (ginev_1 : that .G_1
       E .C_1) => (--- : that Isset (.G_1))]
   {move 1}
   >>> save
   {move 2}
   >>> close
{move 1}
>>> declare C10 obj
```

```
C10 : obj
{move 1}
>>> declare thetaev10 that thetachain \
    C10
thetaev10: that thetachain (C10)
{move 1}
>>> declare G10 obj
G10 : obj
{move 1}
>>> declare ginev10 that G10 E C10
ginev10 : that G10 E C10
{move 1}
>>> define Setsinchains2 Misset thelawchooses, thetaev10 \
    ginev10 : Setsinchains1 thetaev10 ginev10
Setsinchains2 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
          ({def} x_4 E .S_2 : prop)])) =>
       (---: that .thelaw_1 (.S_2) E .S_2)]), (.C10_1)
    : obj), (thetaev10_1 : that thetachain1
    (.M_1, .thelaw_1, .C10_1)), (.G10_1
    : obj), (ginev10_1 : that .G10_1
```

```
E .C10_1) =>
    ({def} Simp1 (Simp2 (ginev10_1 Mp
    .G10_1 Ui Simp1 (Simp1 (Simp2 (thetaev10_1))) Iff1
    .G10_1 Ui Scthm (.M_1))) : that
    Isset (.G10_1))]
Setsinchains2 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
          (\{def\} x_4 E .S_2 : prop)])) =>
       (---: that .thelaw_1 (.S_2) E .S_2)]), (.C10_1)
    : obj), (thetaev10_1 : that thetachain1
    (.M_1, .thelaw_1, .C10_1)), (.G10_1
    : obj), (ginev10_1 : that .G10_1
    E .C10_1) \Rightarrow (--- : that Isset (.G10_1))]
{move 0}
>>> open
   {move 2}
   >>> define Setsinchains thetaev ginev \
       : Setsinchains2 Misset, thelawchooses, thetaev \
       ginev
   Setsinchains : [(.C_1 : obj), (thetaev_1
       : that thetachain (.C_1)), (.G_1
       : obj), (ginev_1 : that .G_1
       E .C_1) \Rightarrow (--- : that Isset (.G_1))]
   {move 1}
   >>> close
```

{move 1} end Lestrade execution

We did some extra work to ensure that **thetachain** is defined in terms of a notion at move 0 which will not be expanded everywhere it occurs.

We then proved that each element of a Θ -chain is a set and again did work to control definitional expansion.

We then need to prove that $\mathcal{P}(M)$ is a Θ -chain.

```
begin Lestrade execution
```

The first two lines establish the first two of the four points needed to show that $\mathcal{P}(M)$ is a Θ -chain.

begin Lestrade execution

```
>>> open
            {move 4}
            >>> declare u obj
            u : obj
            {move 4}
            >>> open
               {move 5}
               >>> declare usinev that u E Sc \
               usinev : that u E Sc (M)
               {move 5}
               >>> define line3 : Fixform \
                   (Isset (prime u), Separation3 \
                   (Refleq prime u))
               line3 : that Isset (prime
                (u))
               {move 4}
end Lestrade execution
```

Note the devious use of Separation3 to avoid having to write out the defining predicate of the prime operation. The use of the axiom Separation2 is essential: the result of applying the prime operation might be empty, and we do want it to be a set.

begin Lestrade execution

```
>>> define line4 usinev : Simp1 \
    (Simp2 (Iff1 (usinev, Ui \
    u (Scthm M))))
line4 : [(usinev_1 : that
    u \in Sc (M) => (---
    : that Isset (u))]
{move 4}
>>> open
   {move 6}
   >>> declare v obj
   v : obj
   {move 6}
   >>> open
      {move 7}
      >>> declare vinev that \
          v \ E \ prime \ u
      vinev : that v E prime
       (u)
      {move 7}
      >>> define line5 : Ui \
          v primeax (Iff1 (usinev, Ui \
          u Scthm M))
```

```
line5 : that (v E prime
    (u)) == (v E u) & \sim (v = thelaw)
    (u))
   {move 6}
   >>> define line6 vinev \
       : Simp1 (Iff1 (vinev, line5))
   line6 : [(vinev_1
       : that v E prime
       (u)) => (---
       : that v E u)]
   {move 6}
   >>> define line7 vinev \
       : Mp line6 vinev (Ui \
       v Simp1 (Iff1 (usinev, Ui \
       u Scthm M)))
   line7 : [(vinev_1
       : that v E prime
       (u)) => (---
       : that v E M)]
   {move 6}
   >>> close
{move 6}
>>> define line8 v : Ded \
    line7
line8 : [(v_1 : obj) =>
    (---: that (v_1 E prime)
```

```
(u)) \rightarrow v_1 E M)
   {move 5}
   >>> close
{move 5}
>>> define line9 usinev : Ug \
    line8
line9 : [(usinev_1 : that
    u \in Sc (M)) => (---
    : that Forall ([(x, 2)]
       : obj) =>
       (\{def\}\ (x'_2 \ E \ prime
       (u)) \rightarrow x'_2 E M : prop)]))]
{move 4}
>>> define line10 usinev : Fixform \
    ((prime u) <<= M, Conj \
    (line9 usinev, Conj (line3, Misset)))
line10 : [(usinev_1 : that
    u \in Sc (M) = (---
    : that prime (u) <<=
    [(M)]
{move 4}
>>> define line11 usinev : Iff2 \
    (line10 usinev, Ui (prime \
    u, Scthm M))
line11 : [(usinev_1 : that
    u \in Sc (M) = (---
    : that prime (u) E Sc
```

```
(M))]
                 {move 4}
                 >>> close
             {move 4}
             >>> define line12 u : Ded line11
             line12 : [(u_1 : obj) => (---
                  : that (u_1 E Sc (M)) \rightarrow
                  prime (u_1) \to Sc (M)
             {move 3}
             >>> close
          {move 3}
          >>> define line13 : Ug line12
          line13 : that Forall ([(x'_2)]
               : obj) =>
              (\{def\} (x'_2 E Sc (M)) \rightarrow
              prime (x'_2) \to Sc (M) : prop)
          {move 2}
end Lestrade execution
   Here is the third statement needed to verify that \mathcal{P}(M) is a \Theta-chain.
begin Lestrade execution
          >>> open
```

{move 4}

```
>>> declare u obj
u : obj
{move 4}
>>> open
   {move 5}
   >>> declare v obj
   v : obj
   {move 5}
   >>> open
      {move 6}
      >>> declare hyp that (u <<= \
          Sc M) & v E u
      hyp : that (u \leq Sc (M)) & v E u
      {move 6}
      >>> define line14 hyp : Simp2 \setminus
          hyp Mp Intax u v
      line14 : [(hyp_1 : that
           (u <<= Sc (M)) & v E u) =>
           (--- : that Forall
           ([(x', 2 : obj) =>
              ({def} (x''_2 E u Intersection
             v) == Forall ([(B1_4)])
                 : obj) =>
```

```
({def} (B1_4
          E u) -> x''_2
          E B1_4 : prop)]) : prop)]))]
{move 5}
>>> open
   {move 7}
   >>> declare w obj
   w : obj
   {move 7}
   >>> open
      {move 8}
      >>> declare hyp2 \
          that w E Intersection \
          u v
      hyp2: that w E u Intersection
       V
      {move 8}
      >>> define line15 \
          hyp2 : Mp (Simp2 \
          hyp, Ui v (Iff1 \
          (hyp2, Ui w line14 \
          hyp)))
      line15 : [(hyp2_1
          : that w E u Intersection
          v) => (--- : that
```

```
w E v)]
   {move 7}
   >>> define line16 \
       : Mp (Simp2 hyp, Ui \
       v Simp1 (Simp1 hyp))
   line16 : that v E Sc
    (M)
   {move 7}
   >>> define line17 \
       : Iff1 (line16, Ui \
       v Scthm M)
   line17 : that v <<=
    Μ
   {move 7}
   >>> define line18 \
       hyp2 : Mp (line15 \
       hyp2, Ui w Simp1 \
       line17)
   line18 : [(hyp2_1
       : that w {\tt E} u {\tt Intersection}
       v) \Rightarrow (--- : that
       w E M)]
   {move 7}
   >>> close
{move 7}
```

```
>>> define line19 w : Ded \
       line18
   line19 : [(w_1 : obj) =>
       (---: that (w_1)
       E u Intersection
       v) -> w_1 E M)]
   {move 6}
   >>> close
{move 6}
>>> define line20 hyp : Ug \setminus
    line19
line20 : [(hyp_1 : that
    (u \iff Sc (M)) \& v E u) =>
    (--- : that Forall
    ([(x, 2 : obj) =>
       (\{def\} (x'_2 E u Intersection
       v) -> x'_2 E M : prop)]))]
{move 5}
>>> define line21 : Fixform \
    (Isset (Intersection \
    u v), Separation3 (Refleq \
    (Intersection u v)))
line21 : that Isset (u Intersection
 v)
{move 5}
>>> define line22 hyp : Fixform \
    ((Intersection u v) <<= \
```

```
M, Conj (line20 hyp, Conj \
       (line21, Misset)))
   line22 : [(hyp_1 : that
       (u \iff Sc (M)) \& v E u) =>
       (---: that (u Intersection
       V = V = V
   {move 5}
   >>> define line23 hyp : Iff2 \setminus
       (line22 hyp, Ui (Intersection \
       u v, Scthm M))
   line23 : [(hyp_1 : that
       (u \iff Sc (M)) \& v E u) =>
       (---: that (u Intersection
       v) E Sc (M))]
   {move 5}
   >>> close
{move 5}
>>> define line24 v : Ded \setminus
    line23
line24 : [(v_1 : obj) =>
    (--- : that ((u <<=
    Sc (M)) & v_1 E u) ->
    (u Intersection v_1) E Sc
    (M))]
{move 4}
>>> close
```

```
{move 4}
            >>> define line25 u : Ug line24
            line25 : [(u_1 : obj) => (---
                 : that Forall ([(x'_2 : obj) =>
                    (\{def\} ((u_1 <<= Sc
                    (M)) & x'_2 E u_1) \rightarrow
                    (u_1 Intersection x'_2) E Sc
                    (M) : prop)]))]
            {move 3}
            >>> close
         {move 3}
         >>> define line26 : Ug line25
         line26 : that Forall ([(x'_2)
              : obj) =>
              (\{def\} Forall ([(x'_3 : obj) =>
                 ({def}) ((x'_2 \ll Sc (M)) & x'_3
                 E x'_2) \rightarrow (x'_2 Intersection)
                 x'_3) E Sc (M) : prop)]) : prop)])
         {move 2}
end Lestrade execution
```

Here is the fourth and last statement needed to verify that the power set of M is a Θ -chain.

begin Lestrade execution

>>> close

{move 2}

```
>>> define thetascm1 : Fixform (thetachain \
       (Sc M), Conj (line1, Conj (line2, Conj \
       (line13, line26))))
   thetascm1 : that thetachain (Sc (M))
   {move 1}
   >>> close
{move 1}
>>> define thetascm2 Misset thelawchooses \
    : thetascm1
thetascm2 : [(.M_1 : obj), (Misset_1)]
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
          ({def} x_4 E .S_2 : prop)])) =>
       (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
    ({def} thetachain1 (.M_1, .thelaw_1, Sc
    (.M_1)) Fixform Misset_1 Mp .M_1
    Ui Inownpowerset Conj Misset_1 Mp .M_1
    Ui Scofsetisset Mp Sc (.M_1) Ui Subsetrefl
    Conj Ug ([(u_6 : obj) =>
       ({def} Ded ([(usinev_7 : that
          u_6 E Sc (.M_1)) =>
          ({def} ((prime2 (.thelaw_1, u_6) <<=
          .M_1) Fixform Ug ([(v_11
             : obj) =>
             ({def} Ded ([(vinev_12
                : that v_11 E prime2 (.thelaw_1, u_6)) =>
                ({def} Simp1 (vinev_12
                Iff1 v_11 Ui Ug ([(u_17
```

```
: obj) =>
({def} Dediff ([(hyp1_18
   : that u_17 E prime2
   (.thelaw_1, u_6)) \Rightarrow
   ({def} Simp1 (hyp1_18
  Iff1 u_17 Ui u_6
  Compax Usc (.thelaw_1
   (u_6))) Conj
  Negintro ([(hyp3_20
      : that u_17 = .thelaw_1
      (u_6)) =>
      ({def} Subs (Eqsymm
      (hyp3_20), [(v_22
         : obj) =>
         ({def} v_22
         E Usc (.thelaw_1
         (u_6)) : prop)], Inusc2
      (.thelaw_1 (u_6))) Mp
      Simp2 (hyp1_18
      Iff1 u_17 Ui u_6
      Compax Usc (.thelaw_1
      (u_6)) : that
      ??)]) : that
   (u_17 E u_6) \& ~ (u_17)
  = .thelaw_1 (u_6))], [(hyp2_18)
   : that (u_17 E u_6) \& ~(u_17)
  = .thelaw_1 (u_6)) =>
   ({def} Simp1 (hyp2_18) Conj
  Negintro ([(hyp4_21
      : that u_17 E Usc
      (.thelaw_1 (u_6))) =>
      ({def} Inusc1
      (hyp4_21) Mp
      Simp2 (hyp2_18) : that
      ??)]) Iff2
  u_17 Ui u_6 Compax
  Usc (.thelaw_1 (u_6)): that
  u_17 E u_6 Complement
```

```
Usc (.thelaw_1 (u_6))): that
               (u_17 E prime2 (.thelaw_1, u_6)) ==
               (u_17 E u_6) \& ~(u_17)
               = .thelaw_1 (u_6)))))) Mp
            v_11 Ui Simp1 (usinev_7
            Iff1 u_6 Ui Scthm (.M_1): that
            v_11 E .M_1)]) : that
         (v_11 E prime2 (.thelaw_1, u_6)) ->
         v_11 E .M_1)]) Conj (Isset
      (prime2 (.thelaw_1, u_6)) Fixform
      Separation3 (Refleq (prime2
      (.thelaw_1, u_6)))) Conj
      Misset_1) Iff2 prime2 (.thelaw_1, u_6) Ui
      Scthm (.M_1): that prime2
      (.thelaw_1, u_6) E Sc (.M_1))]) : that
   (u_6 E Sc (.M_1)) \rightarrow prime2
   (.thelaw_1, u_6) E Sc (.M_1))]) Conj
Ug ([(u_6 : obj) =>
   (\{def\}\ Ug\ ([(v_7 : obj) =>
      ({def} Ded ([(hyp_8 : that
         (u_6 \ll Sc (.M_1)) \& v_7
         E u_6) =>
         ({def} (((u_6 Intersection
         v_7) <<= .M_1) Fixform Ug
         ([(w_12 : obj) =>
            ({def} Ded ([(hyp2_13
               : that w_12 E u_6 Intersection
               v_{-}7) =>
               ({def} Simp2 (hyp_8) Mp
               v_7 Ui hyp2_13 Iff1
               w_12 Ui Simp2 (hyp_8) Mp
               u_6 Intax v_7 Mp w_12
               Ui Simp1 (Simp2 (hyp_8) Mp
               v_7 Ui Simp1 (Simp1
               (hyp_8)) Iff1 v_7
               Ui Scthm (.M_1): that
               w_12 E .M_1)]) : that
            (w_12 E u_6 Intersection)
```

```
v_7) \rightarrow w_12 E .M_1) Conj
              (Isset (u_6 Intersection
             v_7) Fixform Separation3
              (Refleq (u_6 Intersection
             v_7))) Conj Misset_1) Iff2
              (u_6 Intersection v_7) Ui
             Scthm (.M_1): that (u_6)
             Intersection v_7) E Sc (.M_1))]) : that
          ((u_6 \iff Sc (.M_1)) \& v_7
          E u_6) \rightarrow (u_6 Intersection)
          v_{7} E Sc (M_{1}): that
       Forall ([(x'_7 : obj) =>
          (\{def\} ((u_6 \iff Sc (.M_1)) \& x'_7)
          E u_6) \rightarrow (u_6 Intersection)
          x'_{7} E Sc (.M_{1} : prop)]))]) : that
    thetachain1 (.M_1, .thelaw_1, Sc
    (.M_1))
thetascm2 : [(.M_1 : obj), (Misset_1)]
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
          ({def} x_4 E .S_2 : prop)])) =>
       (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
    (---: that thetachain1 (.M_1, .thelaw_1, Sc
    (.M_1))
{move 0}
>>> open
   {move 2}
   >>> define thetascm : thetascm2 Misset, thelawchooses
   thetascm : that thetachain1 (M, [(S'_2
```

```
: obj) =>
     ({def} thelaw (S'_2) : obj)], Sc
     (M))

{move 1}
end Lestrade execution
```

Here we have proved that $\mathcal{P}(M)$ is a Θ -chain.

Notice that we take this theorem down to move 0 then bring it back up and define a new move 1 theorem with the same content in terms of the move 0 concept. This prevents future references to this theorem from expanding to the very large term appearing above.

```
{move 4}
>>> declare hyp1 that thetachain \
hyp1 : that thetachain (C)
{move 4}
>>> declare hyp2 that C E Thetachain
hyp2 : that C E Thetachain
{move 4}
>>> define line1 hyp1 : Iff2 \
    (Simp1 (Simp2 hyp1), Ui C Scthm \setminus
    Sc M)
line1 : [(hyp1_1 : that thetachain
    (C)) => (--- : that C \to Sc
    (Sc (M)))]
{move 3}
>>> define line2 hyp1 : Fixform \
    (C E Thetachain, Iff2 (Conj \
    (line1 hyp1, hyp1), Ui (C, Separation \
    ((Sc (Sc M)), thetachain))))
line2 : [(hyp1_1 : that thetachain
    (C)) => (--- : that C E Thetachain)]
{move 3}
>>> define line3 hyp2 : Simp2 \
    (Iff1 (hyp2, Ui (C, Separation \
    ((Sc (Sc M)), thetachain))))
```

```
line3 : [(hyp2_1 : that C E Thetachain) =>
                (---: that thetachain (C))]
            {move 3}
            >>> close
         {move 3}
         >>> define line4 C : Dediff line3, line2
         line4 : [(C_1 : obj) => (---
             : that (C_1 E Thetachain) ==
             thetachain (C_1))]
         {move 2}
         >>> close
      {move 2}
      >>> define Thetachainax : Ug line4
      Thetachainax : that Forall ([(x'_2)]
          : obj) =>
          ({def}) (x'_2 E Thetachain) ==
          thetachain (x'_2) : prop)])
      {move 1}
end Lestrade execution
```

We prove that the collection of all Θ -chains is a set, and in particular a subset of $\mathcal{P}^2(M)$.

We now define the Θ -chain which implements the desired well-ordering (though we have to verify subsequently that that is what it is).

```
begin Lestrade execution
      >>> define Mbold1 : Intersection Thetachain \
          Sc M
      Mbold1 : obj
      {move 1}
      >>> close
   {move 1}
   >>> define Mbold2 Misset thelawchooses \
       : Mbold1
   Mbold2 : [(.M_1 : obj), (Misset_1
       : that Isset (.M_1)), (.thelaw_1
       : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
       : [(.S_2 : obj), (subsetev_2 : that
          .S_2 \ll .M_1), (inev_2 : that
          Exists ([(x_4 : obj) =>
             ({def} x_4 E .S_2 : prop)])) =>
          (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
       ({def} (Sc (Sc (.M_1)) Set [(C_3
          : obj) =>
          ({def} thetachain1 (.M_1, .thelaw_1, C_3) : prop)]) Intersection
       Sc (.M_1) : obj)]
   Mbold2 : [(.M_1 : obj), (Misset_1
       : that Isset (.M_1)), (.thelaw_1
```

 $: [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)$

 $(\{def\} x_4 E .S_2 : prop)])) \Rightarrow (--- : that .thelaw_1 (.S_2) E .S_2)]) \Rightarrow$

: [(.S_2 : obj), (subsetev_2 : that
 .S_2 <<= .M_1), (inev_2 : that</pre>

Exists ($[(x_4 : obj) =>$

(--- : obj)]

```
{move 0}

>>> open

{move 2}

>>> define Mbold : Mbold2 Misset, thelawchooses

Mbold : obj

{move 1}
end Lestrade execution
```

We now have the tedious task of directly verifying that M is a Θ -chain, which Zermelo dismisses as a side remark!

We note that Zermelo's text suggests that we should prove that any intersection of Θ -chains is a Θ -chain, but it appears that the only case of this we need is that \mathbf{M} itself is a Θ -chain.

```
>>> open
   {move 3}
   >>> define Mboldax1 : Intax Thetachain \
       Sc M
  Mboldax1 : that (Sc (M) E Thetachain) ->
   Forall ([(x,',3:obj)=>
       (\{def\} (x'', 3 E Thetachain
       Intersection Sc (M)) == Forall
       ([(B1_5 : obj) =>
          ({def} (B1_5 E Thetachain) ->
          x''_3 E B1_5 : prop)]) : prop)])
   {move 2}
   >>> define line1 : Ui Sc M Thetachainax
   line1 : that (Sc (M) E Thetachain) ==
   thetachain (Sc (M))
   {move 2}
   >>> define line2 : Iff2 thetascm \
       line1
   line2 : that Sc (M) E Thetachain
   {move 2}
   >>> close
{move 2}
>>> define Mboldax : Fixform (Forall \
    [C \Rightarrow (C E Mbold) == Forall [D \Rightarrow \
          (D E Thetachain) -> C E D]], Mp \
```

Above, we develop the most convenient definition of the extension of **M**. I am not sure it is actually used much (though it is used at least once). I believe that development of **Separation4** caused separation axioms for particular constructions to be used much less.

```
begin Lestrade execution

>>> clearcurrent
{move 2}

>>> open

{move 3}

>>> declare F obj

F : obj

{move 3}

>>> open

{move 4}

>>> declare ftheta that F E Thetachain
```

```
ftheta : that F E Thetachain
      {move 4}
      >>> define line1 ftheta : Iff1 \setminus
          (ftheta, Ui F Thetachainax)
      line1 : [(ftheta_1 : that F E Thetachain) =>
          (---: that thetachain (F))]
      {move 3}
      >>> define line2 ftheta : Simp1 \
          line1 ftheta
      line2 : [(ftheta_1 : that F E Thetachain) =>
          (--- : that M E F)]
      {move 3}
      >>> close
   {move 3}
   >>> define Linea1 F : Ded line2
  Linea1 : [(F_1 : obj) => (---
       : that (F_1 E Thetachain) ->
       M E F_1)]
   {move 2}
   >>> close
{move 2}
>>> define Lineb1 : Ug Linea1
```

Here is the first component of the proof that ${\bf M}$ is a Θ -chain.

```
begin Lestrade execution
```

```
>>> open
    {move 3}

>>> open
    {move 4}

    >>> declare A obj

    A : obj
    {move 4}

    >>> open
```

```
{move 5}
      >>> declare ainev that A E Mbold
      ainev : that A E Mbold
      {move 5}
      >>> define line1 ainev : Mp \
          (Iff2 (thetascm, Ui Sc \
          M Thetachainax), Ui Sc M, Iff1 \
          (ainev, Ui A Mboldax))
      line1 : [(ainev_1 : that
          A E Mbold) \Rightarrow (--- : that
          A E Sc (M))]
      {move 4}
      >>> close
   {move 4}
   >>> define line2 A : Ded line1
   line2 : [(A_1 : obj) => (---
       : that (A_1 E Mbold) ->
       A_1 E Sc (M))]
   {move 3}
   >>> close
{move 3}
>>> define Line3 : Ug line2
Line3 : that Forall ([(x'_2 : obj) =>
```

Here is the second component of the proof that ${\bf M}$ is a Θ -chain.

```
begin Lestrade execution
```

```
>>> open
{move 3}

>>> declare F obj
F : obj
{move 3}

>>> open
```

```
{move 4}
>>> declare finmbold that F E (Mbold)
finmbold : that F E Mbold
{move 4}
>>> open
   {move 5}
  >>> declare G obj
  G : obj
   {move 5}
   >>> open
      {move 6}
      >>> declare gtheta that \
          G E Thetachain
      gtheta : that G E Thetachain
      {move 6}
      >>> define line1 gtheta \
          : Ui (F, Simp1 Simp2 \
          Simp2 Iff1 (gtheta, Ui \
          G Thetachainax))
      line1 : [(gtheta_1 : that
          G E Thetachain) =>
          (--- : that (F E G) \rightarrow
          prime2 (thelaw, F) E G)]
```

```
{move 5}
   >>> define line2 gtheta \
       : Mp (gtheta, Ui (G, Iff1 \
       (finmbold, Ui F Mboldax)))
   line2 : [(gtheta_1 : that
       G E Thetachain) =>
       (--- : that F E G)]
   {move 5}
   >>> define line3 gtheta \
       : Mp line2 gtheta line1 \
       gtheta
   line3 : [(gtheta_1 : that
       G E Thetachain) =>
       (---: that prime2
       (thelaw, F) E G)]
   {move 5}
   >>> close
{move 5}
>>> define line4 G : Ded line3
line4 : [(G_1 : obj) =>
    (--- : that (G_1 E Thetachain) ->
    prime2 (thelaw, F) E G_1)]
{move 4}
>>> close
```

```
{move 4}
   >>> define line5 finmbold : Ug \
       line4
   line5 : [(finmbold_1 : that
       F \in Mbold) \Rightarrow (--- : that
       Forall ([(x'_2 : obj) =>
          (\{def\}\ (x'_2 \to Thetachain) \to
          prime2 (thelaw, F) E x'_2
          : prop)]))]
   {move 3}
   >>> define line6 finmbold : Iff2 \
       (line5 finmbold, Ui (prime \
       F, Mboldax))
   line6 : [(finmbold_1 : that
       F \in Mbold) \Rightarrow (--- : that
       prime (F) E Mbold)]
   {move 3}
   >>> close
{move 3}
>>> define line7 F : Ded line6
line7 : [(F_1 : obj) => (---
    : that (F_1 E Mbold) -> prime
    (F_1) E Mbold)]
{move 2}
>>> close
```

```
{move 2}
   >>> define Linea8 : Ug line7
   Linea8 : that Forall ([(x'_2 : obj) =>
       ({def} (x'_2 E Mbold) \rightarrow prime
       (x'_2) E Mbold : prop)])
   {move 1}
   >>> save
   {move 2}
   >>> close
{move 1}
>>> define Lineb8 Misset thelawchooses \
    : Linea8
Lineb8 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
          ({def} x_4 E .S_2 : prop)])) =>
       (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
    (\{def\}\ Ug\ ([(F_2 : obj) =>
       ({def} Ded ([(finmbold_3 : that
          F_2 E Misset_1 Mbold2 thelawchooses_1) =>
          (\{def\}\ Ug\ ([(G_5 : obj) =>
              ({def} Ded ([(gtheta_6
                 : that G_5 \to Sc (Sc (.M_1)) Set
                 [(C_9 : obj) =>
                    ({def} thetachain1
                    (.M_1, .thelaw_1, C_9) : prop)]) =>
```

```
({def} gtheta_6 Mp G_5
Ui finmbold_3 Iff1 F_2
Ui Forall ([(C_13 : obj) =>
   ({def} (C_13 E Misset_1
   Mbold2 thelawchooses_1) ==
   Forall ([(D_15 : obj) =>
      ({def} (D_15 E Sc
      (Sc (.M_1)) Set
      [(C_18 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_18) : prop)]) ->
      C_13 E D_15 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
Iff2 Sc (.M_1) Ui Ug
([(C_16 : obj) =>
   ({def} Dediff ([(hyp2_17
      : that C_16 E Sc
      (Sc (.M_1)) Set
      [(C_20 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_20) : prop)]) =>
      ({def} Simp2 (hyp2_17
      Iff1 C_16 Ui Sc (Sc
      (.M_1)) Separation
      [(C_21 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop)]) : that
      thetachain1 (.M_1, .thelaw_1, C_16))], [(hyp1_17
      : that thetachain1
      (.M_1, .thelaw_1, C_16)) =>
      ({def} (C_16 E Sc
      (Sc (.M_1)) Set
      [(C_20 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_20) : prop)]) Fixform
      Simp1 (Simp2 (hyp1_17)) Iff2
      C_16 Ui Scthm (Sc
      (.M_1)) Conj hyp1_17
```

```
Iff2 C_16 Ui Sc (Sc
      (.M_1)) Separation
      [(C_21 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop): that
      C_16 E Sc (Sc (.M_1)) Set
      [(C_19 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_19) : prop)])]) : that
   (C_16 E Sc (Sc (.M_1)) Set
   [(C_19 : obj) =>
      ({def} thetachain1
      (.M_1, .thelaw_1, C_19) : prop)]) ==
   thetachain1 (.M_1, .thelaw_1, C_16))]) Mp
(Sc (Sc (.M_1)) Set
[(C_15 : obj) =>
   ({def} thetachain1
   (.M_1, .thelaw_1, C_15) : prop)]) Intax
Sc (.M_1) Mp F_2 Ui Simp1
(Simp2 (Simp2 (gtheta_6
Iff1 G_5 Ui Ug ([(C_14
   : obj) =>
   ({def} Dediff ([(hyp2_15
      : that C_14 E Sc
      (Sc (.M_1)) Set
      [(C_18 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_18) : prop)]) =>
      ({def} Simp2 (hyp2_15
      Iff1 C_14 Ui Sc (Sc
      (.M_1)) Separation
      [(C_19 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_19) : prop)]) : that
      thetachain1 (.M_1, .thelaw_1, C_14))], [(hyp1_15
      : that thetachain1
      (.M_1, .thelaw_1, C_14)) =>
      (\{def\}\ (C_14\ E\ Sc
```

```
(Sc (.M_1)) Set
            [(C_18 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_18) : prop)]) Fixform
            Simp1 (Simp2 (hyp1_15)) Iff2
            C_14 Ui Scthm (Sc
            (.M_1)) Conj hyp1_15
            Iff2 C_14 Ui Sc (Sc
            (.M_1)) Separation
            [(C_19 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_19) : prop)] : that
            C_14 E Sc (Sc (.M_1)) Set
            [(C_17 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_17) : prop)])]) : that
         (C_14 E Sc (Sc (.M_1)) Set
         [(C_17 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_17) : prop)]) ==
         thetachain1 (.M_1, .thelaw_1, C_14)))))): that
      prime2 (.thelaw_1, F_2) E G_5)]) : that
   (G_5 E Sc (Sc (.M_1)) Set
   [(C_8 : obj) =>
      ({def} thetachain1 (.M_1, .thelaw_1, C_8) : prop)]) ->
   prime2 (.thelaw_1, F_2) E G_5)]) Iff2
prime2 (.thelaw_1, F_2) Ui
Forall ([(C_7 : obj) =>
   ({def} (C_7 E Misset_1 Mbold2
   thelawchooses_1) == Forall
   ([(D_9 : obj) =>
      ({def} (D_9 E Sc (Sc
      (.M_1)) Set [(C_12)
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_12) : prop)]) ->
      C_7 E D_9 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
```

```
Iff2 Sc (.M_1) Ui Ug ([(C_10
   : obj) =>
   ({def} Dediff ([(hyp2_11
      : that C_{10} \to Sc (Sc (.M_1)) Set
      [(C_14 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_14) : prop)]) =>
      ({def} Simp2 (hyp2_11
      Iff1 C_10 Ui Sc (Sc (.M_1)) Separation
      [(C_15 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_15) : prop)]) : that
      thetachain1 (.M_1, .thelaw_1, C_10))], [(hyp1_11
      : that thetachain1 (.M_1, .thelaw_1, C_10)) =>
      ({def} (C_10 E Sc (Sc
      (.M_1)) Set [(C_14)
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_14) : prop)]) Fixform
      Simp1 (Simp2 (hyp1_11)) Iff2
      C_10 Ui Scthm (Sc (.M_1)) Conj
      hyp1_11 Iff2 C_10 Ui Sc
      (Sc (.M_1)) Separation
      [(C_15 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_15) : prop)] : that
      C_10 E Sc (Sc (.M_1)) Set
      [(C_13 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_13) : prop)])]) : that
   (C_10 E Sc (Sc (.M_1)) Set
   [(C_13 : obj) =>
      (\{def\} thetachain1 (.M_1, .thelaw_1, C_13) : prop)]) ==
   thetachain1 (.M_1, .thelaw_1, C_10))]) Mp
(Sc (Sc (.M_1)) Set [(C_9)]
   : obj) =>
   ({def} thetachain1 (.M_1, .thelaw_1, C_9) : prop)]) Intax
Sc (.M_1): that prime2 (.thelaw_1, F_2) E Misset_1
```

```
Mbold2 thelawchooses_1)]) : that
          (F_2 E Misset_1 Mbold2 thelawchooses_1) ->
          prime2 (.thelaw_1, F_2) E Misset_1
          Mbold2 thelawchooses_1)]) : that
       Forall ([(x'_2 : obj) =>
          ({def} (x'_2 E Misset_1 Mbold2
          thelawchooses_1) -> prime2 (.thelaw_1, x'_2) E Misset_1
          Mbold2 thelawchooses_1 : prop)]))]
   Lineb8 : [(.M_1 : obj), (Misset_1
       : that Isset (.M_1)), (.thelaw_1
       : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
       : [(.S_2 : obj), (subsetev_2 : that
          .S_2 \ll .M_1), (inev_2 : that
          Exists ([(x_4 : obj) =>
             ({def} x_4 E .S_2 : prop)])) =>
          (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
       (---: that Forall ([(x'_2: obj) =>
          ({def} (x'_2 E Misset_1 Mbold2
          thelawchooses_1) -> prime2 (.thelaw_1, x'_2) E Misset_1
          Mbold2 thelawchooses_1 : prop)]))]
   {move 0}
   >>> open
      {move 2}
      >>> define Line8 : Lineb8 Misset, thelawchooses
      Line8 : that Forall ([(x'_2 : obj) =>
          ({def} (x'_2 E Misset Mbold2 thelawchooses) ->
          prime2 ([(S'_5 : obj) =>
             (\{def\} thelaw (S'_5) : obj)], x'_2) E Misset
          Mbold2 thelawchooses : prop)])
      {move 1}
end Lestrade execution
```

Here is the third component of the proof that M is a Θ -chain. Note the importance of preventing definitional expansion here!

begin Lestrade execution

```
>>> open
   {move 3}
   >>> declare H obj
   H : obj
   {move 3}
   >>> open
      {move 4}
      >>> declare J obj
      J : obj
      {move 4}
      >>> open
         {move 5}
         >>> declare thehyp that (H <<= \setminus
              Mbold) & J E H
         thehyp : that (H <<= Mbold) & J E H
         {move 5}
         >>> open
```

```
{move 6}
>>> declare K obj
K : obj
{move 6}
>>> open
   {move 7}
   >>> declare ktheta that \
       K E Thetachain
   ktheta: that K E Thetachain
   {move 7}
   >>> define line1 ktheta \
       : Iff1 (ktheta, Ui \
       K Thetachainax)
   line1 : [(ktheta_1
       : that K E Thetachain) =>
       (--- : that thetachain
       (K))]
   {move 6}
   >>> define line2 ktheta \
       : Ui J, Ui H, Simp2 \
       Simp2 Simp2 line1 ktheta
   line2 : [(ktheta_1
       : that K E Thetachain) =>
       (--- : that ((H <<=
```

```
K) & J E H) ->
    (H Intersection
    J) E K)]
{move 6}
>>> open
   {move 8}
   >>> declare P obj
  P : obj
   {move 8}
   >>> open
      {move 9}
     >>> declare phyp \
          that P E H
      phyp : that P E H
      {move 9}
      >>> define line3 \
          phyp : Mp (phyp, Ui \
          P Simp1 Simp1 \
          thehyp)
     line3 : [(phyp_1
          : that P E H) =>
          (--- : that
          P E Mbold)]
      {move 8}
```

```
>>> define line4 \setminus
          phyp : Mp (ktheta, K Ui \
          Iff1 line3 phyp, Ui \
          P Mboldax)
      line4 : [(phyp_1
          : that P E H) =>
          (--- : that
          P E K)]
      {move 8}
      >>> close
   {move 8}
   >>> define line5 \
       P : Ded line4
   line5 : [(P_1 : obj) =>
       (--- : that (P_1
       E H) \rightarrow P_1 E K
   {move 7}
   >>> close
{move 7}
>>> define test1 ktheta \
    : Ug line5
test1 : [(ktheta_1
    : that K E Thetachain) =>
    (--- : that Forall
    ([(x,_2 : obj) =>
       ({def} (x'_2)
```

```
E H) \rightarrow x'_2
       E K : prop)]))]
{move 6}
>>> define test2 ktheta \
    : Inhabited Simp2 thehyp
test2 : [(ktheta_1
    : that K E Thetachain) =>
    (--- : that Isset
    (H))]
{move 6}
>>> define test3 ktheta \
    : Inhabited (Mp (Simp2 \
    thehyp, line5 J))
test3 : [(ktheta_1
    : that K E Thetachain) =>
    (---: that Isset
    (K))]
{move 6}
>>> define line6 ktheta \
    : Fixform (H <<= K, Conj \setminus
    (test1 ktheta, Conj \
    (test2 ktheta, test3 \
    ktheta)))
line6 : [(ktheta_1
    : that K E Thetachain) =>
    (--- : that H <<=
    K)]
{move 6}
```

```
>>> define linea7 ktheta \
          : Mp (Conj (line6 \
          ktheta, Simp2 thehyp), line2 \
          ktheta)
      linea7 : [(ktheta_1
          : that K E Thetachain) =>
          (--- : that (H Intersection
          J) E K)]
      {move 6}
      >>> close
   {move 6}
   >>> define line8 K : Ded \
       linea7
   line8 : [(K_1 : obj) =>
       (--- : that (K_1 E Thetachain) ->
       (H Intersection J) E K_1)]
   {move 5}
   >>> close
{move 5}
>>> define line9 thehyp : Ug \
    line8
line9 : [(thehyp_1 : that
    (H <<= Mbold) & J E H) =>
    (---: that Forall ([(x'_2)
       : obj) =>
       ({def} (x'_2 E Thetachain) \rightarrow
```

```
(H Intersection J) E x'_2
          : prop)]))]
   {move 4}
   >>> define line10 : Ui (H Intersection \
       J, Mboldax)
   line10 : that ((H Intersection
    J) E Mbold) == Forall ([(D_3)])
       : obj) =>
       ({def} (D_3 E Thetachain) ->
       (H Intersection J) E D_3
       : prop)])
   {move 4}
   >>> define line11 thehyp : Iff2 \setminus
       (line9 thehyp, line10)
   line11 : [(thehyp_1 : that
       (H <<= Mbold) & J E H) =>
       (---: that (H Intersection
       J) E Mbold)]
   {move 4}
   >>> close
{move 4}
>>> define line12 J : Ded line11
line12 : [(J_1 : obj) => (---
   : that ((H <<= Mbold) & J_1
    E H) -> (H Intersection
    J_1) E Mbold)]
```

```
{move 3}
         >>> close
      {move 3}
      >>> define line13 H : Ug line12
      line13 : [(H_1 : obj) => (---
          : that Forall ([(x'_2 : obj) =>
             (\{def\} ((H_1 \le Mbold) \& x'_2)
             E H_1) -> (H_1 Intersection
             x'_2) E Mbold : prop)]))]
      {move 2}
      >>> close
   {move 2}
   >>> define Linea14 : Ug line13
   Linea14 : that Forall ([(x'_2 : obj) = 
       (\{def\} Forall ([(x'_3 : obj) =>
          (\{def\} ((x'_2 \le Mbold) \& x'_3)
          E x'_2) \rightarrow (x'_2 Intersection)
          x'_3) E Mbold : prop)]) : prop)])
   {move 1}
   >>> save
   {move 2}
   >>> close
{move 1}
```

```
>>> define Lineb14 Misset thelawchooses \
    : Linea14
Lineb14 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
           ({def} x_4 E .S_2 : prop)])) =>
       (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
    (\{def\}\ Ug\ ([(H_2 : obj) =>
       (\{def\}\ Ug\ ([(J_3:obj)=>
          ({def} Ded ([(thehyp_4 : that
              (H_2 <<= Misset_1 Mbold2
             thelawchooses_1) & J_3 E H_2) =>
              (\{def\}\ Ug\ ([(K_6 : obj) =>
                 ({def} Ded ([(ktheta_7
                    : that K_6 E Sc (Sc
                    (.M_{-}1)) Set [(C_{-}10)]
                       : obj) =>
                       ({def} thetachain1
                       (.M_1, .thelaw_1, C_10) : prop)]) =>
                    (\{def\} ((H_2 <<=
                    K_6) Fixform Ug ([(P_12
                       : obj) =>
                       ({def} Ded ([(phyp_13
                          : that P_12 E H_2) =>
                          ({def} ktheta_7
                          Mp K_6 Ui phyp_13
                          Mp P_12 Ui Simp1
                          (Simp1 (thehyp_4)) Iff1
                          P_12 Ui Forall
                          ([(C_19 : obj) =>
                              ({def}) (C_19)
                             E Misset_1
                             Mbold2 thelawchooses_1) ==
                             Forall ([(D_21
```

```
: obj) =>
      ({def} (D_21
      E Sc (Sc
      (.M_1)) Set
      [(C<sub>24</sub>
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_24) : prop)]) ->
      C_19 E D_21
      : prop)]) : prop)]) Fixform
Misset_1 thetascm2
thelawchooses_1
Iff2 Sc (.M_1) Ui
Ug ([(C_22
   : obj) =>
   ({def} Dediff
   ([(hyp2_23
      : that C_22
      E Sc (Sc
      (.M_1)) Set
      [(C<sub>26</sub>
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_26) : prop)]) =>
      ({def} Simp2
      (hyp2_23
      Iff1 C_22
      Ui Sc (Sc
      (.M_1)) Separation
      [(C_27
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_27) : prop)]) : that
      thetachain1
      (.M_1, .thelaw_1, C_22)), [(hyp1_23)
      : that thetachain1
      (.M_1, .thelaw_1, C_22)) =>
```

 $({def}) (C_22$

```
E Sc (Sc
      (.M_1)) Set
      [(C_26
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_26) : prop)]) Fixform
      Simp1 (Simp2
      (hyp1_23)) Iff2
      C_22 Ui
      Scthm (Sc
      (.M_1)) Conj
      hyp1_23
      Iff2 C_22
      Ui Sc (Sc
      (.M_1)) Separation
      [(C_27
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_27) : prop): that
      C_22 E Sc
      (Sc (.M_1)) Set
      [(C_25
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_25) : prop)])]) : that
   (C_22 E Sc
   (Sc (.M_1)) Set
   [(C_25 : obj) =>
      ({def} thetachain1
      (.M_1, .thelaw_1, C_25) : prop)]) ==
   thetachain1
   (.M_1, .thelaw_1, C_22))]) Mp
(Sc (Sc (.M_1)) Set
[(C_21 : obj) =>
   ({def} thetachain1
   (.M_1, .thelaw_1, C_21) : prop)]) Intax
Sc(.M_1): that
P_{12} E K_{6}): that
```

```
(P_12 E H_2) \rightarrow
   P_12 E K_6)]) Conj
Inhabited (Simp2 (thehyp_4)) Conj
Inhabited (Simp2 (thehyp_4) Mp
Ded ([(phyp_15 : that
   J_3 E H_2) =>
   ({def} ktheta_7
   Mp K_6 Ui phyp_15
   Mp J_3 Ui Simp1 (Simp1
   (thehyp_4)) Iff1
   J_3 Ui Forall ([(C_21
      : obj) =>
      ({def} (C_21
      E Misset_1 Mbold2
      thelawchooses_1) ==
      Forall ([(D_23
         : obj) =>
         ({def}) (D_23)
         E Sc (Sc (.M_1)) Set
         [(C_26 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_26) : prop)]) ->
         C_21 E D_23
         : prop)]) : prop)]) Fixform
   Misset_1 thetascm2
   thelawchooses_1 Iff2
   Sc (.M_1) Ui Ug
   ([(C_24 : obj) =>
      ({def} Dediff
      ([(hyp2_25
         : that C_24
         E Sc (Sc (.M_1)) Set
         [(C_28 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_28) : prop)]) =>
         ({def} Simp2
         (hyp2_25 Iff1
         C_24 Ui Sc
```

```
(Sc (.M_1)) Separation
      [(C_29 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_29) : prop)]) : that
     thetachain1
      (.M_1, .thelaw_1, C_24))], [(hyp1_25
      : that thetachain1
      (.M_1, .thelaw_1, C_24)) =>
      ({def}) (C_24
     E Sc (Sc (.M_1)) Set
      [(C_28 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_28) : prop)]) Fixform
     Simp1 (Simp2
      (hyp1_25)) Iff2
     C_24 Ui Scthm
      (Sc (.M_1)) Conj
     hyp1_25 Iff2
     C_24 Ui Sc
      (Sc (.M_1)) Separation
      [(C_29 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_29) : prop)] : that
     C_24 E Sc (Sc
      (.M_1)) Set
      [(C_27 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_27) : prop)])]) : that
   (C_24 E Sc (Sc
   (.M_1)) Set
   [(C_27 : obj) =>
      ({def} thetachain1
      (.M_1, .thelaw_1, C_27) : prop)]) ==
  thetachain1 (.M_1, .thelaw_1, C_2^{-24})]) Mp
(Sc (Sc (.M_1)) Set
[(C_23 : obj) =>
   ({def} thetachain1
   (.M_1, .thelaw_1, C_23) : prop)]) Intax
```

```
Sc (.M_1) : that
   J_3 E K_6)))) Conj
Simp2 (thehyp_4) Mp
J_3 Ui H_2 Ui Simp2
(Simp2 (Simp2 (ktheta_7
Iff1 K_6 Ui Ug ([(C_16
   : obj) =>
   ({def} Dediff ([(hyp2_17
      : that C_16 E Sc
      (Sc (.M_1)) Set
      [(C_20 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_20) : prop)]) =>
      ({def} Simp2
      (hyp2_17 Iff1
      C_16 Ui Sc (Sc
      (.M_1)) Separation
      [(C_21 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop)]) : that
      thetachain1 (.M_1, .thelaw_1, C_16))], [(hyp1_17
      : that thetachain1
      (.M_1, .thelaw_1, C_16)) =>
      ({def} (C_16
      E Sc (Sc (.M_1)) Set
      [(C_20 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_20) : prop)]) Fixform
      Simp1 (Simp2
      (hyp1_17)) Iff2
      C_16 Ui Scthm
      (Sc (.M_1)) Conj
      hyp1_17 Iff2 C_16
      Ui Sc (Sc (.M_1)) Separation
      [(C_21 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop)] : that
      C_16 E Sc (Sc
```

```
(.M_1)) Set
            [(C_19 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_19) : prop)])]) : that
         (C_16 E Sc (Sc
         (.M_{-}1)) Set [(C_{-}19)]
            : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_19) : prop)]) ==
         thetachain1 (.M_1, .thelaw_1, C_16)))))) : that
      (H_2 Intersection J_3) E K_6)]) : that
   (K_6 E Sc (Sc (.M_1)) Set
   [(C_9 : obj) =>
      ({def} thetachain1
      (.M_1, .thelaw_1, C_9) : prop)]) ->
   (H_2 Intersection J_3) E K_6)]) Iff2
(H_2 Intersection J_3) Ui
Forall ([(C_8 : obj) =>
   ({def} (C_8 E Misset_1
   Mbold2 thelawchooses_1) ==
   Forall ([(D_10 : obj) =>
      ({def} (D_10 E Sc
      (Sc (.M_1)) Set
      [(C_13 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_13) : prop)]) ->
      C_8 E D_10 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
Iff2 Sc (.M_1) Ui Ug ([(C_11
   : obj) =>
   ({def} Dediff ([(hyp2_12
      : that C_11 E Sc (Sc
      (.M_1)) Set [(C_15)
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_15) : prop)]) =>
      ({def} Simp2 (hyp2_12
      Iff1 C_11 Ui Sc (Sc
```

```
(.M_1)) Separation
            [(C_16 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_16) : prop)]) : that
            thetachain1 (.M_1, .thelaw_1, C_11))], [(hyp1_12
            : that thetachain1 (.M_1, .thelaw_1, C_11)) =>
            ({def} (C_11 E Sc
            (Sc (.M_1)) Set
            [(C_15 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_15) : prop)]) Fixform
            Simp1 (Simp2 (hyp1_12)) Iff2
            C_11 Ui Scthm (Sc (.M_1)) Conj
            hyp1_12 Iff2 C_11 Ui
            Sc (Sc (.M_1)) Separation
            [(C_16 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_16) : prop): that
            C_11 E Sc (Sc (.M_1)) Set
            [(C_14 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_14) : prop)])]) : that
         (C_11 E Sc (Sc (.M_1)) Set
         [(C_14 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_14) : prop)]) ==
         thetachain1 (.M_1, .thelaw_1, C_11))]) Mp
      (Sc (Sc (.M_1)) Set [(C_10)]
         : obj) =>
         (\{def\}\ thetachain1\ (.M_1,\ .thelaw_1,\ C_10)\ :\ prop)]) Intax
      Sc (.M_1): that (H_2 Intersection)
      J_3) E Misset_1 Mbold2 thelawchooses_1)]) : that
   ((H_2 <<= Misset_1 Mbold2 thelawchooses_1) & J_3
   E H_2) -> (H_2 Intersection
   J_3) E Misset_1 Mbold2 thelawchooses_1)]) : that
Forall ([(x'_3 : obj) =>
   ({def} ((H_2 <<= Misset_1
   Mbold2 thelawchooses_1) & x'_3
```

```
E H<sub>2</sub>) -> (H<sub>2</sub> Intersection
          x'_3) E Misset_1 Mbold2 thelawchooses_1
           : prop)]))]) : that Forall
    ([(x'_2 : obj) =>
       (\{def\} Forall ([(x'_3 : obj) =>
           ({def}) ((x'_2 <<= Misset_1)
          Mbold2 thelawchooses_1) & x'_3
          E x'_2) \rightarrow (x'_2 Intersection)
          x'_3) E Misset_1 Mbold2 thelawchooses_1
           : prop)]) : prop)]))]
Lineb14 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
       Exists ([(x_4 : obj) =>
           ({def} x_4 E .S_2 : prop)])) =>
       (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
    (---: that Forall ([(x'_2: obj) =>
       (\{def\} Forall ([(x'_3 : obj) =>
           ({def}) ((x'_2 <<= Misset_1)
          Mbold2 thelawchooses_1) & x'_3
          E x'_2) \rightarrow (x'_2 Intersection)
          x'_3) E Misset_1 Mbold2 thelawchooses_1
           : prop)]) : prop)]))]
{move 0}
>>> open
   {move 2}
   >>> define Line14 : Lineb14 Misset, thelawchooses
   Line14: that Forall ([(x'_2 : obj) =>
       (\{def\} Forall ([(x'_3 : obj) =>
           (\{def\}\ ((x'_2 \lessdot Misset\ Mbold2)))
```

```
thelawchooses) & x'_3 E x'_2) \rightarrow
             (x'_2 Intersection x'_3) E Misset
             Mbold2 thelawchooses : prop)]) : prop)])
      {move 1}
end Lestrade execution
  Here is the fourth component of the proof that M is a \Theta-chain.
begin Lestrade execution
      >>> define Mboldtheta1 : Fixform (thetachain \
          (Mbold), Conj (Line1, Conj (Line4, Conj \
          (Line8, Line14))))
      Mboldtheta1: that thetachain (Mbold)
      {move 1}
      >>> close
   {move 1}
   >>> define Mboldtheta2 Misset thelawchooses \
       : Mboldtheta1
   Mboldtheta2 : [(.M_1 : obj), (Misset_1
       : that Isset (.M_1)), (.thelaw_1
       : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1
       : [(.S_2 : obj), (subsetev_2 : that
          .S_2 \ll .M_1), (inev_2 : that
          Exists ([(x_4 : obj) =>
             ({def} x_4 E .S_2 : prop))) =>
          (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
       ({def} thetachain1 (.M_1, .thelaw_1, Misset_1
       Mbold2 thelawchooses_1) Fixform Ug
```

 $([(F_5 : obj) =>$

```
({def} Ded ([(ftheta_6 : that
   F_5 E Sc (Sc (.M_1)) Set
   [(C_9 : obj) =>
      ({def} thetachain1 (.M_1, .thelaw_1, C_9) : prop)]) =>
   ({def} Simp1 (ftheta_6 Iff1
   F_5 Ui Ug ([(C_10 : obj) =>
      ({def} Dediff ([(hyp2_11
         : that C_10 E Sc (Sc (.M_1)) Set
         [(C_14 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_14) : prop)]) =>
         ({def} Simp2 (hyp2_11
         Iff1 C_10 Ui Sc (Sc (.M_1)) Separation
         [(C_15 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_15) : prop)]) : that
         thetachain1 (.M_1, .thelaw_1, C_10))], [(hyp1_11
         : that thetachain1 (.M_1, .thelaw_1, C_10)) =>
         ({def} (C_10 E Sc (Sc
         (.M_1)) Set [(C_14)
            : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_14) : prop)]) Fixform
         Simp1 (Simp2 (hyp1_11)) Iff2
         C_10 Ui Scthm (Sc (.M_1)) Conj
         hyp1_11 Iff2 C_10 Ui Sc
         (Sc (.M_1)) Separation
         [(C_15 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_15) : prop)] : that
         C_10 E Sc (Sc (.M_1)) Set
         [(C_13 : obj) =>
            ({def} thetachain1
            (.M_1, .thelaw_1, C_13) : prop)])]) : that
      (C_10 E Sc (Sc (.M_1)) Set
      [(C_13 : obj) =>
         (\{def\} thetachain1 (.M_1, .thelaw_1, C_13) : prop)]) ==
      thetachain1 (.M_1, .thelaw_1, C_10))])) : that
```

```
.M_1 E F_5)): that (F_5)
   E Sc (Sc (.M_1)) Set [(C_8
      : obj) =>
      ({def} thetachain1 (.M_1, .thelaw_1, C_8) : prop)]) ->
   .M_1 E F_5)]) Iff2 .M_1 Ui Forall
([(C_7 : obj) =>
   ({def} (C_7 E Misset_1 Mbold2
   thelawchooses_1) == Forall ([(D_9
      : obj) =>
      (\{def\}\ (D_9\ E\ Sc\ (Sc\ (.M_1))\ Set
      [(C_12 : obj) =>
         ({def} thetachain1 (.M_1, .thelaw_1, C_12) : prop)]) ->
      C_7 E D_9 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
Iff2 Sc (.M_1) Ui Ug ([(C_10 : obj) =>
   ({def} Dediff ([(hyp2_11 : that
      C_10 E Sc (Sc (.M_1)) Set
      [(C_14 : obj) =>
         (\{def\} thetachain1 (.M_1, .thelaw_1, C_14) : prop)]) =>
      ({def} Simp2 (hyp2_11 Iff1
      C_10 Ui Sc (Sc (.M_1)) Separation
      [(C_15 : obj) =>
         (\{def\}\ thetachain1\ (.M_1, .thelaw_1, C_15): prop)]): that
      thetachain1 (.M_1, .thelaw_1, C_10))], [(hyp1_11
      : that thetachain1 (.M_1, .thelaw_1, C_10)) =>
      ({def}) (C_10 E Sc (Sc (.M_1)) Set
      [(C_14 : obj) =>
         ({def} thetachain1 (.M_1, .thelaw_1, C_14) : prop)]) Fixform
      Simp1 (Simp2 (hyp1_11)) Iff2
      C_10 Ui Scthm (Sc (.M_1)) Conj
      hyp1_11 Iff2 C_10 Ui Sc (Sc
      (.M_1)) Separation [(C_15)
         : obj) =>
         (\{def\}\ thetachain1\ (.M_1, .thelaw_1, C_15): prop)]: that
      C_10 E Sc (Sc (.M_1)) Set
      [(C_13 : obj) =>
         ({def} thetachain1 (.M_1, .thelaw_1, C_13) : prop)])]) : that
```

 $(C_10 E Sc (Sc (.M_1)) Set$

```
[(C_13 : obj) =>
      (\{def\} thetachain1 (.M_1, .thelaw_1, C_13) : prop)]) ==
   thetachain1 (.M_1, .thelaw_1, C_10))]) Mp
(Sc (Sc (.M_1)) Set [(C_9 : obj) =>
   ({def} thetachain1 (.M_1, .thelaw_1, C_9) : prop)]) Intax
Sc (.M_1) Conj ((Misset_1 Mbold2
thelawchooses_1 <<= Sc (.M_1)) Fixform</pre>
Ug ([(A_7 : obj) =>
   ({def} Ded ([(ainev_8 : that
      A_7 E Misset_1 Mbold2 thelawchooses_1) =>
      ({def} Misset_1 thetascm2 thelawchooses_1
      Iff2 Sc (.M_1) Ui Ug ([(C_12
         : obj) =>
         ({def} Dediff ([(hyp2_13
            : that C_12 \to Sc (Sc (.M_1)) \to Set
            [(C_16 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_16) : prop)]) =>
            ({def} Simp2 (hyp2_13
            Iff1 C_12 Ui Sc (Sc (.M_1)) Separation
            [(C_17 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_17) : prop)]) : that
            thetachain1 (.M_1, .thelaw_1, C_12))], [(hyp1_13
            : that thetachain1 (.M_1, .thelaw_1, C_12)) =>
            ({def} (C_12 E Sc (Sc
            (.M_{1}) Set [(C_{1}6)
               : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_16) : prop)]) Fixform
            Simp1 (Simp2 (hyp1_13)) Iff2
            C_12 Ui Scthm (Sc (.M_1)) Conj
            hyp1_13 Iff2 C_12 Ui Sc
            (Sc (.M_1)) Separation
            [(C_17 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_17) : prop): that
            C_12 E Sc (Sc (.M_1)) Set
```

```
[(C_15 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_15) : prop)])]) : that
   (C_12 E Sc (Sc (.M_1)) Set
   [(C_15 : obj) =>
      (\{def\} thetachain1 (.M_1, .thelaw_1, C_15) : prop)]) ==
   thetachain1 (.M_1, .thelaw_1, C_12))]) Mp
Sc (.M_1) Ui ainev_8 Iff1 A_7
Ui Forall ([(C_14 : obj) =>
   ({def} (C_14 E Misset_1
   Mbold2 thelawchooses_1) ==
   Forall ([(D_16 : obj) =>
      (\{def\}\ (D_16\ E\ Sc\ (Sc
      (.M_1)) Set [(C_19)
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_19) : prop)]) ->
      C_14 E D_16 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
Iff2 Sc (.M_1) Ui Ug ([(C_17
   : obj) =>
   ({def} Dediff ([(hyp2_18
      : that C_17 \to Sc (Sc (.M_1)) \to Set
      [(C_21 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop)]) =>
      ({def} Simp2 (hyp2_18
      Iff1 C_17 Ui Sc (Sc (.M_1)) Separation
      [(C_22 : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_22) : prop)]) : that
      thetachain1 (.M_1, .thelaw_1, C_17))], [(hyp1_18
      : that thetachain1 (.M_1, .thelaw_1, C_17)) =>
      ({def} (C_17 E Sc (Sc
      (.M_1)) Set [(C_21)
         : obj) =>
         ({def} thetachain1
         (.M_1, .thelaw_1, C_21) : prop)]) Fixform
```

```
Simp1 (Simp2 (hyp1_18)) Iff2
            C_17 Ui Scthm (Sc (.M_1)) Conj
            hyp1_18 Iff2 C_17 Ui Sc
            (Sc (.M_1)) Separation
            [(C_22 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_22) : prop)] : that
            C_17 E Sc (Sc (.M_1)) Set
            [(C_20 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_20) : prop)])]) : that
         (C_17 E Sc (Sc (.M_1)) Set
         [(C_20 : obj) =>
            (\{def\} thetachain1 (.M_1, .thelaw_1, C_20) : prop)]) ==
         thetachain1 (.M_1, .thelaw_1, C_17))]) Mp
      (Sc (Sc (.M_1)) Set [(C_16
         : obj) =>
         ({def} thetachain1 (.M_1, .thelaw_1, C_16) : prop)]) Intax
      Sc (.M_1) : that A_7 E Sc (.M_1))]) : that
   (A_7 E Misset_1 Mbold2 thelawchooses_1) ->
  A_7 E Sc (.M_1))]) Conj Inhabited
(Ug ([(F_10 : obj) =>
   ({def} Ded ([(ftheta_11 : that
     F_10 E Sc (Sc (.M_1)) Set
      [(C_14 : obj) =>
         (\{def\} thetachain1 (.M_1, .thelaw_1, C_14) : prop)]) =>
      ({def} Simp1 (ftheta_11 Iff1
      F_10 Ui Ug ([(C_15 : obj) =>
         ({def} Dediff ([(hyp2_16
            : that C_15 \to Sc (Sc (.M_1)) \to Set
            [(C_19 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_19) : prop)]) =>
            ({def} Simp2 (hyp2_16
            Iff1 C_15 Ui Sc (Sc (.M_1)) Separation
            [(C_20 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_20) : prop)]) : that
```

```
thetachain1 (.M_1, .thelaw_1, C_15))], [(hyp1_16
            : that thetachain1 (.M_1, .thelaw_1, C_15)) =>
            ({def} (C_15 E Sc (Sc
            (.M_1)) Set [(C_19)
               : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_19) : prop)]) Fixform
            Simp1 (Simp2 (hyp1_16)) Iff2
            C_15 Ui Scthm (Sc (.M_1)) Conj
            hyp1_16 Iff2 C_15 Ui Sc
            (Sc (.M_1)) Separation
            [(C_20 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_20) : prop): that
            C_15 E Sc (Sc (.M_1)) Set
            [(C_18 : obj) =>
               ({def} thetachain1
               (.M_1, .thelaw_1, C_18) : prop)])]) : that
         (C_{15} E Sc (Sc (.M_{1})) Set
         [(C_18 : obj) =>
            (\{def\} thetachain1 (.M_1, .thelaw_1, C_18) : prop)]) ==
         thetachain1 (.M_1, .thelaw_1, C_15))])) : that
      .M_1 E F_{10}) : that (F_{10}
   E Sc (Sc (.M_1)) Set [(C_13
      : obj) =>
      ({def} thetachain1 (.M_1, .thelaw_1, C_13) : prop)]) ->
   .M_1 \to F_{10}) Iff2 .M_1 \to F_{10}
([(C_12 : obj) =>
   ({def} (C_12 E Misset_1 Mbold2
   thelawchooses_1) == Forall ([(D_14
      : obj) =>
      ({def}) (D_14 E Sc (Sc (.M_1)) Set
      [(C_17 : obj) =>
         (\{def\} thetachain1 (.M_1, .thelaw_1, C_17) : prop)]) \rightarrow
      C_12 E D_14 : prop)]) : prop)]) Fixform
Misset_1 thetascm2 thelawchooses_1
Iff2 Sc (.M_1) Ui Ug ((C_15 : obj) =>
   ({def} Dediff ([(hyp2_16 : that
```

```
[(C_19 : obj) =>
             (\{def\} thetachain1 (.M_1, .thelaw_1, C_19) : prop)]) =>
          ({def} Simp2 (hyp2_16 Iff1
          C_15 Ui Sc (Sc (.M_1)) Separation
          [(C_20 : obj) =>
             ({def} thetachain1 (.M_1, .thelaw_1, C_20) : prop)]) : that
          thetachain1 (.M_1, .thelaw_1, C_15))], [(hyp1_16
          : that thetachain1 (.M_1, .thelaw_1, C_15)) =>
          ({def}) (C_15 E Sc (Sc (.M_1)) Set
          [(C_19 : obj) =>
             ({def} thetachain1 (.M_1, .thelaw_1, C_19) : prop)]) Fixform
          Simp1 (Simp2 (hyp1_16)) Iff2
          C_15 Ui Scthm (Sc (.M_1)) Conj
          hyp1_16 Iff2 C_15 Ui Sc (Sc
          (.M_1)) Separation [(C_20
             : obj) =>
             (\{def\}\ thetachain1\ (.M_1, .thelaw_1, C_20): prop)]: that
          C_{15} E Sc (Sc (.M_1)) Set
          [(C_18 : obj) =>
             ({def} thetachain1 (.M_1, .thelaw_1, C_18) : prop)])]) : that
       (C_15 E Sc (Sc (.M_1)) Set
       [(C_18 : obj) =>
          (\{def\} thetachain1 (.M_1, .thelaw_1, C_18) : prop)]) ==
       thetachain1 (.M_1, .thelaw_1, C_15))]) Mp
    (Sc (Sc (.M_1)) Set [(C_14 : obj) =>
       ({def} thetachain1 (.M_1, .thelaw_1, C_14) : prop)]) Intax
    Sc (.M_1)) Conj Sc2 (.M_1)) Conj
    Misset_1 Lineb8 thelawchooses_1 Conj
    Misset_1 Lineb14 thelawchooses_1 : that
    thetachain1 (.M_1, .thelaw_1, Misset_1
    Mbold2 thelawchooses_1))]
Mboldtheta2 : [(.M_1 : obj), (Misset_1
    : that Isset (.M_1)), (.thelaw_1)
    : [(S_2 : obj) \Rightarrow (--- : obj)]), (thelawchooses_1)
    : [(.S_2 : obj), (subsetev_2 : that
       .S_2 \ll .M_1), (inev_2 : that
```

C_15 E Sc (Sc (.M_1)) Set

```
Exists ([(x_4 : obj) =>
             ({def} x_4 E .S_2 : prop)])) =>
          (--- : that .thelaw_1 (.S_2) E .S_2)]) =>
       (---: that thetachain1 (.M_1, .thelaw_1, Misset_1
       Mbold2 thelawchooses_1))]
   {move 0}
   >>> open
      {move 2}
      >>> define Mboldtheta : Mboldtheta2 \
          Misset, thelawchooses
      Mboldtheta : that thetachain1 (M, [(S'_2)]
          : obj) =>
          ({def} \ thelaw (S'_2) : obj)], Misset
       Mbold2 thelawchooses)
      {move 1}
end Lestrade execution
```