Robert Ackerman April 18, 2016

#### **APIMPowerR Documentation**

APIMPowerR (available at <a href="https://robert-a-ackerman.shinyapps.io/APIMPowerRdis/">https://robert-a-ackerman.shinyapps.io/APIMPowerRdis/</a>) estimates power for the Actor-Partner Interdependence Model (APIM) with indistinguishable or distinguishable dyads. Power can be determined for a given sample size or sample size can be determined given a desired level of power.

Although great effort has been undertaken to ensure the accuracy of results, no complete guarantee can be made about their accuracy. It is your responsibility to check the results for accuracy. Should the user notice any problems with the program, he or she should notify Robert Ackerman at <a href="mailto:real10030@utdallas.edu">real10030@utdallas.edu</a>.


#### **Table of Contents**

1.	Input F	Panel and Output Panel3
2.	Task T	ab from Input Panel4
	a.	Task Tab when Dyad Type is Indistinguishable4
	b.	Task Tab when Dyad Type is Distinguishable4
3.	Effect	Size Tab from Input Panel5
	a.	Effect Size Tab5
4.	Miscel	laneous Tab from Input Panel6
	a.	Miscellaneous Tab when Dyad Type is Indistinguishable and Effect Size Measure is Beta or partial r6
	b.	Miscellaneous Tab when Dyad Type is Indistinguishable and Effect Size Measure is Cohen's d6
	C.	Miscellaneous Tab when Dyad Type is Distinguishable and Effect Size Measure is Beta or partial r7
	d.	Miscellaneous Tab when Dyad Type is Distinguishable and Effect Size Measure is Cohen's d
5.	Study	Information Tab from Input Panel9
	a.	Study Information Tab when Dyad Type is Indistinguishable and Task is to Compute Power Given N9
	b.	Study Information Tab when Dyad Type is Indistinguishable and Task is to  Determine Sample Size Given Desired Level of Power11
	C.	Study Information Tab when Dyad Type is Distinguishable and Task is to Compute Power Given N

	d.	Study Information Tab when Dyad Type is Distinguishable and Task is to Determine Sample Size Given Desired Level of Power
6.	Model	Figure from Output Panel16
	a.	Model Figure when Dyad Type is Indistinguishable16
	b.	Model Figure when Dyad Type is Distinguishable16
7.	Power	Estimates Tab from Output Panel17
	a.	Power Estimates Tab when Dyad Type is Indistinguishable and Task is to Compute Power Given N
	b.	Power Estimates Tab when Dyad Type is Indistinguishable and Task is to Determine Sample Size Given Desired Level of Power
	C.	Power Estimates Tab when Dyad Type is Distinguishable and Task is to Compute  Power Given N
	d.	Power Estimates Tab when Dyad Type is Distinguishable and Task is to Determine Sample Size Given Desired Level of Power

### (Note that some screen shots differ a bit due to program revision.)

#### Input Panel and Output Panel for APIMPowerR



The app consists of an input panel to the left and an output panel to the right. The input panel contains four green tabs (i.e., Task, Effect Size, Miscellaneous, and Study Information) that permit the user to specify different features of the analysis (e.g., alpha level, effect size measure). To facilitate the specification of different parameters in the Study Information tab (e.g., Correlation of the Errors), a depiction of the Actor-Partner Interdependence Model with the corresponding parameters labeled is provided in the purple Model Figure tab in the output panel. The user is advised to click the four green tabs sequentially and choose the appropriate options. Once the analysis is completed, results are presented in the purple Power Estimates tab in the output panel.

### **Task Tab from Input Panel**

### Task Tab when Dyad Type is Indistinguishable




**Task:** This tab enables users to specify the type of analysis they would like to conduct as well as the dyad type with which they are working.

**Compute:** Users are provided two options:

- a) Power Given N (i.e., determine the levels of power available to detect the actor and partner effects given a particular sample size and alpha), or
- b) N Given Desired Power (i.e., determine the minimum sample sizes necessary to detect the actor and partner effects given a desired level of power and alpha).

**Dyad Type:** Users can specify whether their design entails indistinguishable dyads (i.e., dyad members that cannot be meaningfully differentiated by a categorical variable that only varies within dyads; for instance, same-sex roommates) or distinguishable dyads (i.e., dyad members that can be meaningfully differentiated by a categorical variable that only varies within dyads; for instance, gender in heterosexual dating relationships).

### Task Tab When Dyad Type Is Distinguishable



If users choose distinguishable dyads, they are given the option to provide labels for 'Person 1' and 'Person 2' (e.g., Man and Woman or Supervisor and Subordinate) so that these can be used as labels for other inputs and outputs in the program.

### **Effect Size Tab from Input Panel**

#### **Effect Size Tab**




Effect Size: This tab is used to specify the effect size measure to be used in the power analysis.

**Effect Size Measure:** Users can specify their effect size measure to be the standardized regression coefficient (i.e., Beta), Cohen's d (i.e., d), or partial r. The program defaults to using Beta as the effect size measure.

If Cohen's *d* or partial *r* is chosen by the user, the program converts the value for the effect size measure to the corresponding Beta value before conducting the power analysis.

### Miscellaneous Tab from Input Panel

Miscellaneous Tab when Dyad Type is Indistinguishable and Effect Size Measure is Beta or partial r



Miscellaneous: This tab is used to specify the desired Type I Error Rate (i.e., alpha).

**Alpha:** Users specify their desired Type I Error Rate here. The program defaults to .05, two-sided.

Miscellaneous Tab When Dyad Type Is Indistinguishable and Effect Size Measure Is Cohen's d




**Miscellaneous:** This tab is used to specify the desired Type I Error Rate (i.e., alpha) and the proportion of participants in Category 1 of the X variable.

**Alpha:** Users specify their desired Type I Error Rate here. The program defaults to .05, two-sided.

**Proportion of Subjects in Category 1:** Users specify the proportion of participants that are in Category 1 of the X variable (which is assumed to be a dichotomy) here. The program defaults to .50. Note if the user expects an 80/20 split, one can put .8 or .2 in this box.

# Miscellaneous Tab When Dyad Type Is Distinguishable and Effect Size Measure Is Beta or Partial r




**Miscellaneous:** This tab is used to specify the desired Type I Error Rate (i.e., alpha) and the Ratios of Variances between the dyad members.

**Alpha:** Users specify their desired Type I Error Rate here. The program defaults to .05, two-sided.

Ratio of Person 2 Predictor Variance to Person 1 Predictor Variance: Users specify how much bigger (or smaller) the variance in the predictor is for Person 1 compared to Person 2 in the form of a ratio here. The program defaults to 1 (i.e., assumes the variances are equal).

Ratio of Person 2 Error Variance to Person 1 Error Variance: Users specify how much bigger (or smaller) the error variance is for Person 1 compared to Person 2 in the form of a ratio here. The program defaults to 1 (i.e., assumes the variances are equal in size).

#### Miscellaneous Tab when Dyad Type Is Distinguishable and Effect Size Measure Is Cohen's d



**Miscellaneous:** This tab is used to specify the desired Type I Error Rate (i.e., alpha), the Ratios of Variances between the dyad members, and the Proportion of Participants in Category 1 of the X variable.

**Alpha:** Users specify their desired Type I Error Rate here. The program defaults to .05, two-sided.


Ratio of Person 2 Error Variance to Person 1 Error Variance: Users specify how much bigger (or smaller) the error variance is for Person 1 compared to Person 2 in the form of a ratio here. The program defaults to 1 (i.e., assumes the variances are equal in size).

**Proportion of Person 1 Subjects in Category 1:** When users choose *d* as the Effect Size Measure, the X variable is assumed to be a dichotomy. As such, users can specify the proportion of Person 1 participants that are in Category 1 of the X variable here. The program defaults to .50.

**Proportion of Person 2 Subjects in Category 1:** When users choose *d* as the Effect Size Measure, the X variable is assumed to be a dichotomy. As such, users can specify the proportion of Person 2 participants that are in Category 1 of the X variable here. The program defaults to .50.

#### **Study Information Tab from Input Panel**

Study Information Tab when Dyad Type is Indistinguishable and Task is to Compute Power Given N



**Study Information:** This tab is used to specify the primary effect size values for the analysis and the given sample size.

**Effect Size Value of the Actor Effect:** Users specify the effect size value for the actor effect here. The program defaults to .25. Note if *d* or *r* is chosen earlier, the effect size is for that measure.

Effect Size Value of the Partner Effect: Users specify the effect size value for the partner effect here. The program defaults to .15.


**Correlation of the Actor and Partner Variables:** Users specify the value of the correlation between the two dyad members' predictor variables here. The program defaults to .30.

**Correlation of the Errors:** Users specify the value of the correlation between the two dyad members' residuals here. The program defaults to .30.

**Number of Dyads with Complete Data (at least 10):** Users specify the number of dyads with complete data here (i.e., dyads for which both members supply data). The program defaults to 100.

**Number of Singles (if non-zero, at least 5):** Users specify the number of singles here (i.e., dyads for which only one of the members supply data). The program defaults to 0.

# Study Information Tab When Dyad Type Is Indistinguishable and Task Is to Determine N Given Desired Level of Power



**Study Information:** This tab is used to specify the primary effect size values for the analysis and the desired level of power.

**Desired Power:** Users specify their desired level of power here. The program defaults to .80. The value should be larger than alpha and less than one.


**Effect Size Value of the Actor Effect:** Users specify the effect size value for the actor effect here. The program defaults to .25.

**Effect Size Value of the Partner Effect:** Users specify the effect size value for the partner effect here. The program defaults to .15.

**Correlation of the Actor and Partner Variables:** Users specify the value of the correlation between the two dyad members' predictor variables here. The program defaults to .30.

**Correlation of the Errors:** Users specify the value of the correlation between the two dyad members' residuals here. The program defaults to .30.

## Study Information Tab When Dyad Type Is Distinguishable and Task Is to Compute Power Given N



**Study Information:** This tab is used to specify the effect size values for the power analysis and the given sample size.

Effect Size Value of the Actor Effect for Person 1: Users specify the effect size value for the actor effect for Person 1 here. The program defaults to .25.

Effect Size Value of the Actor Effect for Person 2: Users specify the effect size value for the actor effect for Person 2 here. The program defaults to .25.

Effect Size Value of the Partner Effect for Person 1: Users specify the effect size value for the partner effect for Person 1 here. The program defaults to .15.

Effect Size Value of the Partner Effect for Person 2: Users specify the effect size value for the partner effect for Person 2 here. The program defaults to .15.

**Correlation of the Actor and Partner Variables:** Users specify the value of the correlation between the two dyad members' predictor variables here. The program defaults to .30.


**Correlation of the Errors:** Users specify the value of the correlation between the two dyad members' residuals here. The program defaults to .30.

**Number of Dyads with Complete Data (at least 10):** Users specify the number of dyads with complete data here (i.e., dyads for which both members supply data). The program defaults to 100.

**Number of Person 1 Singles:** Users specify the number of Person 1 singles here (i.e., dyads for which only Person 1 supplies data). The program defaults to 0.

**Number of Person 2 Singles:** Users specify the number of Person 2 singles here (i.e., dyads for which only Person 2 supplies data). The program defaults to 0.

# Study Information Tab When Dyad Type Is Distinguishable and Task Is to Determine Sample Size Given a Desired Level of Power



**Study Information:** This tab is used to specify the primary effect size values for the analysis and the desired level of power.

**Desired Power:** Users specify their desired level of power here. The program defaults to .80. The value should be larger than alpha and less than one.

Effect Size Value of the Actor Effect for Person 1: Users specify the effect size value for the actor effect for Person 1 here. The program defaults to .25.

Effect Size Value of the Actor Effect for Person 2: Users specify the effect size value for the actor effect for Person 2 here. The program defaults to .25.

Effect Size Value of the Partner Effect for Person 1: Users specify the effect size value for the partner effect for Person 1 here. The program defaults to .15.

Effect Size Value of the Partner Effect for Person 2: Users specify the effect size value for the partner effect for Person 2 here. The program defaults to .15.


**Correlation of the Actor and Partner Variables:** Users specify the value of the correlation between the two dyad members' predictor variables here. The program defaults to .30.

**Correlation of the Errors:** Users specify the value of the correlation between the two dyad members' residuals here. The program defaults to .30.

### **Model Figure from Output Panel**

### Model Figure When Dyad Type is Indistinguishable






**Model Figure:** When users choose "indistinguishable" as their Dyad Type, the APIM with Indistinguishable Dyads is displayed.

### Model Figure when Dyad Type is Distinguishable



### **APIM with Distinguishable Dyads**



**Model Figure:** When users choose 'Distinguishable' as their Dyad Type, the APIM with Distinguishable Dyads is displayed. In addition, if the labels for 'Person 1' and 'Person 2' are modified, those changes are reflected in the figure.

#### **Power Estimates Tab from Output Panel**

# Power Estimates Tab When Dyad Type Is Indistinguishable and Task Is to Compute Power Given N

Model	Figu	re	Powe	er Est	Estimates  Beta r partial r ncp		
	Size	Powe	r N	Beta	r	partial r	пср
Actor	.250	.959	100	.250	.295	.245	3.714
Partner	.150	.602	100	.150	.225	.150	2.229

The task is to determine the levels of power available to detect the actor and partner effects for an Actor-Partner Interdependence Model analysis with indistinguishable dyads given a particular sample size and alpha.

Alpha is set to .050. N refers to the number of dyads. There are 100 dyads (and 0 singles).

The measure of effect size is beta, the standardized regression coefficient. The correlation between the two members' scores on X is .300, and the correlation of the errors is .300. The term "ncp" is the non-centrality parameter or the regression coefficient divided by its standard error.

There is .959 power to detect an actor effect of size .250 (i.e., a beta of .250 or a partial r of .245).

There is .602 power to detect a partner effect of size .150 (i.e., a beta of .150 or a partial r of .150).

**Power Estimates:** This tab provides users with the results of the analysis (i.e., the power available to detect the actor and partner effects).

**Table:** The 'Size' column contains the effect size value that was specified on the Study Information tab of the Input Panel. The 'Power' column contains the estimated level of power available to detect the effect. The term "N" refers to the number of complete dyads that were specified on the Study Information tab of the Input Panel (note: if 'Singles' is specified to be greater than 0, this would be reflected in an additional column in the table). The 'Beta' column contains the size of the effect in terms of the standardized regression coefficient. The 'r' column contains the zero-order correlation coefficient for the effect. The 'partial r' column contains the size of the effect in terms of the partial correlation coefficient. The 'ncp' column contains the non-centrality parameter for the effect.

# Power Estimates Tab When Dyad Type Is Indistinguishable and Task Is to Determine Sample Size Given Desired Level of Power

Model	Figu	re l	Powe	er Estim					
	Size	Power	N	df	Beta	r	partial r	ncp	
Actor	.250	.803	59	114.97	.250	.295	.245	4.697	
Partner	.150	.802	159	314.99	.150	.225	.150	2.818	

The task is to determine the minimum sample sizes necessary to detect the actor and partner effects for an Actor-Partner interdependence Model analysis with indistinguishable dyads given a desired level of power and alpha.

Alpha is set to .050. N refers to the number of dyads. The N given is the smallest number of dyads required to detect the effect when power is at least 0.8.

The measure of effect size is beta, the standardized regression coefficient. The correlation between the two members' scores on X is .300, and the correlation of the errors is .300. The term "ncp" is the non-centrality parameter or the regression coefficient divided by its standard error.

At minimum, 59 dyads are needed to have adequate power to detect an actor effect of size .250 (i.e., a beta of .250 or a partial r of .245).

At minimum, 159 dyads are needed to have adequate power to detect a partner effect of size .150 (i.e., a beta of .150 or a partial r of .150).

**Power Estimates:** This tab provides users with the results of the analysis (i.e., the minimum number of dyads needed to have adequate power to detect the actor and partner effects)

**Table:** The 'Size' column contains the effect size value that was specified on the Study Information tab of the Input Panel. The 'Power' column contains the desired level of power to detect the effect. N refers to the minimum number of complete dyads that are needed to detect the effect with the desired power. Note the N is almost certainly a different value for actor and partner. The 'df' column contains the degrees of freedom associated with the minimum number of dyads needed to detect the effect with adequate power. The 'Beta' column contains the size of the effect in terms of the standardized regression coefficient. The 'r' column contains the zero-order correlation coefficient for the effect. The 'partial r' column contains the size of the effect in terms of the partial correlation coefficient. The 'ncp' column contains the non-centrality parameter for the effect.

### Power Estimates Tab when Dyad Type Is Distinguishable and Task Is to Compute Power Given N

Model Figure	Power Esti	mates							
		Effect	Power	N	df	Beta	r	partial r	ncp
Actor Effect	for Person 1	.250	.692	100	97	.250	.295	.245	2.486
Actor Effect	for Person 2	.250	.692	100	97	.250	.295	.245	2.486
Partner Effect	for Person 1	.150	.315	100	97	.150	.225	.150	1.492
Partner Effect	for Person 2	.150	.315	100	97	.150	.225	.150	1.492
Difference in .	Actor Effects	.000	.050	100					0.000
Difference in Pa	rtner Effects	.000	.050	100					0.000
The task is to determine the levels of power available to detect the actor and partner effects for an distinguishable dyads given a particular sample size and alpha.  Alpha is set to .050. N refers to the number of dyads. There are 100 dyads (and 0 Person 1 singles)  The measure of effect size is beta, the standardized regression coefficient. The correlation between of the errors is .300. The term "ncp" is the non-centrality parameter or the regression coefficient div									
There is .692 power to detect an actor effect for Person 1 of size .250 (i.e., a beta of .250 or a partial r of .245).									
There is .692 power t	o detect an actor	effect fo	r Persor	2 of	size	.250 (i.	e., a b	eta of .250	or a p
There is .315 power to	o detect a partne	r effect f	or Perso	n 1 of	size	: .150 (	i.e., a	beta of .15	i0 or a p

**Power Estimates:** This tab provides users with the results of the analysis (i.e., the power to detect the actor and partner effects for persons 1 and 2, as well as the difference in the actor effects and the difference in the partner effects).

There is .315 power to detect a partner effect for Person 2 of size .150 (i.e., a beta of .150 or a partial r of .150).

Table: The 'Effect' column contains the effect size value that was specified on the Study Information tab of the Input Panel. The 'Power' column contains the level of power available to detect the effect. N refers to the number of complete dyads that were specified on the Study Information tab of the Input Panel (note: if 'Singles' is specified to be greater than 0, this would be reflected in an additional column in the table). The 'df' column contains the degrees of freedom associated with the number of dyads (and/or singles) specified in the Study Information tab from the Input Panel. The 'Beta' column contains the size of the effect in terms of the standardized regression coefficient. The 'r' column contains the zero-order correlation coefficient for the effect. The 'partial r' column contains the size of the effect in terms of the partial correlation coefficient. (If Cohen's d is chosen as the Effect Size Measure, an additional column for the effect size value for d will be reflected in the table). The 'ncp' column contains the non-centrality parameter for the effect.

### Power Estimates Tab when Dyad Type is Distinguishable and Task is to Determine Sample Size Given Desired Level of Power

M	odel Figure	Power Esti	mates							
			Effect	Power	N	df	Beta	r	partial r	ncp
	Actor Effect	for Person 1	.250	.803	129	126	.250	.295	.245	2.834
	Actor Effect	for Person 2	.250	.803	129	126	.250	.295	.245	2.834
P	artner Effect	for Person 1	.150	.801	348	345	.150	.225	.150	2.813
P	artner Effect	for Person 2	.150	.801	348	345	.150	.225	.150	2.813
D	ifference in A	Actor Effects	.000	.05	0					0.000
Dif	ference in Par	tner Effects	.000	.05	0					0.000

The task is to determine the minimum sample sizes necessary to detect the actor and partner effects for an Actor-Partner Interdependence Model analysis with distinguishable dyads given a desired level of power and alpha.

Alpha is set to .050. N refers to the number of dyads. The N given is the smallest number of dyads required to detect the effect when power is at least 0.8.

The measure of effect size is beta, the standardized regression coefficient. The correlation between the two members' scores on X is .300, and the correlation of the errors is .300. The term "ncp" is the non-centrality parameter or the regression coefficient divided by its standard error.

At minimum, 129 dyads are needed to have adequate power to detect an actor effect for Person 1 of size .250 (i.e., a beta of .250 or a partial r of .245).

At minimum, 129 dyads are needed to have adequate power to detect an actor effect for Person 2 of size .250 (i.e., a beta of .250 or a partial r of .245).

At minimum, 348 dyads are needed to have adequate power to detect a partner effect for Person 1 of size .150 (i.e., a beta of .150 or a partial r of .150).

At minimum, 348 dyads are needed to have adequate power to detect a partner effect for Person 2 of size .150 (i.e., a beta of .150 or a partial r of .150).

**Power Estimates:** This tab provides users with the results of the analysis (i.e., the minimum number of dyads needed to have adequate power to detect the actor and partner effects for persons 1 and 2, as well as the difference in the actor effects and the difference in the partner effects)

Table: The 'Effect' column contains the effect size value that was specified on the Study Information tab of the Input Panel. The 'Power' column contains the level of power available to detect the effect. N refers to the minimum number of complete dyads that are needed to detect the effect with adequate power. The 'df' column contains the degrees of freedom associated with the minimum number of dyads needed to detect the effect with adequate power. The 'Beta' column contains the size of the effect in terms of the standardized regression coefficient. The 'r' column contains the zero-order correlation coefficient for the effect. The 'partial r' column contains the size of the effect in terms of the partial correlation coefficient. The 'ncp' column contains the non-centrality parameter for the effect.