

D - No-Subsequence Substring

分值: 400 分

Problem Statement

You are given strings S and T consisting of lowercase English letters.

给定由小写英文字母组成的字符串 S 和 T 。

Among the non-empty substrings s of S , count those that do **not** contain T as a (not necessarily contiguous) subsequence.

统计 S 的所有非空子串 s 中, **不包含** T 作为 (不一定连续的) 子序列的数量。

Here, two substrings of S are distinguished if they are taken from different positions, even if they are equal as strings.

这里, 只要两个子串在 S 中的位置不同, 即使它们的字符串内容相同, 也视为不同的子串。

What is a substring?

什么是子串?

A substring of a string X is a string obtained by deleting zero or more characters from the beginning and zero or more characters from the end of X .

字符串 X 的子串是指从 X 的开头删除零个或多个字符, 再从末尾删除零个或多个字符后得到的字符串。

What is a subsequence?

什么是子序列?

A subsequence of a string X is a string obtained by deleting zero or more elements from X and arranging the remaining elements in their original order.

字符串 X 的子序列是指从 X 中删除零个或多个元素, 并将剩余元素保持原有顺序排列后得到的字符串。

Constraints

- S is a string consisting of lowercase English letters.
 - $1 \leq |S| \leq 2 \times 10^5$, where $|S|$ is the length of S .
 - T is a string consisting of lowercase English letters.
 - $1 \leq |T| \leq 50$, where $|T|$ is the length of T .
 - S 是由小写英文字母组成的字符串。
 - $1 \leq |S| \leq 2 \times 10^5$, 其中 $|S|$ 是 S 的长度。
 - T 是由小写英文字母组成的字符串。
 - $1 \leq |T| \leq 50$, 其中 $|T|$ 是 T 的长度。
-

Input

The input is given from Standard Input in the following format:

输入按照以下格式从标准输入给出：

S
 T

Output

Output the answer.

输出答案。

Sample Input 1

```
abrakadabra  
aba
```

Sample Output 1

```
51
```

For example, the substring `abr` consisting of the first through third characters of S does not contain T as a subsequence. Including this, there are 51 substrings satisfying the condition, such as `k` (only the fifth character of S) and `akada` (the fourth through eighth characters of S).

例如，由 S 的第 1 到第 3 个字符组成的子串 `abr` 不包含 T 作为子序列。包括这个子串在内，共有 51 个满足条件的子串，例如 `k`（仅 S 的第 5 个字符）和 `akada`（ S 的第 4 到第 8 个字符）。

Note that the string `abr` can be obtained both as the substring from the first to third characters of S and as the substring from the eighth to tenth characters of S , but they are taken from different positions, so they are counted separately.

注意，字符串 `abr` 既可以作为 S 第 1 到第 3 个字符的子串得到，也可以作为 S 第 8 到第 10 个字符的子串得到，但由于它们的位置不同，所以会被分别计数。

Sample Input 2

```
aaaaa
a
```

Sample Output 2

```
0
```

All non-empty substrings of S contain T as a subsequence.

S 的所有非空子串都包含 T 作为子序列。

Thus, there are no substrings satisfying the condition, so output 0.

因此没有满足条件的子串，输出 0。

Sample Input 3

```
rddrdtdcdrrdcredctdordoeecrotet
dcre
```

Sample Output 3

263

