

10.4	JOTUN PAINTING or Equivalent		
10.4.1	For interior Areas(walls, exposed beams, columns, shear walls and RC ceiling) : Three coats of approved quality acrylic emulsion Matt finish. Painting System: Initial Coat (s): One coat of PVA Primer acrylic co-polymer emulsion. Finishing Coat (s): Two coats of acrylic copolymer emulsion as per ISO 3233, VOC <10 gms/ltr as per ISO 11890 EU, Matt finish with the following properties: Performance Properties: 1) Low VOC Emission as per CDPH IAQ Version 1.1 or 1.2 2) Washability or Scrub Resistance of 5000 passes as per DIN 53778 3) Surface Burning Characteristics of Class A as per ASTM E 84	m ²	235.00
10.4.2	For External Concrete, Plastered Surfaces JOTUN texotile system Paint System: Initial Coat (s): One coat water based acrylic co-polymer-based alkali resistant primer/sealer, vol. solids 37± 2% as per ISO 3233: 1998 (E) referred as Jotashield Alkali Resistance Primer. Intermediate Coat: Exterior emulsion based on acrylic copolymer emulsion with Volume Solid 62 ± 2 %. VOC as per ISO 11890 EU referred as Texo Compound. Finishing Coat (s): Two coats of pure acrylic emulsion with Vol. Solids: 35% ± 2 %. solids, referred to as" Jotashield Eterna a High Quality Pure acrylic exterior topcoat with anti-dust technology as per SS 500:2002, washability, UV resistance as per ASTM D4587-23 and breathability as per EN ISO 7783:2011, Crack-bridging according to BS EN 1062-7.	m ²	660.00

Prepared by/ Checked by:-Henok Abebe




Approved by:-Hirut Ayalew

