

[< Back](#)Arrays Basics : Coding Progress

16.67 %



ARRAYS BASICS

5 / 5



What is the output of the following code

```
aList = ["PYnative", [4, 8, 12, 16]]  
print(aList[0][1])  
print(aList[1][3])
```

P 8
Y 16

P
12

✓ Y
16

[Get Results](#)

EXPLANATION

NONE

[< Back](#)Arrays Basics : Coding Progress 

16.67 %



ARRAYS BASICS

4 / 5



What is the output of the following program?

```
sampleList = [10, 20, 30, 40, 50]
```

```
sampleList.append(60)
```

```
print(sampleList)
```

```
sampleList.append(60)
```

```
print(sampleList)
```

☐ [10, 20, 30, 40, 50, 60] [10, 20, 30, 40, 50, 60]

☒ [10, 20, 30, 40, 50, 60] [10, 20, 30, 40, 50, 60, 60]

[Next](#)

EXPLANATION

NONE

[< Back](#)Arrays Basics : Coding Progress

16.67 %



ARRAYS BASICS

3 / 5



What will be the output of the following code?

```
s="a@b@c@d"  
a=list(s.partition("@"))  
print(a)  
b=list(s.split("@",3))  
print(b)
```

☐ ['a','b','c','d'] ['a','b','c','d']

☐ ['a','@','b','@','c','@','d'] ['a','b','c','d']

☒ ['a','@','b@c@d'] ['a','b','c','d']

☐ ['a','@','b@c@d'] ['a','@','b','@','c','@','d']

[Next](#)

EXPLANATION

THE PARTITION FUNCTION ONLY SPLITS FOR THE FIRST PARAMETER ALONG WITH THE SEPARATOR WHILE SPLIT FUNCTION SPLITS FOR THE NUMBER OF TIMES GIVEN IN THE SECOND ARGUMENT BUT WITHOUT THE SEPARATOR.

[< Back](#)Arrays Basics : Coding Progress 

16.67 %



ARRAYS BASICS

2 / 5



What will be the output of the following code?

```
a = [1, 2, 3]
b = a.copy()
print(b is a)
```

☐ True☒ False[Next](#)

EXPLANATION

LIST B IS JUST A COPY OF THE ORIGINAL LIST

[< Back](#)Arrays Basics : Coding Progress

16.67 %



ARRAYS BASICS

1 / 5



What is the output of the following list function?

```
sampleList = [10, 20, 30, 40, 50]
sampleList.pop()
print(sampleList)
```

```
sampleList.pop(2)
print(sampleList)
```

☐ [20, 30, 40, 50] [10, 20, 40]

☐ [10, 20, 30, 40] [10, 20, 30, 50]

☒ [10, 20, 30, 40] [10, 20, 40]

Next

EXPLANATION

NONE