Software Reengineering Project

Mitchel Pyl & Randy Paredis

1 Introduction

This document is meant as additional information on the reengineering/refactoring of the JFreeChart project, which was the assignment of the Software Reengineering course of 2019, at the University of Antwerp.

JFreeChart is a Java library that can be used to add/show professional-looking graphs and charts in your Java applications. This inheritly implies that is it useful in a lot of different contexts and scenarios that require this kind of feature.

The ability for such a library for being flexible and expandable with a vast amount of new features would therefore be an incredible advantage for this.

1.1 Problem at Hand

At this point in time, JFreeChart has a wide range of possible graphs, charts and plots it can generate for any kind of data you'd like. Unfortunately the core of this software; i.e. the drawing of a set of points can be considered legacy code and is quite solidly hardcoded within the project.

If a user or a client would, for instance, like to create graphs in which every datapoint has a different, predetermined and userdetermined, symbol associated with it¹, this would be impossible with the current state of the code. A general fix for this kind of problems within the software-world is to refactor the code so it becomes more flexible and easier to understand.

 $^{^{1}\}mathrm{As}$ was the assignment.

2 Project Management

3 Project Analysis and Tool Usage

In order to solidly identify the issues with JFreeChart and find possible refactoring targets, we made use of a few helpful tools that allowed for clear identification of possible problem areas.

3.1 Repository Visualization with Gource

The first tool we made use of was Gource. It is a clean and fancy piece of software that can turn the history of a git repository into a visual representation. This is useful for a few reasons. First, it allows us to see clearly who the main contributers are. There was no surprise that this was *David Gilbert*.

A second thing we could deduce from this simulation is that the code was not made using TDD². We can clearly see that there are first adaptations to the codebase, before changing the tests.

Thirdly and finally, we can identify the possible points in time when a refactoring stage happened in this project. These are moments when a lot of files are added, removed, or modified; which is highlighted in Gource. Granted, it is possible that some of these changes are due to merging multiple branches together.

We've identified that possible refactorings happened in November 2008 (increase in functionality), March 2013 (update to almost all files), December 2014 (update to almost all files and removal of a lot of files), July 2017 (file tree restructuring) and July 2018 (general changes).

3.2 Repository Mining with CodeScene

Another tool we made use of was CodeScene, the powerful visualization tool using *Predictive Analytics* to find hidden risks and social patterns in your code.

CodeScene allowed us to get a general feel of the current state of JFreeChart. It gave us a clear representation of possible refactoring targets (see *attachment 4*) and hotspots (see *attachment 1*) within the code³.

When we take a deeper look into the code (or at least the graphical representation thereof), we can identify that we most probably will need to

²Test Driven Development

³Please refer to the attachments at the end of this document.

take a look at the org.jfree.chart.renderer package (see attachment 2) and the org.jfree.chart.plot package (see attachment 3), as far as the hotspots are concerned.

On the topic of refactoring targets, it is clear that the org.jfree.chart.plot package (see attachment 5) really inquires our attention. More specifically the XYPlot (attachment 7), CategoryPlot (attachment 8), PiePlot (attachment 9), AbstractXYItemRenderer (attachment 10) and AbstractCategoryItemRenderer (attachment 11) classes. In the attachments, the most complex functions are listed (sorted from high to low complexity). These top functions⁴ are most likely to be refactoring targets.

3.3 Code Coverage with Cobertura

Using the already available Cobertura in the project, we were able to get an overview of the general coverage of the project. This overview gives us enough information in order to determine which classes and functions were not covered in the project, also yielding possible refactoring targets.

In general, we can deduce that the code coverage of JFreeChart at this point in time is way below comfortable for us.

We also noticed that there is currently no mutation testing being done on this project. Even though we do realize this would give way too much situations and possibilities to cover, we currently have no idea of how good the tests currently are.


4 Attachments

On the following pages, we've included a set of screenshots from CodeScene that are referred to in the previous sections. The attachment number is overlayed over the image.


⁴The ones in red.

Hotspots identify the modules with most development activity -- often technical debt. €

Defects Hotspots Refactoring Targets Code Age Programming Language System ■ jfreechart Hotspots identify the modules with most development activity -- often technical debt. €




Hotspots identify the modules with most development activity -- often technical debt. lacktriangledown



Prioritize improvements to the highlighted files. Red is most serious. 🛨



Prioritize improvements to the highlighted files. Red is most serious. lacktriangledown



Refactoring Targets

Prioritize improvements to these files since they have the highest technical debt interest rate.

jfreechart/src/main/java/org/jfree/chart/plot/XYPlot.java	<u>Le^</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/plot/CategoryPlot.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/plot/PiePlot.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/renderer/xy/AbstractXYItemRenderer.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/renderer/category/AbstractCategoryItemRenderer.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/plot/Plot.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/plot/PolarPlot.java	<u>Le^</u>
jfreechart/src/main/java/org/jfree/chart/renderer/xy/XYLineAndShapeRenderer.java	<u>∠</u> X-Ray
jfreechart/src/main/java/org/jfree/chart/axis/ValueAxis.java	<u>∠</u> X-Ray
jfreechart/src/test/java/org/jfree/chart/plot/XYPlotTest.java	<u>✓</u> X-Ray

6

jfreechart/src/main/java/org/jfree/chart/axis/CategoryAxis.java

jfreechart/src/main/java/org/jfree/chart/renderer/category/BarRenderer.java

X-Ray File Results				
Projects / jfreechart / Files / jfreechart/src/main/java/org/jfree/chart/plot/XYPlot.java				
Hotspots Internal Temporal Coupling Structural	Recommendations			
	Change Frequency	<pre></pre>		
equals	7	206	112	<u>✓</u>
draw	6	245	45	<u>✓</u> ⟨/>
drawQuadrants	2	106	24	<u>✓</u>
getDataRange	3	95	20	<u>✓</u> ⟨/>
render	5	83	18	<u>₩</u>
drawRangeGridlines	3	39	13	<u> </u>
clone	6	68	12	<u></u> ⟨/>
drawDomainGridlines	2	37	11	<u>✓/></u>
getLegendItems	1	30	11	<u>✓</u> ⟨/>
clearDomainMarkers	2	45	10	<u>✓</u>
clearRangeMarkers	2	45	10	<u>✓</u>
removeRangeMarker	5	31	9	<u>₩</u>
readObject	3	55	9	<u>✓</u>
removeDomainMarker	3	29	9	<u>✓</u>
drawAxes	1	73	9	∠
addDomainMarker	4	38	8	∠ ⟨/>
setRangeAxis	2	36	8	<u>✓</u>
addRangeMarker	2	35	8	<u>✓</u>
zoomDomainAxes	3	35	7	∠
zoomRangeAxes	3	35	7	∠
setRangeAxisLocation	2	23	7	∠
setDomainAxisLocation calculateDomainAxisSnace	1	36	7	<u>₩</u>
calculateDomainAxisSpace calculateRangeAxisSpace	1	36	7	<u>✓</u>
calculateRangeAxisSpace checkAxisIndices	1	19	7	△ ⟨/>
checkAxisIndices drawDomainMarkers	0	23	7	
drawDomainMarkers drawRangeMarkers	0	22	7	
setDomainAxis	2	23	6	
XYPlot	7	96	5	\(\langle \)
getDatasetsMappedToDomainAxis	4	18	5	
getDatasetsMappedToRangeAxis	4	18	5	
panDomainAxes	3	15	5	✓
setRenderer	2	23	5	✓/>
panRangeAxes	2	15	5	✓/>
getDomainMarkers	0	17	5	✓
getRangeMarkers	0	17	5	<u>~</u> ⟨/>
removeAnnotation	5	12	4	
getDomainAxis	1	14	4	<u>✓</u>
getRangeAxis	1	14	4	<u>✓</u>
getRendererForDataset	1	11	4	<u>✓</u>
getIndexOf	1	9	4	<u>~</u> ⟨/>
indexOf	1	87	4	<u>✓</u>
getQuadrantPaint	1	7	4	<u>₩</u>

Projects / jfreechart / Files / jfreechart/src/main/java/org/jfree/chart/plot/CategoryPlot.java Hotspots Internal Temporal Coupling Structural Recommendations Change Frequency \$ Function \$ Complexity/Size ▼ Cyclomatic Complexity equals

equals	6	180	101	<u>✓</u>
draw	9	211	34	<u>₩</u>
drawRangeGridlines	4	43	15	<u>✓</u>
render	2	60	13	<u>✓</u>
drawAxes	1	82	13	<u>₩</u>
clone	5	65	12	<u>₩</u>
clearDomainMarkers	1	49	10	<u>//</u>
clearRangeMarkers	1	49	10	<u>//</u>
removeRangeMarker	5	29	9	<u>//</u>
removeDomainMarker	3	28	9	<u>₩</u>
checkAxisIndices	0	24	9	<u>✓</u>
readObject	4	41	8	<u>₩</u>
addDomainMarker	4	36	8	<u>₩</u>
addRangeMarker	2	34	8	<u>✓</u>
calculateDomainAxisSpace	1	43	8	<u>✓</u>
zoomRangeAxes	3	35	7	<u>₩</u>
setDomainAxisLocation	2	23	7	<u>₩</u>
setRangeAxisLocation	2	21	7	<u>₩</u>
calculateRangeAxisSpace	1	33	7	<u>₩</u>
drawDomainGridlines	1	24	7	<u>✓</u>
datasetsMappedToDomainAxis	4	22	6	<u>✓</u>
setRangeAxis	3	23	6	<u>✓</u>
setRenderer	2	26	6	<u>✓</u>
setDomainAxis	2	23	6	<u>₩</u>
getLegendItems	2	17	6	<u>₩</u>
CategoryPlot	9	93	5	<u>~</u>
datasetsMappedToRangeAxis	3	19	5	<u>₩</u>
getDataRange	1	21	5	<u>₩</u>

panRangeAxes 1 11 ${\tt getRendererForDataset}$ ${\tt drawDomainMarkers}$ getDomainMarkers 17 17 ${\tt getRangeMarkers}$ <u>✓</u> </> 13 <u>✓</u> </> removeAnnotation 4 9 4 ${\tt getDomainAxisIndex}$ <u>✓</u> </> getDomainAxis 14 <u>✓</u> </> 148 1 4 getRangeAxis </>

getCategoriesForAxis 14 <u>✓</u> </>

Projects / jfreechart / Files / jfreechart/src/main/java/org/jfree/chart/plot/PiePlot.java

Hotspots Internal Temporal Coupling Structural Recommendations

	<pre>\$ Change Frequency</pre>	<pre>\$ Complexity/Size</pre>	Cyclomatic Complexity	
equals	7	172	99	<u> </u> ✓/>
drawItem	5	83	16	∠
drawPie	5	125	14	<u>✓</u>
drawSimpleLabels	5	82	11	<u>✓</u>
getLegendItems	4	62	10	<u>✓</u>
lookupSectionPaint	5	42	8	<u>~</u>
clone	3	35	7	<u>~</u>
drawLabels	4	61	6	<u>✓</u>
draw	4	57	6	<u>✓</u>
lookupSectionOutlineStroke	3	29	6	<u>✓</u>
lookupSectionOutlinePaint	3	29	6	∠
getArcCenter	0	42	6	<u>✓</u>
getMaximumExplodePercent	1	15	5	∠
getSectionKey	0	12	5	∠
drawLeftLabels	7	47	4	∠
drawRightLabels	6	49	4	∠
drawLeftLabel	3	43	4	∠
drawRightLabel	1	44	4	∠
setInteriorGap	1	13	4	∠
getArcBounds	1	20	3	∠
getExplodePercent	1	9 10	3	∠
PiePlot	8	59	2	<u>₩</u>

 ${\tt calculateRangeMarkerTextAnchorPoint}$

Projects / jfreechart / Files / jfreechart/src/main/java/org/jfree/chart/renderer/xy/AbstractXYItemRenderer.java

Hotspots Internal Temporal Coupling Structural Recomm	nendations			
⇒ Function	Change Frequency	<pre>\$ Complexity/Size</pre>		
equals	5	45	25	<u>₩</u>
drawRangeMarker	3	157	22	<u></u>
drawDomainMarker	3	157	22	<u>✓</u>
findRangeBounds	4	39	12	<u>✓</u>
getLegendItem	2	51	9	<u>✓</u>
findDomainBounds	3	21	8	<u>✓</u>
getLegendItems	0	21	7	<u>✓</u>
addEntity	3	28	5	<u>✓</u>
updateCrosshairValues	4	27	4	<u>✓</u>
addAnnotation	4	21	4	<u>✓</u>
drawDomainLine	3	28	4	<u>✓</u>
drawAnnotations	2	22	4	<u>✓</u>
drawRangeLine	1	0 27	4	<u>₩</u>

17

3

1

 ${\tt calculateDomainMarkerTextAnchorPoint}$

Projects / jfreechart / Files / jfreechart/src/main/java/org/jfree/chart/renderer/category/AbstractCategoryItemRenderer.java

Hotspots Internal Temporal Coupling Structural Recomm	endations			
	<pre>\$ Change Frequency</pre>	<pre></pre>	▼ Cyclomatic Complexity	
equals	4	47	23	<u>₩</u> ⟨/>
drawRangeMarker	4	163	22	<u>₩</u>
clone	4	71	16	<u>₩</u>
getLegendItems	2	33	12	<u>₩</u>
drawDomainMarker	3	72	9	<u>₩</u>
getLegendItem	1	44	9	<u>✓</u>
findRangeBounds	3	23	8	<u>✓</u>
addEntity	1	31	6	<u>✓</u>
addItemEntity	3	20	4	<u>✓</u>
initialise	2	29	4	<u>✓</u>
drawDomainGridline	1	32	4	<u>✓</u>
drawRangeLine	1	27	4	<u>✓</u>
calculateRangeMarkerTextAnchorPoint	1 1	1 16	3	

15

3