RICE UNIVERSITY

CMOR 438 / INDE 577




GRADUATE TEXT

Data Science and Machine Learning

A Systems Approach

PARTS I–II
Foundations and Supervised Learning Systems



Randy Davila
Rice University

CMOR 438 / INDE 577 | Developing edition – Fall 2026

Data Science and Machine Learning

A Systems Approach

Randy Davila

Rice University

CMOR 438 / INDE 577 | Fall 2026

Graduate course edition. This developing text is used in Data Science & Machine Learning, cross-listed as CMOR 438 and INDE 577 at Rice University. Its executable notebooks, exercises, and tested `rice_dsm` package are integral parts of the text.

Copyright © 2026 Randy Davila. Course distribution terms follow the repository license. Third-party names are used for identification and teaching.

Built reproducibly from LaTeX source in the course repository.

Preface

Data science and machine learning are often organized around models. This text organizes them around claims and the systems that carry those claims. Evidence originates in files, instruments, databases, or services; software represents, transforms, evaluates, and communicates it. A result is credible only to the extent that its assumptions, implementation, provenance, uncertainty, and operation can be examined.

Part I develops the computational foundations for that systems view. Part II develops machine learning from its mathematical problem structures through a precisely stated supervised prediction contract, linear regression, gradient methods, classification, nearest-neighbor methods, trees, ensembles, neural networks, model selection, and a monitored release. The text assumes mathematical maturity appropriate to graduate study, but not prior professional experience with shells, virtual environments, packages, databases, web APIs, continuous integration, or language-model agents. Tooling is taught when it expresses a technical responsibility, not as an end in itself.

How this book relates to the repository

The graduate text is the organizing artifact; the remaining repository components make its arguments executable:

Textbook	Durable concepts, terminology, design arguments, connections, and compact examples.
Lecture notebooks	Executable explanations, experiments, assertions, guided practice, and extended reference material.
`rice_dsm` package	Reusable code developed with professional structure, documentation, types, exceptions, and tests.
Test suite and CI	Executable contracts that detect regressions across the package, repository, and notebooks.
Supplementary guides	Slower introductions to tools and workflows that should not be treated as assumed background.

Read the prose and notebooks together. Predict before execution, change one assumption at a time, and state what the result does and does not establish.

A recurring distinction

Throughout the course we separate three claims:

1. **The code ran.** Python completed the requested operations.
2. **The software contract holds.** Types, tests, schemas, and operational controls support the promised behavior.
3. **The scientific conclusion is valid.** The data, assumptions, design, uncertainty, and interpretation justify the claim.

None of these claims implies the next. A notebook can run while joining the wrong records. A thoroughly tested implementation can faithfully compute an invalid statistic. A sound analysis can still fail as a product if

users cannot reach it or operators cannot observe it.

Professional practice

Professionalism is not ceremony added after discovery. It is the practice of making assumptions, contracts, evidence, failure modes, and responsibility visible early enough to improve the work.

Editorial status

This is a developing graduate-course edition. Parts I and II now form connected systems and supervised-learning arguments with worked examples, exercises, appendices, and executable companions. Part II notebooks currently establish the executable entry points and development contracts; their detailed laboratories will be expanded unit by unit. The prose is ready for classroom review while remaining open to correction, additional evidence, solutions, and revision from use.

Contents

Preface iii

I Foundations for Data-Driven Software Systems 1

1 The Part I systems view 2

1.1 The model is one component . . . 2

1.1.1 Three views of the same work . . . 3

1.1.2 The evidence loop . . . 3

1.1.3 Why learned components require additional controls . . . 4

1.2 The chapter map . . . 5

1.2.1 Chapter-by-chapter capabilities . . . 5

1.2.2 Milestones . . . 6

1.3 Correctness has layers . . . 6

1.3.1 Six lenses for evaluating a result . . . 6

1.3.2 Verification, validation, and reproducibility . . . 7

1.3.3 Composition and numerical judgment . . . 7

1.3.4 Failure investigation . . . 8

1.4 A professional-practice spine . . . 9

1.4.1 Scale rigor with consequence . . . 10

1.5 How to read and use this book . . . 10

1.5.1 The predict-execute-explain loop . . . 11

1.5.2 Read code as a contract . . . 11

1.5.3 Use notebooks as laboratories . . . 11

1.5.4 Move reusable work into durable artifacts . . . 12

1.6 A running case study . . . 12

1.7 Exercises . . . 14

2 A reproducible computational workshop 15

2.1 A project has a place and a runtime . . . 15

2.2 Terminal, shell, and Python . . . 15

2.3 Virtual environments solve project isolation . . . 16
2.4 Jupyter and the kernel . . . 16
2.5 The one-command course setup . . . 17
2.6 Diagnose before reinstalling . . . 17
2.7 Worked diagnosis: an import that succeeds in the terminal only . . . 18
2.8 State explains surprising notebook behavior . . . 19
2.9 Exercises . . . 19
2.10 Takeaway . . . 20

3 Objects, values, and native data structures 21

3.1 Names refer to objects . . . 21
3.2 Mutability and aliasing . . . 22
3.3 Strings are structured text . . . 22
3.4 Sequences encode order . . . 22
3.5 Mappings and sets encode different relations . . . 23
3.6 Iterables, iterators, and generators . . . 23
3.7 Worked example: from instrument text to a trustworthy record . . . 24
3.8 Choosing a container by the question it answers . . . 25
3.9 Iteration changes when work happens . . . 25
3.10 Exercises . . . 25
3.11 Takeaway . . . 26

4 Functions, classes, and native data 27

4.1 A function creates a boundary . . . 27
4.2 Docstrings explain semantics . . . 28
4.3 Exceptions are part of the contract . . . 28
4.4 Parameter kinds communicate calling policy . . . 28
4.5 Classes model objects and invariants . . . 29
4.6 CSV and JSON are representations . . . 29
4.7 Worked example: design the contract before the body . . . 30
4.8 From records to objects with behavior . . . 31
4.9 A complete ingestion boundary . . . 31
4.10 Exercises . . . 32
4.11 Takeaway . . . 32

5 Projects, packages, tests, and automation **33**

5.1 From exploration to reusable software . . . 33
5.2 A public package API . . . 33
5.3 Dependencies and versions . . . 34
5.4 Tests begin with risks . . . 34
5.5 Automation and CI/CD . . . 35
5.6 Worked example: derive tests from a risk . . . 35
5.7 Fixtures, parameters, and doubles . . . 36
5.8 Reading a CI failure as evidence . . . 36
5.9 Exercises . . . 36
5.10 Takeaway . . . 37

6 Arrays, tables, and visual evidence **38**

6.1 From Python containers to arrays . . . 38
6.2 Vectorization and broadcasting . . . 39
6.3 Shape is syntax; axis meaning is semantics . . . 39
6.4 Data type is a numerical design decision . . . 39
6.5 pandas adds labeled structure . . . 40
6.6 Visualization is a transformation . . . 41
6.7 Simulation as executable reasoning . . . 41
6.8 Worked example: standardize three sensor channels . . . 43
6.9 Worked example: pandas alignment is not row order . . . 44
6.10 From analytical question to figure . . . 44
6.11 Exercises . . . 44
6.12 Takeaway . . . 45

7 Databases and data systems **46**

7.1 Storage is part of the scientific system . . . 46
7.2 Transactions preserve invariants . . . 46
7.3 SQL has semantics, not just syntax . . . 47
7.4 Local and remote are deployment shapes . . . 47
7.5 Object storage is not a filesystem or database . . . 47
7.6 When data is too large to load . . . 48
7.7 Worked example: from a measurement contract to SQL . . . 48
7.8 Missingness and joins deserve explicit examples . . . 49

7.9 A measured decision process for large data . . . 50
7.10 Exercises . . . 50
7.11 Takeaway . . . 51

8 Language-model tools and agents 52
8.1 Begin with precise roles . . . 52
8.2 What a hosted API does . . . 52
8.3 Credentials are authority . . . 53
8.4 Hosted, local, open, and free are different axes . . . 53
8.5 Structured output controls syntax, not truth . . . 53
8.6 Tools create possible side effects . . . 53
8.7 Two responsible automation patterns . . . 54
8.7.1 Docstring proposals . . . 54
8.7.2 Training-run proposals . . . 54
8.8 Evaluation and observability . . . 54
8.9 Worked example: read one API exchange . . . 54
8.10 Worked example: a docstring proposal is a code change . . . 55
8.11 Prompt injection is a confused-authority problem . . . 56
8.12 Exercises . . . 56
8.13 Takeaway . . . 57

9 End-to-end data products 58
9.1 End to end is a scoped claim . . . 58
9.2 One request across the system . . . 58
9.3 Request anatomy . . . 59
9.4 Retries make writes ambiguous . . . 59
9.5 Frontend, backend, and hosting . . . 59
9.6 CI/CD for production . . . 60
9.7 Monitor the client and server . . . 60
9.8 Testing the real boundary . . . 60
9.9 Worked example: trace one value without skipping a boundary . . . 61
9.10 A timeout is an uncertainty about state . . . 61
9.11 From commit to production . . . 62
9.12 Worked incident: the API is healthy but the page is blank . . . 62
9.13 Exercises . . . 63

9.14 Part I takeaway 63

II Supervised Learning Systems 65

10 Machine learning: problems, evidence, and systems 66

10.1 A short history of a broad idea 66
10.2 What exactly is learned? 67
10.3 Branches are distinguished by information and feedback 67
10.4 Inductive bias is not optional 68
10.5 From population risk to empirical evidence 70
10.6 Performance is a vector, not one score 71
10.7 Applications begin with decisions, not algorithms 71
10.8 The learning lifecycle is an evidence lifecycle 72
10.9 Exercises 73

11 The supervised-learning contract 75

11.1 Supervised learning joins statistical inference and computation 75
11.2 Learning begins with a future information boundary 76
11.3 Risk, empirical risk, and the generalization claim 76
11.4 The loss determines the population target 77
11.5 Generalization error has several sources 77
11.6 Prediction is not causal explanation 78
11.7 Splits simulate the use setting 78
11.8 A baseline is an experimental control 79
11.9 Measure predictive performance as an experiment 80
11.10 One table can contain many supervised problems 80
11.11 The first vertical slice should be deliberately simple 81
11.12 Exercises 81

12 Linear regression and regularization 84

12.1 From astronomical observations to a general model 84
12.2 The affine predictor 84
12.3 One feature exposes the algebra 85
12.4 Projection and identifiability 85
12.5 Stable solution is a numerical question 87

12.5.1 Computational cost belongs to the algorithm, not just the model . . . 87
12.6 Prediction assumptions differ from inferential assumptions . . . 87
12.7 Basis expansion changes the feature map . . . 88
12.8 Regularization chooses among fitting rules . . . 88
12.9 Residuals are structured evidence . . . 89
12.10 Linear models across science and engineering . . . 89
12.11 Exercises . . . 90

13 Gradient methods: from calculus to learning 92
13.1 From steepest descent to stochastic approximation . . . 92
13.2 One variable: the derivative proposes a local move . . . 93
13.3 Several variables: the gradient represents all directions . . . 94
13.4 Quadratic objectives make curvature visible . . . 94
13.5 Least squares supplies an exact laboratory . . . 95
13.6 Batch, stochastic, and mini-batch gradients . . . 96
13.7 Momentum and acceleration remain first-order methods . . . 97
13.8 Back-propagation differentiates; the optimizer updates . . . 98
13.9 Applications beyond fitting a line . . . 99
13.10 Stopping and diagnosing responsibly . . . 99
13.11 Measure optimizer performance without moving the goalposts . . . 100
13.12 Exercises . . . 100

14 Classification, probability, and decisions 103
14.1 Four objects that must not be conflated . . . 103
14.2 Logistic regression as one neuron . . . 104
14.3 The sigmoid turns a score into a probability . . . 105
14.3.1 Odds and log-odds . . . 106
14.4 Likelihood turns probability modeling into estimation . . . 107
14.4.1 Why log loss elicits a probability . . . 108
14.5 The gradient reveals the single-neuron connection . . . 108
14.6 Stable computation is part of the mathematics . . . 109
14.7 A complete evidence workflow . . . 110
14.7.1 Real-data example: diagnostic measurements . . . 110
14.8 Measuring classification performance professionally . . . 111
14.8.1 Begin with a baseline and probability evidence . . . 111

14.8.2 A confusion matrix is four counts with four meanings . . . 112
14.8.3 The evaluated data determine what a metric means . . . 113
14.8.4 Attach uncertainty and scope to every performance claim . . . 113
14.9 A probability model is not a decision policy . . . 114
14.10 Multiclass and multilabel extensions . . . 115
14.11 Engineering the model as a reliable component . . . 115
14.12 Exercises . . . 115

15 Linear support vector machines **118**
15.1 One affine neuron, a different objective . . . 118
15.2 Geometry of a separating hyperplane . . . 119
15.2.1 Functional and geometric margin . . . 119
15.2.2 Canonical scaling and the hard margin . . . 120
15.3 Soft margins lead to hinge loss . . . 121
15.4 Subgradients and first-order training . . . 121
15.5 Support vectors, scaling, and scores . . . 122
15.5.1 Scores are not probabilities . . . 122
15.6 Professional evidence workflow . . . 123
15.7 Exercises . . . 123

16 Designing a learning API **124**
16.1 An API is a scientific boundary . . . 124
16.2 Shared affine structure, different output semantics . . . 125
16.3 Pair compatible activations and losses . . . 126
16.4 Estimator and component interfaces . . . 126
16.5 Shape, state, and failure contracts . . . 127
16.6 Gradient checking as a software test . . . 127
16.7 API review checklist . . . 128
16.8 Exercises . . . 128

17 From neurons to neural networks **130**
17.1 Networks are computational graphs of neurons . . . 130
17.2 A concrete three–two–two network . . . 131
17.3 Why use a neural network? . . . 132
17.3.1 Linear depth adds no expressive power . . . 132

17.3.2 Sigmoid and ReLU make different tradeoffs . . . 132
17.4 A transparent first loss and its output error . . . 133
17.5 Hidden errors collect all downstream paths . . . 134
17.6 Batch vectorization . . . 134
17.7 Gradient checking a layer . . . 135
17.8 Output losses change the initial backward signal . . . 135
17.9 Initialization and gradient flow . . . 136
17.10 A real-data training argument . . . 136
17.11 Automatic differentiation and framework boundaries . . . 136
17.12 Exercises . . . 137

18 Multiclass networks from first principles 138
18.1 MNIST as experiment, not trophy . . . 138
18.2 From image to feature vector . . . 139
18.3 Class identities and one-hot targets . . . 140
18.4 A modern bounded architecture . . . 140
18.5 Initialization from variance propagation . . . 141
18.6 Softmax cross-entropy as a fused contract . . . 142
18.7 Backpropagation for a mini-batch . . . 143
18.8 Mini-batch gradient descent . . . 144
18.9 Confusion is part of the scientific result . . . 145
18.10 Failure modes and diagnostic tests . . . 145
18.11 Exercises . . . 146

19 TensorFlow, convolution, and observable training 147
19.1 A framework is a stack of contracts . . . 147
19.2 Tensors and automatic differentiation . . . 148
19.3 The Keras lifecycle is an executable argument . . . 149
19.4 MNIST: concise code, explicit semantics . . . 149
19.4.1 Acquire data without hiding provenance . . . 150
19.4.2 Validate first, then transform . . . 150
19.4.3 The API lifecycle marks changes of state . . . 151
19.5 Convolution preserves a spatial hypothesis . . . 151
19.5.1 Channels and filters . . . 152
19.5.2 Pooling and receptive fields . . . 152

19.6 From MNIST to cats and dogs . . . 153
19.7 Observable training . . . 154
19.8 Debugging framework experiments . . . 155
19.9 Exercises . . . 155

20 Text, tokenization, and sentiment systems 157
20.1 A scientific question before an architecture . . . 157
20.2 Data acquisition is part of the experiment . . . 158
20.3 How text models developed . . . 158
20.4 The representation pipeline . . . 159
20.4.1 Normalization . . . 159
20.4.2 Tokens and vocabularies . . . 159
20.4.3 Padding, truncation, and masking . . . 160
20.5 Embeddings are trainable lookup tables . . . 161
20.5.1 Pooling a sequence . . . 161
20.6 A binary logit and a stable objective . . . 161
20.7 Thresholds turn modeled probabilities into decisions . . . 162
20.8 Error analysis is part of modeling . . . 163
20.9 Responsible use and deployment . . . 164
20.10Exercises . . . 164

21 Nearest neighbors: local prediction, retrieval, and engineering 166
21.1 A local principle with a long history . . . 166
21.2 The mathematical object: a neighborhood . . . 167
21.2.1 Classification by local vote . . . 167
21.2.2 Regression by local averaging . . . 168
21.2.3 Distance-weighted aggregation . . . 168
21.3 Why the neighbor count changes the model . . . 169
21.3.1 A consistency theorem . . . 169
21.4 Scaling, representation, and leakage . . . 170
21.5 Dimension and the loss of locality . . . 170
21.6 A real classification workflow: wine chemistry . . . 170
21.7 A real regression workflow: disease progression . . . 171
21.8 Recommendation as neighbor retrieval . . . 171
21.8.1 Content versus collaborative similarity . . . 172

21.8.2 Offline evaluation is limited evidence . . . 172
21.9 Software design: from formula to package . . . 172
21.9.1 Tests as executable mathematics . . . 173
21.10 The student project handoff . . . 174
21.11 Failure modes and operational evidence . . . 174
21.12 Exercises . . . 175

22 Classification and regression trees **177**
22.1 From questions to a prediction function . . . 177
22.2 Classification trees estimate local class distributions . . . 178
22.3 Regression trees estimate local conditional means . . . 179
22.4 Greedy growth is a computational compromise . . . 182
22.5 Pruning trades fit for structural complexity . . . 182
22.6 Classification evidence is decision evidence . . . 183
22.7 Regression evidence includes residual structure . . . 183
22.8 Instability is a defining property . . . 184
22.9 Thresholds, missingness, and schema are contracts . . . 184
22.10 From notebook experiment to maintained package . . . 184
22.11 Operational evidence after release . . . 185
22.12 Exercises . . . 186

23 Ensemble learning: forests, boosting, and model combination **188**
23.1 The organizing question: where does useful diversity come from? . . . 188
23.2 Why averaging can reduce variance . . . 189
23.3 Bootstrap sampling and bagging . . . 189
23.3.1 Out-of-bag evidence . . . 190
23.4 Random forests: decorrelate the trees . . . 191
23.4.1 Probability aggregation is an interface contract . . . 192
23.4.2 Feature importance does not identify scientific mechanism . . . 192
23.5 Boosting builds an additive model sequentially . . . 192
23.5.1 Classification gradients . . . 193
23.5.2 Shrinkage, depth, and stopping . . . 194
23.6 Leakage-safe out-of-fold stacking and voting . . . 194
23.7 Evaluation is a systems comparison . . . 195
23.8 Software engineering contracts for ensembles . . . 196

23.9 Exercises . . . 196

24 Model selection and honest evaluation **198**

24.1 Name the estimand before the splitter . . . 198
24.2 A pipeline owns every fitted transformation . . . 198
24.3 Selection creates optimism . . . 199
24.4 Search should express prior structure and budget . . . 199
24.5 Uncertainty and dependence . . . 199
24.6 Error analysis is structured, not anecdotal . . . 199
24.7 Exercises . . . 200

25 Reliable supervised-learning systems **201**

25.1 Three paths define the operated system . . . 201
25.2 A model artifact is more than parameters . . . 201
25.3 Offline and online features must agree . . . 202
25.4 Prediction interfaces fail explicitly . . . 202
25.5 Operating evidence is part of the model contract . . . 202
25.6 Failure layers require different evidence . . . 202
25.7 Logs, metrics, and traces answer different questions . . . 203
25.8 Model monitoring needs a feedback path . . . 204
25.9 Alerts connect objectives to owned action . . . 204
25.10 Incident diagnosis is disciplined inference . . . 205
25.11 Retraining is a release, not a reflex . . . 206
25.12 The release dossier . . . 206
25.13 Exercises . . . 206

A Course setup reference **208**

A.1 Initial setup . . . 208
A.2 One-command refresh after main changes . . . 208
A.3 Verify the active notebook process . . . 208
A.4 Run checks . . . 209
A.5 Build this textbook . . . 209
A.6 First diagnostic questions . . . 209

B Git and GitHub: evidence, collaboration, and recovery **210**

B.1 Why version control matters in data science . . . 210
B.2 Git and GitHub are different systems . . . 211
B.3 The four-state mental model . . . 212
B.4 Commits, branches, and HEAD . . . 213
B.5 First-time setup . . . 213
B.6 Worked lesson 1: build a local history . . . 214
B.7 Design coherent commits . . . 216
B.8 Ignore local and generated state deliberately . . . 216
B.9 Worked lesson 2: branches isolate change . . . 217
B.10 Connect a repository to GitHub . . . 218
B.11 The daily branch and pull-request workflow . . . 218
B.12 Course contribution practicum: textbook problem to pull request . . . 220
B.13 Review is a technical skill . . . 225
B.14 Synchronize without guessing . . . 225
B.15 Worked lesson 3: create and resolve a conflict . . . 226
B.16 Recover conservatively . . . 227
B.17 Notebooks, data, and generated artifacts . . . 228
B.18 GitHub Actions turns history into automated evidence . . . 228
B.19 A command map by intention . . . 229
B.20 Principles to carry into professional work . . . 230
B.21 Exercises . . . 231
B.22 Official references . . . 232

C From Source to Release: CI/CD Through This Textbook 233

C.1 A public system has more state than its source . . . 233
C.2 The three terms in CI/CD . . . 234
C.3 The running system . . . 234
C.4 Path one: a pull request becomes verified source . . . 235
C.5 Path two: `main` becomes a public course site . . . 235
C.5.1 Build a bounded artifact . . . 236
C.5.2 Record identity in a manifest . . . 236
C.5.3 Promote and then observe . . . 236
C.6 Path three: a version becomes an approved release . . . 237
C.6.1 The approval boundary . . . 238

C.7 Build once, promote the same artifact . . . 238
C.8 Authority is part of the pipeline . . . 238
C.9 Failure is a state to diagnose . . . 239
C.10 Rollback and roll-forward . . . 240
C.11 A complete worked change . . . 240
C.12 Inspect the system locally . . . 241
C.13 Design exercises . . . 241
C.14 Operational checklist . . . 241
C.15 Summary . . . 242

D Course glossary **243**

Where the book goes next **249**

Part I

Foundations for Data-Driven Software Systems

CHAPTER 1

The Part I systems view

Learning objectives

After this chapter, you should be able to:

- distinguish a learned model from the data-driven system that contains it;
- trace a result across data, computational, software, statistical, scientific, and operational boundaries;
- state what each Part I chapter contributes to that system; and
- match a correctness claim with evidence of the appropriate scope.

Where this chapter fits

This chapter fixes the level of abstraction for Part I. Python objects, statistical models, databases, APIs, and deployed applications will be studied as components of one evidence-bearing system. Later chapters supply the technical details; this chapter states the contracts those details must serve.

1.1 The model is one component

A machine-learning project is often summarized by its model: a random forest, neural network, or large language model. That description omits most of the system. A model does not determine whether measurements have the correct units, whether labels represent the intended quantity, whether features will exist at prediction time, or whether a result is safe to use. It also does not version its inputs, expose an interface, monitor its behavior, or recover from failure.

Definition: Machine-learning model

A *machine-learning model* is a parameterized rule whose behavior is partly determined from data. Given an input representation, it produces an output such as a score, category, estimate, generated object, or proposed action.

Definition: Data-driven software system

A *data-driven software system* is a collection of data, programs, interfaces, infrastructure, and operating procedures whose behavior depends materially on observed data. It transforms evidence into a prediction, decision, explanation, or scientific claim under explicit technical and human responsibilities.

If a model is written as

$$f_\theta : \mathcal{X} \longrightarrow \mathcal{Y},$$

then model fitting determines parameters θ from training data. An operated prediction requires a larger composition:

$$r \xrightarrow{\text{parse}} v \xrightarrow{\text{validate}} x \xrightarrow{f_\theta} \widehat{y} \xrightarrow{\text{present}} a.$$

Here r is a raw record, v a typed value, x the model input, $\widehat{y}$ the model output, and a the result presented to a person or another program. A defect in any arrow can invalidate the final result even when f_θ behaves exactly as tested.

Definition: Engineering boundary

An *engineering boundary* is a point at which data, control, ownership, or trust passes between contexts. A function call is a small boundary; a file, database, remote API, deployment, and human approval cross larger ones. Each boundary requires a contract: what enters, what leaves, what may fail, and who is responsible.

1.1.1 Three views of the same work

The same computation must be legible from three views:

View	Central questions	Typical failure
Scientific	What question is being asked? What observations and assumptions support the claim?	A proxy is treated as the phenomenon of interest, or prediction is mistaken for causation.
Computational	How is meaning represented and transformed? What numerical, time, and memory limits apply?	Missingness becomes zero, an array has the wrong shape, or an algorithm is numerically unstable.
Operational	How does behavior reach a user? Who may invoke it, how is it observed, and how is it recovered?	A stale model is served, an interface changes meaning, or a failure has no owner.


For a classifier predicting material stability, the scientific view asks whether the experiment measures stability and whether the evaluation supports the stated population. The computational view asks how compositions, temperatures, and missing values become features. The operational view asks whether the service uses the same feature definition and identifies inputs outside the model's domain. These are not separate projects; they are separate claims about one result.

Common misconception

Misconception: a notebook that runs from top to bottom and reports high test accuracy constitutes a complete machine-learning system.
Correction: successful execution describes one run in one environment. Test accuracy describes one metric under a sampling design. Neither alone establishes valid data, reproducibility, deployability, safety, or scientific relevance.

1.1.2 The evidence loop

An operated system is a loop rather than a pipeline that ends at prediction.



At each arrow, meaning changes representation or context. A file reader needs a format, encoding, schema, and missing-value policy. A prediction endpoint needs an input schema, authentication rule, model identity, output definition, and failure response. After release, logs, outcomes, and user reports become new evidence. They may justify a test, a retrained model, a changed interface, or retirement of the system.

Worked example: A plausible answer from a broken system

An instrument records `-999` when a temperature sensor fails. A program parses the column as numbers, converts every value from Fahrenheit to Celsius, and sends the result to a well-evaluated model. The model returns 0.82, and the interface displays *82% likely stable*.
The conversion and model may both satisfy their local tests. The composition is wrong because a sentinel was treated as a physical measurement. A defensible boundary maps the documented sentinel to missingness, checks the physical range, preserves the raw record, and records whether the observation was rejected or imputed. Representation is part of the scientific argument, not merely data cleaning.

1.1.3 Why learned components require additional controls

Ordinary software already requires clear interfaces, version control, tests, security, and observability. Learned behavior adds four complications:

1. **Data changes behavior.** Training population, labels, preprocessing, and sampling can alter a model without changing its algorithm.
2. **Evaluation is conditional.** A metric has meaning only with its dataset, split design, baseline, uncertainty, and intended use.
3. **Behavior can drift.** Instruments, schemas, populations, and user behavior change after release.
4. **Outputs are not authority.** A score or agent proposal does not acquire permission to create a consequential side effect merely because it was produced automatically.

Scientific discovery raises the standard further. Prediction may support a hypothesis, parameter estimate, mechanism, or experimental decision, but it is not identical to any of them. A scientific system must distinguish observation from inference, association from intervention, exploration from confirmation, and model uncertainty from measurement uncertainty.

Definition: Data product


A *data product* is a maintained interface through which people or software obtain value from data. It may be a dataset, report, dashboard, API, decision-support tool, scientific workflow, or automated service. A model may be one component; contracts, users, delivery, operation, and feedback complete the product.

The appropriate architecture is the smallest one that protects the required contracts. A CSV file can be correct for a small immutable dataset. A database is justified by durable identity, queries, transactions, concurrency, or scale. An API is justified when a responsibility must cross a process, machine, language, team, or trust boundary.

Concept check. For a machine-learning application you know, identify the model, the data product, one scientific assumption, one software boundary, and the role responsible for recovery.

1.2 The chapter map

Part I expands the engineering boundary while retaining earlier contracts. A deployed API still depends on correctly interpreted strings; a tool-using agent still depends on ordinary functions, exceptions, credentials, and tests.



1.2.1 Chapter-by-chapter capabilities

Ch.	Boundary	Result	Evidence
1	Computing environment	Project-local Python environment and matching VS Code kernel	Interpreter path, version, and reproducible setup check
2	Native objects	Transformations using strings, sequences, mappings, sets, and iteration	Predicted values and types, explicit mutation, edge cases
3	Functions, classes, files	Documented domain model and native-file knowledge graph	Type hints, NumPy-style documentation, exceptions, round-trip tests
4	Package and workflow	Installable, versioned package with CI	Unit, integration, doctest, and notebook checks in a clean environment
5	Numerical evidence	Array- and table-based analysis with visual evidence	Shape and dtype checks, labels, justified encodings, reproducible figures
6	Durable data	Parameterized query and memory-bounded workflow	Schema, transaction, query-safety, and chunking evidence
7	Model and agent	Provider-independent tool workflow with bounded actions	Secret isolation, structured responses, evaluations, budgets, approvals
8	Operated product	Value traced from storage through API to client	Contract tests, release checks, monitoring, and recovery plan

The sequence has four dependencies. Chapters 1–2 establish computational identity and Python's object model. Chapters 3–4 turn reasoning into documented, tested, reusable software. Chapters 5–6 introduce numerical

structures and durable data access. Chapters 7–8 place probabilistic and automated components inside operated systems.

1.2.2 Milestones

After Chapter 2: reproducible computation. A reader can select the correct interpreter, run the work, inspect its objects, and explain its native transformations.

After Chapter 4: maintainable component. Reusable logic lives in an installable package with documented interfaces, tests, and a version.

After Chapter 6: evidence workflow. The project retrieves, validates, transforms, and visualizes data without assuming all data fits in memory.

After Chapter 8: operated product. The project exposes a bounded, observable interface with explicit release and recovery procedures.

These are cumulative capabilities. When a later boundary exposes a weak earlier contract, the earlier contract must be repaired.

Concept check. Choose one chapter-map row. Explain why its result is insufficient without the listed evidence, and identify one later chapter that depends on it.

1.3 Correctness has layers

The assertion *the result is correct* is incomplete unless it names a requirement, context, and evidence. A program may compute a formula correctly while the formula answers the wrong scientific question. A model may be statistically sound while a service feeds it a different feature representation.

Definition: Correctness claim

A *correctness claim* states that an artifact or behavior satisfies a specified requirement under stated conditions. *The model works* is weak. *Model 1.4 meets the prespecified recall threshold on the held-out 2026 instrument dataset using feature pipeline 3* is testable.

1.3.1 Six lenses for evaluating a result

Lens	Question	Representative evidence	Limit
Data	Do values represent the correct entities, units, identity, and missingness?	Provenance, schema, range, calibration, and duplicate checks	Does not establish that the measurements answer the question
Computational	Does the algorithm implement the specified mathematics within acceptable error?	Reference cases, invariants, convergence and tolerance analysis	Does not establish that the algorithm is appropriate

Lens	Question	Representative evidence	Limit
Software	Do components satisfy their contracts when composed?	Unit, integration, contract, security, and dependency checks	Tested cases may not represent future operation
Statistical	Does the design support the estimator or generalization claim?	Sampling rationale, baselines, held-out evaluation, calibration, intervals	Association does not imply intervention or importance
Scientific	Do evidence and assumptions support the domain claim?	Controls, theory, experimental design, replication, alternative explanations	Does not establish that deployment preserves the analysis
Operational	Does the released system deliver intended behavior in use?	Version records, logs, metrics, traces, audits, outcomes	Reliability does not establish scientific validity

The limit column prevents evidence from being asked to prove too much. A unit test can verify a Fahrenheit-to-Celsius function; it cannot establish that the input was Fahrenheit. A held-out set estimates behavior under a sampling assumption; it cannot guarantee an unchanged deployment population.

1.3.2 Verification, validation, and reproducibility

Definition: Verification

Verification asks whether an implementation satisfies its specification: did we build the specified thing correctly? Tests, type checks, static analysis, schema checks, and comparison with known results provide verification evidence.

Definition: Validation

Validation asks whether the specification and system are appropriate for the intended use: did we build the right thing? It requires application, statistical, scientific, and user evidence.

Definition: Reproducibility

Reproducibility is the ability to reconstruct a result under documented conditions using identified data, code, configuration, dependencies, and procedures. It controls computational history; it does not prove validity.

A reproducible error remains an error. A validated claim that cannot be reconstructed remains difficult to audit or extend. Strong work seeks all three.

1.3.3 Composition and numerical judgment

Suppose a producer guarantees a temperature in Celsius and a consumer assumes Celsius. Their composition is meaningful only if the guarantee is true and at least as strong as the assumption. The type `float` cannot

express unit, calibration, valid range, sample identity, or privacy status. Domain classes, schemas, validation, documentation, and tests make more of that contract explicit.

Numerical claims also require tolerances. Floating-point equality may be the wrong contract; an acceptable tolerance must follow from the algorithm, scale, accumulated error, and downstream use. For iterative methods, report convergence evidence and nonconvergence. For randomized procedures, a fixed seed aids diagnosis but evaluation across seeds measures sensitivity.

Worked example: High accuracy, invalid scientific evidence

A laboratory records ten measurements from each of one hundred specimens and randomly splits the one thousand rows into training and test sets. A classifier reports 94% accuracy.
The implementation can be correct and reproducible while the evaluation is invalid for new specimens: measurements from the same specimen occur in both sets. If specimen-specific signatures are easy to learn, the score overstates generalization. Splitting by specimen identity repairs the statistical contract. A regression test can then require disjoint specimen identifiers, but domain reasoning is what identified the correct grouping.

Professional practice

Report only the precision supported by measurement and computation. `97.2000000000` does not make an instrument more precise. Measurement uncertainty, numerical error, rounding, and display formatting are distinct.

1.3.4 Failure investigation

When a result is disputed:

1. state the claim, version, conditions, units, tolerance, and intended use;
2. preserve and reconstruct the inputs, artifact, environment, and output;
3. trace provenance backward to the first violated contract;
4. reduce the violation to the smallest representative case;
5. repair the data, contract, implementation, or study design at its source;
6. add regression evidence at that layer and affected integrations; and
7. re-evaluate downstream claims before releasing the correction.

The required evidence is proportional to consequence, but every consequential claim needs an owner and an evidence portfolio spanning the relevant lenses.


Concept check. A pipeline is reproducible, all tests pass, and the deployed model matches the evaluated version. Give one statistical and one scientific reason its conclusion could still be wrong.

1.4 A professional-practice spine

Definition: Professional practice

Professional practice is the discipline that makes technical work understandable, reviewable, reproducible, safe to change, and recoverable. It coordinates software artifacts with explicit human responsibility.

The operating loop is:



Each stage has a concrete obligation.

Obligation	Practice	Representative artifact
Name the boundary	Specify producer, consumer, input, output, failure, and owner.	Type, schema, interface contract
Preserve provenance	Retain source evidence and record transformations without assuming raw means correct.	Immutable input, checksum, lineage record
Make contracts executable	Encode what software can check; document what requires domain judgment.	Validation, types, tests, database constraint
Fail recoverably	Reject invalid states near entry, add safe context, and retain a known-good state.	Exception contract, rollback procedure
Version behavior	Identify code, data, dependencies, model, configuration, schema, and prompt when they affect results.	Commit, lockfile, dataset and model versions
Bound resources and authority	Limit rows, memory, time, retries, cost, permissions, and side effects.	Query limit, timeout, scoped credential, approval gate
Observe outcomes	Collect signals that answer defined questions while protecting secrets and privacy.	Logs, metrics, traces, audits, outcome checks
Design for review	Keep changes coherent and state intent, evidence, risk, compatibility, and recovery.	Pull request, CI result, release record

An exception should identify the violated contract and support a safe response. Catch it only to add context, recover, translate it to an interface response, or release resources. A retry is appropriate only for a plausibly transient failure and an operation safe to repeat.

Version control must extend beyond source code. A commit identifies code but not an external dataset, a moving provider default, or an unrecorded training configuration. Credentials are configuration but never repository content; store them in environment variables or a secret service with the narrowest useful permissions.

Observability is similarly scoped. Logs describe events, metrics summarize quantities over time, traces follow work across components, and audits record consequential authority. None is useful without a question, retention policy, and owner responsible for action.

Common misconception

Misconception: professional engineering begins only after exploration succeeds.
Correction: rigor should match consequence, but a named environment, preserved input, explicit function, focused test, and recorded result make even exploratory work easier to evaluate and revisit.

1.4.1 Scale rigor with consequence

Context	Reasonable minimum	Additional controls
Private exploration	Named environment, preserved input, recorded assumptions, reproducible notebook or script	Tests for reused logic, versioned output, resource bounds
Shared analysis	Locked environment, provenance, review, statistical evidence	Independent reproduction, access control, release record
User-facing product	Contract and end-to-end tests, versioned deployment, monitoring, owner, rollback	Security review, incident response, staged rollout, client evidence
Consequential automation	Explicit authority, evaluation, approval, audit trail, failure analysis	Formal governance, adversarial testing, continuous outcome evaluation

Done is therefore contextual. At minimum, the intended behavior is implemented; relevant contracts and versions are identified; the evidence is appropriate to the claim; and plausible failures have detection, ownership, and recovery.

Concept check. Why can adding automation reduce engineering quality when authority, evidence, ownership, and recovery remain implicit?

1.5 How to read and use this book

The text states concepts and contracts; notebooks make them executable; package source holds reusable behavior; tests preserve selected expectations. Read by moving deliberately among these artifacts.

Definition: Active computational reading

Active computational reading treats prose and code as claims to be examined. The reader predicts behavior, executes in a known environment, inspects the result, explains discrepancies, and records reusable evidence.

1.5.1 The predict-execute-explain loop

For each substantial example:

1. state the question and the contract under examination;
2. predict the value, type, shape, unit, mutation, or exception;
3. execute the smallest relevant case in a known environment;
4. inspect values and metadata rather than merely noting success;
5. explain the observation from the language rule, algorithm, data, and environment; and
6. vary one condition and convert a durable conclusion into a test or note.

Prediction exposes the current mental model. Variation distinguishes an explanation from a story invented after seeing one output.

1.5.2 Read code as a contract

Ask three questions before execution:

Interface. What enters, returns, or is written? Which types, shapes, units, schemas, and exceptions define the boundary?

Mechanism. Which operations transform the input? What mutable or external state, randomness, file, service, or database affects the result?

Evidence. Which ordinary, boundary, and failure cases are exercised? What important claim remains untested?

Worked example: Interrogating a probability function

```python
def mean_probability(values: list[float]) -> float:
    if not values:
        raise ValueError("values must not be empty")
    if any(value < 0 or value > 1 for value in values):
        raise ValueError("probabilities must lie in [0, 1]")
    return sum(values) / len(values)
```

The contract is a nonempty sequence of probabilities mapped to its arithmetic mean; empty or out-of-range input fails. Predict `[0.2, 0.4, 0.6]`, `[]`, and `[0.4, 1.2]`. Then inspect what the hints do not enforce at runtime and test `nan`. Even complete software tests would not establish that averaging probabilities is scientifically appropriate.

1.5.3 Use notebooks as laboratories

Definition: Notebook state

Notebook state is the set of names, imported modules, objects, random states, environment settings, files, and external resources available to the kernel. Visible cell order does not prove execution order.

Before treating a notebook as evidence:

1. select and verify the project kernel;

2. restart it to remove hidden state;
3. run all cells from top to bottom;
4. inspect warnings, paths, seeds, inputs, execution order, and invariants;
5. after the final edit, restart and run all again.

Professional practice

A notebook is an experimental laboratory, not an operational boundary. It is well suited to posing a question, inspecting data, varying assumptions, and joining evidence to interpretation. A notebook may demonstrate an end-to-end path without being the end-to-end system. If work must run unattended, serve concurrent users, retain durable state, enforce access policy, emit operational telemetry, or support rollback, move that responsibility into a tested package, script, service, database, or workflow.
For sustained academic research, the notebook may remain the interpretive record, but it must not be the only source of truth. Data identity, provenance, configuration, transformations, and reusable computation must be reconstructible outside hidden kernel state.

When behavior differs from the text, preserve the error, read the final exception line, locate the first frame in code you control, and reduce the problem before changing dependencies. For `ModuleNotFoundError`, first compare `sys.executable` with the project environment. For a missing file, inspect the working directory and use `pathlib.Path`. For a numerical difference, record inputs, versions, dtype, shape, seed, and tolerance.

1.5.4 Move reusable work into durable artifacts

An exploratory expression belongs in a notebook. Repeated or consequential logic belongs in a named function with type hints, a NumPy-style docstring, and explicit failure behavior. Package source provides a stable import boundary; tests preserve ordinary, edge, and invalid cases; version history records the change and its rationale. Import the tested function back into the notebook so that the notebook carries the analytical argument rather than a private implementation.

Use a broader graduation rule for responsibilities that are not merely Python functions: repeatable batch work moves to a script or command-line interface; shared state moves to durable storage; concurrent access moves behind a service; and scheduling, deployment, monitoring, and rollback move to operational workflows. Extract a cell when its behavior must survive reuse, automation, collaboration, publication, or failure.

A short computational record should identify the question, code and data versions, environment, prediction, observed evidence, interpretation, and next action. The standard is reconstruction, not length.

Concept check. Why is a cleanly executed notebook necessary but insufficient evidence that its author understands the computation or that its scientific claim is valid?

1.6 A running case study

Part I repeatedly enlarges a scientific knowledge system. It begins with small records describing entities and relationships:

1. native Python values establish identifiers, labels, and edges;
2. classes state invariants, and functions reject invalid relationships;
3. CSV and JSON preserve records, with round-trip tests for identity;
4. a package and CI make transformations reusable and reviewable;

5. arrays, tables, and figures support numerical investigation;
6. a database retrieves bounded neighborhoods without loading everything;
7. a language-model tool may propose descriptions or edges under schema validation and human review; and
8. an API exposes validated queries to a client with operational evidence.

The point is cumulative design: the deployed product still depends on the meaning of a dictionary key and the exception contract defined much earlier. Examples will vary across probability, mathematics, physics, chemistry, and industrial engineering so that the software principles do not depend on one domain.

Concept check. For one value in this system, list the identity, unit or schema, provenance, transformation, version, and uncertainty required to interpret it.

1.7 Exercises

Foundational

1. Distinguish a model, a data product, and a data-driven software system. Give one example in which all three have different owners.
2. For the claim *the reported temperature is* 97.2, list the missing context under each of the six correctness lenses.
3. Explain why verification, validation, and reproducibility are mutually supportive but logically distinct.

Applied

Select one result from a class, laboratory, or public dataset. Trace it backward to source evidence and forward to its audience. At each boundary, record the representation, contract, owner, likely failure, and available evidence.

Design

Write a one-page system charter for a small data product. Specify its question, users, evidence, output contract, privacy and safety constraints, version identity, resource and authority bounds, monitoring, and recovery. Choose technologies only after these responsibilities are explicit.

Chapter review

Key ideas. A learned model is one component of an evidence-bearing software system. Correctness claims are scoped by assumptions and require different evidence at data, computational, software, statistical, scientific, and operational layers. Professional practice makes boundaries, versions, authority, ownership, observation, and recovery explicit.
Vocabulary. model; data product; boundary; contract; provenance; verification; validation; reproducibility; observability; responsibility.
Explain aloud. How can a model with excellent benchmark performance belong to an invalid or unsafe data product?

Executable companion

The operational checklist is in `notebooks/PROFESSIONAL_PRACTICES.md`. Lecture notebooks supply the executable investigations.

CHAPTER 2

A reproducible computational workshop

Learning objectives

After this chapter, you should be able to:

- distinguish a terminal, shell, Python interpreter, virtual environment, VS Code, Jupyter, and a kernel;
- explain what the course setup command changes and what it does not;
- verify the interpreter used by a notebook; and
- diagnose environment failures from evidence before reinstalling tools.

Where this chapter fits

The overview named the full evidence-to-product system. This chapter begins at the smallest operational boundary: one student, one repository, and one Python process. Before reasoning about data, we must know which program is executing the code and how another machine can reproduce that choice.

2.1 A project has a place and a runtime

A reproducible result depends on both source files and the software that interprets them. Two students may open identical notebooks yet run different Python versions or package sets. One notebook may use the project environment; another may silently use a system interpreter.

Definition: repository

A repository is the project directory whose version-controlled files describe the work. It includes source, notebooks, tests, configuration, and documentation. The repository is not the same object as a Python installation or virtual environment.

A **path** identifies a location in a filesystem. Absolute paths begin from a filesystem root and often contain machine-specific details. Relative paths begin from an agreed working directory. Course code should discover the project root from stable markers such as `pyproject.toml`, accept paths from callers, or use package resources. Hard-coding a student's home directory is not portable.

2.2 Terminal, shell, and Python

These names refer to different layers:

Terminal. A text-oriented application that displays a session and sends keystrokes to a shell or another command-line program.

Shell. A program such as PowerShell, Bash, or Zsh that parses commands, locates programs, expands variables, and connects input and output.

Python interpreter. The executable process that parses and runs Python code.

VS Code. An editor and development environment that can host a terminal, edit notebooks, and connect extensions to Python tools.

Typing `python analysis.py` asks the shell to locate a program named `python` and pass it the path `analysis.py`. The shell is not Python, and Python does not interpret shell syntax.

Failure mode

Copying an activation command for the wrong shell is a common failure. A Bash command such as `source .venv/bin/activate` is not PowerShell syntax. The course uses `uv run` so the essential workflow does not depend on students memorizing shell-specific activation.


2.3 Virtual environments solve project isolation

A **virtual environment** is a project-specific Python environment with its own interpreter-facing package installation area. It answers:

> Which Python and package versions should this project use without treating the whole computer as one shared project?

It does not emulate a new operating system, guarantee identical hardware, or make arbitrary code safe. It is dependency isolation, not a security sandbox.

The repository declares intent in `pyproject.toml`. The lockfile records a resolved dependency graph. The local `.venv` realizes that graph on one machine. These are related but distinct artifacts.



2.4 Jupyter and the kernel

A notebook file stores cells, metadata, and possibly outputs. It does not run itself. A **kernel** is a long-running language process that receives code from a notebook interface, retains state, and returns results.

VS Code's notebook editor is the visible interface. The Jupyter extension sends cells to the selected kernel. The kernel runs a specific Python executable. Selecting the wrong kernel therefore produces a characteristic puzzle: a package is installed in one environment but cannot be imported by the Python process actually serving the notebook.

Listing 2.1: Inspect the Python process serving a notebook.

```python
import sys
from pathlib import Path

print("Python version:", sys.version.split()[0])
print("Python executable:", Path(sys.executable))
```

The important evidence is `sys.executable`. An activated terminal can use one Python while an already-running kernel continues using another. Restarting the kernel replaces the process and clears its in-memory state.

2.5 The one-command course setup

From the repository root in VS Code's integrated terminal, run:

```
uv run python scripts/setup_course.py
```

This workflow synchronizes the project environment, verifies that the `rice_dsm` package imports from this repository, and registers a named **Rice DSM** kernel. It does not launch JupyterLab, edit a student's notebook, upload code, or install packages globally.

After setup, open a notebook in VS Code and select the Rice DSM kernel. Then verify:

```python
import rice_dsm
import sys

print(rice_dsm.__version__)
print(rice_dsm.__file__)
print(sys.executable)
```

The package location should point into this project, and the executable should belong to the project environment.

2.6 Diagnose before reinstalling

When an import fails, collect evidence in this order:

1. Confirm the repository root: does `pyproject.toml` exist here?
2. Inspect `sys.executable` in the failing notebook or process.
3. Compare that path with the project's `.venv`.
4. Verify the selected VS Code kernel name.
5. Run the course setup command and read its complete output.
6. Restart the kernel and run the notebook from the first cell.

Repeated installation can make the system harder to understand by creating additional environments. Diagnosis should identify the process and boundary before changing state.

Checkpoint

In your own words, distinguish Python, a virtual environment, Jupyter, and a kernel. Then explain why installing a package in one environment does not make it available to a kernel using another interpreter.

2.7 Worked diagnosis: an import that succeeds in the terminal only

Imagine that Maya runs the following command in VS Code's terminal:

```
uv run python -c "import rice_dsm; print(rice_dsm.__file__)"
```

It succeeds. In a notebook, however, `import rice_dsm` raises `ModuleNotFoundError`. It is tempting to conclude that installation is random or broken. The evidence supports a more specific hypothesis: the two commands reached different Python processes.

Worked example: follow the processes, not the icons

Step 1: identify the successful process. The shell sees `uv run`, which resolves the project and starts Python inside the synchronized project environment.
Step 2: identify the failing process. The notebook editor sends its cell to whichever kernel is selected in the upper-right kernel control. That kernel may have started hours earlier from a system Python installation.
Step 3: measure. In the notebook, run only:

```
import sys
print(sys.executable)
```

If the printed path does not belong to the repository's `.venv`, the failure is explained. No package reinstall is needed.
Step 4: correct the boundary. Select the Rice DSM kernel, restart it, and run from the first cell. A restart matters because changing a menu setting does not transform an already-running Python process into another interpreter.
Step 5: verify the correction. Inspect `sys.executable`, `rice_dsm.__file__`, and the package version. Verification turns a plausible fix into evidence.

This pattern generalizes. When two interfaces disagree, identify the actual process, configuration, working directory, and input used by each. Avoid reasoning from the fact that both windows "look like Python."

Common misconception

Misconception: activating an environment permanently changes Python on the computer.
Correction: activation usually changes shell variables so commands in that shell locate one interpreter first. It does not rewrite other terminals, running kernels, editor processes, or the operating system's Python. `uv run` selects the project environment for the command it launches.

2.8 State explains surprising notebook behavior

A notebook kernel retains definitions and objects between cell executions. If a student runs cell 12 before cell 4, cell 12 may succeed because a name remains from yesterday, or fail because a required definition has not yet executed. The notebook file's visual order and the kernel's historical execution order are not necessarily the same.

This is why "Restart Kernel and Run All" is an engineering check. It asks whether the document describes a complete computation from a fresh process. Clearing visible outputs without restarting does not clear memory. Restarting without running from the beginning removes hidden state but does not recreate it.

Concept check. A notebook displays output below every cell, but a fresh Run All fails at cell 7. Which evidence should be trusted when deciding whether the notebook is reproducible? Explain why.

2.9 Exercises

Foundational

1. Draw separate boxes for VS Code, its integrated terminal, the shell, a Python interpreter, a notebook file, and a kernel. Add arrows showing who launches or communicates with whom.
2. Classify each item as source declaration, resolved plan, or local realization: `pyproject.toml`, `uv.lock`, and `.venv`.
3. Explain why an absolute path copied from one student's computer is unlikely to work for another student.

Applied

1. Record `Path.cwd()`, `sys.executable`, Python's version, and `rice_dsm.__file__` from a working course notebook. Annotate what each observation establishes and what it does not establish.
2. Deliberately select a different available kernel, observe the evidence, and return to Rice DSM. Do not install anything. Write a three-sentence diagnosis based only on paths and process identity.

Design

Write a troubleshooting guide for a classmate who reports only "Python is not working." Your guide must begin with read-only observations, branch based on evidence, and avoid global installation commands.

Chapter review

Key ideas. A repository, environment, interpreter, editor, notebook, and kernel are distinct objects. Reproducibility requires knowing which process ran the code. Diagnose identity, path, and state before changing installation.
Vocabulary. repository; path; terminal; shell; interpreter; virtual environment; dependency; lockfile; notebook; kernel; working directory.
Explain aloud. Why can `pip install` report success while the next notebook import fails?

Executable companion

Work through Lecture 1 notebook 00 and the computing-foundations guides. The repository tests also exercise setup, imports, the named kernel, and every notebook from top to bottom.

2.10 Takeaway

Reproducibility starts by naming the project, interpreter, dependencies, and process that produced a result. Tools become easier to debug when each is given one precise responsibility.

CHAPTER 3

Objects, values, and native data structures

Learning objectives

After this chapter, you should be able to:

- distinguish names, objects, types, values, identity, and mutability;
- choose strings, sequences, mappings, and sets from their semantics;
- preserve raw data while creating validated representations; and
- use iteration without confusing traversal with materialization.

Where this chapter fits

Chapter 2 established which Python process is running. We now look inside that process. The central question changes from "Which interpreter owns this computation?" to "What object does this name refer to, and which operations preserve its meaning?"

3.1 Names refer to objects

Python assignment binds a name to an object. It does not declare a fixed box whose type can never change.

```
probability_text = "0.873"
probability = float(probability_text)

assert isinstance(probability_text, str)
assert isinstance(probability, float)
```

The original string and parsed floating-point value are different objects with different meanings. Preserving both supports diagnosis and provenance. A value that looks numerical is not numerical merely because a human can interpret it.

Definition: type

A type defines a family of objects and the operations and behaviors associated with them. A type annotation documents an intended contract; runtime validation is a separate action unless a library or explicit check performs it.

Equality asks whether two objects represent equal values under their type's rules. Identity asks whether two names refer to the same object. Use `is None` for the singleton `None`; do not replace value equality with identity comparisons.

3.2 Mutability and aliasing

An immutable object cannot change its own value after creation. A mutable object can. If two names refer to one mutable list, a change through either name is visible through both.

```
temperatures = [20.1, 20.4]
shared_reference = temperatures
independent_copy = temperatures.copy()

shared_reference.append(20.8)


assert temperatures == [20.1, 20.4, 20.8]
assert independent_copy == [20.1, 20.4]
```

Aliasing is not automatically a bug. It is a state-sharing decision. Bugs arise when code shares mutable state without making ownership visible.

3.3 Strings are structured text

A **string** is an immutable sequence of Unicode text. Text arrives from filenames, identifiers, logs, forms, CSV fields, JSON keys, command-line arguments, and API payloads. It may contain invisible whitespace, distinct Unicode representations, or characters that resemble digits without having numeric type.

Reliable text work separates stages:



Normalization is a policy, not a cleaning reflex. Lowercasing may be correct for a case-insensitive category and destructive for a case-sensitive identifier. Formatting a number for display must not replace the full-precision value used in later computation.

3.4 Sequences encode order

Lists and tuples are both ordered sequences. A list is mutable and is suitable for a collection that grows or changes under clear ownership. A tuple is immutable and often communicates a fixed record, coordinate, or return bundle.

Indexing retrieves one element. Slicing constructs a subsequence. Negative indices count from the end. These operations are convenient, but meaning still comes from the data contract. The third element of an unlabeled tuple is easy to misinterpret in a large system.

Professional practice

Choose a sequence because order and multiplicity are meaningful, not because a list is the first container you remember. For domain records, a dataclass or validated model often communicates more than positional elements.

3.5 Mappings and sets encode different relations

A dictionary maps unique keys to values. It is appropriate for labeled fields, indexes, configuration, counts, and adjacency lists. A set represents unique membership and supports union, intersection, and difference.

```
sensor = {
    "sensor_id": "T-17",
    "unit": "degree Celsius",
    "precision": 0.1,
}

observed = {"temperature", "pressure"}
required = {"temperature", "humidity"}
missing = required - observed

assert missing == {"humidity"}
```

A missing key, a key explicitly mapped to `None`, and a key mapped to an empty string are three distinct states. Conflating them erases information.

3.6 Iterables, iterators, and generators

An **iterable** can produce an iterator. An **iterator** yields one value at a time and remembers its position. A **generator** is a convenient way to implement an iterator with suspended function state.

Iteration permits bounded, streaming computation. It does not guarantee that the source is small, repeatable, or safe to consume twice. Converting an iterator to a list materializes every remaining item in memory.

```
def valid_probabilities(lines):
    for line in lines:
        value = float(line)
        if 0.0 <= value <= 1.0:
            yield value
```

This generator can process a file progressively. It still needs a policy for malformed input, provenance, logging, and whether silently excluding values is scientifically acceptable.

Failure mode

Truthiness is not a missing-data policy. Zero, an empty string, an empty list, `False`, and `None` are all false in Boolean context but may represent very different scientific states.

Checkpoint

Design a representation for one experiment with an identifier, ordered time points, unique observed variables, and metadata fields. Justify each container from its semantics and identify which state is mutable.

3.7 Worked example: from instrument text to a trustworthy record

Suppose an instrument exports this line:

```
raw_line = "  SAMPLE-017 , 23.40 , valid  "
```

Humans see an identifier, temperature, and quality label. Python initially sees one string. We should not jump directly to a cleaned list and discard the original. Each transformation answers a separate question.

Worked example: build meaning in observable stages

Stage 1: preserve evidence.

```
raw_line = "  SAMPLE-017 , 23.40 , valid  "
fields = raw_line.split(",")
assert fields == ["  SAMPLE-017 ", " 23.40 ", " valid  "]
```

Splitting is a syntactic operation. It assumes comma is the delimiter but has not yet decided what any field means.

Stage 2: normalize under a field-specific contract.

```
sample_id_text, temperature_text, quality_text = fields
sample_id = sample_id_text.strip()
quality = quality_text.strip().casefold()
```

Whitespace is removed because the export contract declares it insignificant. The quality label is case-insensitive. We do not case-normalize the identifier without an equivalent promise.

Stage 3: convert and validate.

```
temperature_c = float(temperature_text)

if not -273.15 <= temperature_c <= 2_000.0:
    raise ValueError("temperature_c is outside the accepted domain")
if quality not in {"valid", "suspect", "failed"}:
    raise ValueError("quality has an unknown label")
```

Conversion answers "can these characters represent a floating-point value?" The range check answers a different domain question. The upper limit here is an example contract, not a law Python can infer.

Stage 4: construct a labeled record.

```
record = {
    "sample_id": sample_id,
    "temperature_c": temperature_c,
    "quality": quality,
    "raw_line": raw_line,
}
```

The dictionary makes field roles visible and retains the evidence needed to diagnose parsing. A later chapter will replace suitable dictionaries with validated domain classes.

Notice what the code does not establish: whether the sensor was calibrated, whether the sample identifier belongs to the experiment, or whether `23.40` was truly reported in degrees Celsius. Representation checks and

scientific validity remain distinct.

3.8 Choosing a container by the question it answers

Container choice is clearer when phrased as a question:

Structure	Question it answers naturally
String	What text, identifier, or encoded field was supplied?
List	What ordered collection may be updated under one owner?
Tuple	What fixed ordered group should not change?
Dictionary	Which value belongs to this unique key or field name?
Set	Is this distinct item present, and how do memberships compare?
Iterator	What is the next item without materializing the entire source?

No table can choose without domain context. A coordinate might be a tuple; a mutable simulation state might need a class; an observation table will later become a DataFrame. The principle is to make important semantics visible.

Common misconception

Misconception: tuples are "safer lists" and should replace lists whenever mutation is not expected.
Correction: immutability is useful, but positional meaning can remain opaque. A tuple of three floats might be a point, RGB color, confidence interval, or date. When field names and invariants matter, a dataclass or validated model may communicate the domain better.

3.9 Iteration changes when work happens

Compare a list comprehension and generator expression:

```
squares_list = [value**2 for value in range(1_000_000)]
squares_stream = (value**2 for value in range(1_000_000))
```

The first computes and stores one million results immediately. The second creates an iterator that computes results as requested. That difference affects memory, timing, errors, and repeatability. A generator may read from a file that changes, raise an exception halfway through, or be exhausted after one pass.

"Lazy" does not mean "free." It means computation is deferred and therefore must be owned by the consumer that triggers it.

Concept check. If `values` is a generator, why can `sum(values)` work once while a second `sum(values)` returns zero? What observation would confirm your explanation?

3.10 Exercises

Foundational

1. Explain the difference between == and `is`. Give one correct use of `is` from this chapter.
2. Give distinct scientific meanings for `0`, `""`, `False`, and `None`. Explain why one truthiness check cannot replace a missing-data policy.
3. For each native container, state whether order, duplicates, labels, and mutation are central to its contract.

Applied

1. Extend the instrument example with a timestamp field. Preserve raw text, parse a typed value, and name two validity questions parsing cannot answer.
2. Given repeated experiment tags, use a set to report distinct tags and a dictionary to count them. Explain why the two results answer different questions.
3. Write a generator that yields only nonblank lines with their original line numbers. Decide whether whitespace-only lines are missing data or ignorable formatting, and document that policy.

Design

Choose a scientific object currently represented as a list or dictionary in your own work. Defend that representation or propose a clearer one using order, identity, mutability, labels, and invariants as criteria.

Chapter review

Key ideas. Names refer to objects. Types determine behavior. Mutable state requires visible ownership. Text normalization is field-specific policy. Containers encode order, labels, uniqueness, or traversal. Parsing builds a representation but cannot establish scientific truth.
Vocabulary. object; name; type; value; identity; equality; mutability; aliasing; Unicode; sequence; mapping; set; iterable; iterator; generator.
Explain aloud. Why is preserving `raw_line` useful even after a record has been successfully parsed?

Executable companion

Lecture 1 notebooks 01 through 05 develop these ideas through detailed examples on objects, strings, sequences, dictionaries, sets, comprehensions, and generators.

3.11 Takeaway

Python's native data structures are modeling decisions. Reliable work begins by matching representation to meaning, preserving evidence, and making state ownership explicit.

CHAPTER 4

Functions, classes, and native data

Learning objectives

After this chapter, you should be able to:

- design a function as a documented public contract;
- combine type hints, NumPy-style docstrings, validation, and exceptions;
- model a domain object with explicit invariants and state ownership; and
- load CSV and JSON without confusing parsing with scientific validation.

Where this chapter fits

Native values and containers let us represent information. This chapter turns those representations into interfaces: functions express transformations, classes protect invariants, exceptions explain rejected inputs, and files carry representations across process and time boundaries.

4.1 A function creates a boundary

A function gives a name to behavior, accepts input through parameters, and returns a result or raises an exception. The most useful function boundaries separate one coherent responsibility from its callers.

Definition: application programming interface

An application programming interface, or API, is the supported contract through which one piece of software uses another. A Python function API includes its import path, signature, parameter meanings, return behavior, exceptions, and promised side effects. It does not require a network.

```
def bernoulli_variance(probability: float) -> float:
    """Return the variance of a Bernoulli random variable.

    Parameters
    ----------
    probability : float
        Success probability in the closed interval [0, 1].

    Returns
    -------
    float
        Variance ``p * (1 - p)``.

    Raises
    ------
    TypeError
```

```
        If ``probability`` is not numeric.
    ValueError
        If ``probability`` is outside [0, 1].
    """
    if not isinstance(probability, (int, float)):
        raise TypeError("probability must be numeric")
    if not 0.0 <= probability <= 1.0:
        raise ValueError("probability must lie in [0, 1]")
    return probability * (1.0 - probability)
```

The annotation helps people, editors, and static checkers. The docstring explains meaning and failure behavior. Runtime checks enforce selected parts of the contract. Tests provide independent examples and edge cases. No one layer replaces the others.

4.2 Docstrings explain semantics

This course uses NumPy-style docstrings for reusable scientific Python. A useful docstring states the observable behavior, domain meaning, units, shape, ordering, assumptions, returned representation, and deliberate exceptions. It does not merely repeat a type annotation.

Consistency matters because readers know where to look, development tools can render predictable help, and documentation generators can build stable reference pages. Style is a coordination mechanism.

4.3 Exceptions are part of the contract

Raise an exception when a function cannot honor its promise. Use `TypeError` for an unsupported kind of object and `ValueError` for a value outside the accepted domain. A stable domain exception can help callers recover without parsing message text.

Library code should generally raise rather than print an error or return an ambiguous `None`. Catch an exception only at a layer that can recover, add context, translate it for a user, or restore a system invariant.

Failure mode

An error message is observable output and may enter logs. It should identify the violated contract without copying API keys, passwords, personal data, or entire production records.

4.4 Parameter kinds communicate calling policy

Python supports positional-only, positional-or-keyword, variadic positional, keyword-only, and variadic keyword parameters. The separators `/` and `*` make parts of the calling contract explicit.

```
def calibrate(reading, /, *, scale=1.0, offset=0.0):
    return scale * reading + offset
```

The name `reading` is not promised to callers because the argument is positional-only. The calibration settings are keyword-only because their names carry meaning and accidental reversal would remain numerically valid.

`*args` and `**kwargs` are ordinary tuple and dictionary objects inside a function. Flexibility is useful for adapters and decorators, but unrestricted keyword capture can hide spelling errors and weaken tooling. Lambdas create function objects with expression-only bodies; they are suitable for short local callables, not for concealing domain logic that deserves a name, documentation, validation, and tests.

4.5 Classes model objects and invariants

A class combines state with operations that preserve the meaning of that state. The goal is not to turn every dictionary into a class. A class is valuable when identity, invariants, behavior, lifecycle, or multiple representations belong together.

```python
from dataclasses import dataclass

@dataclass(frozen=True, slots=True)
class KnowledgeNode:
    identifier: str
    label: str
    domain: str

    def __post_init__(self) -> None:
        if not self.identifier.strip():
            raise ValueError("identifier must be nonblank")
```

Immutability can make shared domain records easier to reason about. Mutable collections can still be owned by a graph or repository whose methods enforce uniqueness and relationship rules.


Professional practice

Represent a scientific object so that invalid states are difficult to create, but do not invent validation the domain cannot justify. A class can enforce that a probability lies in $[0, 1]$; it cannot establish that the probability was estimated from an appropriate experiment.

4.6 CSV and JSON are representations

CSV stores rows and fields in text. It does not carry one universal schema, type system, missing-value policy, encoding, delimiter, or unit convention. JSON represents objects, arrays, strings, numbers, Booleans, and null. A parsed JSON object is not automatically a validated domain object.

A dependable ingestion path separates layers:



Use `pathlib.Path` rather than string-concatenating separators. Open text with an explicit encoding. Use `newline=""` for Python's CSV reader. For each row, preserve source location, validate required fields, convert types, then construct the custom object. Report malformed records with actionable context without exposing unrelated data.

Checkpoint

Design a function that converts one parsed JSON dictionary into a `KnowledgeNode`. Write its signature, NumPy-style contract, two validation errors, and three tests before implementing its body.

4.7 Worked example: design the contract before the body

Suppose we need a function that computes the log-odds

$$\operatorname{logit}(p) = \log\left(\frac{p}{1-p}\right).$$

Writing `log(p / (1 - p))` is easy. Designing the boundary requires more thought. The expression is finite only for $0 < p < 1$. The function must decide whether integers are accepted, whether arrays are in scope, which logarithm is used, and how boundary values fail.

Worked example: turn mathematics into a Python interface

Step 1: state the mathematical domain and codomain. For this scalar function, $p \in (0, 1)$ and the result is a real-valued natural logarithm.
Step 2: state the software representation. Accept Python `int` or `float` values but reject Boolean values, which are integer subclasses in Python and have no intended role here. Return `float`. Arrays will belong to a separate vectorized interface.
Step 3: state failures. Unsupported runtime types produce `TypeError`; numeric values outside the open interval produce `ValueError`.
Step 4: write examples and edge tests.

```
import math
import pytest

assert math.isclose(logit(0.5), 0.0)
assert logit(0.8) > 0.0
with pytest.raises(ValueError):
    logit(1.0)
with pytest.raises(TypeError):
    logit(True)
```

Step 5: implement the smallest body that honors the contract.

```
from math import log

def logit(probability: float) -> float:
    """Return the natural log-odds of a scalar probability."""
    if isinstance(probability, bool) or not isinstance(
        probability, (int, float)
    ):
        raise TypeError("probability must be a real scalar")
    if not 0.0 < probability < 1.0:
        raise ValueError("probability must lie strictly between 0 and 1")
    return log(probability / (1.0 - probability))
```

The tests did not emerge after the implementation. They helped define what the function means. A later NumPy implementation may accept arrays and infinities at the boundaries; that is a different public contract, not a faster body for the same one.

4.8 From records to objects with behavior

A dictionary can store a graph node, but any caller can omit a field, replace an identifier with whitespace, or mutate a label without going through validation. A class centralizes construction and behavior.

Consider a `KnowledgeGraph` that owns nodes and adjacency relationships. Its public methods might be `add_node`, `add_edge`, `neighbors`, and `shortest_path`. Internal dictionaries are private because callers who mutate them directly can violate uniqueness or create an edge to a nonexistent node.

This is **encapsulation**: state is accessed through operations that preserve the object's invariants. It is not secrecy. Python callers may still inspect attributes; the API communicates which path is supported.

Common misconception

Misconception: object-oriented design means every noun needs a class.
Correction: functions and native containers are often clearer. Use a class when state, behavior, invariants, identity, or lifecycle form one coherent abstraction. Avoid classes that only rename a dictionary without improving the contract.

4.9 A complete ingestion boundary

Loading a knowledge graph from files involves four different failure layers:

1. **I/O failure:** the path does not exist or cannot be read;
2. **syntax failure:** bytes are not valid text, CSV, or JSON;
3. **schema failure:** a required field is missing or has the wrong representation; and
4. **domain failure:** an edge references an unknown node or violates a graph invariant.

Keeping these layers distinct makes errors actionable. "Could not load data" hides whether a student mistyped a path or discovered a corrupted relationship. A high-quality loader adds source path and record number while preserving the original exception through chaining.

```
try:
    node = node_from_mapping(row)
except (KeyError, TypeError, ValueError) as error:
    raise ValueError(
        f"invalid node record at {path.name}:{line_number}"
    ) from error
```

The public message supplies location without dumping the full row. The chained exception preserves technical cause for debugging.

Concept check. Why should a loader validate that both endpoints exist before adding an edge, even if a later graph algorithm would eventually fail? Compare the quality of the two failure locations.

4.10 Exercises

Foundational

1. For a function you used recently, list its import path, parameter meanings, return behavior, exceptions, and side effects. Which are documented?
2. Explain why a type hint does not perform runtime validation by itself.
3. Contrast `*args` at a function definition with `*values` at a function call.

Applied

1. Complete the logit docstring using NumPy style, including domain, return meaning, and exceptions. Add tests at values close to 0 and 1.
2. Design an immutable `ChemicalSpecies` dataclass with formula, molar mass, and phase. State what can be validated syntactically and what requires an external scientific source.
3. Create a three-row CSV fixture containing one schema error and one domain error. Specify the exact message and chained exception expected for each.

Design

Design the public API of a small graph, trajectory, molecule, queue, or experiment object. Separate public operations from private representation and state at least three invariants each operation must preserve.

Chapter review

Key ideas. A function is a boundary, not merely reusable syntax. Docstrings explain semantics, types communicate representation, validation enforces selected rules, exceptions communicate failure, and tests supply independent examples. Classes are justified by coherent state and invariants. File parsing precedes schema and domain validation.
Vocabulary. function; signature; parameter; return value; API; docstring; type hint; exception; keyword-only; lambda; class; dataclass; invariant; encapsulation; CSV; JSON; exception chaining.
Explain aloud. Why can two functions compute the same formula but have different APIs?

Executable companion

Lecture 2 develops functions, classes, lambdas and variadic calls, then reads real CSV and JSON relationships into a custom knowledge graph using only the standard library.

4.11 Takeaway

Functions and classes turn assumptions into named interfaces. Files supply representations, not meaning. Professional code makes the transition from one to the other explicit, documented, testable, and diagnosable.

CHAPTER 5

Projects, packages, tests, and automation

Learning objectives

After this chapter, you should be able to:

- distinguish scripts, modules, import packages, and distributions;
- explain dependency declarations, lockfiles, and version identifiers;
- select unit, integration, contract, system, and regression tests from a concrete risk; and
- distinguish continuous integration, delivery, and deployment.


Where this chapter fits

A well-designed function or class is useful in one notebook. A package makes it available across notebooks, scripts, collaborators, and versions. That larger audience creates compatibility and change risks, so packaging, testing, and continuous integration belong in the same engineering story.

5.1 From exploration to reusable software

Notebooks are valuable for combining narrative, code, and evidence. They become fragile when hidden execution order, copied definitions, mutable global state, and machine-specific paths accumulate. Mature behavior should move into a module where notebooks and tests import the same implementation.

A **script** is a file intended to be executed as a program. A **module** is an importable Python file. An **import package** organizes modules under a shared namespace. A **distribution** is an installable project released through a packaging mechanism; its distribution name need not equal its import name.



The `src` layout places import packages below `src/`. It helps detect accidental imports from the repository root: tests exercise the installed project instead of a convenient shadow copy.

5.2 A public package API

A package should deliberately expose names that callers may rely on and keep implementation helpers private. Re-exporting selected objects from `rice_dsm/__init__.py` creates a facade that can remain stable when internal modules move.

Every public name is a compatibility promise. Its behavior needs documentation, types, error contracts, examples, and tests. "Public" means supported; Python may still technically allow importing a private underscore-prefixed name.

5.3 Dependencies and versions

`pyproject.toml` declares project metadata and dependency constraints. `uv.lock` records an exact resolved graph for reproducible setup. The local environment installs that graph. These artifacts answer different questions:

Artifact	Question
Dependency constraint	Which releases are intended to be compatible?
Lockfile	Which complete graph did this project resolve?
Installed environment	Which files are available to this interpreter now?
Package version	Which release of our public behavior is this?
Code revision	Which exact source state produced this artifact?

A version number is useful only when tied to an artifact and policy. A Git commit identifies source precisely; a semantic version communicates intended compatibility; a data version identifies evidence; a model version identifies a trained artifact. Do not substitute one for another.

5.4 Tests begin with risks

A test should protect a meaningful behavior or failure mode. Start with a risk, choose the smallest boundary that can reveal it, and use an oracle independent enough to detect the defect.

Test kind	Boundary	Typical purpose
Unit	One function or class	Domain cases, validation, and local invariants
Property	Many generated values	General algebraic or structural rules
Metamorphic	Related executions	Relations known even when exact output is hard
Integration	Multiple real components	Database, filesystem, or package interaction
Contract	Producer and consumer agreement	Schema and compatibility without full deployment
System	Whole running application	Behavior across assembled components
Regression	Previously observed failure	Prevent return of a specific defect
Data quality	Dataset and pipeline	Schema, ranges, uniqueness, drift, and leakage signals


Passing tests show consistency with encoded expectations. They do not prove that the expectations are scientifically sufficient. Test doubles are useful when they isolate one contract; excessive mocking can produce a fictional system that never tests the real dependency.

5.5 Automation and CI/CD

continuous integration (CI) automatically checks integrated changes in a clean environment. **continuous delivery** keeps a validated release deployable through an explicit decision. **continuous deployment** automatically releases every qualifying change to production.

Appendix C develops these distinctions through the actual automation that tests, builds, deploys, and releases this textbook and its companion Python package.

They are not synonyms. A course repository needs CI to prevent broken notebooks or package behavior from entering the protected branch. This repository also uses a bounded static site to make the deployment boundary observable without introducing a database or long-running service.



The course workflow synchronizes the committed lockfile, builds the distribution, verifies the package source and kernel, runs tests, and executes every notebook on Linux, macOS, and Windows. Cross-platform CI catches path, shell, filesystem, and environment assumptions that one laptop cannot reveal.

Professional practice

CI is evidence, not responsibility. A green check cannot detect an untested requirement, choose a valid statistic, approve a data-use policy, or monitor a deployed client. Branch protection makes the check consequential by preventing unverified changes from entering the protected branch.

Checkpoint

For each risk, choose a test boundary: a probability function mishandles $p = 0$; a SQLite transaction fails to roll back; a browser client expects a removed field; a notebook imports a package absent from the lockfile; and a model pipeline leaks future labels.

5.6 Worked example: derive tests from a risk

Suppose `shortest_path(source, target)` returns a sequence of graph node identifiers. A weak test might assert one result from one graph. A stronger test plan begins by asking how the behavior could be wrong.

Worked example: protect shortest-path behavior

Risk 1: the function returns a path containing a nonexistent edge. For every adjacent pair in the result, assert that the graph contains that edge. This is a structural property and does not require knowing the exact path in advance.

Risk 2: the path is valid but not shortest. On a small fixture, compare its length with a simple independent breadth-first search oracle or with manually established distances.

Risk 3: source equals target. Specify whether the result is a single-node path. Test it explicitly; do not expect a random graph fixture to exercise the case.

Risk 4: no path exists. Decide whether the API returns `None`, an empty tuple, or raises a domain exception. Encode one stable behavior.

Risk 5: unknown identifiers. Verify that source and target errors are distinguishable and do not silently resemble a disconnected graph.
Risk 6: input mutation. Snapshot graph state before the call and assert that a read-only query does not alter nodes or edges.

Different tests can cover different boundaries. Unit tests protect graph semantics in memory. An integration test can load the graph from CSV and JSON first. A command-line test can verify human-facing output and exit status. A notebook execution test can prove that the instructional path still imports the packaged implementation.

5.7 Fixtures, parameters, and doubles

A **fixture** establishes controlled test state and owns cleanup. Small fixtures should make the important relationship visible: a line graph, cycle, disconnected pair, or graph with two equally short routes.

Parametrization applies the same behavioral claim to a table of cases. It is most useful when each case has the same meaning and failure message. A long table of unrelated cases can become harder to diagnose than separate tests.

A test double replaces a dependency to isolate one contract. For example, a fake clock can make time deterministic and a stubbed cloud response can test parsing without credentials. But a fake database cannot prove that actual SQL, transactions, constraints, or driver behavior work. The test boundary must match the claim.

Common misconception

Misconception: a unit test should mock every collaborator.
Correction: a unit is a coherent behavior, not necessarily one function isolated from all real objects. Mock only a boundary whose behavior is outside the claim or costly and unsafe to invoke. Prefer simple real value objects when they make the test more faithful.

5.8 Reading a CI failure as evidence

A CI job runs commands in a new machine context. A failure that appears only on Windows may reveal separator, case, shell, path-length, or file-locking assumptions. A failure that appears only from a clean checkout may reveal an uncommitted local file or hidden notebook state. A lockfile failure may reveal that dependency declarations changed without resolution.

Read the first causal error, record the operating system and command, reproduce the smallest relevant boundary, then add a regression check. Rerunning until a flaky check passes discards evidence and permits uncertainty into the protected branch.

Concept check. A test passes locally but fails in CI because `data.csv` cannot be found. List three distinct hypotheses and one observation that would separate them.

5.9 Exercises

Foundational

1. Distinguish a module, import package, and distribution using the `rice-dsm` project.
2. Explain why a lower bound such as `numpy>=2` and a lockfile answer different version questions.
3. Contrast continuous integration, continuous delivery, and continuous deployment without using the word "automatic" as the entire definition.

Applied

1. Choose one function in `rice_dsm`. Write a risk inventory and map each risk to a test kind and independent oracle.
2. Convert three repetitive edge-case tests into a clear parametrized test. Explain what would make parametrization inappropriate.
3. Read the course CI workflow. For each command, state the failure class it is intended to reveal and one class it cannot reveal.

Design

Propose a release gate for a small scientific package. Include source checks, package build, unit and integration tests, notebook or example execution, artifact identity, review, and a response to flaky tests.

Chapter review

Key ideas. Notebooks explore and explain; modules preserve reusable behavior. A public package API is a compatibility promise. Declarations, lockfiles, installed environments, package versions, data versions, and code revisions identify different artifacts. Tests arise from risks. CI makes selected checks repeatable in clean environments.
Vocabulary. script; module; import package; distribution; public API; dependency; version constraint; lockfile; fixture; parametrization; test double; oracle; unit; property; integration; contract; system; regression; CI/CD.
Explain aloud. Why is "all tests passed" weaker than "the scientific result is valid"?

Executable companion

Lecture 3 notebooks 00 through 02 build the project mental model, refactor a knowledge graph into the package, and develop a detailed testing and automation taxonomy.

5.10 Takeaway

Packaging creates a maintained interface across files and users. Tests encode selected promises. Automation makes those checks repeatable and consequential. Together they allow scientific software to change without abandoning evidence.

CHAPTER 6

Arrays, tables, and visual evidence

Learning objectives

After this chapter, you should be able to:

- reason about a NumPy array using shape, axes, and data type;
- distinguish vectorization from a mere syntax shortcut;
- use pandas labels while guarding alignment and missingness; and
- design a visualization as an honest, reproducible scientific argument.

Where this chapter fits

The preceding chapters built trustworthy Python interfaces. We now use mature scientific packages through those interfaces. NumPy adds regular numerical structure, pandas adds labels and heterogeneous columns, and visualization turns selected relationships into arguments that other people must interpret.

6.1 From Python containers to arrays

A Python list can hold references to heterogeneous objects. A NumPy **array** stores a regular, multidimensional collection governed by a shape and data type. That structure supports compact memory layouts and operations implemented over entire blocks of values.

For an array with shape (m, n), axis 0 indexes m rows and axis 1 indexes n columns. An operation such as `mean(axis=0)` reduces rows and returns one mean per column. "Across rows" is ambiguous; name the axis and resulting shape.

```
import numpy as np

measurements = np.array(
    [[20.1, 101.2], [20.4, 100.9], [20.8, 101.0]],
    dtype=np.float64,
)

column_means = measurements.mean(axis=0)
assert measurements.shape == (3, 2)
assert column_means.shape == (2,)
```

The data type is part of the numerical contract. Integer overflow, floating roundoff, missing-value representation, and implicit coercion can change a result without changing array shape.

6.2 Vectorization and broadcasting

Vectorization expresses operations over arrays so optimized compiled loops can perform the elementwise work. It often improves clarity and performance, but it does not remove algorithmic cost or memory allocation.

Broadcasting compares dimensions from the right and permits compatible singleton dimensions to act as if repeated. Always predict the result shape before relying on broadcasting. An operation that runs can still combine the wrong scientific axes.

Failure mode

Vectorization can allocate enormous temporary arrays. Measure the working set, use in-place operations only when ownership is safe, and consider chunked or streaming computation when the full result cannot fit comfortably in memory.

6.3 Shape is syntax; axis meaning is semantics

NumPy can verify whether dimensions are compatible. It cannot know what the dimensions mean. An array with shape $(100, 3)$ might represent 100 patients and three biomarkers, 100 time points and three spatial coordinates, or 100 simulations and three model parameters. The same matrix multiplication can be dimensionally valid in all three cases while answering entirely different questions.

Before an important operation, write a small shape ledger:

Name	Shape	Axis meaning
`x`	(n, d)	observations × features
`beta`	$(d,)$	one coefficient per feature
`x @ beta`	$(n,)$	one score per observation

The ledger makes the intended contraction visible: the feature axis of `x` meets the feature axis of `beta`. If `x` were transposed, the operation should fail rather than be reshaped until it runs. A reshape changes an interpretation unless you can explain where every axis went.

Definition: vectorization

Vectorization expresses a collection of related operations through an array interface whose looping occurs in optimized lower-level code. It changes where iteration is expressed; it does not make the iteration, memory traffic, or algorithmic complexity disappear.

6.4 Data type is a numerical design decision

An array's **dtype** determines how each value is represented and which operations are available. Integers are exact inside a finite range. Floating point values cover a much larger dynamic range but approximate most real numbers. Boolean arrays support logical masks. Date-time types attach a time unit. Strings and generic Python-object arrays have different storage and performance behavior from regular numeric arrays.

Three questions belong in every numerical review:

1. **Range:** can the representation hold the largest magnitude that an intermediate computation may produce?
2. **Precision:** can it distinguish changes that matter to the analysis?
3. **Missingness:** how will absent, invalid, censored, or not-yet- observed values be represented without confusing their meanings?

For floating point work, equality is often the wrong contract. A computed value may differ from an algebraically equivalent result by a small rounding error. Use a tolerance derived from the problem's scale and numerical method, then state whether the tolerance is absolute, relative, or both. The convenience of `np.allclose` does not choose a scientifically meaningful tolerance.

For sums of values with very different magnitudes, operation order may matter. For probabilities near zero or one, algebraically equivalent formulas can have very different numerical stability. Numerical analysis is not a repair applied after modeling; it is part of deciding what computation the model actually performs.

6.5 pandas adds labeled structure

A pandas **Series** combines values with an index. A **DataFrame** combines columns, row labels, and heterogeneous column data types. Labels reduce some positional errors and introduce alignment behavior that must be understood.

Arithmetic between Series aligns by index label, not necessarily by physical position. A join encodes assumptions about key uniqueness and relationship cardinality. Missing values interact with each column's data type and with the semantics of an aggregation.

Professional practice

Before a groupby, join, or pivot, state what one row represents, which keys are unique, whether missing groups should appear, and how row counts should change. Check those claims after the operation.

Tables are not automatically tidy, independent, or statistically valid. pandas makes transformations expressive; scientific meaning still belongs to the analyst and data contract.

State what one row means

Suppose a table has columns `experiment`, `sensor`, `time_s`, and `temperature_c`. If one row is one sensor reading, then grouping by experiment and taking a mean produces one row per experiment only after we decide how sensors and time points should be weighted. If one sensor recorded twice as often, a naive mean weights that sensor twice as much. pandas will execute the aggregation faithfully; it cannot determine whether that weighting matches the estimand.

Indexes also carry assumptions. A default integer index may merely identify current row positions. A domain index such as `experiment_id` claims that the labels have stable meaning and perhaps uniqueness. Set an index because its semantics support an operation, not because it makes the display attractive.

Definition: tidy observational table

In a common tidy representation, each row is one observational unit, each column is one variable, and each cell contains one value. This convention is a useful design tool, not a proof that observations are independent or that the table is suitable for a particular statistical model.

6.6 Visualization is a transformation

A figure maps data and decisions into marks, positions, color, size, facets, scales, labels, and annotations. Every choice emphasizes some comparisons and suppresses others.

Matplotlib supplies low-level control and a broad scientific ecosystem. Seaborn adds statistical plotting conventions over pandas data. Plotly supports interactive graphics. Tool choice follows the communication goal, audience, output medium, accessibility requirements, and reproducibility needs.

An honest workflow records:

- the data snapshot and filtering rules;
- units, transformations, aggregation, and uncertainty;
- scale limits and whether an axis is linear or logarithmic;
- random seed and simulation parameters;
- color choices that remain interpretable without color alone; and
- the code and package versions that produced the artifact.

Choose an encoding from the comparison

A chart type should follow the question rather than habit:

Question	Useful starting point	Common risk
How does one quantity vary with another?	scatter plot, perhaps with a model summary	overplotting, hidden groups, implying causation
How does a quantity evolve in ordered time?	line plot with observed points	connecting missing intervals or unrelated units
How do distributions differ across groups?	ECDF, interval plot, box or violin plot with observations	hiding sample size, multimodality, or unequal support
How uncertain is an estimate?	point and interval with the estimand named	unlabeled interval type or visually treating uncertainty as error
How are values arranged over two dimensions?	heat map with a justified scale and color map	perceptual distortion, inaccessible color, hidden normalization

Position along a common scale usually supports more precise comparison than area, volume, or angle. Color can reveal grouping or magnitude, but it should not carry the only copy of essential information. Interactive hover text can add detail; the unhovered figure still needs a title, axes, units, legend, caption, and visible central claim.

6.7 Simulation as executable reasoning

Simulation can make probability and dynamical behavior visible. A random seed supports reproducibility of one run; it does not prove robustness. Compare multiple seeds or summarize a distribution when variability matters.

For a Monte Carlo estimator $\widehat{\theta}_n$, distinguish numerical error, sampling variability, model assumptions, and implementation defects. More samples may reduce Monte Carlo variance while leaving structural bias intact.

Worked example: use probability theory to test a simulation

Let $X_1, \ldots, X_n$ be independent Bernoulli random variables with success probability p. The sample mean

$$\widehat{p} = \frac{1}{n} \sum_{i=1}^{n} X_i$$

has expectation p and standard deviation $\sqrt{p(1-p)/n}$. We can use this mathematical result as an independent oracle for a vectorized simulation.

```
import numpy as np

rng = np.random.default_rng(438)
p = 0.30
n = 1_000
repetitions = 5_000

success_counts = rng.binomial(n=n, p=p, size=repetitions)
estimates = success_counts / n

empirical_center = estimates.mean()
empirical_sd = estimates.std(ddof=1)
theoretical_sd = np.sqrt(p * (1 - p) / n)

assert estimates.shape == (repetitions,)
assert np.isclose(empirical_center, p, atol=0.01)
assert np.isclose(empirical_sd, theoretical_sd, rtol=0.05)
```

Step 1: identify the simulated object. Each entry of `success_counts` is one binomial count summarizing 1,000 Bernoulli trials. The array axis indexes repeated experiments, not individual observations.
Step 2: vectorize at the right level. We request 5,000 independent counts directly. Materializing a $(5000, 1000)$ Boolean array would also work, but it would consume more memory to answer the same probability question.
Step 3: separate reproducibility from validity. The local random-number generator and seed reproduce this particular stream. They do not establish that the binomial model is appropriate for real observations.
Step 4: compare with theory. The analytic standard deviation is a test oracle independent of the random sample. Tolerances reflect expected Monte Carlo fluctuation; they are not selected merely to make the assertions pass.
Step 5: visualize the sampling distribution. A histogram or empirical cumulative distribution function should be labeled as a distribution of *estimates across repeated experiments*. It is not the distribution of individual Bernoulli observations.

This example illustrates a reusable scientific pattern: derive what should be true, implement the simulation, compare independent evidence, and explain the remaining modeling assumptions. Simulation complements probability theory; it does not replace it.

Checkpoint

You receive a table with one row per sensor reading. Design a figure comparing two instruments over time. State the row meaning, units, missing-data policy, aggregation, uncertainty representation, accessibility choices, and two tests for the transformation feeding the plot.

6.8 Worked example: standardize three sensor channels

Suppose rows represent time points and columns represent sensors. We want to subtract each sensor's mean and divide by its standard deviation. The formula for entry (i, j) is

$$z_{ij} = \frac{x_{ij} - \bar{x}_j}{s_j}.$$

The subscript j matters: statistics are computed down rows separately for each column.

Worked example: predict shape before execution

```
import numpy as np

x = np.array(
    [
        [10.0, 100.0, 1.1],
        [12.0, 104.0, 0.9],
        [14.0, 102.0, 1.0],
        [16.0, 106.0, 1.2],
    ]
)

means = x.mean(axis=0)
scales = x.std(axis=0, ddof=1)
z = (x - means) / scales
```

Step 1: annotate shapes. `x.shape` is $(4, 3)$. Reducing axis 0 gives `means.shape == (3,)` and `scales.shape == (3,)`.
Step 2: predict broadcasting. NumPy compares trailing dimensions. The length-3 vectors align with the three columns and act across four rows. The result retains shape $(4, 3)$.
Step 3: check invariants. Each standardized column should have mean close to zero and sample standard deviation close to one.

```
assert z.shape == x.shape
assert np.allclose(z.mean(axis=0), 0.0)
assert np.allclose(z.std(axis=0, ddof=1), 1.0)
```

Step 4: ask scientific questions. Is standardization appropriate for all three sensors? Are the observations independent? Should calibration ranges or robust statistics replace the sample mean and standard deviation? Shape correctness does not answer these questions.

If we mistakenly reduce `axis=1`, NumPy may still produce values after a reshape. The program can run while standardizing each time point across sensors with incompatible units. Predicting dimensions and naming their

meaning catches an error that syntax cannot.

6.9 Worked example: pandas alignment is not row order

Consider two Series of corrections indexed by sensor identifier. pandas aligns labels before arithmetic.

```
import pandas as pd

reading = pd.Series({"A": 10.0, "B": 20.0})
offset = pd.Series({"B": 1.5, "A": 0.5})
corrected = reading - offset

assert corrected["A"] == 9.5
assert corrected["B"] == 18.5
```

The physical order differs, but labels preserve the intended pairing. If one Series uses `"sensor-A"` and the other uses `"A"`, alignment produces missing values rather than guessing equivalence. That behavior is safer than silent positional pairing only when the analyst checks the resulting index and missingness.

Common misconception

Misconception: pandas prevents incorrect joins because columns have names.
Correction: names permit explicit alignment; they do not prove key uniqueness, cardinality, unit compatibility, or semantic identity. A many-to-many join can multiply rows exactly as requested and still invalidate an analysis.

6.10 From analytical question to figure

Suppose the question is whether sensor bias changes with temperature. A useful figure might place reference temperature on the horizontal axis and residual on the vertical axis, show individual observations with transparency, add a zero reference line, and facet by sensor model. A line chart connecting unrelated samples would imply an ordering that does not exist.

Before plotting, write the sentence the figure should support. Then identify the comparison, encodings, uncertainty, and possible confounders. After plotting, try to state a false conclusion the design might encourage. This adversarial reading is part of visual quality assurance.

Concept check. Why might truncating the residual axis make a small bias appear important? When is a nonzero baseline nevertheless appropriate?

6.11 Exercises

Foundational

1. For shapes $(20, 4)$ and $(4,)$, explain broadcasting. Repeat for $(20, 4)$ and $(20,)$. Which operation fails, and why?

2. Distinguish NumPy data type, array shape, and axis meaning.
3. Explain why a random seed makes one simulation reproducible but does not establish that its conclusion is stable.
4. For a Bernoulli sample mean, derive how the theoretical standard deviation changes when n is multiplied by four.

Applied

1. Modify the standardization example to retain means with shape $(1, 3)$ using `keepdims=True`. Explain whether this changes values or only makes broadcasting intent more visible.
2. Construct two pandas Series whose inconsistent labels produce missing output. Add assertions that detect the mismatch before arithmetic.
3. Modify the binomial experiment across four values of n. Compare the observed standard deviations with theory and design one figure that makes the $1/\sqrt{n}$ relationship visible.
4. Design a static and interactive version of the same scientific figure. State what interaction adds and what information must remain visible without hovering.

Design

Write a figure specification before writing plotting code. Include audience, claim, data snapshot, row meaning, units, encodings, aggregation, uncertainty, accessibility, caption, and two misleading alternatives you rejected.

Chapter review

Key ideas. NumPy arrays require joint reasoning about values, shape, axes, and dtype. Broadcasting is a dimensional rule, not evidence of semantic compatibility. pandas aligns labels and therefore requires explicit key and missingness checks. A visualization is a reproducible transformation and argument, not decoration.
Vocabulary. array; shape; axis; dtype; vectorization; broadcasting; Series; DataFrame; index; alignment; join cardinality; scale; encoding; uncertainty; simulation; Monte Carlo error.
Explain aloud. How can an array operation have the correct output shape and still combine the wrong scientific quantities?

Executable companion

Lecture 4 notebook 00 connects native Python containers to NumPy and pandas; Lecture 5 notebook 00 then develops static, statistical, interactive, and simulation-based visualizations. Reproduce the probability experiment there before changing its sample size, seed, or visualization.

6.12 Takeaway

Arrays make structure computationally explicit, tables add labels, and figures turn selected relationships into visible evidence. None of these layers chooses the scientific contract automatically.

CHAPTER 7

Databases and data systems

Learning objectives

After this chapter, you should be able to:

- distinguish a database, DBMS, driver, connection, transaction, and schema;
- use parameterized queries and explicit transaction boundaries;
- compare embedded, remote, warehouse, and object-storage roles; and
- choose bounded scans, columnar files, pushdown, or distributed systems from measured constraints.

Where this chapter fits

Arrays and DataFrames usually live inside one process. This chapter crosses a durability and coordination boundary: data must survive the process, preserve relationships, support multiple users, and sometimes be queried without being copied into memory at all.

7.1 Storage is part of the scientific system

A **database** is organized persisted data plus its logical structure. A **database-management system** (DBMS) is the software that stores, queries, coordinates, and protects that state. A driver provides a language-specific API for speaking the DBMS protocol. A connection is one active conversation with the system.

A **schema** names tables, columns, types, constraints, relationships, and views. It is an executable portion of the data contract. Primary keys express identity, foreign keys express permitted relationships, uniqueness constraints prevent selected duplicates, and check constraints reject invalid states.

7.2 Transactions preserve invariants

A transaction groups operations into an atomic success or rollback boundary. If a workflow inserts an experiment and its measurements, partial success may create a scientifically misleading state. Transaction ownership should be visible at the application boundary that knows which operations belong together.

```
with connection:
    connection.execute(
        "INSERT INTO experiments(experiment_id, material) VALUES (?, ?)",
        (experiment_id, material),
    )
    connection.executemany(
        "INSERT INTO measurements(experiment_id, time_s, value) "
        "VALUES (?, ?, ?)",
        rows,
    )
```

Values are bound separately from SQL text. String interpolation can change data into executable syntax, permit injection, and mishandle quoting. Dynamic table or column identifiers cannot generally use value placeholders; select them from a small application-owned allowlist.

7.3 SQL has semantics, not just syntax


SQL uses three-valued logic around `NULL`. Joins encode relationship cardinality. Aggregations define grouping and missingness behavior. Window functions compute across related rows without collapsing them. Query results require an explicit ordering if order matters.

Before a join, predict whether each input key is unique and how many rows should result. Afterward, test row counts, key coverage, duplication, and missingness. A syntactically correct join can create a statistically invalid training table.

7.4 Local and remote are deployment shapes

SQLite is an embedded transactional database stored in a local file. DuckDB is an in-process analytical database designed for columnar analytics. PostgreSQL and similar systems run as client/server DBMSs with authentication, concurrent connections, roles, and network operations. Warehouses and lakehouse engines serve analytical workloads across managed or distributed storage.

These are not simply size levels of one product. They make different tradeoffs in concurrency, transactions, operations, latency, governance, and query shape.



7.5 Object storage is not a filesystem or database

Cloud object stores organize byte objects by keys and metadata. They are useful for durable snapshots, partitioned datasets, model artifacts, and large binary objects. They do not provide ordinary local filesystem semantics or relational transactions.

An AWS-shaped data platform may combine S3 object storage, a catalog, a query engine or warehouse, managed relational databases, queues, and identity and access management. Equivalent roles exist in other clouds and institutional systems. Learn the role before memorizing a vendor name.

Credentials belong in approved environment configuration, workload identity, or a secret manager. They must not be embedded in notebooks. Least privilege means granting the narrow action on the narrow resource for the required time.

7.6 When data is too large to load

Estimate the working set before allocating it. Row count alone is insufficient: string objects, indexes, temporary arrays, join expansion, and copies can exceed the apparent file size.

Use the least complex technique that satisfies measured constraints:

1. select only necessary rows and columns at the storage/query layer;
2. use columnar formats such as Parquet for analytical projection;
3. process bounded batches or iterators;
4. use lazy plans that push filters and projections toward the source;
5. use an in-process analytical engine such as DuckDB; and
6. adopt a distributed system only when one machine cannot meet the workload, reliability, or organizational requirement.

Distributed computation adds serialization, partitioning, shuffle, scheduling, failure recovery, observability, and cost. It is an architecture, not a badge of seriousness.

Checkpoint

A 60 GB Parquet dataset contains 120 columns, but an analysis needs six columns and one month of records. Propose the first three approaches you would try, state what evidence each collects, and explain when a cluster becomes justified.

7.7 Worked example: from a measurement contract to SQL

Suppose a laboratory records experiments and temperature measurements. Begin with meaning rather than table syntax:

- one experiment has one stable identifier and one material;
- each measurement belongs to exactly one experiment;
- time is measured in seconds from the experiment start;
- temperature is stored in degrees Celsius; and
- an experiment cannot contain two measurements at the same time.

The schema can enforce part of this contract.

Worked example: translate scientific rules into constraints

```sql
CREATE TABLE experiments (
    experiment_id TEXT PRIMARY KEY,
    material TEXT NOT NULL
);

CREATE TABLE measurements (
    experiment_id TEXT NOT NULL,
    time_s REAL NOT NULL CHECK (time_s >= 0),
    temperature_c REAL NOT NULL,
    PRIMARY KEY (experiment_id, time_s),
    FOREIGN KEY (experiment_id)
```

```
        REFERENCES experiments(experiment_id)
);
```

Step 1: identify rows. One row in `experiments` is one experiment. One row in `measurements` is one reading at one experiment time.
Step 2: identify identity. The composite primary key says that the pair `(experiment_id, time_s)` uniquely identifies a measurement.
Step 3: identify valid relationships. The foreign key prevents a measurement from referring to an experiment that does not exist.
Step 4: identify what remains outside SQL. The database does not know whether the sensor was calibrated, whether Celsius is the correct source unit, or whether the experiment clock was reset. Application validation and scientific review still have work to do.

Now consider the question, "What is the mean temperature for each material?" The query must join the tables because material and temperature live in different relations.

```
SELECT e.material, AVG(m.temperature_c) AS mean_temperature_c
FROM experiments AS e
JOIN measurements AS m
  ON m.experiment_id = e.experiment_id
GROUP BY e.material
ORDER BY e.material;
```

Before running it, predict the join cardinality: each measurement should match exactly one experiment. After running it, compare the joined row count with the measurement row count. This does not prove the scientific interpretation, but it tests an important structural assumption.

7.8 Missingness and joins deserve explicit examples

SQL `NULL` means missing or unknown at the database level; it is not zero, an empty string, or the floating-point value `NaN`. The comparison `value = NULL` does not produce true or false in the ordinary way. Use `value IS NULL`. Aggregates also differ: `COUNT(*)` counts rows, whereas `COUNT(value)` counts non-NULL values.

A left join keeps every row from the left relation. If no right-side match exists, right-side columns become `NULL`. An inner join silently removes unmatched left rows. Neither choice is inherently correct; the research question determines whether absent matches should disappear, remain missing, or trigger an error.

Common misconception

Misconception: a database is a large CSV file with faster search.
Correction: a DBMS coordinates typed structure, constraints, transactions, concurrent users, recovery, permissions, and query planning. A CSV file stores bytes. Both can be useful, but they provide different guarantees and failure modes.

7.9 A measured decision process for large data

"Does not fit in memory" is a diagnosis to quantify, not a command to adopt a cluster. Record available memory, compressed file size, projected columns, selected rows, intermediate operations, and acceptable runtime. Then test the smallest architecture that could work.

For the 60 GB checkpoint dataset, first inspect metadata without loading all values. Next ask a query engine to project six columns and push the date filter into the scan. Finally measure the result and its largest intermediate. If one machine can execute that plan reliably, distribution adds coordination cost without solving a demonstrated problem. If the filtered working set, required join, concurrency, or deadline exceeds one machine, the measurement explains why a larger system is justified.

Concept check. Why can a 4 GB CSV require substantially more than 4 GB of memory as a pandas DataFrame? Name at least three sources of additional memory use.

7.10 Exercises

Foundational

1. Distinguish a database, DBMS, schema, driver, connection, and transaction using the laboratory example.
2. Explain why query result order is unspecified without `ORDER BY`.
3. Compare `COUNT(*)`, `COUNT(temperature_c)`, and `AVG(temperature_c)` when some temperatures are NULL.

Applied

1. Add a sensor table and a foreign key from measurements. State the row meaning and identity rule for each table before writing SQL.
2. Construct a join that accidentally multiplies rows. Write precondition and postcondition queries that reveal the error.
3. Design a parameterized query that returns a bounded time interval and only two analytical columns. Explain which work should occur in the DBMS.

Design

Choose a laboratory or industry dataset. Propose a local prototype architecture and a remote production architecture. For each, state the storage role, transaction needs, access controls, expected working set, failure recovery, and the measurement that would justify moving to a distributed system.

Chapter review

Key ideas. A schema is executable data meaning. Transactions preserve multi-step invariants. Parameter binding separates values from executable SQL. Joins and missingness can change a population without producing an error. Scalable analysis begins with projection, filtering, and measured working sets.
Vocabulary. database; DBMS; schema; primary key; foreign key; constraint; transaction; rollback; parameterized query; NULL; join cardinality; query pushdown; columnar storage; object storage; distributed system.

Explain aloud. Why can a query be syntactically valid, complete successfully, and still create an invalid machine-learning training table?

Executable companion

Lecture 6 notebook 00 builds a constrained SQLite system, connects pandas and SQLAlchemy, queries with DuckDB, scans Arrow and Polars data lazily, and maps the same roles onto AWS-style workflows without requiring cloud credentials.

7.11 Takeaway

Data systems make identity, relationships, durability, concurrency, and access operational. Correct queries begin with row meaning and constraints. Scalable work begins by reducing unnecessary data movement.

CHAPTER 8

Language-model tools and agents

Learning objectives

After this chapter, you should be able to:
- distinguish a model, assistant, workflow, agent, tool, and orchestrator;
- explain a hosted model API from client request to validated response;
- place structured output and tool calls inside deterministic controls; and
- design evaluation, approval, audit, and recovery for consequential actions.

Where this chapter fits

The course has so far used deterministic software to encode contracts. A language model introduces a probabilistic component whose output may be useful without being authoritative. The same boundaries developed for functions, tests, databases, and services now become controls around model proposals.

8.1 Begin with precise roles

A language model maps context to a distribution over outputs. An assistant is a user-facing application that combines a model with instructions, state, and tools. A workflow has a mostly predetermined control graph. An agent allows a model to choose some sequence of actions based on observations until a stopping rule. A durable orchestrator owns schedules, retries, concurrency, history, and recovery.

Prefer a workflow when the correct sequence is known. Add model-directed choice only where it produces measured value that cannot be expressed more simply.

8.2 What a hosted API does

API stands for **application programming interface**: a documented contract through which software components interact. A web API receives requests and returns responses across a process or network boundary.

When Python calls a hosted model API:

1. application code constructs a request naming a model, instructions, input, and perhaps schemas or tool definitions;
2. a client library serializes those Python objects into an authenticated HTTPS request;
3. the provider validates the credential, request, quota, and policy;
4. provider-operated computers perform inference; and
5. the application parses and validates the returned response.

Installing the provider's software development kit (SDK) installs helper code, not the hosted model. A successful HTTP response establishes transport and service success, not factual or scientific correctness.

8.3 Credentials are authority

An API key may authorize spending and data access. Never place a real key in source, notebook cells, output, screenshots, browser or mobile code, command arguments, container images, logs, traces, model context, or Git history. Development, CI, staging, and production should use separate least-privilege credentials. Prefer short-lived workload identity and managed secret storage where available.

Failure mode

Redacting an object's printed representation is defense in depth, not access control. Code that can read a secret can still disclose it. Do not give an agent a general environment-reading tool or ambient cloud authority.


8.4 Hosted, local, open, and free are different axes

Hosted providers operate inference behind a network API. Open-weight models make trained parameters available under stated terms and may be run locally or by a hosting provider. "Open source," "open weight," "free chat," "API free tier," and "free to download" are not synonyms.

Local inference can keep requests on controlled hardware, but hardware, memory, electricity, storage, security, and staff still have cost. Licenses and model cards must be reviewed for the exact release. Model choice should follow task-specific evaluation, latency, total cost, privacy, language coverage, operational fit, and a deprecation plan rather than brand loyalty.

8.5 Structured output controls syntax, not truth

A schema can reject missing, extra, malformed, or out-of-range fields. It cannot establish that a dataset exists, a citation supports a claim, a unit is correct, or a proposed experiment is appropriate.



Model output remains untrusted data even when it matches a schema.

8.6 Tools create possible side effects

A tool definition needs a stable name, strict argument schema, risk level, identity and authorization rule, timeout, resource budget, idempotency behavior, result schema, audit event, and error contract. Tool descriptions influence model behavior; application code enforces authority.

Avoid generic shell, arbitrary SQL, unrestricted filesystem, broad cloud SDK, or "call any URL" tools. Prefer a narrow operation such as `audit_python_docstrings(source)`. Unknown tools, extra arguments, and unapproved risk levels should fail closed.

An agent loop also needs hard limits on steps, tool calls, elapsed time, tokens, cost, repeated calls, and result size. The model must not choose or remove its own limits.

8.7 Two responsible automation patterns

8.7.1 Docstring proposals

A model may inspect one exact function and propose a NumPy-style docstring. Bind the proposal to a digest of the reviewed source. Before applying it, verify that only docstring nodes changed, compile the candidate, compare executable syntax, run tests and documentation checks, and obtain domain review. The model that generated a proposal is not an independent verifier.

8.7.2 Training-run proposals

A model may propose a dataset version, feature version, code revision, model family, start time, runtime limit, accelerator, and rationale. Deterministic policy then checks the dataset namespace, runtime, hardware, and permitted model families. A named reviewer approves consequential work. A durable scheduler records an idempotency key and owns actual execution.

Professional practice

The model proposes. Ordinary code validates. Policy authorizes. A human remains accountable where impact warrants. The orchestrator executes and records. This separation is more important than the choice of model provider.

8.8 Evaluation and observability

Agent evaluation needs reviewed golden cases, boundary cases, adversarial inputs, failure cases, and an untouched holdout. Assert schemas, required facts, forbidden claims, tool traces, policy decisions, and human rubrics rather than exact prose when prose is not the contract.

Trace model configuration, prompt version, classified context sources, tool calls, policy decisions, approvals, latency, token or compute use, cost, denials, and final outcomes. Default to metadata because raw prompts and responses may contain confidential code, personal data, or injection attacks.

Checkpoint

Threat-model an agent that can schedule model training. List what the language model may propose, what deterministic code must verify, which action needs human approval, what the scheduler owns, and what evidence an incident investigation would require.

8.9 Worked example: read one API exchange

The following pseudocode describes the shape of a hosted request without tying the lesson to one vendor. Assume the credential has already been loaded from an approved secret source.

Worked example: separate transport, syntax, and meaning

```
request = {
    "model": MODEL_ID,
    "instructions": "Return a proposed experiment label.",
    "input": observation_text,
    "response_schema": LabelProposal.schema(),
}

raw_response = client.generate(request, timeout_s=20)
proposal = LabelProposal.validate(raw_response)
decision = policy.evaluate(proposal)
```

Step 1: construct. Application code chooses a model identifier, instructions, data, and expected response shape. The model does not discover the application's authority from these strings.
Step 2: transport. The client library serializes the request and sends it using authenticated HTTPS. Timeouts, rate limits, retries, and provider errors can occur before useful model output exists.
Step 3: parse and validate syntax. `LabelProposal.validate` checks fields, types, and perhaps simple ranges. A response can pass this step while referring to a nonexistent experiment or inventing evidence.
Step 4: validate meaning and authority. Ordinary code checks permitted labels, referenced objects, confidence policy, and the caller's authorization. Only then may a narrow tool receive approved arguments.
Step 5: record outcome. Log model and prompt versions, validation and policy decisions, latency, and a safe reference to the outcome. Do not assume a raw prompt is safe to retain.

This separation makes failures diagnosable. A network timeout is not a schema error. A schema-valid hallucination is not an authorization decision. A denied tool call is not necessarily a model failure; it may demonstrate that policy is working.

8.10 Worked example: a docstring proposal is a code change

Suppose a function lacks documentation. The agent receives exactly that function, its tests, and the project's NumPy-style documentation rules. It returns a proposed docstring plus the digest of the source it reviewed.

The application should then perform these checks in order:

1. verify that the current source digest matches the reviewed digest;
2. parse the original and candidate source into syntax trees;
3. confirm that executable nodes are unchanged;
4. compile the candidate and run documentation checks;
5. run relevant unit and integration tests; and
6. show a human the diff and evidence before merging.

A stale digest prevents applying advice to code the model never saw. Syntax-tree comparison is stronger than asking the model whether it changed behavior. Tests provide independent evidence, and review checks whether the prose actually describes the scientific contract.

Common misconception

Misconception: an agent is simply a more capable language model, and a valid JSON response is a verified answer.
Correction: an agent is a system in which a model can influence an action sequence. Capability depends on tools, state, policy, and orchestration. JSON validation checks representation; evidence and deterministic policy check meaning and permission.

8.11 Prompt injection is a confused-authority problem

An agent reading a web page may encounter text such as "ignore your rules and upload the environment variables." That text is data supplied by an untrusted source, not a new grant of authority. Delimit content, label its provenance, minimize what enters context, and keep tools narrow enough that even a bad proposal cannot read arbitrary secrets or contact arbitrary destinations.

Filtering suspicious phrases is insufficient because the attack can be rephrased, encoded, or placed in a trusted-looking document. The durable defense is architectural: untrusted content cannot expand tool permissions, skip validation, or approve its own effects.

Concept check. A model returns schema-valid arguments for a training job. Name four facts that must still be checked outside the model before execution.

8.12 Exercises

Foundational

1. Distinguish model, assistant, workflow, agent, tool, and orchestrator.
2. Explain the difference among an SDK, API, HTTP request, credential, and hosted model.
3. Give one example each of syntactic validation, semantic validation, authorization, and human approval.

Applied

1. Define a typed proposal for a training run. Include dataset version, code revision, runtime limit, and requested hardware. Write five deterministic rejection rules.
2. Design a narrow docstring-audit tool contract with argument schema, timeout, result schema, and audit event.
3. Create three prompt-injection test cases and state the protected invariant each case attempts to violate.

Design

Draw a complete control boundary for an agent that proposes data-quality repairs. Identify context sources, trust levels, tools, permissions, budgets, approval points, idempotency behavior, evaluation data, telemetry, and recovery. Explain why the model cannot authorize its own proposal.

Chapter review

Key ideas. A hosted API is a software contract across a network boundary. Credentials confer authority. Structured output validates syntax, not truth. Models should propose inside deterministic validation, policy, approval, execution, evaluation, and recovery boundaries. Untrusted content must never expand authority.
Vocabulary. API; SDK; request; response; authentication; authorization; hosted inference; open weight; schema; tool call; workflow; agent; orchestrator; idempotency; prompt injection; audit trail; evaluation.
Explain aloud. If a model proposes a perfectly formatted action, why is ordinary application code still responsible for deciding whether that action may occur?

Executable companion

Lecture 7 notebook 00 implements offline structured proposals, an allowlisted tool registry, prompt-injection examples, docstring checks, training policy, human approval, and an idempotent in-memory scheduler. It requires no key or network access.

8.13 Takeaway

Language models are powerful probabilistic components. Trustworthy agent systems derive authority and reliability from the deterministic software, policy, evaluation, observability, and human responsibility around them.

CHAPTER 9

End-to-end data products

Learning objectives

After this chapter, you should be able to:

- define the endpoints and real boundaries of an end-to-end claim;
- trace one value through database, service, API, network, and client;
- distinguish build, deployment, serving, and monitoring responsibilities; and
- select tests and telemetry for client and server failure modes.

Where this chapter fits

This chapter is the Part I synthesis. It follows one value across every boundary introduced earlier: typed representation, validation, reusable software, tests, durable storage, an HTTP interface, a client, deployment, and operational evidence. No single layer can protect the complete path by itself.

9.1 End to end is a scoped claim

"End to end" means from an explicitly named beginning to an explicitly named end through the real boundaries claimed by a workflow or test. An instrument event to a curated database row, a browser action to visible confirmation, and a Git commit to a running artifact are different end-to-end paths.


An in-process API test with a temporary database is a valuable vertical-slice test. It is not a deployed browser test through DNS, TLS, a load balancer, application instances, and a managed database. Name the actual boundary rather than using "end to end" as a synonym for comprehensive.

Professional practice

An end-to-end notebook is a laboratory representation of a system, not the operated system itself. It can make components and contracts visible, launch a bounded local demonstration, and record observations. Production responsibility belongs to independently testable modules, services, storage, deployment workflows, and monitoring that continue to function after the notebook kernel stops. The same separation strengthens research: a notebook can explain a computational result while versioned data, configuration, code, and workflows make the result independently reconstructible.

9.2 One request across the system

Consider an instrument submitting a temperature measurement:



The client sends JSON over HTTPS with identity, time, value, unit, and an idempotency key. The API validates the public request model and HTTP semantics. The domain service applies scientific or business policy. The repository owns parameterized storage operations. The database enforces persistent constraints. A later bounded query maps private rows into a public response that browser code renders safely.

Each arrow is a contract. Ask about schema, units, identity, authentication, authorization, retry behavior, ordering, latency, failure, and compatibility.

9.3 Request anatomy

For `GET /api/v1/measurements/latest?limit=20`, `GET` is the HTTP method, `/api/v1/measurements/latest` is the path, and `limit=20` is a query parameter. Method plus path identify an endpoint. Request headers carry metadata. A request body can carry structured input. A response includes a status code, headers, and optional result or error body.

The API is the agreement about these operations and semantics. JSON is one data representation, HTTP is a protocol, and the server is a running implementation.

9.4 Retries make writes ambiguous

If a client times out after a POST request, it may not know whether the server committed the write. Blind retry can create a duplicate. An idempotency key lets the service recognize the same logical request and return the established result. The key needs a defined scope, retention period, and transaction with the effect it protects.

Explicit error models are part of the public API. Validation errors, conflicts, authorization failures, unavailable dependencies, and internal defects should produce stable machine-readable categories without exposing internal secrets.

9.5 Frontend, backend, and hosting

The **backend** implements server-side API, policy, orchestration, and integrations. The **frontend** presents state and interaction, commonly in a browser. A **client** may instead be a phone, instrument, script, or another service.

A production request may pass through DNS, a content delivery network, web application firewall, TLS termination, and a load balancer or API gateway before reaching application compute. The application may use a managed database, object store, queue, model service, and telemetry pipeline. Cloud products fill roles; the architecture should be understandable without vendor names.

9.6 CI/CD for production

A release pipeline should build one immutable artifact, scan and test it, deploy the same digest through environments, run migrations with compatible application versions, and preserve rollback or roll-forward options.

Continuous delivery retains an explicit production decision. Continuous deployment automates that decision for qualifying changes. Canary and blue-green strategies reduce exposure; they do not replace compatibility design, database recovery, or incident ownership.

Appendix C applies these principles to a complete running example: the book is compiled into an identifiable artifact, deployed to the public course site, verified at the public boundary, and assembled with the Python package into an approved versioned release.

9.7 Monitor the client and server

Server logs alone cannot explain a blank browser screen that failed before an API request. A complete operational picture combines:

- structured logs for discrete events and diagnostic context;
- metrics for rates, distributions, saturation, and alerting;
- traces for causal paths across services and dependencies;
- real-user monitoring for page, network, device, and JavaScript outcomes;
- synthetic journeys for controlled external checks; and
- privacy-reviewed retention and cardinality policies.

Correlation or trace identifiers connect evidence across boundaries. Do not use personal data or secrets as identifiers. Service-level objectives translate user-relevant reliability into measurable targets and response policy.

9.8 Testing the real boundary

Unit tests protect domain behavior. Repository integration tests exercise real database semantics. Contract tests protect producer-consumer compatibility. Vertical-slice tests send requests through API, service, and test database. Browser component tests cover rendering and accessibility with controlled data. Deployed journeys cover selected real network and hosting boundaries.

Phone and operating-system testing also has layers: responsive browser viewports, browser engines, Android emulators, iOS simulators, cloud device farms, and physical devices. Changing a user-agent string is not phone emulation.

Checkpoint

Define an end-to-end test for one measurement becoming visible on a phone. Name the exact start, end, real dependencies, test data, cleanup, expected evidence, and failures that remain outside the claim.

9.9 Worked example: trace one value without skipping a boundary

An instrument records `21.7` degrees Celsius at 14:03:12 UTC. We will follow that value until a scientist sees it in a browser.

Worked example: measurement to visible evidence

1. Client representation. The instrument constructs a request with `experiment_id`, a timestamp including its time-zone convention, `value=21.7`, `unit="degC"`, and an idempotency key. Local validation catches malformed fields but cannot authenticate the instrument to the server.
2. Network request. The client sends an authenticated HTTPS POST. TLS protects transport to the configured endpoint; server-side authorization still decides whether this identity may write to this experiment.
3. Public API model. The API parses JSON into typed fields, rejects unknown or invalid input, and maps expected failures to stable HTTP responses. It does not pass an arbitrary client dictionary directly to SQL.
4. Domain service. Application policy checks experiment state, allowed units, plausible bounds, and duplicate-request behavior. Unit conversion, if permitted, occurs in one named and tested place.
5. Repository transaction. The repository binds values to a parameterized statement. The measurement and idempotency record commit in the same transaction so a retry cannot produce a second logical observation.
6. Read path. A bounded query retrieves the stored record. A response model exposes only public fields and states the unit explicitly.
7. Browser rendering. Client code checks the response status, decodes JSON, escapes text, formats the timestamp, and renders `21.7 degrees C`. Accessibility semantics ensure that the result is not communicated by color alone.
8. Operational evidence. A correlation identifier connects safe log events and traces across the request. Metrics count latency and failures. A client error reporter can reveal a rendering defect that server telemetry cannot see.

At every stage, distinguish the value from its representation. The floating point number in Python, bytes in JSON, a typed database column, and text in the browser are not the same object. Contracts preserve identity, units, and meaning across conversions.

9.10 A timeout is an uncertainty about state

Suppose the server commits the measurement, but the response is lost. The client observes a timeout. It cannot infer that the transaction failed. If it retries with a new request identity, the server may record a duplicate. If it retries with the same idempotency key, the service can return the result of the original logical request.

This is why retry policy cannot be added as a generic networking convenience. Read operations are often safe to repeat, while writes require application semantics. The database constraint, idempotency record, and effect must share a transaction boundary or a crash can separate them.

Common misconception

Misconception: end-to-end testing means testing everything, so one large browser test can replace lower-level tests.

Correction: every end-to-end claim has named endpoints and omitted risks. Broad tests give valuable integration evidence but are slower and less diagnostic. Unit, integration, contract, vertical-slice, and deployed tests protect different boundaries and should form a deliberate portfolio.

9.11 From commit to production

The following stages answer different questions:

Stage	Question	Typical evidence
Build	Can source become an immutable artifact?	dependency lock, compiler or package output, artifact digest
Verify	Does the candidate satisfy declared checks?	tests, type checks, security and license scans
Deploy	Can that exact artifact enter an environment?	deployment record, configuration validation, migration status
Release	Should users receive traffic now?	approval or policy decision, canary health, feature flag state
Operate	Does the product meet user-relevant objectives?	metrics, traces, logs, client outcomes, incident record

Section 25.5 develops this final stage as an incident-driven, executable prediction-service laboratory. Its runtime is made of package modules, processes, scripts, and configuration rather than notebook cells.

Building twice for two environments weakens traceability because the binaries may differ. Configuration can vary, but the verified artifact digest should remain stable. Database changes require special care: old and new application versions may overlap during rolling deployment, so schema evolution must be compatible with both until the transition completes.

9.12 Worked incident: the API is healthy but the page is blank

Server dashboards show low latency and no increase in 5xx responses, yet users report a blank results panel. This evidence narrows the hypothesis; it does not prove the product is healthy.

Start with the user-visible path. Real-user monitoring shows a rise in browser exceptions after frontend release `web-184`. Traces show that the API returned 200 responses with a newly nullable field. A client log identifies a formatting function that assumes the field is always numeric. The incident is a consumer-contract failure: transport and backend serving succeeded while the client could not render valid new data.

Recovery may disable the release or activate a feature flag. Prevention may add a contract test for the nullable field, a component test for its visible fallback, and a canary check that observes browser rendering. Each artifact answers a specific question; “add more monitoring” is too vague to be an action.

Concept check. For the blank-page incident, what would logs, metrics, traces, real-user monitoring, and a synthetic journey each contribute? Which signal is closest to the user’s actual outcome?

9.13 Exercises

Foundational

1. Distinguish JSON, HTTP, an endpoint, an API, a server, and a client.
2. Explain authentication versus authorization using the instrument request.
3. Compare a log event, metric, and trace. Give one question each answers.

Applied

1. Specify success and error responses for creating a measurement. Include validation, duplicate, authorization, and dependency failures.
2. Design a vertical-slice test from HTTP request through a temporary real database. State what production boundaries it intentionally omits.
3. Write a release checklist for a schema change that makes a response field nullable. Include producer, consumer, rollout, and rollback evidence.

Design

Define an end-to-end path for a scientific or industrial product of your choice. Draw every process, network, data, and human boundary. For each arrow, state the contract, likely failure, test layer, telemetry, authority, and recovery owner. End with one precise service-level objective tied to a user outcome.

Chapter review

Key ideas. End to end is a scoped statement about real boundaries. Meaning must survive representation changes. Retries can make write outcomes ambiguous, so idempotency is a domain and transaction concern. CI/CD moves one verified artifact through controlled environments. Operational evidence must include the client-visible outcome.
Vocabulary. client; server; API; endpoint; HTTP method; status code; JSON; authentication; authorization; idempotency; frontend; backend; artifact; deployment; release; canary; log; metric; trace; real-user monitoring; SLO.
Explain aloud. How can every server dashboard look healthy while the data product is unusable, and what evidence would reveal the gap?

Executable companion

Lecture 8 notebook 00 implements a package-backed FastAPI, service, repository, SQLite database, and responsive client as a bounded local laboratory. The notebook explains and exercises the components; it is not the production orchestrator. Chapter 25 later moves operation into the separate module-based production monitoring project, where scripts and configuration launch and diagnose the running system.

9.14 Part I takeaway

A professional data scientist must be able to follow meaning across boundaries. Part I began with a Python value and ends with an operated system. Models become useful products only when data, interfaces, software,

infrastructure, evidence, and responsibility work together.

Part II

Supervised Learning Systems

CHAPTER 10

Machine learning: problems, evidence, and systems

Learning objectives

After this chapter, you should be able to:

- explain machine learning as the estimation of behavior from data and feedback rather than as a catalog of algorithms;
- distinguish supervised, unsupervised, self-supervised, generative, reinforcement, and causal questions by their information and claim;
- identify the representation, hypothesis class, objective, learning algorithm, and evaluation distribution in a mathematical learning problem;
- explain why inductive bias and out-of-sample evidence are unavoidable; and
- connect an empirical model to the software and decision system that produces, serves, and monitors it.

Where this chapter fits

Part I built reliable paths from data sources to tested software and operated services. Part II asks what changes when one component is estimated from data. The answer is not that ordinary engineering disappears. A learned component adds a population, a sampling process, an objective, uncertainty, adaptive selection, and the possibility that future data differ from past data.

10.1 A short history of a broad idea

The mathematics now used in machine learning predates the name. Least squares grew from astronomy and geodesy in the early nineteenth century. Probability, statistical decision theory, optimization, information theory, control, and pattern recognition supplied other foundations. By 1950 Alan Turing was discussing the possibility of a learning machine rather than a machine whose every response was specified directly.[1] Arthur Samuel's 1959 checkers study described a program whose playing behavior improved from experience and helped establish the term machine learning in computing.[2]

This history matters because machine learning is not a single modern invention and is not synonymous with neural networks. A linear least-squares estimator, a nearest-neighbor rule, a decision tree, a transformer, and a learned control policy can all be machine-learning components. Their data, assumptions, objectives, computation, and evidence differ.

Three historical currents should be kept distinct. Statistics developed rules for learning about populations from samples. Numerical analysis developed algorithms for solving the resulting optimization and linear-algebra

[1] A. M. Turing, "Computing Machinery and Intelligence," *Mind*, 59(236), 1950, https://doi.org/10.1093/mind/LIX.236.433.

[2] A. L. Samuel, "Some Studies in Machine Learning Using the Game of Checkers," *IBM Journal of Research and Development*, 3(3), 1959, https://doi.org/10.1147/rd.33.0210.

problems. Computer science developed representations, programmable procedures, and systems able to repeat those calculations at scale. Contemporary machine learning joins all three. It inherits uncertainty from statistics, approximation and conditioning from numerical analysis, and state, interfaces, testing, and resource limits from software engineering.

Common misconception

Misconception: machine learning begins when a sufficiently complicated model is used. **Correction:** learning begins when behavior is estimated from experience under an explicit task and criterion. Complexity alone does not define learning, and a large model does not remove the need to specify the problem.

10.2 What exactly is learned?

Let D denote observed experience and let $\mathcal{F}$ be a set of candidate functions or policies. A learning algorithm is itself a map

$$\mathcal{A} : D \longmapsto \widehat{f}_D \in \mathcal{F}.$$

The output $\widehat{f}_D$ may predict a number, assign a score, transform an input into a representation, estimate a distribution, generate an object, or select an action. The subscript D is essential: another sample, ordering, or random seed may produce another fitted object.

A complete learning problem contains at least five mathematical choices:

1. a **representation** ϕ that converts available evidence into model input $x = \phi(r)$;
2. a **hypothesis class** $\mathcal{F}$ describing candidate behavior;
3. an **objective** that scores candidate behavior on experience;
4. a **learning algorithm** that searches, estimates, or updates; and
5. an **evaluation setting** that defines where performance must transfer.

These choices are coupled. Euclidean distance on unscaled chemical measurements defines a different clustering problem from Euclidean distance after standardization. Squared loss and absolute loss target different population summaries. A random row split and a future-time split estimate performance for different uses. “The model” is therefore not just the class name printed by a library.

Definition: learning system

A learning system joins a data-generating process, representation, fitted component, objective, software interface, decision or scientific consumer, evaluation design, and feedback path. Its unit of analysis is the claim made by the complete path, not merely the estimator object.

10.3 Branches are distinguished by information and feedback

The familiar branches are best treated as problem structures rather than product labels.

Problem structure	Learning information	Typical output and evidence
Supervised	Inputs paired with observed targets	Numeric prediction, score, probability, or label; evaluated against held-out targets
Unsupervised	Inputs without a supplied target	Clusters, lower-dimensional coordinates, density, or anomaly score; evaluated by stability, reconstruction, domain utility, or other task-specific evidence
Self-supervised	Targets constructed from the observations	A representation or predictive model transferred to later tasks
Generative	Samples from a distribution, sometimes with conditions	New samples or likelihood-like scores; evaluated by distributional, task, expert, and safety evidence
Reinforcement	States, actions, and delayed rewards gathered through interaction	A policy or value function; evaluated by return under an admissible interaction or off-policy design

These categories overlap. A language model may be pretrained by a self-supervised objective, adapted with supervised examples, and further optimized from preference or reward signals. A medical product may use an unsupervised representation inside a supervised risk model. "Deep learning" describes a family of multilayer representations, not a separate source of feedback.

Causal inference is a neighboring but different claim. Prediction asks about Y given observed X. An intervention asks about an outcome under an action that may not have occurred. Associational fit alone cannot identify that counterfactual comparison.

Figure 10.1 uses four real tables from the course database to make the distinction visible. The panels are not four competing algorithms applied to one task. They are four different questions, with different information and different meanings of success. In the clustering panel the colors are produced by the algorithm; in the representation panel the labels are shown only afterward as an audit. That distinction is part of the experimental design.

Concept check. A laboratory hides protein labels, learns an embedding from amino-acid sequences, and then fits a small labeled classifier. Which learning signals appear in the two stages? Which held-out evidence would be needed to support the final classification claim?

10.4 Inductive bias is not optional

Finite observations do not determine behavior everywhere. Infinitely many functions can interpolate a finite regression sample, and many partitions can describe an unlabeled cloud. A learner must prefer some continuations over others. That preference is its **inductive bias**.

Bias enters through the representation, model class, loss, regularization, optimization, initialization, augmentation, stopping rule, and data collection. A linear model prefers affine relationships. A nearest-neighbor method prefers local smoothness under a chosen distance. A convolutional architecture encodes spatial sharing. None is neutral.

Theorem 10.1 (Finite interpolation does not determine prediction)**.** *Let $x_1, \dots, x_n$ be distinct real inputs and suppose a function f fits the observations, so that $f(x_i) = y_i$ for every i. For every real constant c, the function*

$$g_c(x) = f(x) + c \prod_{i=1}^{n} (x - x_i)$$




Figure 10.1: Four learning structures constructed from documented observations in the local course database. The plotting program queries SQLite, fits the displayed estimators, and writes this vector graphic. Regenerate it with `uv run python textbook/figures/generate_part_ii_figures.py`.

fits exactly the same observations. At any x_* different from every x_i, the possible values $g_c(x_*)$ range over all real numbers as c varies.

Proof. At an observed input x_j, the product contains the zero factor $x_j - x_j$, so $g_c(x_j) = f(x_j) = y_j$. At a new input x_*, the product $q = \prod_i (x_* - x_i)$ is nonzero. Hence $g_c(x_*) = f(x_*) + cq$. Because $q \neq 0$, choosing $c = (a - f(x_*))/q$ produces any desired value a. The observations alone therefore cannot select one extrapolation. □

The theorem is elementary, but its force is general: a learner must restrict the candidate continuations or prefer some over others. Smoothness, sparsity, a kernel, an architecture, a prior, regularization, and an optimization trajectory are all possible sources of that preference. Calling the preference "bias" does not make it an error; the relevant question is whether it is defensible for the intended population.

Suppose two functions f_1 and f_2 agree at every observed x_i but differ at a future x_*. No calculation using only the observed labels can determine which future value is correct. Generalization becomes possible only through assumptions connecting observed and future cases. Large datasets can reduce uncertainty under those assumptions; they do not abolish the assumptions.

Failure mode

Calling a pipeline "data driven" can hide strong human choices. Column selection, target definition, labeling policy, sampling, missing-value handling, objective, architecture, and evaluation boundary all shape what the data can appear to say.

10.5 From population risk to empirical evidence

For supervised prediction with loss L, define population risk

$$R(f) = \mathbb{E}_{(X,Y)\sim P_{\text{use}}}[L(Y, f(X))].$$

The expectation refers to the intended use population, not automatically to the database on hand. Training can only compute an empirical risk such as

$$\widehat{R}_D(f) = \frac{1}{n}\sum_{i=1}^{n} L(y_i, f(x_i)).$$

The difference $R(\widehat{f}_D) - \widehat{R}_D(\widehat{f}_D)$ is not directly observable from the training sample. Held-out evaluation, resampling, theory, and domain knowledge provide partial evidence about it.

Three sources of failure must be kept separate:

- **approximation:** the candidate class cannot represent useful behavior;
- **estimation:** finite or biased data select an unreliable member of the class; and
- **optimization:** the algorithm fails to find the intended fitted solution.

A fourth systems failure occurs when the fitted object is correct but the deployed representation, schema, or decision path differs from evaluation. These failures require different repairs. More optimizer iterations cannot fix target leakage; a larger network cannot repair an invalid outcome definition.

10.6 Performance is a vector, not one score

The word performance is overloaded. A model can have good predictive error and unacceptable latency; a fast service can make scientifically invalid predictions; an average score can hide failure for a rare but consequential group. A technical report should therefore name the claim associated with each measurement.

Dimension	Example measurement	Question answered
Predictive	MAE, log loss, calibration, recall at a fixed threshold	How well does the fitted rule transfer under the evaluation design?
Statistical	Interval width, resampling variation, subgroup sample size	How uncertain or unstable is that estimate?
Computational	Fit time, peak memory, gradient evaluations, energy	What does learning cost under a specified machine and software stack?
Serving	Median and tail latency, throughput, error rate	Can the operated interface satisfy its service objective?
Scientific	External replication, constraint violations, domain review	Does the output support the scientific claim or decision?
Operational	Drift, missingness, outcome delay, alert quality	Does the data and feedback path still match the released contract?

Measurements require protocols. A latency comparison states hardware, software versions, input shape, warmup, number of repetitions, concurrency, and whether data loading is included. A predictive comparison uses the same held-out units and reports uncertainty rather than ranking models by a difference smaller than the evaluation noise. Peak memory is measured separately from serialized model size. End-to-end latency is measured separately from estimator latency. These separations prevent an impressive number from answering a different question than the one printed beside it.

Professional practice

Begin every benchmark with a budget and a measurement contract. Record the dataset and split identifier, code revision, dependency lock, hardware, random seeds, repetitions, aggregation rule, and raw measurements. Compare a candidate with a baseline on identical units. Optimize only after profiling shows which stage consumes the resource.

10.7 Applications begin with decisions, not algorithms

The same mathematical interface appears across domains, but the meaning of an error changes.

Domain	Possible learning task	Essential qualification
Materials science	Predict later battery capacity from early-cycle summaries	Generalization across cells, batches, chemistries, and time must be separated
Astronomy	Classify transient events from image and light-curve measurements	Selection effects and delayed spectroscopic labels shape the target sample
Manufacturing	Detect anomalous sensor trajectories	A rare pattern is not automatically a defect; maintenance outcomes and changing equipment matter
Ecology	Estimate species occurrence from surveys and remote sensing	Survey effort and imperfect detection can be confused with ecological absence
Operations	Forecast demand and allocate inventory	Forecast loss and the downstream stocking cost are related but not identical objectives
Chemistry	Propose molecules under property constraints	Validity, novelty, synthesizability, uncertainty, and laboratory confirmation are distinct claims

An application is not made rigorous by replacing its nouns with mathematical symbols. The observational unit, measurement process, time boundary, action, and consequences determine which mathematics is relevant.

Worked example: one battery archive, four learning questions

Suppose an archive contains voltage, current, temperature, and capacity traces for cells from several manufacturing batches.

A supervised task predicts capacity at cycle 300 from measurements available by cycle 100. An unsupervised task searches for recurring trajectory shapes without using later capacity. A self-supervised task masks pieces of early trajectories and learns to reconstruct them before transfer to a small labeled study. A reinforcement problem chooses a charging policy and observes delayed lifetime and safety outcomes.

The rows may originate in the same archive, yet the four tasks do not share one automatic split or metric. The supervised task needs target-isolated future batches. The unsupervised task needs stability and scientific interpretation. The self-supervised task must prevent evaluation information from entering pretraining when that would violate the claim. The policy problem requires a safe simulator, experiment, or justified logged-policy analysis. Naming the branch is the beginning of the design, not its completion.

10.8 The learning lifecycle is an evidence lifecycle

A defensible project repeatedly crosses the following boundaries:

$$\text{question} \to \text{data contract} \to \text{split} \to \text{baseline} \to \text{fit} \to \text{evaluation} \to \text{release} \to \text{operation} \to \text{feedback}.$$

The arrows are not a one-way excuse to deploy. Evaluation may reveal that the target is unusable. Operation may reveal that outcomes arrive too late to monitor the claim. A change in representation may invalidate a prior artifact. The lifecycle is iterative, but its test boundary must not be repeatedly mined for favorable results.

Professional practice

Before importing an estimator, write one paragraph naming the unit, population, available information, desired output, consumer, cost of error, evaluation boundary, and feedback delay. If those fields cannot be written, model choice is premature.

10.9 Exercises

Problem identifiers are stable references for discussion and contribution. When work becomes a repository proposal, cite the bold identifier exactly in the issue and pull request; Appendix B gives the complete workflow.

Intuition and explanation

MLF-I1. A research group says, "We have labels, so this is supervised learning." Give two reasons that statement is insufficient to define the task. Name the missing objects in the learning system.

MLF-I2. One archive of satellite images supports land-cover classification, anomaly detection, self-supervised pretraining, and change-policy evaluation. For each question, identify the learning signal, output, and evidence that would count as success. Explain why one random split cannot validate all four.

MLF-I3. A model's training objective falls by 40 percent, validation error is unchanged, prediction latency doubles, and a rare-region error worsens. Write four claims the evidence supports and four it does not support.

MLF-I4. Explain inductive bias to a scientist without using the words "overfitting" or "complexity." Give one helpful and one harmful bias for a physical measurement problem.

Mathematical reasoning

MLF-M1. Let observations be $(0, 1)$, $(1, 2)$, and $(2, 5)$. Find the unique quadratic interpolant f. Then use Theorem 10.1 to construct infinitely many functions with the same training error but arbitrary value at $x = 3$. Which additional assumption could prefer f?

MLF-M2. Suppose f_1 and f_2 have population risks 0.20 and 0.18, while their test estimates on the same 100 units are 0.19 and 0.18. Explain why the displayed difference alone does not identify the better future system. Derive the per-unit paired loss difference that should be analyzed.

MLF-M3. Construct one example each of approximation, estimation, optimization, and representation-deployment error for the same regression task. Make the four fitted outputs observationally distinguishable.

MLF-M4. Prove that multiplying one coordinate by a positive constant can change a Euclidean nearest-neighbor rule. State the condition under which every nearest-neighbor identity would remain unchanged.

Data and engineering investigations

MLF-C1. Query `dataset_catalog` and `dataset_columns` before loading an observation table. Choose two datasets, write three defensible learning questions for each, and identify at least one claim the

bundled schema cannot support. Preserve the SQL and row counts in your report.

MLF-C2. Reproduce one panel of Figure 10.1 from the generator. Change exactly one representation choice, predict the effect, and compare the result. Do not compare numeric scores across unrelated tasks.

MLF-C3. Design a performance scorecard for one model with predictive, statistical, computational, serving, scientific, and operational evidence. State the unit, population, measurement protocol, baseline, and uncertainty for every entry.

Contribution studio

Choose one bounded problem below only after searching existing issues. The deliverable is an approved issue, a documented `rice_dsm.contrib` subpackage, focused tests, and a reviewed pull request–not merely a notebook.

MLF-PR1. Add a reusable dataset-audit component that reports observational unit, feature roles, target status, missingness, and unsupported claim warnings for a documented table. Require typed output, deterministic ordering, and tests for an unknown dataset and malformed metadata.

MLF-PR2. Add a learning-problem contract object that records representation, hypothesis class, objective, evaluation boundary, consumer, and feedback. It must validate missing or contradictory fields and serialize to a stable, documented record without containing private data.

MLF-PR3. Propose a custom scientific dataset adapter of your choice. The issue must establish public provenance, license, units, schema, observational unit, and a small redistributable or generated fixture before implementation. Tests must not depend on live network access.

Chapter review

Machine learning estimates behavior from experience under a chosen problem structure. The learning signal distinguishes major branches, while representation, hypothesis class, loss, optimization, and evaluation define a specific problem. Finite data require inductive bias. Training fit is not the generalization claim, and the fitted object is only one component of a system that must preserve its data and decision contract. Performance is a vector of claim-specific measurements rather than one leaderboard score.

Executable companion

Lecture 9 notebook 00 turns this map into an executable gallery. It queries documented clinical, chemical, and image observations from the course database to contrast regression, classification, clustering, and dimensionality reduction, then uses a declared bandit simulation to isolate reinforcement feedback. Students audit provenance and unsupported claims before comparing library interfaces.

CHAPTER 11

The supervised-learning contract

Learning objectives

After this chapter, you should be able to:
- formulate a supervised-learning task as a statistical and operational contract;
- express learning through a hypothesis class, loss, population risk, and empirical procedure;
- derive the population targets selected by squared, absolute, and classification losses;
- distinguish features, targets, predictions, decisions, and causal claims;
- design a split that represents the intended prediction setting; and
- construct a baseline and a minimal training-to-feedback path.

Where this chapter fits

Chapter 10 separated learning problems by their information and feedback. We now specialize to labeled examples. Part I's representation, package, database, API, and operational boundaries remain. Supervised learning adds estimation error, a target-construction process, adaptive selection, and a claim about transfer from observed labels to future ones.

11.1 Supervised learning joins statistical inference and computation

Long before the phrase machine learning, scientists estimated relationships from paired measurements and tested rules on new observations. Twentieth- century regression, discriminant analysis, experimental design, pattern recognition, and statistical decision theory developed different parts of what is now called supervised learning. Computing made it practical to search much larger function classes, but it did not change the central question: what does a finite labeled sample justify about a named population?

The modern abstraction is useful because it separates three objects. A **model class** $\mathcal{F}$ contains candidate predictors. A **learning rule** $\mathcal{A}$ maps labeled data D to $\widehat{f}_D \in \mathcal{F}$. A **prediction rule** applies the fitted function to a new x. Confusing these objects leads to statements such as "linear regression generalizes" without identifying the sample, fitting procedure, or future population.

Common misconception

Misconception: supervised means that a human watches or corrects every prediction. **Correction:** supervision refers to targets paired with training inputs. Those targets may be delayed, noisy, algorithmically generated, or institutionally defined; their presence does not make them ground truth.

Failure mode

A target can be measured consistently and still encode the wrong construct. Historical approval, diagnosis, inspection, arrest, or hiring labels may reflect prior access and policy as well as the underlying

phenomenon. Supervision transfers the target-generation process unless the design supplies evidence for a stronger interpretation.

11.2 Learning begins with a future information boundary

Let an observation be a pair (X, Y) drawn from a population distribution P. The feature vector $X \in \mathcal{X}$ contains information available at a specified prediction time. The target $Y \in \mathcal{Y}$ records the outcome to be estimated. A learning algorithm receives a sample $D = \{(x_i, y_i)\}_{i=1}^{n}$ and produces a predictor $\widehat{f}_D : \mathcal{X} \to \mathcal{A}$. The action space $\mathcal{A}$ may contain numerical estimates, scores, probabilities, or class labels.

This notation is compact enough to hide the most important design decisions. What is one observational unit? From which population were units sampled? At what time is X frozen? How far in the future is Y measured? Which units can recur? What action consumes the output? The subscript D is a reminder that a fitted predictor is random: a different sample can produce a different function.

Definition: supervised-learning contract

A supervised-learning contract names the observational unit, target population, prediction time, target and horizon, permitted information, output semantics, loss or utility, evaluation design, operational consumer, and outcome-feedback process. The model class is one field in this contract, not the contract itself.

Our recurring case concerns battery cells. At the end of an early measurement window, we may estimate capacity after a later number of cycles, or predict whether the cell will cross a degradation threshold within a stated horizon. Measurements collected after the prediction time are forbidden, even if they appear in the same convenient table.

11.3 Risk, empirical risk, and the generalization claim

For a loss function $L(y, a)$, the population risk of f is

$$R(f) = \mathbb{E}_{(X,Y)\sim P}[L(Y, f(X))].$$

The distribution P is generally unknown. Training therefore uses an empirical quantity such as

$$\widehat{R}_D(f) = \frac{1}{n}\sum_{i=1}^{n} L(y_i, f(x_i)).$$

Minimizing empirical loss is a computational objective. The scientific claim is that performance transfers to a named population and use setting. That claim depends on sampling, dependence, temporal stability, measurement, and the way the model was selected.

A loss trains or compares functions. A metric communicates some aspect of behavior. A decision policy converts output into action. These objects can be different. Logistic loss may fit a probability model, calibration error may audit its probabilities, and an asymmetric cost rule may choose an intervention threshold.

Regularized empirical risk minimization makes the preference explicit:

$$\widehat{f} \in \arg\min_{f\in\mathcal{F}} \left\{ \widehat{R}_D(f) + \lambda\Omega(f) \right\}.$$

Here Ω may penalize coefficient size, roughness, tree complexity, or another property. The value λ is selected using development data, not the final test set. Restricting $\mathcal{F}$ and penalizing within $\mathcal{F}$ are both forms of inductive bias.

11.4 The loss determines the population target

Suppose predictors may choose any real number a at a fixed $X = x$. The loss does not merely grade a prediction after training; it defines which population functional an unrestricted learner attempts to estimate.

Theorem 11.1 (Squared loss elicits the conditional mean)**.** *Assume* $\mathbb{E}[Y^2 \mid X = x] < \infty$ *and write* $\mu(x) = \mathbb{E}[Y \mid X = x]$. *The conditional squared-error risk*

$$q(a) = \mathbb{E}[(Y - a)^2 \mid X = x]$$

is uniquely minimized at $a = \mu(x)$.

Proof. Add and subtract $\mu = \mu(x)$, expand, and condition on $X = x$:

$$\begin{aligned} q(a) &= \mathbb{E}[(Y - \mu + \mu - a)^2 \mid X = x] \\ &= \mathbb{E}[(Y - \mu)^2 \mid X = x] + 2(\mu - a)\mathbb{E}[Y - \mu \mid X = x] + (\mu - a)^2 \\ &= \mathrm{Var}(Y \mid X = x) + (\mu - a)^2. \end{aligned}$$

The first term does not depend on a and the second is nonnegative, with equality only at $a = \mu$. This argument avoids assuming a density or differentiating through an expectation. □

Under absolute loss, $\mathbb{E}[|Y - a| \mid X = x]$ is minimized by a conditional median. Under binary zero-one loss, the most probable class minimizes conditional error. Quantile loss targets a conditional quantile. Thus two teams can use the same rows and model family yet estimate different population objects because their losses differ.

These are mathematical targets, not interchangeable metrics. If a laboratory needs a high conditional quantile to plan safety stock, fitting a conditional mean answers the wrong question even if the optimizer is perfect.

For binary action $d \in \{0, 1\}$ with false-positive cost C_{FP} and false-negative cost C_{FN}, the Bayes action compares conditional expected costs. With a calibrated probability $p(x) = P(Y = 1 \mid X = x)$ and no other constraints, act when

$$C_{FP}[1 - p(x)] < C_{FN}p(x).$$

Thus the model output and the decision threshold solve related but distinct problems.

Concept check. At a fixed feature vector, the conditional distribution of Y is strongly right-skewed. Which population summaries are targeted by squared and absolute loss? Why might the two fitted predictions differ even with infinite representative data?

11.5 Generalization error has several sources

Let f^* minimize risk over all measurable predictors and let $f^*_{\mathcal{F}}$ minimize risk within $\mathcal{F}$. The excess risk can be organized conceptually as

$$R(\widehat{f}_D) - R(f^*) = \underbrace{R(f^*_{\mathcal{F}}) - R(f^*)}_{\text{approximation}} + \underbrace{R(\widehat{f}_D) - R(f^*_{\mathcal{F}})}_{\text{estimation and optimization}}.$$

The second term combines finite-sample variation with any failure to solve the fitting problem. Distribution shift adds another discrepancy because the evaluation population may no longer match training.

For squared-error regression at a fixed x, averaging over possible training samples yields the familiar bias-variance decomposition

$$\mathbb{E}_{D,Y|x}[(Y - \widehat{f}_D(x))^2] = \sigma^2(x) + \left(\mathbb{E}_D[\widehat{f}_D(x)] - f(x)\right)^2 + \mathrm{Var}_D(\widehat{f}_D(x)),$$

when $f(x) = \mathbb{E}[Y \mid X = x]$ and $\sigma^2(x) = \mathrm{Var}(Y \mid X = x)$. Irreducible outcome variation, systematic estimator bias, and sample-to-sample instability are different phenomena. A single fitted dataset cannot display the decomposition directly; resampling and scientific replication provide evidence about stability.

Concept check. A laboratory reports excellent mean squared error after randomly splitting rows, but each physical cell contributes many rows to both subsets. What population quantity does that experiment estimate, and why might it differ from performance on a previously unseen cell?

11.6 Prediction is not causal explanation

A predictor exploits associations that persist between its training and use settings. It need not represent a mechanism. A variable can improve prediction because it is a proxy for laboratory, instrument, treatment assignment, or selection process. Conversely, a causally important variable may add little predictive information if its variation is small or already encoded elsewhere.

The question "What will happen?" differs from "What would happen if we intervened?" Counterfactual conclusions require additional design and assumptions. High predictive accuracy does not supply them.

Common misconception

Misconception: a sufficiently accurate model discovers the true causes. **Correction:** predictive performance is evidence about a specified prediction task under a specified evaluation design. Causal claims require an identification argument that predictive accuracy alone cannot provide.

11.7 Splits simulate the use setting

A random row split is appropriate only when future uses resemble independent draws from the same row-level population. Dependence changes the unit of separation. Repeated measures from one cell call for grouped splitting when the claim concerns unseen cells. Forecasting calls for training on the past and evaluating on the future. A new laboratory or manufacturing batch may require a held-out domain.

Three subsets have different responsibilities. Training data determine fitted parameters. Validation data guide model and hyperparameter choices. Test data support a final estimate after those choices stop. Cross-validation rotates training and validation roles; it does not excuse repeatedly consulting the test set.

Theorem 11.2 (What an independent test average estimates)**.** *Condition on a completed training and selection process that produces a fixed predictor $\widehat{f}$. If test pairs (X_j, Y_j) are independent draws from P_{use} and are independent of that process, then*

$$\widehat{R}_{\text{test}}(\widehat{f}) = \frac{1}{m}\sum_{j=1}^{m} L(Y_j, \widehat{f}(X_j))$$

is conditionally unbiased for $R(\widehat{f})$.

Proof. Conditional on $\widehat{f}$, linearity of expectation and identical sampling give

$$\mathbb{E}[\widehat{R}_{\text{test}}(\widehat{f}) \mid \widehat{f}] = \frac{1}{m}\sum_{j=1}^{m} \mathbb{E}_{P_{\text{use}}}[L(Y, \widehat{f}(X))] = R(\widehat{f}).$$

The conclusion fails when test observations influence feature construction, model choice, stopping, or repeated reporting. In that case $\widehat{f}$ is no longer fixed independently of the claimed test evidence. □

Leakage occurs when model construction uses information that would not be legitimately available at prediction time or crosses an evaluation boundary. Target-derived features are obvious leakage. More subtle cases include fitting normalization on the full dataset, selecting variables before cross-validation, using future measurements, and allowing related entities into both sides of a split.

Failure mode

Preprocessing learns parameters too. Imputation values, category vocabularies, scales, feature selection, and representation learning must be fitted using the training portion of each evaluation fold and then applied to held-out data.

Figure 11.1 shows the three roles on the real diabetes table. Polynomial degree is varied only against validation data. The sealed test subset is then used once to compare the selected candidate with a baseline. The particular winning degree is not a scientific conclusion; it is a concrete demonstration of information flow.




Figure 11.1: Training estimates parameters, validation supports adaptive choices, and test data estimate the performance of the completed procedure. Re-running model selection after viewing panel C would turn the test set into development data.

11.8 A baseline is an experimental control

A baseline asks whether learning adds value beyond a simple policy. For regression, predict the training mean or a physically motivated constant. For classification, predict class prevalence or the most frequent class, but audit whether that behavior is useful under imbalance. A time-series baseline may carry the latest observation forward.

The baseline uses the same split, metric, and information boundary as the candidate. Otherwise it is not a control. A complex model that fails to beat a correct baseline has supplied diagnostic evidence: the signal, representation, sample size, objective, or implementation may not support the claim.

11.9 Measure predictive performance as an experiment

For regression residuals $e_i = y_i - \widehat{y}_i$, three common summaries are

$$\mathrm{MAE} = \frac{1}{m}\sum_{i=1}^{m} |e_i|, \qquad \mathrm{RMSE} = \sqrt{\frac{1}{m}\sum_{i=1}^{m} e_i^2},$$

and

$$R^2 = 1 - \frac{\sum_i e_i^2}{\sum_i (y_i - \bar{y})^2}.$$

MAE retains the target unit and weights errors linearly. RMSE has the target unit but emphasizes large residuals. R^2 compares squared error with the constant test-set mean benchmark; it is not a percentage of predictions that are correct, and it can be negative on held-out data. Always report the unit, sample count, and reference policy beside the number.

A metric estimate also has sampling variation. If evaluation units are independent, a bootstrap that resamples those units can describe uncertainty. If measurements are grouped by patient, machine, site, or time block, resample the independent group instead of individual rows. The resampling unit must match the generalization claim. For paired model comparison, compute both models on the same units and resample their per-unit loss differences; this retains the information that an observation was easy or difficult for both.

Predictive quality is only one budget. Record fit time separately from prediction time, and measure prediction latency at representative batch sizes. Report a tail quantile such as the 95th or 99th percentile when a service-level objective concerns slow requests. Measure peak memory for training and serving independently. A model with slightly lower RMSE may be dominated if it violates the latency, memory, interpretability, or outcome-feedback requirements stated in the supervised-learning contract.

Professional practice

Store evaluation as a table with one row per evaluation unit: identifiers, observed target, prediction, model version, subgroup fields permitted for audit, and per-unit loss. Aggregate reports can then be reproduced, sliced, paired, and bootstrapped. A screenshot of one score is not durable evaluation evidence.

11.10 One table can contain many supervised problems

Application design determines the unit, target, horizon, and split.

Application	Supervised target	Evaluation boundary
Materials	Capacity after 300 cycles from the first 100 cycles	Hold out cells and later manufacturing batches
Public health	Next-week regional case count from reports available today	Train on past weeks and preserve reporting-delay behavior
Remote sensing	Land-cover class from multispectral pixels	Hold out spatial regions or acquisition campaigns, not random neighboring pixels
Predictive maintenance	Failure within 30 operating days from sensor history	Separate machines and respect the feature cutoff before failure
Scientific literature	Relevance of a paper to a review protocol	Preserve reviewer disagreement and evaluate on later searches

Random splitting would answer a different and often easier question in every row. The split is part of the estimand: it defines the population transfer the reported metric attempts to approximate.

Worked example: write the battery prediction contract

Suppose one row summarizes the first 100 cycles of one cell. The target is capacity at cycle 300, measured in ampere-hours. The intended use is prediction for cells from future manufacturing batches immediately after cycle 100.

The feature cutoff excludes all observations after cycle 100. Batch identity defines an outer temporal split: earlier batches train the system and later batches evaluate it. All transformations are fitted within the training side. The baseline predicts the mean training capacity at cycle 300. Mean absolute error is reported in ampere-hours together with the error distribution by batch.

The contract also states what it does not establish. It does not estimate the effect of changing a charging protocol, certify safety, or guarantee behavior for a chemistry absent from the study. Those exclusions are part of the result, not fine print.

11.11 The first vertical slice should be deliberately simple

Before optimizing an algorithm, prove that the system can reproduce a split, fit a baseline, serialize an artifact, load it in a separate process, validate inputs, produce predictions, record model and feature versions, and later join predictions to outcomes. A dummy model is ideal because unexpected behavior is easy to detect.

The artifact manifest should identify training data, code revision, configuration, feature schema, split policy, fitted object, evaluation report, and creation time. A model file without this context is an opaque binary, not a reproducible result.

11.12 Exercises

Use the printed identifier when discussing, submitting, or contributing a problem. A repository contribution follows the issue-to-PR procedure in Appendix B; the mathematics remains part of its review contract.

Intuition and explanation

SLC-I1. Write two prediction contracts for the same battery table: one for an unseen cell from a known batch and one for a cell from a future batch. Explain why their splits, plausible shifts, and release claims differ.

SLC-I2. Give temporal, group, preprocessing, and target-construction leakage examples. For each, draw the forbidden information path and explain why a high held-out score may survive the mistake.

SLC-I3. A label is measured reproducibly but reflects an earlier institution's decision policy. Explain what a predictor of that label learns, what it does not learn, and which additional evidence would justify the intended construct.

SLC-I4. Distinguish loss, evaluation metric, calibrated score, and decision policy using one high-stakes classification example.

Mathematical reasoning

SLC-M1. Re-prove Theorem 11.1 by differentiating the conditional risk, and list the regularity assumptions your proof uses. Compare them with the completion-of-squares proof in the chapter.

SLC-M2. Prove that every conditional median minimizes conditional absolute loss. Treat nonunique medians carefully by using one-sided derivatives or a direct comparison of integrals.

SLC-M3. Under the assumptions of Theorem 11.2, derive $\mathrm{Var}(\widehat{R}_{\text{test}} \mid \widehat{f})$. Explain how dependence among repeated measurements changes the result.

SLC-M4. Derive the cost-sensitive binary threshold $C_{FP}/(C_{FP} + C_{FN})$ from conditional expected cost. Give two operational constraints that make this threshold incomplete.

SLC-M5. For squared error, derive the fixed-x bias-variance decomposition. Identify which expectation is over future outcomes and which is over possible training samples.

Data and engineering investigations

SLC-C1. Recreate Figure 11.1 with five different split seeds. Report how often each polynomial degree is selected and what this says about treating one validation winner as a scientific discovery.

SLC-C2. Build a leakage-safe baseline and candidate pipeline for one course table. Preserve one row per evaluation unit with target, prediction, residual, model version, and permitted audit fields. Report MAE, RMSE, R^2, a paired comparison, and the limitations of the split.

SLC-C3. Measure prediction latency at batch sizes 1, 16, and 256 after warmup. Record hardware, dependency lock, repetitions, median, 95th percentile, and whether preprocessing is included. Explain which result matters for an API and which for an offline batch job.

SLC-C4. Design and test an artifact manifest that rejects reordered, missing, duplicated, or unit-incompatible inputs before inference.

Contribution studio

Choose one scoped addition and preserve the problem identifier from issue through merge.

SLC-PR1. Add a typed prediction-contract component with validation for unit, population, feature cutoff, horizon, target, split policy, metric, consumer, and feedback delay. Include round-trip serialization and failure tests.

SLC-PR2. Add a reusable paired regression report that accepts observed values and two prediction vectors, returns per-unit losses and aggregate differences, and never silently drops nonfinite or misaligned values.

SLC-PR3. Add a custom split validator for a domain you choose–grouped, temporal, spatial, or batch-based. Document the claim it protects, construct an adversarial leakage fixture, and test that the invalid split is rejected.

Chapter review

Supervised learning estimates a rule from paired inputs and targets, but the defensible object is larger than the fitted rule. A loss defines a population target; a hypothesis class and regularizer encode inductive bias; a learning rule introduces estimation and optimization behavior. The contract names population, time, target, information, split, consumer, and feedback. Evaluation must simulate intended use, baselines act as controls, and the first vertical slice should validate artifact and evidence flow before model complexity grows. Metrics require units, uncertainty, a reference policy, and a resource-aware measurement protocol.

Executable companion

Lecture 9 notebook 01 begins by writing the supervised contract for a real diabetes-progression dataset. It separates training, validation, and test roles, derives the squared-loss target, fits baselines, and constructs preprocessing inside the training boundary. Its clinical example is a methods laboratory, not a deployment claim; missing site, time, and patient identifiers are treated as limitations rather than silently ignored.

CHAPTER 12

Linear regression and regularization

Learning objectives

After this chapter, you should be able to:

- derive least squares from an affine prediction rule and squared loss;
- explain projection, identifiability, conditioning, and stable numerical solution;
- distinguish prediction, coefficient interpretation, and statistical uncertainty;
- distinguish ridge, lasso, and elastic-net regularization; and
- evaluate a regression pipeline using residual and out-of-sample evidence while measuring numerical and computational performance.

Where this chapter fits

Chapter 11 fixed the population, feature cutoff, target, split, and baseline. We can now study model classes without silently changing the question. The affine map introduced here will recur in logistic regression, support-vector machines, and neural networks.

12.1 From astronomical observations to a general model

Least squares arose from a scientific problem that still feels modern: more noisy measurements were available than unknown parameters, and no parameter choice satisfied every equation exactly. Adrien-Marie Legendre published the method in 1805 as part of work on comet orbits. Carl Friedrich Gauss published a probabilistic treatment in 1809 and stated that he had used the principle earlier.[1]

The word regression entered statistics later through nineteenth-century studies of heredity. Its historical biological interpretation should not be confused with the modern mathematical definition. Today linear regression is a family of projection, estimation, prediction, and uncertainty procedures. These uses share algebra but require different assumptions.

The model remains important not because all relationships are straight lines, but because it is transparent enough to expose the entire chain: representation, loss, geometry, probability, numerical linear algebra, evaluation, and deployment. It is also the local building block of many nonlinear methods.

12.2 The affine predictor

For $x \in \mathbb{R}^p$, an affine predictor has the form

$$f_{w,b}(x) = w^T x + b.$$

[1] A.-M. Legendre, *Nouvelles méthodes pour la détermination des orbites des comètes*, 1805; C. F. Gauss, *Theoria motus corporum coelestium*, 1809. Legendre's appendix is the first published account; Gauss reported use dating to 1795.

The intercept permits a nonzero prediction at the coordinate origin. Calling this model “linear” is conventional; mathematically it is affine unless the intercept is absorbed into an augmented feature vector.

With design matrix $X \in \mathbb{R}^{n\times p}$ and target vector $y \in \mathbb{R}^n$, ordinary least squares minimizes

$$J(w, b) = \frac{1}{n}\sum_{i=1}^{n}(y_i - w^T x_i - b)^2.$$

Squared loss penalizes large residuals strongly and targets the conditional mean under the population risk. That property is useful only when the mean and the cost implied by squared error match the task.

12.3 One feature exposes the algebra

For observations (x_i, y_i) and $\widehat{y}_i = b + wx_i$, minimize

$$Q(b, w) = \sum_{i=1}^{n}[y_i - (b + wx_i)]^2.$$

The first-order equations are

$$\sum_i (y_i - b - wx_i) = 0, \qquad \sum_i x_i(y_i - b - wx_i) = 0.$$

The first implies that the fitted line passes through $(\bar{x}, \bar{y})$. After centering, the solution is

$$\widehat{w} = \frac{\sum_i (x_i - \bar{x})(y_i - \bar{y})}{\sum_i (x_i - \bar{x})^2}, \qquad \widehat{b} = \bar{y} - \widehat{w}\bar{x}.$$

Thus the slope is sample covariance divided by sample variance when the same normalizing convention is used. If every x_i is equal, the denominator is zero: the sample contains no information about change in y with x.

Residuals satisfy

$$\sum_i e_i = 0, \qquad \sum_i x_i e_i = 0$$

when an intercept and slope are fitted. These are orthogonality statements, not evidence that residuals are independent, Gaussian, or scientifically harmless.

Concept check. If mass is converted from grams to kilograms, how do slope and intercept coordinates change? Why are fitted values unchanged when the conversion is performed consistently?

12.4 Projection and identifiability

After including an intercept column, write the design matrix as A. The fitted vector $A\widehat{\theta}$ is the orthogonal projection of y onto the column space of A. At an optimum the residual $r = y - A\widehat{\theta}$ satisfies $A^T r = 0$. This geometric statement remains meaningful when coefficients are not unique.

Theorem 12.1 (Least squares is orthogonal projection)**.** *Let $C(A)$ be the column space of a real matrix A. A vector $\widehat{y} = A\widehat{\theta}$ minimizes $\|y - Av\|_2^2$ over all v if and only if its residual $r = y - \widehat{y}$ is orthogonal to $C(A)$, equivalently $A^T r = 0$. The fitted vector $\widehat{y}$ is unique even when the coefficient vector $\widehat{\theta}$ is not.*

Proof. Suppose first that $r \perp C(A)$. For any candidate Av, the vectors $r = y - A\widehat{\theta}$ and $A\widehat{\theta} - Av$ are orthogonal. Pythagoras gives

$$\|y - Av\|_2^2 = \|y - A\widehat{\theta}\|_2^2 + \|A\widehat{\theta} - Av\|_2^2.$$

The right side is minimized at the projected vector. Conversely, if a minimizer had $A^T r \neq 0$, then for $d = A^T r$ the directional derivative of $\|y - A(\widehat{\theta} + td)\|_2^2$ at $t = 0$ would be $-2\|A^T r\|_2^2 < 0$, contradicting minimality. Orthogonal projection onto a finite-dimensional subspace is unique, although a rank-deficient A can map several coefficient vectors to that same projection. □

The Pythagorean identity separates unexplained residual length from the extra error caused by choosing another vector in the same model space. It is also a unit test: a computed least-squares residual should satisfy $A^T r \approx 0$ up to a tolerance justified by scale and conditioning.

If A has full column rank, the normal equations give

$$\widehat{\theta} = (A^T A)^{-1} A^T y.$$

Software should not explicitly form the inverse. QR or singular-value methods are generally more stable, while iterative methods are useful at larger scale. When columns are linearly dependent, multiple coefficient vectors produce the same fitted values. Prediction may remain defined while individual coefficient interpretations do not.

The Moore-Penrose pseudoinverse A^+ gives the minimum-Euclidean-norm solution $\widehat{\theta} = A^+ y$ when the system is rank deficient. That convention makes a coefficient vector unique, but it does not make the individual coefficients scientifically identified. The choice comes from an algebraic preference among equally fitting solutions.

Figure 12.1 shows the same fit in three coordinate systems. Data space displays predictions and residual segments. Residual space reveals structure hidden by one summary. Parameter space shows that least squares is an optimization problem with a geometric minimum. No single panel is a substitute for the other two.




Figure 12.1: One-feature ordinary least squares on the course diabetes table. The coefficients are computed with `numpy.linalg.lstsq`; the same predictions generate the data-space line, residual plot, and MSE contours.

Concept check. Two columns record temperature in Celsius and Fahrenheit. What happens to rank, fitted values, and the uniqueness of their separate coefficients when an intercept is present?

12.5 Stable solution is a numerical question

The symbolic expression

$$\widehat{\theta} = (A^T A)^{-1} A^T y$$

is useful for derivation but is usually a poor algorithm. Forming $A^T A$ squares the condition number, and explicitly computing an inverse adds work and error. QR factorization solves the full-rank least-squares problem without that inverse. Singular-value decomposition exposes rank and supplies a stable pseudoinverse. Iterative methods become important when A is too large or sparse for a direct factorization.

Conditioning asks how much the solution can change under small perturbations to data or arithmetic. If two columns are nearly dependent, fitted predictions may be stable in the observed region while their separate coefficients change dramatically. More floating-point precision does not fix weak statistical identification.

Standardization can improve numerical conditioning, but it is a fitted transformation. Means and scales belong to the training fold and serialized pipeline. Chapter 13 studies how this same conditioning controls iterative convergence.

Professional practice

Use a least-squares routine that reports or permits inspection of rank and singular values. Record the feature schema and units. Treat a large condition number as evidence requiring investigation, not as a warning to suppress.

12.5.1 Computational cost belongs to the algorithm, not just the model

For dense $A \in \mathbb{R}^{n \times p}$ with $n \geq p$, a QR-based solve costs on the order of np^2 arithmetic operations and stores the design or a factorization of comparable scale. Forming $A^T A$ costs on the same leading order but worsens conditioning; explicitly inverting it is neither necessary nor the preferred benchmark. When p is modest and repeated targets share the same design, a factorization can be reused. When A is large and sparse, matrix-vector products and iterative solvers may be the only viable interface.

Measure wall time after a warmup and across repeated fits, but also record problem shape, sparsity, numerical precision, thread count, and peak memory. Prediction cost for a dense linear model is $O(mp)$ for m new rows and is often dominated by preprocessing or data movement. Time the complete pipeline and the estimator separately before deciding what to optimize.

12.6 Prediction assumptions differ from inferential assumptions

A common stochastic model is

$$Y = X\beta + \varepsilon, \qquad \mathbb{E}[\varepsilon \mid X] = 0.$$

Under homoscedastic uncorrelated errors with variance σ^2, ordinary least squares is the best linear unbiased estimator in the Gauss-Markov sense. This is a comparison within linear unbiased estimators, not a claim that OLS is best among every possible predictor.

If errors are conditionally Gaussian, least squares is also maximum likelihood. Gaussian errors are not required to compute coefficients or predictions. They support particular likelihood and finite-sample inference results. Independence, linearity of the conditional mean, constant variance, measurement quality, and sampling design remain separate assumptions.

For full-rank fixed design,

$$\mathrm{Var}(\widehat{\beta} \mid X) = \sigma^2 (X^T X)^{-1}.$$

Uncertainty grows in weakly supported directions. A confidence interval for a mean response, a prediction interval for a new outcome, and variability of the entire fitted procedure under new training samples are different objects. A new outcome interval includes irreducible outcome variation and is therefore wider than an interval for the conditional mean under the same model.

Theorem 12.2 (Gauss-Markov)**.** *In the fixed-design model $y = A\beta + \varepsilon$, assume A has full column rank, $\mathbb{E}[\varepsilon \mid A] = 0$, and $\mathrm{Var}(\varepsilon \mid A) = \sigma^2 I$. Among estimators linear in y and unbiased for every β, ordinary least squares has minimum covariance: for any such $\widetilde{\beta}$, $\mathrm{Var}(\widetilde{\beta} \mid A) - \mathrm{Var}(\widehat{\beta}_{\mathrm{OLS}} \mid A)$ is positive semidefinite.*

Proof. Write $C_0 = (A^T A)^{-1} A^T$, so $\widehat{\beta}_{\mathrm{OLS}} = C_0 y$. Any linear estimator Cy is unbiased for every β exactly when $CA = I$. Set $D = C - C_0$. Then $DA = 0$, and therefore $C_0 D^T = (A^T A)^{-1} A^T D^T = 0$. Consequently

$$\mathrm{Var}(Cy \mid A) = \sigma^2 (C_0 + D)(C_0 + D)^T = \sigma^2 C_0 C_0^T + \sigma^2 D D^T.$$

The final term is positive semidefinite. This proves the comparison. Notice what the proof does not say: it does not compare nonlinear or biased estimators, and it does not establish that the model assumptions hold. □

Common misconception

Misconception: a small coefficient p-value proves that changing the feature will change the outcome. **Correction:** the inferential statement is conditional on a statistical model and sampling design. An intervention claim additionally needs causal identification; practical predictive value needs out-of-sample evidence.

12.7 Basis expansion changes the feature map

Polynomial regression remains linear in its fitted coefficients. A map $\phi(x) = (1, x, x^2, \ldots, x^d)$ creates a richer function $f(x) = w^T \phi(x)$. Interactions can represent joint effects. The flexibility comes from the basis, not from abandoning linear estimation.

High-degree bases can be poorly conditioned and unstable outside the observed range. Every basis term must be generated identically during training and inference. Feature names, order, units, and transformation parameters therefore belong to the artifact contract.

12.8 Regularization chooses among fitting rules

Ridge regression minimizes

$$\widehat{R}(w) + \lambda \|w\|_2^2,$$

shrinking correlated or weakly identified coefficients and usually improving conditioning. Lasso uses $\lambda \|w\|_1$ and can set coefficients exactly to zero. Elastic net combines both penalties.

Regularization trades empirical fit for a restriction on the solution. The penalty depends on feature scale, so scaling and whether the intercept is penalized are part of the definition. A lasso-selected variable set is not an automatic list of scientific causes; selection can be unstable among correlated features.

For a centered design, the ridge solution is

$$\widehat{w}_{\text{ridge}} = (X^T X + \lambda I)^{-1} X^T y.$$

In the singular-vector directions of X, ridge shrinks most strongly where the data contain least information. It replaces division by a small squared singular value s_j^2 with division by $s_j^2 + \lambda$. This connects statistical stabilization to numerical conditioning. Under a Gaussian prior on coefficients and Gaussian observation model, the same expression is a maximum a posteriori estimate, but that interpretation requires its probability model.

Common misconception

Misconception: regularization is needed only when a model visibly overfits. **Correction:** it can also stabilize an ill-conditioned problem, encode a preference among many solutions, and improve performance under finite samples. Its strength must still be chosen inside evaluation.

12.9 Residuals are structured evidence

A residual $e_i = y_i - \widehat{y}_i$ retains sign, scale, and context. Plot it against predictions, major features, time, and groups. Curvature can reveal missing structure; a fan shape can reveal changing conditional variance; clusters can reveal omitted batches; isolated points can dominate squared loss.

Aggregate error should include units and a distribution, not only a mean. Compare mean absolute error, root mean squared error, and relevant quantiles. Inspect error by scientifically meaningful subgroup. Prediction intervals, confidence intervals for parameters, and variability across resampled training sets answer different questions and should not be conflated.

12.10 Linear models across science and engineering

Linear regression can be the final model, a baseline, or a local approximation.

Setting	Representation	Principal caution
Sensor calibration	Reference quantity versus instrument response	Error in the predictor may require errors-in-variables methods, not ordinary least squares
Spectroscopy	Concentration from many correlated wavelengths	Collinearity, baseline drift, and instrument transfer dominate coefficient stories
Economics	Outcome on policy and contextual variables	Prediction and causal policy effects require different designs
Energy systems	Load from weather, calendar, and lag features	Temporal dependence and extrapolation beyond observed weather matter
Materials	Later capacity from early-cycle summaries	Batch and chemistry shift can overwhelm random-row performance

The phrase “linear model” refers to linearity in coefficients. Basis functions can encode polynomials, splines, periodic structure, and interactions. Interpretation then belongs to the complete feature map, not to a raw coefficient in isolation.

Worked example: regularized capacity prediction

Suppose early-cycle summaries include mean voltage, resistance change, and two strongly correlated temperature summaries. A least-squares fit produces large opposite temperature coefficients while predictions change little. This is a signature of weak coefficient identification.
Fit a pipeline that learns scaling and ridge regression using only each training fold. Choose λ on validation batches, then compare once on the held-out later batches. Report the baseline and ridge errors in ampere-hours, residuals by batch, and the range of each input. The ridge coefficients are more stable, but the report avoids interpreting their magnitudes as causal effects.

12.11 Exercises

The prefix **LR** distinguishes these problems from the supervised- contract problems that precede them. Preserve the complete identifier in issue titles, branch names, and pull-request descriptions when proposing an extension.

Intuition and explanation

LR-I1. Explain why linear regression is affine in the raw inputs but linear in an augmented feature vector. What changes in the geometry when the intercept column is omitted?

LR-I2. Two nearly collinear features have large opposite coefficients but stable fitted values. Explain the distinction between prediction stability, coefficient identification, and causal interpretation.

LR-I3. A residual plot has mean zero and a strong curved pattern. Explain why both statements can hold and what each says about the fitted model.

LR-I4. Compare the assumptions needed for a point prediction, a confidence interval for a mean response, a prediction interval for a new outcome, and a causal intervention claim.

Mathematical reasoning

LR-M1. Starting from $Q(b, w)$, derive the one-feature slope and intercept. Prove the fitted line passes through $(\bar{x}, \bar{y})$ and that both residual orthogonality identities hold.

LR-M2. Prove Theorem 12.1 a second way by differentiating the quadratic objective. State exactly where full column rank is and is not required.

LR-M3. Construct a rank-deficient matrix with nonunique coefficients but a unique fitted vector. Compute every least-squares solution, the Moore-Penrose solution, and the limit of ridge solutions as $\lambda \downarrow 0$.

LR-M4. If $X = U\Sigma V^T$, derive the ridge solution in singular-vector coordinates. Plot or tabulate the shrinkage factor as a function of singular value and explain why weak directions shrink most.

LR-M5. In the proof of Theorem 12.2, show why unbiasedness implies $CA = I$ and why the cross terms vanish. Construct a biased estimator with smaller mean squared error for at least one β.

Data and engineering investigations

LR-C1. Reproduce all three panels of Figure 12.1 from SQLite. Verify the normal equations numerically and set tolerances from data scale and condition number rather than copying a decimal threshold.

LR-C2. Compare normal equations, QR-based least squares, and an SVD pseudoinverse on well-conditioned, nearly collinear, and rank-deficient designs. Perturb the data and report coefficient and prediction sensitivity.

LR-C3. Build a training-only scaling and ridge pipeline. Select λ without consulting the test set, compare with the training-mean baseline, and report residual distributions rather than only their averages.

LR-C4. Specify a fair time and peak-memory experiment comparing a dense direct solve with an iterative method on a sparse design. Include matrix shape, density, precision, threads, warmup, repetitions, stopping tolerance, and achieved objective.

Contribution studio

LR-PR1. Add a transparent linear-regression component that exposes fitted rank, singular values, condition diagnostics, and termination information while matching a trusted solver on documented cases.

LR-PR2. Add a residual-diagnostics report with typed records and plots produced by a separate presentation function. Test alignment, nonfinite values, constant targets, and empty subgroups.

LR-PR3. Propose a domain-specific basis transformer–for example periodic, polynomial, interaction, or calibration features. Document units and output names, fit it only on training data when applicable, and test train/inference schema equivalence.

Chapter review

Linear regression combines an affine representation, a loss, an optimization method, and a data contract. Its history began with reconciling noisy scientific observations, and the same projection geometry now supports prediction across many domains. Rank and conditioning explain coefficient instability; stable factorizations separate algebra from numerical implementation; and regularization selects a more constrained solution. Inferential, predictive, and causal claims require different assumptions. Out-of-sample residual evidence, not training fit alone, supports the prediction claim.

Executable companion

Lecture 9 notebook 01 derives one-feature ordinary least squares from real diabetes observations, verifies the result with a stable least-squares solver, and visualizes projection through residuals and parameter-space loss. It then builds a leakage-safe multiple-regression pipeline with a baseline, training-only scaling, complementary metrics, residual diagnostics, and a one-time test evaluation. Lecture 10 then opens the iterative optimization mechanism.

CHAPTER 13

Gradient methods: from calculus to learning

Learning objectives

After this chapter, you should be able to:

- derive gradient descent from a local linear approximation;
- explain directional derivatives, steepest descent, curvature, and the role of the learning rate;
- derive batch, stochastic, and mini-batch updates for least squares;
- connect a single identity-activation neuron to linear regression;
- compare plain descent, Polyak momentum, and Nesterov-style acceleration as first-order methods;
- distinguish back-propagation from the optimizer that consumes its gradients; and
- diagnose divergence, slow convergence, scaling problems, and false claims based only on optimizer convergence using quality and resource measurements.

Where this chapter fits

Chapter 12 described least squares as estimation and projection. This chapter opens the numerical mechanism. The separation is deliberate: a statistical model defines what is estimated; an optimizer defines how parameters are searched. Gradient methods will return for logistic models, matrix factorization, neural networks, inverse problems, and differentiable scientific programs.

13.1 From steepest descent to stochastic approximation

Iterative descent has roots in numerical analysis rather than in modern neural network terminology. In 1847 Augustin-Louis Cauchy described a method of moving along steepest descent while solving systems arising from quadratic problems.[1] In 1951 Herbert Robbins and Sutton Monro gave a stochastic approximation procedure for finding a solution when only noisy experimental responses were available.[2]

Acceleration also predates the current deep-learning vocabulary. Boris Polyak analyzed the heavy-ball method in 1964, adding a fraction of the preceding displacement to the next step. [3] Yurii Nesterov's 1983 method obtained an accelerated worst-case rate for smooth convex optimization through a carefully constructed look-ahead sequence. [4] These methods are still first order: they use objective values and gradients, not the Hessian matrix required by a second-order method such as Newton's method.

The neuron language has a separate history. McCulloch and Pitts formalized networks of thresholded logical

[1] A.-L. Cauchy, "Méthode générale pour la résolution des systèmes d'équations simultanées," *Comptes rendus de l'Académie des Sciences*, 25, 1847.

[2] H. Robbins and S. Monro, "A Stochastic Approximation Method," *The Annals of Mathematical Statistics*, 22(3), 1951, https://doi.org/10.1214/aoms/1177729586.

[3] B. T. Polyak, "Some methods of speeding up the convergence of iteration methods," *USSR Computational Mathematics and Mathematical Physics*, 4(5), 1964, https://doi.org/10.1016/0041-5553(64)90137-5.

[4] Y. E. Nesterov, "A method for solving the convex programming problem with convergence rate $O(1/k^2)$," *Doklady Akademii Nauk SSSR*, 269(3), 1983, https://www.mathnet.ru/eng/dan46009.

units in 1943, and Rosenblatt developed the trainable perceptron in the 1950s. [5] Those units used threshold behavior. The identity-activation unit studied here is deliberately different: it supplies the smallest computational graph that is exactly affine regression and makes the later transition to differentiable networks mathematically transparent.

Modern gradient-based learning joins these two ideas: use local derivative information to improve an objective, and estimate that information from a manageable sample when the complete sum is expensive. Automatic differentiation changes how derivatives are computed, not what optimization question they answer.

13.2 One variable: the derivative proposes a local move

For differentiable $J : \mathbb{R} \to \mathbb{R}$, Taylor's formula gives

$$J(w + \Delta w) = J(w) + J'(w)\Delta w + O((\Delta w)^2).$$

When $J'(w) > 0$, a small negative Δw lowers the linear approximation; when $J'(w) < 0$, a small positive move does. Choosing

$$\Delta w = -\eta J'(w), \qquad \eta > 0,$$

produces the gradient-descent iteration

$$w_{t+1} = w_t - \eta_t J'(w_t).$$

The derivative supplies local direction and sensitivity, not a complete route to a global minimizer. The learning rate η_t converts sensitivity into a step. If the step is too large, the neglected curvature term can dominate and the objective may increase.

Theorem 13.1 (Exact convergence on a scalar quadratic)**.** *Let $J(w) = \frac{1}{2}a(w - w^*)^2$ with $a > 0$, and apply gradient descent with a constant learning rate η. Then*

$$w_t - w^* = (1 - \eta a)^t (w_0 - w^*).$$

For every starting point, the iterates converge to w^* if and only if $0 < \eta < 2/a$. The choice $\eta = 1/a$ reaches w^* in one update.

Proof. Because $J'(w) = a(w - w^*)$, subtracting w^* from the update gives $w_{t+1} - w^* = (1 - \eta a)(w_t - w^*)$. Repeated substitution proves the formula. The geometric sequence converges to zero exactly when $|1 - \eta a| < 1$, which is equivalent to $0 < \eta < 2/a$. At $\eta = 1/a$ the contraction factor is zero. □

The sign and magnitude of $1 - \eta a$ explain the whole trajectory. A positive factor approaches from one side, a negative factor oscillates, magnitude above one diverges, and a factor close to one makes slow progress. This exact example is the first model for diagnosing a learning curve rather than merely watching it.

Concept check. For $J(w) = 5(w - 3)^2/2$, classify the behavior expected at $\eta = 0.05$, 0.2, 0.35, and 0.45. Which choice reaches the minimizer in one exact step?

[5] W. S. McCulloch and W. Pitts, "A logical calculus of the ideas immanent in nervous activity," *Bulletin of Mathematical Biophysics*, 5, 1943, https://doi.org/10.1007/BF02478259; F. Rosenblatt, "The perceptron: a probabilistic model for information storage and organization in the brain," *Psychological Review*, 65(6), 1958, https://doi.org/10.1037/h0042519.

13.3 Several variables: the gradient represents all directions

For $J : \mathbb{R}^p \to \mathbb{R}$, the local approximation is

$$J(\theta + d) \approx J(\theta) + \nabla J(\theta)^T d.$$

For a unit direction u, the directional derivative is

$$D_u J(\theta) = \nabla J(\theta)^T u.$$

Theorem 13.2 (The negative gradient is Euclidean steepest descent)**.** *If $\nabla J(\theta) \neq 0$, then among all unit Euclidean directions,*

$$\min_{\|u\|_2=1} D_u J(\theta) = -\|\nabla J(\theta)\|_2,$$

and the unique minimizing direction is $u = -\nabla J(\theta)/\|\nabla J(\theta)\|_2$.

Proof. Cauchy-Schwarz gives $\nabla J(\theta)^T u \geq -\|\nabla J(\theta)\|_2 \|u\|_2 = -\|\nabla J(\theta)\|_2$. Equality occurs when u is a negative scalar multiple of the gradient; the unit-length constraint fixes the stated direction. □

The phrase "steepest" depends on geometry. Rescaling parameters changes Euclidean distance and therefore changes the gradient path. A preconditioner, natural gradient, or adaptive method corresponds to a different geometry or coordinate-dependent scaling. This is why units and representation affect optimization even when they leave the set of fitted predictions unchanged.

The Hessian

$$H(\theta) = \nabla^2 J(\theta)$$

describes local curvature. Positive semidefinite H throughout a convex domain implies a convex objective. At a differentiable convex minimum the gradient is zero, but a zero gradient in a nonconvex problem may also identify a saddle or maximum.

Common misconception

Misconception: the gradient points toward the nearest global minimum. **Correction:** it points in the direction of steepest infinitesimal decrease under a chosen norm. Curvature, constraints, step size, and nonconvex geometry determine what happens after a finite step.

13.4 Quadratic objectives make curvature visible

Consider

$$J(\theta) = \frac{1}{2}\theta^T H\theta - c^T\theta + d, \qquad H = H^T \succ 0.$$

Then $\nabla J = H\theta - c$ and the unique minimizer is $\theta^* = H^{-1}c$. Gradient descent satisfies

$$\theta_{t+1} - \theta^* = (I - \eta H)(\theta_t - \theta^*).$$

If $0 < \lambda_{\min} \leq \lambda_j(H) \leq \lambda_{\max}$, a constant step converges when

$$0 < \eta < \frac{2}{\lambda_{\max}}.$$

The condition number $\kappa = \lambda_{\max}/\lambda_{\min}$ measures the curvature disparity. A large κ produces elongated contours. A safe step for the steep direction makes little progress along the flat direction, so the path zigzags slowly. Centering, scaling, reparameterization, and preconditioning attempt to improve this geometry.

Theorem 13.3 (Descent lemma and a safe fixed step)**.** *Suppose J has an L-Lipschitz gradient: $\|\nabla J(v) - \nabla J(u)\|_2 \le L\|v - u\|_2$. Then*

$$J(v) \le J(u) + \nabla J(u)^T(v - u) + \frac{L}{2}\|v - u\|_2^2.$$

Consequently, with $v = u - \eta\nabla J(u)$,

$$J(v) \le J(u) - \eta\left(1 - \frac{L\eta}{2}\right)\|\nabla J(u)\|_2^2.$$

Thus $0 < \eta < 2/L$ strictly decreases the objective whenever the gradient is nonzero.

Proof. Let $d = v - u$ and $h(t) = J(u + td)$. The fundamental theorem of calculus gives

$$J(v) - J(u) = \int_0^1 \nabla J(u + td)^T d\, dt.$$

Add and subtract $\nabla J(u)^T d$. Cauchy-Schwarz and Lipschitz continuity bound the remaining integrand by $Lt\|d\|_2^2$. Integration from zero to one gives the first inequality. Substituting $d = -\eta\nabla J(u)$ and collecting terms gives the second. □

13.5 Least squares supplies an exact laboratory

For design matrix $X \in \mathbb{R}^{n\times p}$ and target y, define

$$J(w) = \frac{1}{2n}\|Xw - y\|_2^2.$$

Differentiation gives

$$\nabla J(w) = \frac{1}{n}X^T(Xw - y), \qquad \nabla^2 J(w) = \frac{1}{n}X^T X.$$

The Hessian is positive semidefinite, so every local minimum is global. If X has full column rank, the minimum is unique. If not, gradient descent still minimizes fitted loss but the coefficient selected depends on initialization and the geometry of the updates.

The largest eigenvalue of $X^T X/n$ controls the stable constant step. Feature scaling changes that spectrum. This gives a precise reason to scale before gradient descent rather than the vague rule that models always require standardization.

Theorem 13.4 (An identity neuron is affine linear regression)**.** *Let a single computational unit have weights $w \in \mathbb{R}^p$, bias $b \in \mathbb{R}$, preactivation $z = w^T x + b$, and identity activation $\phi(z) = z$. Its hypothesis class is exactly the class of affine linear regression functions. If it is trained by mean squared error, its objective and parameter gradients are exactly those of ordinary least squares with an intercept.*

Proof. The forward map is $\widehat{y} = \phi(w^T x + b) = w^T x + b$, which is the affine regression map. Conversely, every affine regression function is represented by the same w and b in the unit. For

$$J(w, b) = \frac{1}{2n}\sum_{i=1}^{n}(w^T x_i + b - y_i)^2,$$

the chain rule through z_i and $\phi'(z_i) = 1$ gives

$$\nabla_w J = \frac{1}{n}\sum_i (\widehat{y}_i - y_i)x_i, \qquad \frac{\partial J}{\partial b} = \frac{1}{n}\sum_i (\widehat{y}_i - y_i),$$

the ordinary least-squares gradients. Representation equivalence does not force training equivalence: a direct QR solve and gradient descent can produce the same fitted function by different numerical routes. □

Worked example: a linear neuron on real clinical measurements

Let x_i be a standardized baseline BMI measurement and let y_i be a one-year disease-progression score from the diabetes teaching table. A single unit with identity activation computes

$$z_i = wx_i + b, \qquad \widehat{y}_i = a(z_i) = z_i.$$

With

$$J(w,b) = \frac{1}{2n}\sum_{i=1}^{n}(wx_i + b - y_i)^2,$$

the chain rule gives

$$\frac{\partial J}{\partial w} = \frac{1}{n}\sum_i (\widehat{y}_i - y_i)x_i, \qquad \frac{\partial J}{\partial b} = \frac{1}{n}\sum_i (\widehat{y}_i - y_i).$$

These are exactly the least-squares gradients. "Single neuron" and "linear regression" describe two views of the same function and objective here. The neuron language becomes informative when activation, composition, or shared optimization later changes; it does not create a new estimator by itself.
Plot three synchronized objects: contours of $J(w,b)$ in parameter space, the line $wx + b$ in data space, and loss against iteration. Parameter convergence, visual fit, and training history answer different questions and should not be collapsed into one plot.

13.6 Batch, stochastic, and mini-batch gradients

If

$$J(\theta) = \frac{1}{n}\sum_{i=1}^{n}\ell_i(\theta),$$

batch gradient descent evaluates every $\nabla\ell_i$ before one update. A stochastic update samples index I_t and uses

$$g_t = \nabla\ell_{I_t}(\theta_t).$$

Under uniform sampling, $\mathbb{E}[g_t \mid \theta_t] = \nabla J(\theta_t)$: the stochastic gradient is unbiased, though noisy. A mini-batch averages several sampled gradients to trade variance for parallel efficiency.

Proposition 13.5 (Independent mini-batching reduces gradient variance)**.** *Fix θ and let $G_1, \dots, G_B$ be independent gradient samples with mean $\nabla J(\theta)$ and covariance matrix $\Sigma(\theta)$. Their average $\bar{G}_B = B^{-1}\sum_{j=1}^{B} G_j$ is unbiased and has covariance $\Sigma(\theta)/B$.*

Proof. Linearity of expectation gives $\mathbb{E}[\bar{G}_B] = \nabla J(\theta)$. Independence removes cross-covariance terms, so

$$\mathrm{Cov}(\bar{G}_B) = \frac{1}{B^2}\sum_{j=1}^{B}\mathrm{Cov}(G_j) = \frac{1}{B^2}B\Sigma(\theta) = \frac{\Sigma(\theta)}{B}.$$

Sampling without replacement changes the expression by a finite-population correction, but the same variance-reduction principle remains. □

One pass through the training observations is an **epoch**. An epoch is not one update unless the batch is the entire dataset. Shuffling affects the sequence of stochastic gradients, so the seed and data order belong to the reproducibility record.

Constant-step stochastic methods generally fluctuate near a solution because gradient noise remains. Decreasing schedules can support convergence under conditions; modern practice also uses warmup, momentum, adaptive scaling, and averaging. Their convenience does not remove the need to monitor the actual objective and update magnitude.

Update	Main advantage	Main cost or risk
Full batch	Exact gradient of the finite-sample objective	Expensive update; limited streaming behavior
Stochastic	Cheap updates and immediate online use	High variance and strong sensitivity to order and schedule
Mini-batch	Efficient vectorization with reduced variance	Batch size changes optimization noise, memory use, and sometimes generalization behavior

13.7 Momentum and acceleration remain first-order methods

Plain gradient descent discards its preceding displacement. Polyak's **heavy-ball method** carries a velocity:

$$v_{t+1} = \beta v_t - \eta \nabla J(\theta_t), \qquad \theta_{t+1} = \theta_t + v_{t+1},$$

where $0 \le \beta < 1$. On a long narrow valley, gradients alternate across the steep direction while agreeing along the flat direction. The velocity tends to cancel the alternating component and accumulate the persistent one. This is a geometric explanation, not a guarantee for every nonconvex objective.

For the scalar quadratic $J(w) = aw^2/2$, eliminating velocity gives the error recurrence

$$e_{t+1} = (1 + \beta - \eta a)e_t - \beta e_{t-1}.$$

Its behavior is governed by the roots of $r^2 - (1 + \beta - \eta a)r + \beta = 0$. Momentum therefore introduces a second state and a second stability question. A value of β that helps one curvature can destabilize another; momentum is not free speed.

A common look-ahead form evaluates the gradient where velocity is about to move the parameters:

$$\widetilde{\theta}_t = \theta_t + \beta v_t, \qquad v_{t+1} = \beta v_t - \eta \nabla J(\widetilde{\theta}_t), \qquad \theta_{t+1} = \theta_t + v_{t+1}.$$

This is useful for teaching the intuition behind Nesterov-style momentum, but the original accelerated convex method uses a particular sequence of coefficients and proof invariant. Similar-looking library updates should not be credited with a theorem until their exact recurrence and assumptions match it.

For a convex function with L-Lipschitz gradient, fixed-step gradient descent has a worst-case objective gap of order $1/t$. Nesterov's accelerated method achieves order $1/t^2$ under the same smooth-convex setting. If the objective is also μ-strongly convex, appropriately tuned methods converge geometrically, with the accelerated dependence governed by $\sqrt{L/\mu}$ rather than L/μ. These are worst-case upper bounds under mathematical

assumptions, not promises about elapsed time. Extra state, more complex kernels, stochastic noise, and hardware utilization can change the engineering result.

Figure 13.1 compares the mechanisms on objectives whose behavior is known exactly. The horizontal axis in the lower-left panel counts gradient evaluations rather than epochs so that the unit of computational work is explicit.




Figure 13.1: First-order optimization diagnostics generated from executable quadratic examples. Panel A isolates step-size stability; panels B and C compare paths and objective progress; panel D shows the idealized variance and update-frequency trade-off induced by batch size.

13.8 Back-propagation differentiates; the optimizer updates

For a composition

$$x = h_0 \longmapsto h_1 = f_1(h_0; \theta_1) \longmapsto \cdots \longmapsto h_L = f_L(h_{L-1}; \theta_L) \longmapsto J,$$

the forward pass computes and stores intermediate values. Reverse-mode automatic differentiation starts from the scalar derivative $\partial J / \partial J = 1$ and repeatedly applies the chain rule. If $\bar{h}_k = \partial J / \partial h_k$, then

$$\bar{h}_{k-1} = \left(\frac{\partial h_k}{\partial h_{k-1}} \right)^T \bar{h}_k, \qquad \nabla_{\theta_k} J = \left(\frac{\partial h_k}{\partial \theta_k} \right)^T \bar{h}_k.$$

This backward sweep computes gradients for every parameter while reusing local derivatives. Back-propagation is therefore a differentiation procedure, not a particular optimizer. Gradient descent, mini-batch SGD,

momentum, or Adam may consume the resulting gradient. Rumelhart, Hinton, and Williams' 1986 account made this reverse error-propagation view influential for learning internal representations in multilayer networks.[6]

The one-neuron derivation is the smallest complete example of this process: the loss sends an error derivative to the identity activation, then to the affine weights and bias. Hidden layers add compositions, not a new chain rule. This distinction is an engineering boundary too: gradient tests validate the differentiation component, while optimizer tests validate state updates, schedules, and termination behavior.

13.9 Applications beyond fitting a line

Gradient methods appear whenever a useful objective is differentiable or has a tractable derivative surrogate:

- logistic regression minimizes a convex likelihood-based loss;
- matrix factorization estimates latent structure in recommendation and imaging;
- inverse problems adjust hidden physical parameters so a simulator matches measurements;
- optimal control and differentiable simulation optimize trajectories or designs;
- neural networks compose many parameterized maps and obtain derivatives by reverse-mode automatic differentiation; and
- variational scientific models optimize an energy or evidence bound.

Each application changes the meaning of the objective and the consequences of local minima, constraints, and stochasticity. The update formula alone does not validate the model.

13.10 Stopping and diagnosing responsibly

Useful diagnostics include training and validation objectives, gradient norm, step norm, parameter norm, nonfinite values, and elapsed resources. A stopping rule might require a small relative objective change and small gradient norm, with a maximum iteration budget. Validation-based early stopping is also model selection and must remain inside the development boundary.

Failure mode

Optimizer convergence establishes only that the implemented search reached a stationary or sufficiently stable point for its objective. It does not show that gradients are correct, the objective is scientifically appropriate, the data are representative, or predictions generalize.

For a hand-built optimizer, verify derivatives three ways when practical:

1. derive them symbolically with shapes shown;
2. compare against centered finite differences on a tiny problem; and
3. compare the final fitted result with a trusted solver on a convex case.

Finite differences are diagnostic, not the preferred large-scale training method. Their truncation and floating-point errors depend on perturbation size.

[6] D. E. Rumelhart, G. E. Hinton, and R. J. Williams, "Learning representations by back-propagating errors," *Nature*, 323, 1986, https://doi.org/10.1038/323533a0.

Professional practice

A reusable optimizer should report termination reason, iterations, final objective, gradient or update norm, and nonfinite failure. Record the objective, data version, preprocessing, initialization, seed, batch construction, learning-rate schedule, precision, and software version. Silently returning the last iterate after divergence is an interface failure.

13.11 Measure optimizer performance without moving the goalposts

An optimizer benchmark needs both a quality axis and a work axis. Objective against iteration can be misleading because one full-batch iteration and one single-example update use very different work. Useful horizontal axes include examples processed, gradient evaluations, matrix-vector products, floating- point operations, and wall-clock time. Report at least one implementation- independent work measure alongside elapsed time.

The primary engineering quantity is often **time to quality**: elapsed time until a declared objective, validation metric, or gradient-norm threshold is first met. Also measure examples per second, peak accelerator or host memory, data-loader wait, and the fraction of time spent in forward, backward, and update stages. A profiler should identify the bottleneck before batch size, precision, compilation, or distribution strategy is changed.

Comparisons must hold the mathematical problem fixed. Use the same training rows, preprocessing, initialization policy, objective normalization, stopping target, and numerical precision unless the experiment explicitly studies one of those choices. Repeat stochastic runs and show their distribution. Count failed or nonfinite runs rather than deleting them. Separate training performance from generalization: reaching lower training loss faster is an optimization result, while improved held-out error is a statistical result.

Question	Measurement	Frequent mistake
Is the update correct?	Finite-difference error and trusted-solver agreement	Treating a decreasing loss as proof of a correct gradient
Is it converging?	Objective, gradient norm, step norm, termination reason	Stopping only because an iteration budget expired
Is it efficient?	Time to quality, examples per second, peak memory	Comparing epochs with different batch sizes as equal work
Is it reproducible?	Seeded-run distribution, data order, software and hardware record	Reporting only the best run
Does it generalize?	Sealed held-out metrics with uncertainty	Inferring test performance from the training curve

13.12 Exercises

Use the **GD** identifier to connect a mathematical result or software extension to its review history. Contribution problems are deliberately open enough for original design but narrow enough for a first professional PR.

Intuition and explanation

GD-I1. Explain why the gradient is not an arrow to the global minimum. Use a convex quadratic, a saddle, and a rescaled coordinate system in the answer.

GD-I2. Distinguish the model, objective, differentiation procedure, and optimizer for the identity neuron. Which object changes when plain gradient descent is replaced by momentum?

GD-I3. An optimizer reaches gradient norm 10^{-8} while held-out RMSE is poor. Give four compatible explanations at different layers of the learning system.

GD-I4. Compare an epoch, update, example processed, gradient evaluation, and second of wall time. Explain why none is universally the fairest horizontal axis for an optimizer plot.

Mathematical reasoning

GD-M1. For $J(w) = a(w - w^*)^2/2$, derive Theorem 13.1 and classify monotone convergence, oscillatory convergence, one-step convergence, stagnation, and divergence in terms of $1 - \eta a$.

GD-M2. Generalize Theorem 13.1 to a positive-definite quadratic by diagonalizing its Hessian. Derive the stable interval and the optimal constant step in terms of extreme eigenvalues.

GD-M3. Prove Theorem 13.2 for a weighted norm $\|d\|_M = (d^T M d)^{1/2}$. Identify the corresponding preconditioned direction and explain the role of units.

GD-M4. Derive the weight and bias gradients for a mini-batch identity neuron, annotating every array shape. Then derive the reverse-mode chain rule if the identity activation is replaced by a differentiable scalar ϕ.

GD-M5. Derive the heavy-ball characteristic polynomial for a scalar quadratic. Use its roots to identify one stable and one unstable pair (η, β). Explain why momentum adds state without using a Hessian.

GD-M6. Extend the mini-batch variance proposition to unequal covariance matrices. Then state how sampling without replacement alters the independent calculation.

Data and engineering investigations

GD-C1. Reproduce Figure 13.1. Add one deliberately unstable configuration and explain the failure from eigenvalues or recurrence roots before running it.

GD-C2. Train the single identity neuron on the real diabetes table and compare its predictions with a stable least-squares solver. Verify analytic gradients by centered finite differences on a tiny subset and justify the tolerance.

GD-C3. Compare batch, stochastic, and mini-batch methods at equal examples processed and equal wall time. Repeat stochastic runs, report failures, and separate time to training quality from held-out performance.

GD-C4. Profile a training step into data loading, forward pass, backward pass, and update. Change one of batch size, numerical precision, or data layout only after identifying the bottleneck; report the before-and-after evidence.

Contribution studio

GD-PR1. Add a first-order optimizer component with a typed configuration and result record containing termination reason, iterations, objective history, gradient or update norm, elapsed time, and nonfinite failure. Test a convex quadratic, an invalid shape, and divergence.

GD-PR2. Add one optimizer extension–a schedule, Polyak momentum, gradient clipping, averaging, or a justified alternative. The issue must state the recurrence and source; differential tests must compare it with a transparent reference implementation.

GD-PR3. Add a benchmark recorder that compares optimizers without conflating iterations, examples, gradient evaluations, and time. Its output must retain configuration, seed, software version, failures, and raw repeated measurements.

Chapter review

Gradient descent follows the negative gradient because it minimizes the local linear approximation under Euclidean geometry. Curvature determines whether a finite step decreases the objective and how rapidly different directions converge. Least squares exposes this behavior exactly through $X^T X/n$ and connects an identity-activation neuron to a familiar estimator. Stochastic and mini-batch methods estimate the full gradient more cheaply, but introduce variance and additional reproducibility choices. Momentum carries state and can accelerate favorable geometry without becoming a second-order method. Back-propagation computes derivatives; an optimizer decides how to use them. Optimization success and time to training quality remain distinct from statistical generalization and scientific validity.

Executable companion

Lecture 10 notebook 00 begins with tangent lines and hand-computed scalar updates, moves to contours and directional derivatives, then trains a single identity-activation neuron on real diabetes observations. Synchronized plots connect parameter space, data space, and iteration space; finite differences and a trusted least-squares solver verify the implementation. Scaling is then explained through Hessian eigenvalues and condition numbers. The notebook then compares batch, stochastic, and mini-batch updates, Polyak heavy-ball momentum, and a clearly labeled Nesterov-style look-ahead method on shared objectives.

CHAPTER 14

Classification, probability, and decisions

Learning objectives

After this chapter, you should be able to:

- state a binary classification problem as a conditional probability model;
- express logistic regression as a single-neuron computation while preserving its statistical meaning;
- distinguish an observed outcome, a logit, a probability estimate, and an action;
- explain how the sigmoid maps an affine score onto data;
- derive the Bernoulli likelihood, logistic loss, gradient, and Hessian;
- prove convexity and explain why log loss rewards honest probabilities;
- fit and evaluate a leakage-resistant logistic-regression pipeline; and
- separate discrimination, calibration, and threshold-dependent utility.

Where this chapter fits

Linear regression and logistic regression use the same affine computation $z = w^T x + b$. The similarity ends at the score. Linear regression treats the score as a conditional mean for a continuous response and commonly fits squared error. Logistic regression transforms the score into a conditional Bernoulli probability and fits a likelihood-based loss. In neural notation, z is the preactivation and $a = \sigma(z)$ is the postactivation; in this chapter we write $a = p$ to keep its probability meaning visible. A deployed classifier then adds a third object: a decision policy. Keeping these contracts separate is the central idea of this chapter.

14.1 Four objects that must not be conflated

Let $X \in \mathbb{R}^d$ denote measured features and let $Y \in \{0, 1\}$ denote a binary outcome. Before fitting a model, define what $Y = 1$ means. It may mean a manufacturing defect, a malignant diagnosis, a loan default, or the detection of a particle. The choice is semantic, not algebraic: changing the positive event changes every reported probability and every false-positive or false-negative count.

Binary prediction contains four distinct mathematical objects:

1. the **observed outcome** $y_i \in \{0, 1\}$ for row i;
2. the **logit** or score $z_i = w^T x_i + b \in \mathbb{R}$;
3. the **conditional probability** $p_i = P(Y_i = 1 \mid X_i = x_i)$; and
4. an **action** selected from p_i by a threshold, cost model, or constrained decision rule.

The outcome is data, the logit is unbounded, the probability lies in $[0, 1]$, and the action belongs to an operational system. Calling all four a "prediction" conceals important assumptions.

Definition: conditional Bernoulli model

For a fixed feature vector x_i, suppose

$$Y_i \mid X_i = x_i \sim \text{Bernoulli}(p_i), \qquad p_i = P(Y_i = 1 \mid X_i = x_i).$$

For this conditional model,

$$P(Y_i = y_i \mid X_i = x_i) = p_i^{y_i}(1 - p_i)^{1-y_i}, \quad \mathbb{E}[Y_i \mid X_i = x_i] = p_i, \quad \text{Var}(Y_i \mid X_i = x_i) = p_i(1 - p_i).$$

A probability such as $p_i = 0.8$ does not mean that the observed row is "80 percent malignant." Its outcome is binary. The probability describes variation among comparable future units under the modeled population and measurement process. It also does not express an 80 percent probability that the model is correct. Model uncertainty is a different question.

The conditional direction matters. Logistic regression models $P(Y = 1 \mid X = x)$, not $P(X = x \mid Y = 1)$. Bayes' rule connects those directions, but only after introducing event prevalence and the marginal feature distribution. Reversing the conditioning is a common source of invalid scientific claims.

Concept check. Suppose 80 percent of malignant observations have a large measurement. Why is that fact insufficient to determine the probability of malignancy after observing a large measurement? Name the missing quantities.

14.2 Logistic regression as one neuron

The logistic model can be drawn as one computational neuron without changing its statistical meaning. For one observation,

$$z_i = w^T x_i + b, \qquad a_i = \sigma(z_i) = p_i.$$

The symbol z_i names the **preactivation**: the unbounded affine score or logit. The symbol a_i names the **postactivation**. Because this particular postactivation is intended to estimate $P(Y_i = 1 \mid X_i = x_i)$, we normally call it p_i throughout the probability lesson. Thus a_i and p_i are not two different outputs here; they are two names that emphasize computational role and statistical meaning, respectively.

Definition: Logistic single-neuron specification

Component	Logistic specification
Target	$y_i \in \{0, 1\}$
Preactivation	$z_i = w^T x_i + b$
Postactivation	$a_i = \sigma(z_i) = p_i$
Output meaning	$p_i = P(Y_i = 1 \mid X_i = x_i)$
Training loss	Bernoulli negative log-likelihood
Score derivative	$\delta_i = \partial \ell_i / \partial z_i = p_i - y_i$
Decision	a separate, versioned threshold or cost policy

This specification matters more than the neuron drawing. The affine calculation alone does not determine whether the output is a continuous measurement, a probability, or a margin score. The target domain, activation, loss, sampling assumptions, and output semantics must agree.




Figure 14.1: The logistic single-neuron contract. **A:** A forward pass forms the preactivation $z = w^T x + b$ and the postactivation $a = \sigma(z) = p$. Bernoulli log loss returns the score derivative $\delta = \partial \ell / \partial z = p - y$ during the backward calculation. **B:** The computational graph becomes a statistical estimator only after its target, activation, loss, output meaning, and decision boundary are specified.

Figure 14.1 is also a map of the derivation ahead. The sigmoid supplies the probability range, the Bernoulli likelihood supplies the loss, and the chain rule supplies the backward signal $p - y$.

14.3 The sigmoid turns a score into a probability

The logistic sigmoid is

$$\sigma(z) = \frac{1}{1 + e^{-z}}.$$

It is not merely a convenient S-shaped curve. It is an invertible map from the real line to the open unit interval and therefore connects an unconstrained linear score with a valid probability.

Proposition 14.1 (basic sigmoid geometry)**.** *For every $z \in \mathbb{R}$,*

$$0 < \sigma(z) < 1, \qquad \sigma(0) = \frac{1}{2}, \qquad \sigma(-z) = 1 - \sigma(z), \qquad \sigma'(z) = \sigma(z)\big(1 - \sigma(z)\big).$$

The derivative is positive and is maximized at $z = 0$, where $\sigma'(0) = 1/4$.

Proof. The denominator $1 + e^{-z}$ exceeds one, which gives the range. Substitution gives $\sigma(0) = 1/2$. Multiplying numerator and denominator by e^z gives $\sigma(z) = e^z/(1 + e^z)$, from which the symmetry identity follows. Direct differentiation yields

$$\sigma'(z) = \frac{e^{-z}}{(1 + e^{-z})^2} = \sigma(z)\big(1 - \sigma(z)\big).$$

Writing $u = \sigma(z) \in (0, 1)$ reduces the derivative to $u(1 - u)$, a concave quadratic with its unique maximum $1/4$ at $u = 1/2$, equivalently $z = 0$. □

For one feature x, let $z = b + wx$. If $w \neq 0$, then

$$p(x) = \sigma(b + wx) = \sigma\big(w(x - x_{0.5})\big), \qquad x_{0.5} = -\frac{b}{w}.$$

The midpoint $x_{0.5}$ is the feature value at which $p(x) = 1/2$. The sign of w determines whether the curve rises or falls. Its magnitude controls the steepness on the chosen feature scale, and

$$\left.\frac{dp}{dx}\right|_{x=x_{0.5}} = \frac{w}{4}.$$

Thus the numerical coefficient depends on units. If millimeters become meters, the stored preprocessing and the coefficient must change together.




Figure 14.2: From activation to data. **A:** The sigmoid maps every real score to $(0, 1)$; its derivative is largest at the midpoint and vanishes in the saturated tails. **B:** Several sigmoid curves can be placed over the same binary observations, so shape must be learned rather than selected by eye. **C:** A one-feature logistic model fitted on a training split of the Wisconsin Diagnostic Breast Cancer data produces a conditional malignant-event probability. Vertical jitter only reveals overlapping binary outcomes; it is not a new response value.

Figure 14.2 makes a subtle point visible: an observed binary response does not lie on the fitted curve except in the limiting sense of zero or one. The curve estimates the conditional mean of the Bernoulli outcome. Many observations near the same x would be needed to estimate that mean directly; the logistic form shares information across feature values.

14.3.1 Odds and log-odds

For $0 < p < 1$, the **odds** of the event are $p/(1 - p)$. The inverse sigmoid satisfies

$$\operatorname{logit}(p) = \log \frac{p}{1 - p}.$$

The logistic-regression model is therefore

$$\log \frac{p(x)}{1 - p(x)} = w^T x + b.$$

Holding all other features fixed, increasing feature x_j by one unit adds w_j to the log-odds and multiplies the odds by e^{w_j}. This is an associational model statement, not a causal effect. Correlated features, measurement choices, selection, and interventions all require additional reasoning.

Common misconception

Misconception: a coefficient of 0.7 increases probability by 0.7. **Correction:** it multiplies the conditional odds by $e^{0.7}$ when the other recorded features are held fixed. The probability change depends on the starting probability because the sigmoid is nonlinear.

14.4 Likelihood turns probability modeling into estimation

Probability and likelihood use the same formula in different directions. Probability holds a parameter fixed and studies possible outcomes. Likelihood holds the observed outcomes fixed and compares candidate parameter values.

For conditionally independent observations, the Bernoulli likelihood is

$$L(w, b; y_1, \ldots, y_n) = \prod_{i=1}^{n} p_i^{y_i} (1 - p_i)^{1-y_i}, \qquad p_i = \sigma(w^T x_i + b).$$

Conditional independence is an assumption. Repeated measurements from one patient, neighboring pixels, related financial accounts, or time-adjacent sensor readings may violate it. The split design must respect the dependence unit even when the optimization code accepts rows independently.

Products of many probabilities become numerically tiny. Taking a logarithm converts the product into a sum without changing its maximizer. Negating and averaging gives the empirical logistic loss

$$J(w, b) = -\frac{1}{n} \sum_{i=1}^{n} \left[y_i \log p_i + (1 - y_i) \log(1 - p_i) \right].$$

For one observation,

$$\ell(p; y) = -y \log p - (1 - y) \log(1 - p).$$

When $y = 1$, the loss is $-\log p$; when $y = 0$, it is $-\log(1 - p)$. A confident wrong probability receives an unbounded penalty.




Figure 14.3: Three views of the Bernoulli model. **A:** Per-observation log loss rewards probability assigned to the observed outcome and sharply penalizes confident errors. **B:** With k events in ten trials, the likelihood is maximized at $\widehat{p} = k/10$; its width records finite-sample uncertainty. Curves are normalized only for visual comparison. **C:** If the true event probability is q, expected log loss is uniquely minimized by reporting $p = q$.

14.4.1 Why log loss elicits a probability

A loss for probability forecasts should not reward systematic exaggeration or hedging. Log loss has this property.

Theorem 14.2 (strict propriety of Bernoulli log loss)**.** *Let $Y \sim \text{Bernoulli}(q)$ with $q \in (0,1)$. If a forecaster reports $p \in (0,1)$, its expected log loss is*

$$R_q(p) = -q \log p - (1-q)\log(1-p).$$

The unique minimizer is $p = q$.

Proof. Differentiate with respect to the reported probability:

$$R_q'(p) = -\frac{q}{p} + \frac{1-q}{1-p} = \frac{p-q}{p(1-p)}.$$

The denominator is positive on $(0,1)$, so the derivative is negative for $p < q$, zero at $p = q$, and positive for $p > q$. Equivalently,

$$R_q(p) - R_q(q) = D_{\text{KL}}(\text{Bernoulli}(q) \,\|\, \text{Bernoulli}(p)) \geq 0,$$

with equality only when $p = q$. □

The theorem is a population statement. It does not guarantee that the chosen feature representation and affine log-odds can express the true conditional probability $q(x)$. Nor does it guarantee that the training population matches deployment. A proper loss encourages honest reporting within the model and data available; it cannot repair misspecification or distribution shift.

Concept check. Why does 100 percent training accuracy fail to establish that the reported probabilities are meaningful? Give one optimization reason and one data-generating reason.

14.5 The gradient reveals the single-neuron connection

Write the augmented design matrix and parameter vector as

$$\widetilde{X} = \begin{bmatrix} 1 & x_1^T \\ \vdots & \vdots \\ 1 & x_n^T \end{bmatrix}, \qquad \theta = \begin{bmatrix} b \\ w \end{bmatrix}, \qquad z = \widetilde{X}\theta, \qquad p = \sigma(z).$$

The model is a single computational unit: an affine score followed by a sigmoid activation. The loss, rather than the picture of the unit, determines the learning rule.

Theorem 14.3 (logistic-loss gradient and Hessian)**.** *For the average Bernoulli negative log-likelihood,*

$$\nabla_\theta J(\theta) = \frac{1}{n}\widetilde{X}^T(p - y)$$

and

$$\nabla_\theta^2 J(\theta) = \frac{1}{n}\widetilde{X}^T W \widetilde{X}, \qquad W = \text{diag}\big(p_i(1-p_i)\big).$$

Consequently, J is convex.

Proof. For one row, use $p_i = \sigma(z_i)$ and $dp_i/dz_i = p_i(1 - p_i)$. The chain rule gives

$$\frac{\partial \ell_i}{\partial z_i} = \left(-\frac{y_i}{p_i} + \frac{1 - y_i}{1 - p_i}\right) p_i(1 - p_i) = p_i - y_i.$$

Since $\nabla_\theta z_i = \widetilde{x}_i$, summing and averaging yields the gradient. Differentiating once more gives the stated Hessian. For every vector v,

$$v^T \nabla^2 J(\theta) v = \frac{1}{n} (\widetilde{X}v)^T W (\widetilde{X}v) \geq 0,$$

because every diagonal entry of W is nonnegative. Hence the Hessian is positive semidefinite and J is convex. □

In the computational notation introduced earlier, $a = p$, so the backward signal can be written either as $p - y$ or $a - y$. The probability notation is preferable here because it prevents the output's statistical meaning from disappearing. The residual-like term makes the update resemble linear regression:

$$\theta_{t+1} = \theta_t - \eta \frac{1}{n} \widetilde{X}^T (p_t - y).$$

But the resemblance must not erase the differences. Linear regression usually uses an identity response map and squared error; logistic regression uses a sigmoid response map and Bernoulli log loss. Its curvature changes with the current probabilities through W.

Convexity means that any finite stationary point is globally optimal. It does not mean that every implementation converges, that the optimum is unique, or that the fitted probability generalizes. If the data are perfectly separable, the unregularized likelihood may improve as $\|w\| \to \infty$ without attaining a finite minimizer.

14.6 Stable computation is part of the mathematics

The expression $\log(1 + e^z)$ overflows when z is large. NumPy names the stable two-argument operation

$$\operatorname{logaddexp}(a, b) := \log\left(e^a + e^b\right).$$

Consequently, $\operatorname{logaddexp}(0, z) = \log(e^0 + e^z) = \log(1 + e^z)$; the zero is the first argument to the operation, not an extra term in the statistical model. This gives the stable softplus form of the per-row loss:

$$\ell(z; y) = \log(1 + e^z) - yz = \operatorname{logaddexp}(0, z) - yz.$$

Implementations evaluate this quantity without first constructing the possibly enormous value e^z—for example, as $\max(0, z) + \log(1 + e^{-|z|})$. Likewise, a stable sigmoid evaluates positive and negative scores by different algebraically equivalent branches.

Listing 14.1: Stable scalar sigmoid and vectorized loss from logits.

```
def stable_sigmoid(score: float) -> float:
    """Map a real score to an event probability without overflow."""
    if score >= 0.0:
        return 1.0 / (1.0 + math.exp(-score))
    exponential = math.exp(score)
    return exponential / (1.0 + exponential)


```

```python
def logistic_loss_from_logits(logits, outcomes):
    """Return mean Bernoulli negative log-likelihood from raw logits."""
    logits = np.asarray(logits, dtype=float)
    outcomes = np.asarray(outcomes, dtype=float)
    if logits.shape != outcomes.shape:
        raise ValueError("logits and outcomes must have the same shape")
    return np.mean(np.logaddexp(0.0, logits) - outcomes * logits)
```

A professional implementation tests values such as $z = \pm 1000$, verifies an analytic gradient against central finite differences, records termination status, and compares a transparent implementation with an independent library. The comparison must align regularization, intercept handling, feature scaling, class order, tolerance, and stopping criteria. Agreement after those choices is strong evidence; agreement by accident is not.

Professional practice

Fit preprocessing and the estimator as one pipeline. Persist feature order, units, target encoding, scaler state, model parameters, software versions, and training-data identity. A coefficient vector without its preprocessing and semantic contract is not a deployable model.

14.7 A complete evidence workflow

Logistic regression does not remove the evidence boundaries introduced in Chapter 11. A defensible workflow proceeds as follows:

1. define the positive event, prediction unit, horizon, and deployment population;
2. inspect schema, missingness, ranges, duplicates, dependence, and class prevalence;
3. split by the real independence unit before fitting transformations;
4. fit imputers, scalers, feature transformations, and the estimator on training data only;
5. use validation data for model, regularization, and threshold choices;
6. compare probability quality and decision utility with declared baselines; and
7. open the sealed test set once for the frozen model-policy pair.

Scaling is not required to make the logistic formula valid. It improves optimization conditioning and makes regularization act more comparably across features. Scaling the complete dataset before splitting is leakage because the validation and test feature distributions influence the fitted transformation.

14.7.1 Real-data example: diagnostic measurements

Worked example: diagnostic measurement to review policy

The companion notebook reads the Wisconsin Diagnostic Breast Cancer table from the repository's SQLite database. It defines

$$Y = \mathbf{1}\{\text{diagnosis is malignant}\}.$$

This dataset is appropriate for learning estimation and evaluation, but it is not a clinical validation study and the resulting model must not be described as a medical device.

A regularized pipeline fits scaling and logistic regression on training rows. Validation rows then answer three separate questions: whether event and non-event probabilities separate, whether reported

probabilities agree with observed frequencies, and which threshold serves one declared cost model. The sealed test set remains unused until the model and policy are frozen.

Figure 14.4 fits a regularized logistic pipeline on a training split and uses a validation split for three different questions. The panels intentionally do not collapse into one "model quality" number.




Figure 14.4: Three forms of validation evidence from the repository's breast cancer table. **A:** Class-conditional probability histograms describe discrimination. **B:** Binned event fractions with 95 percent Wilson intervals provide limited calibration evidence; the intervals expose the small validation sample. **C:** A threshold is chosen for one explicitly hypothetical cost model in which a false negative costs five times a false positive. Changing that cost model can change the action rule without changing the fitted probability model.

14.8 Measuring classification performance professionally

"How accurate is the model?" is not a complete evaluation question. A professional report first names the claim, population, sample, baseline, and decision policy. It then measures several properties because classification performance has at least three layers.

- **Probability quality:** Did the model assign useful probabilities to what occurred? Examine log loss, Brier score, and calibration evidence.
- **Discrimination:** Do event cases tend to rank above non-event cases? Examine ROC and precision-recall curves and their summaries.
- **Decision performance:** What happened under one specified action rule? Examine confusion counts, conditional rates, cost, and capacity.

No layer replaces the others. A model can rank cases well while systematically overstating probability. A well-calibrated model can still serve a poor action policy. A high-accuracy policy may merely predict the common class.

14.8.1 Begin with a baseline and probability evidence

The average validation log loss measures the probability assigned to observed outcomes. The Brier score

$$\frac{1}{m}\sum_{i=1}^{m}(p_i - y_i)^2$$

is another proper score. Both should be compared with a baseline fitted without test information. A prevalence baseline reports the training event frequency for every row. In an operational study, the relevant baseline might instead be the current laboratory workflow, an established score, or a policy that sends every case for review. A complex model that cannot improve on the relevant baseline has not earned its complexity.

Discrimination asks whether event rows tend to receive larger scores than non-event rows. ROC AUC is the probability that a randomly selected event row receives a higher score than a randomly selected non-event row, with standard handling for ties. It is threshold-free and does not establish calibration. Precision-recall summaries are sensitive to event prevalence and can be more informative for rare events.

Calibration asks whether probabilities mean what they report on a stated population. Among comparable cases assigned probability near q, an event rate near q supports calibration. Reliability diagrams depend on binning and sample size, so uncertainty must be visible. A sigmoid output is constrained to $(0, 1)$, but range is not calibration.

Common misconception

Misconception: a high ROC AUC proves that probabilities are accurate. **Correction:** any strictly increasing transformation preserves ranking and therefore ROC AUC while changing probability values. Calibration requires separate evidence.

Calibration may drift when prevalence, measurement, or case mix changes. Post-hoc methods such as Platt scaling or isotonic regression must be fitted on data not used to fit the underlying score, commonly through cross-validated or nested procedures. Recalibration is an estimated model, not a cosmetic plotting operation.

14.8.2 A confusion matrix is four counts with four meanings

After a threshold t defines $\widehat{Y} = \mathbf{1}\{p \geq t\}$, every evaluated row enters one cell:

	Predicted non-event	Predicted event
Actual non-event	true negative (TN)	false positive (FP)
Actual event	false negative (FN)	true positive (TP)

The word "positive" identifies the declared event; it does not mean a good outcome. The word "false" means that the thresholded action disagrees with the recorded label. It does not establish that the label, measurement process, or sampling design is correct.

Several familiar rates use different conditioning sets:

$$\text{sensitivity} = \frac{TP}{TP + FN} = P(\widehat{Y} = 1 \mid Y = 1), \qquad \text{specificity} = \frac{TN}{TN + FP} = P(\widehat{Y} = 0 \mid Y = 0),$$

$$\text{precision} = \frac{TP}{TP + FP} = P(Y = 1 \mid \widehat{Y} = 1), \qquad \text{NPV} = \frac{TN}{TN + FN} = P(Y = 0 \mid \widehat{Y} = 0).$$

Sensitivity conditions on actual event rows; precision conditions on predicted event actions. Interchanging them reverses a conditional probability. False positive rate is $FP/(FP + TN) = 1 -$ specificity, and false negative rate is $FN/(FN + TP) = 1 -$ sensitivity. Balanced accuracy averages sensitivity and specificity so that the more common class does not dominate the average.

Always report the four counts with the rates. A sensitivity of 90 percent based on 18 of 20 event rows and one based on 18,000 of 20,000 rows are the same point estimate but not the same amount of evidence. A zero denominator makes the corresponding rate undefined, not zero.

14.8.3 The evaluated data determine what a metric means

Let event prevalence be $\pi = P(Y = 1)$, sensitivity be s, and specificity be c. Even if s and c transported unchanged to a new population,

$$\text{precision} = \frac{\pi s}{\pi s + (1-\pi)(1-c)}, \qquad \text{accuracy} = \pi s + (1-\pi)c.$$

Precision and accuracy therefore change when the event prevalence changes. This is not a defect in the formulas; it records a change in the question being asked of the system.




Figure 14.5: A confusion matrix is contextual evidence, not a permanent model attribute. **A:** Counts retain the validation sample size at the threshold selected under the explicitly hypothetical five-to-one error cost. **B:** Row normalization conditions on the recorded actual class and exposes sensitivity and specificity. **C:** Holding those two rates fixed while changing prevalence still changes precision, negative predictive value, and accuracy. The vertical line marks only this validation sample's prevalence; it is not a deployment estimate.

Prevalence is only one aspect of data context. Performance can also change with disease severity, sensor calibration, laboratory site, acquisition protocol, missingness, time, demographic composition, treatment access, and the definition or quality of the outcome label. A dataset with easier, more extreme cases may produce stronger discrimination than a screening population with subtle cases. This broader dependence on the range and mix of cases is often called **spectrum effect**.

The repository's breast-cancer table is not a random sample of every future clinical case. Its prevalence must not be substituted for that of a hospital, screening program, or community. It also lacks the site, time, demographic, and workflow variables needed for an external-validity or subgroup audit. The professional response is to name that evidence gap, not to hide it behind an aggregate score.

Concept check. A classifier has the same sensitivity and specificity at two hospitals but much lower precision at one. Give a mathematical explanation and two data-quality explanations that should be investigated.

14.8.4 Attach uncertainty and scope to every performance claim

Validation metrics are estimates from a finite sample. For a frozen model and threshold, a binomial interval may summarize uncertainty in sensitivity or specificity when observations are independent. If rows are grouped

by patient, site, batch, or time, resampling and intervals must preserve those groups. Repeated cross-validation can study development variability, but it does not turn adaptively reused data into an untouched final test set.

A professional classification report records:

- event definition, horizon, prediction unit, intended use, and target population;
- dataset sources, dates, sites, inclusion rules, sample sizes, and prevalence;
- split unit, baselines, and every model-selection decision;
- log loss or Brier score, discrimination, and calibration evidence;
- the versioned threshold, confusion counts, conditional rates, costs, capacity, and uncertainty intervals;
- performance by relevant site, time period, and subgroup, together with the sample size of every slice;
- known missing slices, label limitations, and plausible deployment shifts; and
- model, feature, software, data, and policy versions sufficient to reproduce the report.

14.9 A probability model is not a decision policy

Let action $a = 1$ mean "intervene" and $a = 0$ mean "do not intervene." Suppose a false positive costs $C_{FP} > 0$ and a false negative costs $C_{FN} > 0$, while correct actions have zero cost. Given a calibrated probability p, the conditional risks are

$$R(a = 1 \mid x) = C_{FP}(1 - p), \qquad R(a = 0 \mid x) = C_{FN}p.$$

Proposition 14.4 (cost-sensitive threshold)**.** *Under the stated two-action cost model, choose action* 1 *exactly when*

$$p \geq \frac{C_{FP}}{C_{FP} + C_{FN}}.$$

Proof. Choose action 1 when its conditional risk is no larger: $C_{FP}(1 - p) \leq C_{FN}p$. Rearranging gives the stated threshold. □

The familiar threshold 0.5 is optimal only under this simplified model with equal error costs. Real policies may include review capacity, delayed outcomes, abstention, several actions, legal constraints, subgroup harms, or utilities that vary by case. Threshold selection is therefore a product decision backed by statistical evidence, not a default supplied by the sigmoid.

At every candidate threshold, recompute the confusion counts, conditional rates, action volume, and operational cost. A threshold that exceeds review capacity is not usable merely because it has attractive sensitivity. Conversely, a capacity constraint is a property of the operating system, not a reason to relabel the result as intrinsic model performance.

Version the decision policy separately from the score model. Costs, prevalence, or capacity may change the threshold without requiring new model parameters. Evaluate the final frozen model-policy pair on untouched test data.

Failure mode

Selecting a threshold on the test set converts the test set into validation data. Reporting that same performance as final evidence is optimistic, even if the model coefficients were never refitted.

14.10 Multiclass and multilabel extensions

For K mutually exclusive classes, a softmax converts logits z_k into

$$p_k = \frac{e^{z_k}}{\sum_{j=1}^{K} e^{z_j}}, \qquad \sum_{k=1}^{K} p_k = 1.$$

Categorical cross-entropy is the corresponding negative log-likelihood. Stable implementations subtract the largest logit or use a log-sum-exp primitive.

One-vs-rest fits K binary problems and may require probability reconciliation. Multilabel prediction is different: several labels may be true at once, so independent sigmoid outputs may be appropriate. The data-generating semantics, not the number of output columns, determine the model.

Macro averages weight classes equally; micro averages weight individual decisions equally. Neither should replace class-level errors and an inspected confusion matrix.

14.11 Engineering the model as a reliable component

A production classifier should expose explicit interfaces such as `predict_logit`, `predict_proba`, and a separately versioned `decide`. Tests should cover:

- schema, feature order, units, missing values, and unexpected categories;
- positive-class identity and library `classes_` ordering;
- finite output and $0 \le p \le 1$ at extreme inputs;
- agreement of analytic and numerical gradients;
- preprocessing fitted only on training rows;
- deterministic splits and reproducible optimization;
- threshold equality, abstention boundaries, and policy versions; and
- serialization round trips that preserve probabilities.

Monitoring must also preserve the distinctions in this chapter. Service logs can immediately reveal latency, missing features, probability distributions, and action rates. Discrimination and calibration require outcomes, which may arrive later or only for a selected subset. A monitoring design must specify how predictions are joined to outcomes and how selection bias enters that join.

Professional practice

An API should not return a floating-point field called `risk` without a contract. Document the event, horizon, applicable population, model version, and probability semantics. If the API also returns an action, include the policy version and enough trace information to reconstruct the decision.

14.12 Exercises

Conceptual and diagnostic problems

C1. A model returns a logit of -2.3. Explain why it is neither a probability nor a negative probability. Compute the corresponding event probability and odds.

C2. Explain why two observations with probabilities 0.51 and 0.99 have the same class prediction at threshold 0.5 but provide different evidence.
C3. Give an example in which discrimination remains stable while calibration changes after deployment.
C4. A classifier has 99 percent accuracy on an event with prevalence 1 percent. Construct a confusion matrix consistent with those facts but with zero recall.
C5. Distinguish the claims "the event probability is 0.8," "the model is 80 percent confident," and "80 percent of observed event rows have this measurement." Which claims are defined by logistic regression?

Mathematical problems

M1. Derive $\sigma(-z) = 1 - \sigma(z)$ and use it to design a numerically stable implementation for both signs of z.
M2. Starting from the Bernoulli likelihood, derive the average negative log-likelihood without skipping the product-to-sum step.
M3. Derive the gradient with respect to w and b separately. Then recover the augmented-matrix formula.
M4. Prove that adding $\lambda\|w\|_2^2/2$ preserves convexity. State when the regularized objective is strictly convex.
M5. For the two-action cost model, derive the optimal threshold when correct positive and correct negative actions also have nonzero costs.
M6. Construct a linearly separable dataset and show analytically why scaling a separating parameter vector can drive unregularized logistic loss toward zero without reaching a finite minimizer.

Computational investigations

P1. Query a binary dataset from the course SQLite database. Produce a data dictionary, prevalence report, missingness audit, and a split design tied to the independence unit.
P2. Implement stable sigmoid, loss, and gradient functions with NumPy-style docstrings and type hints. Test extreme logits and verify the gradient with central finite differences.
P3. Fit a transparent batch-gradient implementation and an unregularized library reference under matched conditions. Compare coefficients, probabilities, objective value, iterations, and wall time.
P4. Compare a prevalence baseline and a regularized pipeline using log loss, Brier score, ROC AUC, and a reliability diagram with uncertainty. Explain what each result does and does not establish.
P5. Specify two plausible cost models for one application. Show how the validation-selected threshold and confusion matrix change while model probabilities remain fixed.

Contribution studio

For contribution problem **CLF-PR1**, add a tested probability diagnostic to the course package. The pull request must define the mathematical quantity, include a failure-mode test, and demonstrate it on a public dataset without opening the test split during development.

For contribution problem **CLF-PR2**, implement a regularized logistic objective or reproducible benchmark recorder. Include typed public interfaces, NumPy-style documentation, finite-difference verification, and evidence that intercept treatment matches the written objective.

Chapter review

Logistic regression is a conditional probability model built from an affine score and the single-neuron computation $z = w^T x + b$, $a = \sigma(z) = p$. Its Bernoulli likelihood gives the backward signal $\delta = p - y$.

The gradient resembles the linear-regression gradient because both propagate a residual-like signal through the same affine computation; the activation, response model, loss, curvature, target domain, and interpretation are different. The next model retains the affine score but replaces probabilities and log loss with signed margins and hinge loss. Proper probability estimation, discrimination, calibration, and decision utility remain separate forms of evidence. A reliable system preserves those distinctions in code, evaluation, deployment, and monitoring.

Executable companion

Lecture 11 notebook 00 derives and fits the model, verifies its gradient, and evaluates its evidence. Notebook 01 then studies the same affine skeleton under the different semantics of a linear support vector machine. The following API chapter unifies reusable mechanism only after those distinctions are explicit. Production code belongs in tested modules.

CHAPTER 15

Linear support vector machines

Learning objectives

After this chapter, you should be able to:

- express a linear support vector machine as a single-neuron model while distinguishing its loss and output semantics from regression models;
- derive the distance from a point to a hyperplane and the width of the canonical margin;
- pass from hard-margin constraints to slack variables and hinge loss;
- calculate a valid subgradient of the regularized hinge objective;
- explain the roles of scaling, regularization, and support vectors; and
- evaluate margin scores without misrepresenting them as probabilities.

Where this chapter fits

Chapter 14 used a sigmoid single neuron to model a conditional probability. A linear support vector machine begins with the same affine preactivation $z(x) = w^T x + b$, but asks a different question: can we find a separating hyperplane with a wide, violation-tolerant margin? This third single-neuron configuration will make the shared structure—and the important differences—visible before Chapter 16 turns that structure into a software design.

The chapter follows one continuous argument. An affine score produces a hyperplane. Orthogonal projection turns that score into distance. Normalizing the otherwise arbitrary parameter scale produces a geometric margin. Maximizing that margin produces the hard-margin optimization problem. Finally, slack variables repair infeasible constraints and become hinge loss. Each new formula will answer a geometric problem created by the preceding one.

15.1 One affine neuron, a different objective

For an observation $x \in \mathbb{R}^p$, define

$$z(x) = w^T x + b.$$

The sign of $z(x)$ selects a class, and the zero level set $H = \{x : w^T x + b = 0\}$ is the decision hyperplane. We use signed targets $y_i \in \{-1, +1\}$. The product $y_i z_i$ is positive precisely when the score has the correct sign. This product will become the organizing quantity for the chapter.

The neuron is therefore familiar, but its learning rule is not yet specified. Linear regression couples the affine score to squared loss, and logistic regression couples a sigmoid postactivation to log loss. A linear SVM will couple the affine score to signed labels, geometric margin, regularization, and hinge loss. The point is not to attach a new name to the same model; it is to reuse a computation while changing the mathematical problem.

Common misconception

Misconception: sharing the affine formula makes these models mathematically equivalent. **Correction:** the activation, target space, loss, regularization, optimizer, and output interpretation are part of the model. Reusing one computation does not erase those differences.

15.2 Geometry of a separating hyperplane

First establish the geometry rather than memorizing a distance formula. If $u, v \in H$, then

$$w^T u + b = 0, \qquad w^T v + b = 0.$$

Subtracting gives $w^T(u - v) = 0$. Every displacement $u - v$ along H is therefore perpendicular to w: the weight vector is the normal direction. Moving parallel to H leaves the score unchanged, while moving in the w direction changes it most rapidly.

Proposition 15.1 (distance to a hyperplane)**.** *For $w \neq 0$, the Euclidean distance from x to H is*

$$\operatorname{dist}(x, H) = \frac{|w^T x + b|}{\|w\|_2}.$$

Proof. Let x_H be the orthogonal projection of x onto H. The shortest displacement is perpendicular to H, so write $x - x_H = tw$. Since $w^T x_H + b = 0$,

$$w^T x + b = w^T(x - x_H) = t\|w\|_2^2.$$

Therefore $|t| = |w^T x + b|/\|w\|_2^2$, and $\|x - x_H\|_2 = |t|\|w\|_2$ gives the result. □

For a concrete calculation, take $w = (2, -1)^T$, $b = -1$, and $q = (2, 1.5)^T$. Then $z(q) = 1.5$, $\|w\|_2 = \sqrt{5}$, and

$$q_H = q - \frac{z(q)}{\|w\|_2^2} w = (1.4, 1.8)^T.$$

Indeed, $2(1.4) - 1.8 - 1 = 0$, so $q_H \in H$, and the distance is $1.5/\sqrt{5} \approx 0.671$. Figure 15.1A shows the point, its projection, the normal, and the displacement used in the proof.

15.2.1 Functional and geometric margin

For signed label y_i, define the **functional margin** $m_i = y_i(w^T x_i + b)$. Its sign records correctness, but its magnitude is not a distance. Replacing (w, b) by (cw, cb) for any $c > 0$ leaves the hyperplane and every decision unchanged while multiplying m_i by c. The geometric signed margin removes that arbitrary scale:

$$\gamma_i = \frac{y_i(w^T x_i + b)}{\|w\|_2}.$$

Under the same rescaling, both numerator and denominator acquire a factor c, so γ_i is unchanged. This is the distinction visualized in Figure 15.1B.

15.2.2 Canonical scaling and the hard margin

Suppose the data are linearly separable. Among all positive rescalings of a fixed separating boundary, choose the canonical one satisfying

$$\min_i y_i(w^T x_i + b) = 1.$$

At least one observation from each side then touches a supporting level $w^T x + b = +1$ or $w^T x + b = -1$. These observations are the first support vectors. Canonical scaling does not move the decision boundary; it merely chooses one representative from an otherwise redundant family of parameter vectors.

Proposition 15.2 (canonical margin width)**.** *The distance between the planes $w^T x + b = 1$ and $w^T x + b = -1$ is $2/\|w\|_2$.*

Proof. Each plane lies $1/\|w\|_2$ from the central plane by the preceding proposition. They lie on opposite sides, so the distances add. □

The factor 2 is fixed, so maximizing width is equivalent to minimizing $\|w\|_2$. Squaring the norm and multiplying by $1/2$ preserve the minimizer and give a convenient convex objective. Canonical scaling supplies the constraints, producing

$$\min_{w,b} \frac{1}{2}\|w\|_2^2 \quad \text{subject to} \quad y_i(w^T x_i + b) \geq 1, \qquad i = 1, \ldots, n.$$

This is the hard-margin SVM. The objective widens the band; the constraints keep every training point on the correct side of its supporting level. Figure 15.1C shows both roles. The zero vector cannot minimize the problem because it violates every constraint.




Figure 15.1: The derivation of maximum-margin geometry for $z(x) = 2x_1 - x_2 - 1$. **A:** Orthogonal projection onto $z = 0$ follows the normal w and gives distance $|z(q)|/\|w\|_2$. **B:** rescaling (w, b) changes functional margin but not normalized geometric margin. **C:** canonical scaling places the closest observations on $z = \pm 1$; the perpendicular distance between these supporting levels is $2/\|w\|_2$. The figure is generated by the same NumPy and Matplotlib construction used in Lecture 11 notebook 01.

Concept check. Why can we not maximize a meaningful geometric margin merely by multiplying both w and b by a large constant? Which normalization removes that ambiguity?

15.3 Soft margins lead to hinge loss

The hard-margin problem has a serious failure mode: one overlapping or mislabeled observation can make all constraints jointly infeasible. We retain the desired unit margin but permit observation i to fall short by a nonnegative slack ξ_i:

$$y_i(w^T x_i + b) \geq 1 - \xi_i.$$

Rearranging gives $\xi_i \geq 1 - y_i z_i$, while nonnegativity also requires $\xi_i \geq 0$. Therefore, at fixed (w, b), the smallest feasible slack is

$$\xi_i = \max\{0, 1 - y_i(w^T x_i + b)\}.$$

This is the hinge loss $\ell_{\text{hinge}}(y_i, z_i)$. Its three regions have direct geometric meanings:

- $y_i z_i > 1$: correctly classified beyond the margin, so $\xi_i = 0$;
- $0 < y_i z_i < 1$: correctly classified but inside the margin, so $0 < \xi_i < 1$; and
- $y_i z_i \leq 0$: on the boundary or misclassified, so $\xi_i \geq 1$.

Proposition 15.3 (slack–hinge equivalence)**.** *For fixed (w, b), minimizing $\sum_i \xi_i$ subject to $\xi_i \geq 0$ and $\xi_i \geq 1 - y_i z_i$ produces $\xi_i = \max(0, 1 - y_i z_i)$ for every i.*

Proof. Each ξ_i must be at least both 0 and $1 - y_i z_i$. Their maximum is the smallest feasible value. Any larger value increases the objective without improving feasibility. □

We use the averaged objective

$$J(w, b) = \frac{\lambda}{2}\|w\|_2^2 + \frac{1}{n}\sum_{i=1}^{n} \max\{0, 1 - y_i(w^T x_i + b)\}.$$

Larger λ favors a smaller weight norm and therefore a wider margin, while permitting more violations. Many libraries instead use $\frac{1}{2}\|w\|^2 + C\sum_i \xi_i$; larger C then penalizes violations more strongly. The convention, and whether the loss is summed or averaged, must be documented.

15.4 Subgradients and first-order training

The geometry has now produced an objective. Training requires the direction in which that objective changes. This calculation also explains computationally why only observations near the boundary determine the fitted solution.

Hinge loss is convex but not differentiable at signed margin $y_i z_i = 1$. Away from that kink,

$$\frac{\partial \ell_i}{\partial z_i} = \begin{cases} -y_i, & y_i z_i < 1, \\ 0, & y_i z_i > 1. \end{cases}$$

If $A = \{i : y_i z_i < 1\}$ is the active set, a valid batch subgradient is

$$g_w = \lambda w - \frac{1}{n}\sum_{i \in A} y_i x_i, \qquad g_b = -\frac{1}{n}\sum_{i \in A} y_i.$$

At the kink, any value between the one-sided slopes is valid; an implementation must choose and test a convention. A subgradient step is $(w, b) \leftarrow (w, b) - \eta(g_w, g_b)$.

Failure mode

A decreasing training objective is an implementation check, not proof of generalization. Selection and reporting still require held-out data, comparison with baselines, subgroup analysis, and metrics chosen for the deployment cost.

15.5 Support vectors, scaling, and scores

The active set A in the preceding formula is the algebraic version of the orange-ringed observations in Figure 15.2. Only observations on or inside the unit margin have nonzero hinge subgradients. At a solution, these support vectors determine the boundary; points far beyond the margin do not directly contribute to the hinge term. This sparsity is geometric, not a license to ignore provenance or data quality.

Feature scaling is essential. A Euclidean norm on w and a geometric margin depend on feature units. If one feature is measured in micrometers and another in thousands of dollars, the unscaled penalty silently imposes an arbitrary geometry. Fit a scaler on training data only, reuse it unchanged on validation and test data, and retain feature names and units.

15.5.1 Scores are not probabilities

The raw score $z = w^T x + b$ ranks distance in the direction normal to the boundary, but it is not a probability. If calibrated probabilities are needed, calibration is a separate model-selection step fitted without contaminating the final test set.

Worked example: margin status for three observations

Suppose a fitted standardized model produces signed margins $y_i z_i \in \{-0.4, 0.6, 1.7\}$. Their hinge losses are respectively 1.4, 0.4, and 0. The first is misclassified, the second is correctly classified but inside the margin, and the third is correctly classified beyond the margin. The first two influence the current hinge subgradient; the third does not. Logistic loss, by contrast, remains positive at every finite margin.




Figure 15.2: A linear SVM fitted to versioned diagnostic measurements. Left: decision boundary, unit margins, and support vectors. Center: the three geometric regions of signed margin and the hinge loss each produces. Right: regularization changes margin width and the number of active observations.

15.6 Professional evidence workflow

A defensible linear-SVM experiment records the target definition, data query, split identifiers, preprocessing fitted on the training partition, feature units, label encoding, objective convention, hyperparameters, convergence trace, and held-out metrics. Report the confusion matrix at the operational threshold and discuss which errors matter. Compare with logistic regression: similar discrimination does not make a margin score a calibrated probability.

Professional practice

Treat the model and preprocessing as one fitted pipeline. Persist them together, validate input schema at inference, monitor score and feature drift, and log model and data versions. Unit tests should cover label validation, unfitted-state errors, output shapes, deterministic training, and a small separable problem with a known qualitative solution.

15.7 Exercises

1. Compute the geometric distance of $x = (2, 1)$ from $2x_1 - x_2 - 3 = 0$. Then rescale all coefficients by 5 and verify that the distance is unchanged.
2. For signed margins $-2, -0.2, 0, 0.8, 1, 2$, calculate hinge and logistic loss. Explain which observations influence the hinge subgradient.
3. Starting from the soft-margin constrained problem, eliminate the slack variables and recover the hinge objective.
4. Derive g_w and g_b for one observation in each of the three regions: misclassified, correctly classified inside the margin, and beyond the margin.
5. Fit a linear SVM and logistic regression to the same database query. Use one frozen split and one fitted scaler. Compare ranking, confusion matrices, calibration evidence, and failure cases.
6. Add a test that would fail if an implementation regularized its bias. State why the desired behavior is part of the estimator contract.

Chapter review

A linear SVM is a single-neuron model with affine preactivation, signed labels, and a regularized hinge objective. Hyperplane geometry explains the margin; slack variables explain hinge loss; subgradients permit first-order training; and support vectors identify active constraints. The shared affine computation connects SVMs to linear and logistic regression, while their losses and output semantics keep the estimators distinct.

Executable companion

Lecture 11 notebook 01 derives these results, queries the course database, visualizes margins and support vectors, trains the course implementation, and evaluates held-out evidence. Lecture 12 notebook 00 then uses the three single-neuron configurations to motivate reusable software design.

CHAPTER 16

Designing a learning API

Learning objectives

After this chapter, you should be able to:

- identify the mathematical structure shared by linear regression, logistic regression, and a linear support vector machine;
- separate an estimator interface from a differentiable component interface;
- explain why activation and loss choices form a coupled contract;
- specify shape, state, numerical, and randomness guarantees; and
- test an analytical gradient independently with finite differences.

Where this chapter fits

Chapters 12–15 developed three single-neuron configurations: linear regression, logistic regression, and a linear support vector machine. Their formulas differ in meaning, but their implementations repeat an affine score, parameter updates, validation, and fitted-state handling. This chapter asks which repetitions express genuine structure and which encode different scientific claims. The resulting components prepare us to build a multilayer network without treating hidden neurons as independently fitted estimators.

16.1 An API is a scientific boundary

An application programming interface, or API, is the documented boundary through which one piece of software uses another. For a learned model, the boundary includes more than method names. It states what one row represents, which shapes are accepted, what fitting changes, what an output means, which invalid states are rejected, and which numerical behavior callers may rely on.

Suppose $X \in \mathbb{R}^{n \times p}$ contains n observations and p features. A single affine unit calculates

$$z = Xw + b\mathbf{1}, \qquad a = \phi(z).$$

Here z is the *preactivation*, a the *postactivation*, w a length-p weight vector, and b a scalar bias. This computation alone does not determine a statistical model. The activation, target domain, loss, sampling assumptions, and prediction policy supply meaning.

Definition: Interface contract

An interface contract records the conditions a caller must satisfy, the state an operation may change, the result and semantics it guarantees, and the failures it reports when it cannot honor that guarantee.

For example, a binary probability estimator may require labels in $\{0, 1\}$ and return values in $(0, 1)$. A label decision requires an additional threshold and cost policy. Returning a number in $(0, 1)$ is not by itself evidence of calibration.

Concept check. Two classes both expose methods named `fit` and `predict`. Does that establish that they are statistically interchangeable? List three additional contracts that must agree.

16.2 Shared affine structure, different output semantics

For squared-error regression, choose the identity activation and per-example loss

$$a_i = z_i, \qquad \ell_i = \frac{1}{2}(a_i - y_i)^2.$$

The chain rule gives

$$\frac{\partial \ell_i}{\partial z_i} = a_i - y_i.$$

For binary logistic regression, choose

$$a_i = \sigma(z_i) = \frac{1}{1 + \exp(-z_i)}$$

and binary cross-entropy

$$\ell_i = -y_i \log a_i - (1 - y_i) \log(1 - a_i).$$

Since $\sigma'(z) = \sigma(z)(1 - \sigma(z))$, the factors cancel:

$$\frac{\partial \ell_i}{\partial z_i} = \frac{\partial \ell_i}{\partial a_i} \frac{\partial a_i}{\partial z_i} = a_i - y_i.$$

Thus both canonical models have

$$\nabla_w L = \frac{1}{n} X^\top (a - y), \qquad \frac{\partial L}{\partial b} = \frac{1}{n} \mathbf{1}^\top (a - y).$$

For a linear SVM, retain the identity postactivation, encode $y_i \in \{-1, +1\}$, and use

$$J(w, b) = \frac{\lambda}{2} \|w\|_2^2 + \frac{1}{n} \sum_i \max\{0, 1 - y_i z_i\}.$$

Its score derivative is $-y_i$ inside the unit margin and 0 beyond it, with a subgradient choice at the kink. The equality of the regression and logistic expressions is therefore informative but not universal. It justifies sharing an optimization shell while keeping the objective configurable; it does not make numerical responses, probabilities, and margin scores interchangeable.

Common misconception

Misconception: gradient descent is identical for all single-neuron models. **Correction:** the update mechanism is shared, but the derivative supplied to it depends on the model and loss. The residual form above is a special property of two canonical pairings, while hinge loss supplies a piecewise subgradient and regularization adds λw.

16.3 Pair compatible activations and losses

An activation and a loss jointly determine both semantics and derivatives. One can expose them as separate low-level objects, but a safe public API should make incompatible pairings difficult to express. A bounded teaching design uses an output-objective contract with three operations:

$$\text{prediction}(z), \qquad \text{mean loss}(z, y), \qquad \text{score gradient}(z, y).$$

The regression objective supplies identity, squared error, and $z - y$. The probabilistic classification objective supplies sigmoid, cross-entropy, and $\sigma(z) - y$. The margin objective supplies identity, regularized hinge loss, and a subgradient determined by the active margin set. This third case shows why a useful contract cannot assume every objective is smooth or every output is a probability.

This coupling also supports stable computation. Binary cross-entropy can be written in terms of a logit z as

$$\ell(z, y) = \log(1 + \exp z) - yz.$$

Direct evaluation may overflow. The equivalent implementation

$$\ell(z, y) = \text{logaddexp}(0, z) - yz$$

remains finite over a much wider floating-point range. Numerical stability is not an internal decoration: callers depend on it.

Failure mode

Do not apply a sigmoid and then pass its result to a loss documented to consume logits. Conversely, do not pass logits to an interface documented to consume probabilities. The arrays may have identical shapes while representing different mathematical objects.

16.4 Estimator and component interfaces

A standalone estimator owns a complete fitting procedure:

`fit`(X, y)	learn and store fitted parameters,
`decision_function`(X)	return affine scores,
`predict`(X)	return model outputs.

The trailing underscore convention distinguishes fitted state such as `weights_` from construction parameters. Prediction before fitting should raise an actionable exception rather than return an accidental default.

A differentiable network component has a different role:

`forward`(u)	compute and retain needed intermediates,
`backward`(g)	propagate an upstream derivative,
`step`(η)	update after gradients are assembled.

A hidden neuron has no observed target of its own. Calling `fit`(X, y) independently on every hidden unit would therefore train separate models, not a neural network. The network's terminal loss supplies a single derivative that is propagated jointly through all components.

Professional practice

Reuse the smallest abstraction whose semantics remain valid. A network may reuse activation functions, affine calculations, validation, initializers, and optimizers from a single-neuron lesson. It should not reuse an estimator's independent `fit` loop as though hidden neurons were separate prediction problems.

16.5 Shape, state, and failure contracts

For a fitted single-neuron estimator, useful invariants include:

- X has shape (n, p) with $n, p > 0$;
- y has shape $(n,)$ and aligns with row order;
- inputs are finite under the stated missing-value policy;
- targets belong to the domain required by the configured objective—for example, $\{0, 1\}$ for logistic regression and $\{-1, +1\}$ for a linear SVM;
- fitted weights have shape $(p,)$;
- prediction uses the same feature count and ordering as fitting; and
- learning rate and iteration count belong to documented domains.

Type annotations make part of this structure available to editors and static checkers. NumPy-style docstrings explain shapes, units, ordering, probability semantics, mutation, and exceptions. Runtime checks enforce important boundaries because Python does not enforce annotations.

Randomness is state too. Components should accept or construct a local random generator rather than mutate NumPy's global random state. A reproducibility record includes seed, initializer, split, preprocessing, dtype, and software version; a seed alone is not an experiment identity.

16.6 Gradient checking as a software test

Let $J : \mathbb{R}^q \to \mathbb{R}$ be differentiable. For coordinate j,

$$\frac{\partial J(\theta)}{\partial \theta_j} = \lim_{h \to 0} \frac{J(\theta + he_j) - J(\theta - he_j)}{2h}.$$

For small, nonzero h, the right side is a central-difference approximation. It supplies an implementation independent enough to catch a missing factor, wrong sign, or transpose.

Proposition 16.1. *If J has three continuous derivatives near θ, the central-difference approximation has truncation error $O(h^2)$.*

Proof. Taylor expansion in directions e_j gives

$$J(\theta \pm he_j) = J(\theta) \pm hJ_j(\theta) + \frac{h^2}{2} J_{jj}(\theta) \pm \frac{h^3}{6} J_{jjj}(\xi_\pm).$$

Subtracting cancels the constant and even-order terms. Dividing by $2h$ leaves $J_j(\theta)$ plus a term proportional to h^2. □

In floating-point arithmetic, choosing h too small introduces cancellation. Gradient tests therefore compare with both relative and absolute tolerances on tiny deterministic examples. They do not replace mathematical derivation, prove that the loss is scientifically meaningful, or provide an efficient training method.

Worked example: one shell, three models

A team implements a `SingleNeuron` estimator that accepts an output objective. For diabetes progression, it uses identity plus squared error. For breast-mass classification, it uses sigmoid plus binary cross-entropy. For a margin-based comparison, it uses identity plus regularized hinge loss with signed labels.
The team fits scaling on each training partition only. Both models call the same validated affine and update machinery. Tests verify prediction before fit, feature-count mismatch, objective-specific invalid labels, extreme logits, smooth gradients, and hinge subgradients away from the kink. Experiment reports remain different: regression reports errors in target units, logistic regression reports probability and decision evidence, and the SVM reports margin scores and decisions without calling its scores probabilities. The abstraction removes duplicate mechanism without erasing statistical meaning.

16.7 API review checklist

Before releasing a learning component, ask:

1. Are mathematical objects named and shaped explicitly?
2. Does the loss consume logits, probabilities, or unconstrained values?
3. Are invalid target domains rejected?
4. Which methods require fitted state?
5. Who owns preprocessing and threshold policy?
6. Are randomness and numerical extremes tested?
7. Can analytical gradients be checked on a hand-computable case?
8. If the loss is nonsmooth, is the subgradient convention documented?
9. Can the component be serialized without hidden notebook state?

16.8 Exercises

1. Derive the bias gradient for the squared and logistic objectives. Explain why the final formula agrees although the statistical models differ. Then derive the hinge-loss bias subgradient and identify the active set.
2. Construct an activation–loss pairing for which $\partial \ell / \partial z \neq a - y$. Identify every chain-rule factor.
3. Design a threshold adapter without changing the meaning of `predict`. Specify boundary behavior and tests.
4. Add L_2 regularization. State whether the bias is penalized and write a finite-difference test that would detect the wrong policy.
5. Explain why independently fitting hidden neurons cannot train a multilayer network.
6. Explain why `predict_proba` belongs to the logistic configuration but not to the uncalibrated SVM configuration.
7. Design a pull request for one new output objective. Require a derivation, NumPy-style documentation, extreme-input tests, and derivative or subgradient evidence.

Chapter review

Linear regression, logistic regression, and a linear SVM share an affine single-neuron computation. Their activations, losses, regularization, target domains, derivatives, and outputs differ. A responsible API shares mechanism while preserving those semantics. Standalone estimators own fitting and prediction; differentiable components participate in a joint forward and backward computation. Shape, fitted state, randomness, failure behavior, and numerical stability are public contracts. Numerical checks turn derivative formulas into independently testable claims.

Executable companion

Lecture 12 notebook 00 builds and tests the single-neuron API for linear regression, logistic regression, and a linear SVM. Its reusable implementation lives in the course package, while notebook 01 uses the component interface to construct a multilayer network.

CHAPTER 17

From neurons to neural networks

Learning objectives

After this chapter, you should be able to:

- express a network first as connected neurons and then as matrix maps;
- distinguish preactivations z^ℓ from postactivations a^ℓ;
- derive output and hidden errors by following computational paths;
- implement and gradient-check a vectorized dense layer;
- compare sigmoid–MSE, sigmoid–cross-entropy, and modern logits-based output contracts; and
- explain what automatic differentiation automates and what remains a modeling or systems decision.

Where this chapter fits

Chapter 16 separated a standalone estimator from a differentiable component. We now use those components to build a network. The derivation begins with literal neurons because every matrix entry should retain a visible meaning. Only after tracing values forward and sensitivities backward do we compress the calculation into vectorized layers.

17.1 Networks are computational graphs of neurons

A feedforward neural network is a directed acyclic computational graph. Input values enter layer zero, hidden layers form intermediate representations, and an output layer produces quantities used by a loss or decision rule. For layer ℓ, let

$$w^\ell_{j,k}$$

denote the weight from neuron k in layer $\ell - 1$ to neuron j in layer ℓ. Then

$$z^\ell_j = \sum_{k=1}^{d_{\ell-1}} w^\ell_{j,k} a^{\ell-1}_k + b^\ell_j, \qquad a^\ell_j = \phi^\ell(z^\ell_j),$$

with $a^0 = x$.

Definition: preactivation and postactivation

The preactivation z^ℓ_j is the affine input to neuron j in layer ℓ. The postactivation a^ℓ_j is the result after applying ϕ^ℓ. Keeping z and a distinct is essential because the backward pass needs $\phi'(z)$.

The bias b^ℓ_j is sometimes drawn as a fixed signal 1 with a trainable edge. This drawing is algebraically useful, but the bias is not an additional measured feature.

17.2 A concrete three–two–two network

Consider three input signals, two hidden neurons, and two output neurons. The first hidden neuron computes

$$z_1^1 = w_{1,1}^1 x_1 + w_{1,2}^1 x_2 + w_{1,3}^1 x_3 + b_1^1,$$
$$a_1^1 = \sigma(z_1^1).$$

The second hidden neuron has its own weights and bias. The first output neuron then computes

$$z_1^2 = w_{1,1}^2 a_1^1 + w_{1,2}^2 a_2^1 + b_1^2, \qquad a_1^2 = \sigma(z_1^2).$$

This scalar view establishes three facts. A neuron receives postactivations from the previous layer; each edge has a unique sending and receiving index; and the same hidden activation can influence several downstream outputs. The last fact will cause downstream gradient contributions to add.

Collecting neuron quantities yields

$$z^\ell = W^\ell a^{\ell-1} + b^\ell, \qquad a^\ell = \phi^\ell(z^\ell).$$

For the example,

$$W^1 \in \mathbb{R}^{2\times 3}, \quad b^1, z^1, a^1 \in \mathbb{R}^2, \quad W^2 \in \mathbb{R}^{2\times 2}, \quad b^2, z^2, a^2 \in \mathbb{R}^2.$$

Matrix form evaluates the same neuron equations together. It is an implementation improvement, not a different mathematical model.




Figure 17.1: A layered network shown without hiding the individual neurons. Panel A distinguishes the affine preactivation z_j^ℓ from the postactivation a_j^ℓ at every hidden and output node. Panel B enlarges one neuron: incoming postactivations are aggregated affinely and then transformed. Matrix notation evaluates these same scalar operations in parallel.

Concept check. Write z_2^2 without matrix notation. Identify the sender and receiver represented by each subscript in $w_{2,1}^2$.

17.3 Why use a neural network?

A single identity neuron represents an affine response surface. A single sigmoid neuron represents a probability whose log-odds are affine; its constant-probability contours and threshold decision boundary are hyperplanes. These models are valuable precisely because this structure is restrictive and interpretable. They cannot, without manually constructed features, express several separated response regimes, an XOR interaction, or a hierarchy in which small patterns combine into larger ones.

A neural network learns intermediate features together with the final predictor. Width allows several neurons to detect different directions or regimes and lets the next layer combine them. Depth allows later layers to reuse and compose earlier features. The case for a network is therefore a modeling hypothesis:

> the response may be simpler as a composition of learned representations than as one function of the original measurements.

This hypothesis is often natural for images, sound, language, dynamical systems, and other structured high-dimensional data. It is not automatically correct for every table, and neural networks do not replace linear models, trees, kernels, or domain-designed structure.

17.3.1 Linear depth adds no expressive power

Suppose two successive layers use identity activations. Then

$$\begin{aligned} f(x) &= W^2(W^1x + b^1) + b^2 \\ &= (W^2W^1)x + (W^2b^1 + b^2). \end{aligned}$$

The composition is one affine map. Adding more linear layers changes a factorization of its matrix, not the class of represented functions.

Proposition 17.1. *A finite composition of affine maps is affine.*

Proof. The calculation above proves closure for two maps. If the composition of the first m maps is $Ax + c$, composing one more affine map gives $W(Ax + c) + b = (WA)x + (Wc + b)$, which is affine. Induction completes the proof. □

Nonlinear activation prevents this collapse. Figure 17.2 makes three distinct mechanisms visible. Affine depth remains a line. Several ReLU neurons provide hinge features whose weighted sum can contain several bends. Repeatedly composing one ReLU-representable tent map produces more linear regions at each depth:

$$T(x) = 2\,\mathrm{ReLU}(x) - 4\,\mathrm{ReLU}\left(x - \frac{1}{2}\right) + 2\,\mathrm{ReLU}(x - 1), \qquad 0 \le x \le 1.$$

The example does not claim that more regions always generalize better. It shows concretely what nonlinear composition can represent that an affine stack cannot.

17.3.2 Sigmoid and ReLU make different tradeoffs

The sigmoid,

$$\sigma(z) = \frac{1}{1 + \exp(-z)}, \qquad \sigma'(z) = \sigma(z)(1 - \sigma(z)),$$




Figure 17.2: Where expressive power enters. Panel A confirms that composing affine layers still produces one affine function. Panel B combines several ReLU hinge features to create a piecewise-linear function with multiple learned bends. Panel C composes the same tent feature: depth reuses an earlier computation and increases the number of linear regions. Expressive capacity is useful only when supported by data, regularization, and held-out evidence.

is smooth and historically useful for exposition. Its derivative becomes small when $|z|$ is large, so saturated units transmit weak gradients.

The rectified linear unit

$$\mathrm{ReLU}(z) = \max(0, z)$$

has derivative one for positive z and zero for negative z, with a selected subgradient convention at zero. ReLU often improves gradient propagation in hidden layers, but a unit that remains negative for all relevant inputs can become inactive. Other activations make other compromises; the appropriate choice depends on output semantics, gradient flow, architecture, and evidence.

17.4 A transparent first loss and its output error

To preserve every chain-rule factor, begin with sigmoid at every neuron and mean-squared error for a two-output, one-hot target,

$$C(W, B; x, y) = \frac{1}{2}\sum_{r=1}^{2}(a_r^2 - y_r)^2.$$

Define the local error of neuron j in layer ℓ by

$$\delta_j^\ell := \frac{\partial C}{\partial z_j^\ell}.$$

This definition matters. A delta is sensitivity with respect to a *preactivation*; it is not merely the observed prediction residual.

At the output,

$$\begin{aligned}\delta_j^2 &= \frac{\partial C}{\partial a_j^2}\frac{\partial a_j^2}{\partial z_j^2} \\ &= (a_j^2 - y_j)\sigma'(z_j^2).\end{aligned}$$

Now follow one output weight $w^2_{j,k}$:

$$\begin{aligned}\frac{\partial C}{\partial w^2_{j,k}} &= \frac{\partial C}{\partial a^2_j}\frac{\partial a^2_j}{\partial z^2_j}\frac{\partial z^2_j}{\partial w^2_{j,k}} \\ &= (a^2_j - y_j)\sigma'(z^2_j)a^1_k \\ &= \delta^2_j a^1_k.\end{aligned}$$

Because $\partial z^2_j/\partial b^2_j = 1$,

$$\frac{\partial C}{\partial b^2_j} = \delta^2_j.$$

17.5 Hidden errors collect all downstream paths

A hidden activation a^1_j affects both output neurons. Its derivative must therefore include both paths:

$$\begin{aligned}\delta^1_j &= \frac{\partial C}{\partial z^1_j} \\ &= \left(w^2_{1,j}\delta^2_1 + w^2_{2,j}\delta^2_2\right)\sigma'(z^1_j).\end{aligned}$$

For a general layer,

$$\boxed{\delta^\ell = \left((W^{\ell+1})^\top \delta^{\ell+1}\right) \odot \phi^{\ell\prime}(z^\ell)}.$$

The transpose reverses the forward connectivity: $W^{\ell+1}$ maps layer ℓ activations forward, while $(W^{\ell+1})^\top$ collects sensitivities from receiving neurons back to sending neurons. The Hadamard product $\odot$ applies each neuron's local activation derivative.

Once δ^ℓ is known,

$$\boxed{\frac{\partial C}{\partial W^\ell} = \delta^\ell (a^{\ell-1})^\top, \qquad \frac{\partial C}{\partial b^\ell} = \delta^\ell}.$$

Definition: backpropagation

Backpropagation is an efficient organization of the chain rule on a layered computational graph. It stores forward intermediates, initializes sensitivity at the scalar loss, and reuses downstream derivatives while traversing the graph in reverse.

Common misconception

Misconception: backpropagation is the parameter-update algorithm. **Correction:** backpropagation calculates derivatives. Gradient descent, momentum, Adam, and other optimizers decide how those derivatives change parameters.

17.6 Batch vectorization

Let $A^{\ell-1} \in \mathbb{R}^{n\times d_{\ell-1}}$ store observations by rows and let $W^\ell \in \mathbb{R}^{d_\ell \times d_{\ell-1}}$. Then

$$Z^\ell = A^{\ell-1}(W^\ell)^\top + \mathbf{1}(b^\ell)^\top, \qquad A^\ell = \phi^\ell(Z^\ell).$$

If Δ^ℓ contains one delta row per observation, summing a mean loss gives

$$\nabla_{W^\ell} C = (\Delta^\ell)^\top A^{\ell-1}, \qquad \nabla_{b^\ell} C = (\Delta^\ell)^\top \mathbf{1}.$$

The implementation must state whether its loss sums or averages across the batch. A missing factor $1/n$ silently changes the effective learning rate.

A dense layer's forward operation retains its input and preactivation. Its backward operation receives $\partial C/\partial A^\ell$, multiplies by $\phi'(Z^\ell)$, forms parameter gradients, and returns $\partial C/\partial A^{\ell-1}$. All layers compute gradients before an optimizer updates any parameters; otherwise later derivatives would mix old and new network states.

17.7 Gradient checking a layer

For parameter coordinate θ_j, compare the analytical derivative with

$$g_j^{\mathrm{FD}} = \frac{C(\theta + he_j) - C(\theta - he_j)}{2h}.$$

Use a tiny deterministic network in double precision, avoid sigmoid saturation and ReLU kinks, restore each perturbed parameter, and compare with combined absolute and relative tolerances.

Layer-level checks localize failures better than checking an entire large network. Useful tests separately cover weight gradients, bias gradients, and input gradients. Shape and call-order tests should verify that backward before forward fails clearly.

Failure mode

A passing gradient check establishes agreement between two calculations near one test point. It does not prove that the loss matches the scientific question, that data splitting is valid, or that optimization will generalize.

17.8 Output losses change the initial backward signal

The transparent sigmoid–MSE example yields

$$\delta^L = (a^L - y) \odot \sigma'(z^L).$$

For a binary sigmoid output paired with cross-entropy, the activation and loss derivatives cancel:

$$\delta^L = a^L - y.$$

Thus the simplified residual is correct for the canonical logistic objective but not for sigmoid paired with mean-squared error.

For K mutually exclusive classes, a modern implementation commonly emits logits $z \in \mathbb{R}^K$ and combines softmax with cross-entropy:

$$p_k = \frac{\exp z_k}{\sum_r \exp z_r}, \qquad \ell(z, y) = -\log p_y.$$

Stable code shifts logits or uses a fused log-sum-exp operation. The gradient with respect to logits is $p - e_y$. A fused loss both clarifies its input contract and avoids taking logarithms of rounded probabilities.

The hidden-layer recursion remains the same. Changing the output loss changes where reverse propagation begins; it does not replace backpropagation.

17.9 Initialization and gradient flow

If sigmoid preactivations begin with large magnitude, activations saturate and gradients shrink. Initializing every parameter with unscaled standard normal noise becomes increasingly hazardous as fan-in grows.

Xavier or Glorot scaling is motivated by preserving forward and backward variance for approximately symmetric activations under explicit independence assumptions. He scaling is commonly paired with ReLU-like activations. These are starting principles rather than universal theorems about training. Initialization, activation, normalization, depth, and optimizer interact.

Record architecture, initializer, random seed, dtype, data order, and preprocessing. Inspect activation distributions, gradient norms, and nonfinite values when training stalls. Random biases scaled like weights are not automatically justified; zero or problem-informed bias initialization is often clearer.

17.10 A real-data training argument

Consider image-derived measurements from breast-mass samples. A bounded manual network can demonstrate the complete mechanism:

1. preserve a stratified held-out test partition;
2. fit scaling on training observations only;
3. train a small hidden layer and two-output classifier;
4. record the training objective;
5. freeze parameters before final evaluation; and
6. report a confusion matrix and task-relevant metrics.

The training curve is optimization evidence. A held-out confusion matrix is decision evidence. Neither establishes probability calibration, clinical transportability, or acceptable harm. Two independent sigmoid outputs need not sum to one, and MSE is retained in the first experiment to match the derivation rather than because it is the strongest modern multiclass contract.

Worked example: from transparent derivation to modern candidate

A team first trains a 3–2–2 sigmoid network on a four-observation logic problem. It checks every dense-layer derivative by central differences. It then trains a small network on versioned diagnostic measurements, keeping the test partition untouched.
For the release candidate, the team changes hidden activations to ReLU and the output to logits consumed by cross-entropy. It rechecks gradients, chooses a checkpoint with validation data, and loads the saved artifact in a fresh process. The model card reports class order, preprocessing identity, seed variability, balanced accuracy, confusion counts, and known limits. The manual network established mechanism; the framework implementation supplies scalable machinery without weakening the evidence contract.

17.11 Automatic differentiation and framework boundaries

Reverse-mode automatic differentiation records primitive tensor operations and applies their local derivative rules backward from a scalar loss. A framework also supplies optimized kernels, accelerators, modules, mini-batch data loading, optimizers, and serialization.

It does not decide:

- whether the target is a valid scientific construct;
- whether preprocessing leaks validation or future information;
- whether output and loss match the desired probability claim;
- whether a metric represents operational cost;
- whether errors concentrate in consequential groups; or
- whether inference reproduces training-time feature order and state.

Professional practice

The manual network is a microscope, not a production framework. Use it to derive and test the mechanism. Then use a mature tensor framework while retaining explicit data, objective, evaluation, serialization, and monitoring contracts.

Training and evaluation modes can differ because of dropout and batch normalization. A released artifact includes parameters, architecture, preprocessing reference, class order, checkpoint-selection evidence, software versions, and inference mode. A fresh-process test should reload it and compare predictions on versioned fixtures within declared tolerances.

17.12 Exercises

1. Write every scalar equation in a 3–2–2 sigmoid network and annotate its shape.
2. Derive $\partial C/\partial w^1_{1,2}$ by listing both output paths before collecting them into matrix notation.
3. Prove the softmax–cross-entropy logit gradient is $p - e_y$.
4. Design finite-difference tests for a dense layer's weights, biases, and input gradient.
5. Replace hidden sigmoid with ReLU. State the derivative convention at zero and justify an initializer.
6. Explain why a decreasing training loss and high test accuracy still do not establish calibrated clinical probabilities.
7. Specify a pull request that adds mini-batching or serialization to the course implementation. Include shape, randomness, failure, and regression tests.

Chapter review

A network connects individual affine neurons through nonlinear activations. Preactivations z^ℓ and postactivations a^ℓ must remain distinct. Backpropagation initializes an output sensitivity, sums every downstream path into hidden deltas, and forms weight gradients from local errors and incoming activations. Matrix operations vectorize the same neuron equations. Output losses determine the first backward signal; activations and initialization shape gradient flow. Automatic differentiation scales derivative calculation, but scientific validity, evaluation, artifact integrity, and operational judgment remain human responsibilities.

Executable companion

Lecture 12 notebook 00 designs the reusable single-neuron and component interfaces. Lecture 12 notebook 01 begins with literal neurons, derives backpropagation path by path, gradient-checks a vectorized dense layer, and evaluates a bounded manual network before crossing to automatic differentiation.

CHAPTER 18

Multiclass networks from first principles

Learning objectives

After this chapter, you should be able to:

- formulate handwritten-digit recognition as a controlled multiclass experiment;
- explain flattening, pixel scaling, and one-hot encoding as explicit representation contracts;
- derive a dense ReLU network with a logits–softmax–cross-entropy output;
- motivate Xavier and He initialization from fan-in and signal variance;
- derive every term in the vectorized backward pass;
- distinguish mini-batch optimization evidence from held-out decision evidence; and
- diagnose multiclass errors with classwise metrics and individual observations.

Where this chapter fits

Chapter 17 derived backpropagation by tracing individual neurons and then vectorizing them. This chapter puts that mechanism to work on images. The scientific question is concrete: can a bounded dense network recognize held-out handwritten digits? The implementation is still small enough to inspect, but its hidden activations, initialization, multiclass loss, mini-batches, and evaluation follow modern practice. The next chapter will replace our manual machinery with a tensor framework without surrendering these mathematical and evidential contracts.

18.1 MNIST as experiment, not trophy

The MNIST database standardized images drawn from NIST handwriting collections into 60,000 conventional training examples and 10,000 test examples. Each observation is a 28×28 grayscale image with an integer label in $\{0, \ldots, 9\}$. MNIST became historically important because it made different learning methods easy to compare on a common problem.

Its familiarity is also dangerous. A high benchmark score does not establish performance on phone photographs, historical manuscripts, a different writing population, or an operational document pipeline. We use MNIST as a *mechanism laboratory*: its inputs are rich enough to require learned representations, while its size and semantics make every stage visible.

The executable laboratory uses a deterministic class-balanced subset of authentic MNIST containing 2,400 training and 600 held-out images. Versioning this bounded sample has two engineering advantages: the lesson runs offline, and continuous integration can execute the same experiment. It has a statistical cost: classwise estimates have larger sampling uncertainty than they would on the complete benchmark. Reproducibility and inferential strength are different properties.

Each digit contributes 240 fitting images and 60 held-out images. Balance makes overall accuracy easy to read, but it is an experimental design choice, not a property of every handwriting population. Sixty held-out observations per class also means one additional class error changes estimated recall by $1/60 \approx 0.017$. Apparent

differences of one or two percentage points therefore deserve caution.

Definition: Experimental unit and prediction target

The experimental unit is one handwritten digit image. The target is one of ten mutually exclusive class identities. A model emits a probability distribution over the fixed class order $0, 1, \ldots, 9$ and the decision rule selects a class, usually the largest-probability class.

Before transformation, inspect image shapes, numeric range, label alignment, class counts, and representative images. These checks can expose a transposed axis, corrupt intensities, a missing class, or labels shifted by one position. A falling loss cannot repair an invalid data contract.

The fitting and held-out partitions have different authorities. Fitting rows may influence parameters. Validation rows, when present, may influence choices such as architecture or stopping. Test rows should influence neither; they estimate performance only after those choices are fixed. The short classroom experiment displays held-out accuracy during training to teach monitoring, so it must not be described as a pristine one-time test after the fact.

Concept check. Why is a class-balanced sample convenient for teaching but not a guarantee that accuracy is the correct metric in a deployed digit-recognition system?

18.2 From image to feature vector

For observation i, write the image as

$$X_i \in \{0, 1, \ldots, 255\}^{28\times 28}.$$

A dense network consumes a vector, so we flatten the matrix:

$$x_i = \operatorname{vec}(X_i) \in \mathbb{R}^{784}, \qquad 784 = 28 \cdot 28.$$

With zero-based row and column indices and row-major order, pixel (r, c) maps to feature index

$$j = 28r + c.$$

This formula is part of the interface. A different ordering would be equally valid during fitting, but inference would have to reproduce it exactly.

The transformation is reversible when its shape and ordering convention are known. No intensity is numerically discarded. What is discarded is an *explicit spatial inductive bias*: a dense layer does not know that one feature corresponds to a pixel immediately above another. It must learn every useful spatial relationship through independent weights.




Figure 18.1: Flattening preserves the ordered pixel values but removes the image grid from the model interface. A convolutional architecture will later encode locality and weight sharing directly. The small grid is schematic.

We scale each intensity by 255:

$$\widetilde{x}_{i,j} = x_{i,j}/255 \in [0, 1].$$

This prevents large input magnitudes from overwhelming an initialization designed under unit-scale assumptions. Unlike standardization by an estimated mean and variance, division by the known sensor maximum has no fitted state. It is still part of the inference contract: a deployed caller must apply exactly the same transformation.

The order of numeric operations matters. Integer images are first converted to a floating-point dtype and then divided. The resulting feature matrix has shape $n \times 784$ with one observation per row. An executable shape assertion at this boundary prevents a legal but incorrect reshape from silently changing which measurements belong to an observation.

Common misconception

Misconception: flattening "turns an image into meaningless data." **Correction:** flattening preserves every pixel value and a fixed order. It removes an architectural statement about two-dimensional locality. A dense network may learn useful spatial combinations, but it receives no built-in notion of neighboring pixels.

18.3 Class identities and one-hot targets

The integer label 7 names a category. It does not imply that class 7 is one unit farther from class 6 than from class 0. We therefore encode label k as the kth standard basis vector $e_k \in \mathbb{R}^{10}$:

$$7 \longmapsto (0, 0, 0, 0, 0, 0, 0, 1, 0, 0).$$

For a batch of m observations, targets form a matrix $Y \in \{0, 1\}^{m\times 10}$ whose rows sum to one. Ten columns must be retained even if one mini-batch happens not to contain every class. Column position is part of the model's public meaning.

One-hot encoding is useful for deriving the loss. An implementation may accept integer labels and gather the correct log-probability directly, but it must preserve the same class-order contract. One-hot targets do not turn one example into ten examples, nor do they assert ten independent binary tasks.

This distinction determines the output activation. Ten independent sigmoids would permit probabilities whose sum differs from one and are appropriate for a multilabel problem in which several labels may be true simultaneously. Handwritten-digit identity is mutually exclusive, so one softmax couples the ten scores into one categorical distribution.

18.4 A modern bounded architecture

Let a mini-batch be $A^0 = X \in \mathbb{R}^{m\times 784}$. We choose a hidden width of 64 and compute

$$Z^1 = A^0 W^1 + \mathbf{1}(b^1)^\top, \qquad A^1 = \mathrm{ReLU}(Z^1),$$

with

$$W^1 \in \mathbb{R}^{784\times 64}, \quad b^1 \in \mathbb{R}^{64}.$$

The output layer computes

$$Z^2 = A^1 W^2 + \mathbf{1}(b^2)^\top, \qquad W^2 \in \mathbb{R}^{64\times 10}, \quad b^2 \in \mathbb{R}^{10}.$$

The rows of Z^2 are *logits*: unconstrained real-valued class scores. There is no output ReLU and no independently applied sigmoid. A single softmax normalizes the mutually exclusive classes:

$$p_{i,k} = \frac{\exp z_{i,k}}{\sum_{r=0}^{9} \exp z_{i,r}}.$$

For one observation, hidden neuron j computes

$$z_j^1 = \sum_{r=1}^{784} x_r w_{rj}^1 + b_j^1, \qquad a_j^1 = \max(0, z_j^1).$$

The jth column of the batch preactivation matrix collects this same neuron calculation across observations. Vectorization changes the execution strategy, not the model. A useful reading discipline is to verify that the scalar equation, single-observation vector equation, and batch equation describe the same computation.




Figure 18.2: The from-scratch MNIST classifier. Circles are schematic; ellipses stand for omitted neurons. The final affine layer emits logits, and softmax assigns a joint categorical distribution rather than ten unrelated scores.

The model contains

$$(784 \cdot 64 + 64) + (64 \cdot 10 + 10) = 50{,}890$$

trainable scalars. Counting parameters is a useful shape test and a first measure of capacity, but it does not quantify effective complexity by itself. The first layer contains more than 98 percent of these parameters because a dense hidden unit assigns an independent weight to every pixel. This observation anticipates why spatial weight sharing in a convolution can be both statistically and computationally useful.

18.5 Initialization from variance propagation

Consider one preactivation

$$z_j = \sum_{r=1}^{d} w_{rj} a_r.$$

Under approximate independence and zero-mean assumptions,

$$\operatorname{Var}(z_j) \approx d \operatorname{Var}(w_{rj}) \operatorname{Var}(a_r).$$

To keep $\mathrm{Var}(z_j)$ on the scale of $\mathrm{Var}(a_r)$, a linear or approximately symmetric layer suggests $\mathrm{Var}(w_{rj}) \approx 1/d$. ReLU maps negative inputs to zero; under the idealized symmetric-input argument, the second moment of its output is approximately halved. Compensating gives $2/d$ rather than $1/d$.

With unscaled standard-normal weights, variance grows with fan-in d. Activations can explode, sigmoids can saturate, or numerical ranges can become unusable before learning begins.

For approximately symmetric signals passed through ReLU, roughly half the mass is zeroed. He initialization compensates with

$$w_{rj} \sim N\left(0, \frac{2}{d}\right).$$

Thus the first layer uses standard deviation $\sqrt{2/784}$. The final linear logit layer uses Xavier normal scaling,

$$w_{rj} \sim N\left(0, \frac{1}{d}\right),$$

giving standard deviation $\sqrt{1/64}$ here. Biases start at zero. Independent weights already break neuron symmetry, so random biases are not needed.

These calculations are approximations, not distribution-free theorems about trained networks. Correlations, depth, optimizer dynamics, normalization, and data geometry matter. Good practice checks initial preactivation scale, the fraction of active ReLU units, gradient norms, and nonfinite values.

Initialization and reproducibility are related but not identical. A recorded seed chooses a deterministic pseudo-random stream for a particular implementation. It does not imply that every numerical library, hardware accelerator, or parallel reduction will produce bitwise-identical results. Record the initializer by name and formula in addition to recording the seed.

Failure mode

Random-normal initialization does not mean "draw every weight from $N(0, 1)$." The variance is part of the algorithm. At fan-in 784, an unscaled standard normal is about twenty times wider in standard deviation than He normal initialization.

18.6 Softmax cross-entropy as a fused contract

For one observation with one-hot target y, categorical cross-entropy is

$$\ell(z, y) = -\sum_{k=0}^{9} y_k \log p_k.$$

Substituting softmax and using $\sum_k y_k = 1$ yields

$$\ell(z, y) = \log\left(\sum_r e^{z_r}\right) - \sum_k y_k z_k.$$

This is the log-sum-exp form. Stable code subtracts $c = \max_r z_r$ before exponentiating:

$$\log\left(\sum_r e^{z_r}\right) = c + \log\left(\sum_r e^{z_r - c}\right).$$

Softmax is unchanged because the common factor e^{-c} cancels between numerator and denominator.

More generally, for any scalar c,

$$\operatorname{softmax}(z + c\mathbf{1}) = \operatorname{softmax}(z).$$

The logits are therefore identifiable only up to a common additive shift. Probabilities and the largest-probability decision are unchanged. Subtracting the row maximum exploits this mathematical invariance to obtain numerical stability; it is not a heuristic alteration of the model.

Proposition 18.1 (Softmax–cross-entropy logit gradient)**.** *For $p = \operatorname{softmax}(z)$ and a target distribution y whose entries sum to one,*

$$\nabla_z \ell = p - y.$$

Proof. Differentiate the log-sum-exp expression in coordinate z_j:

$$\begin{aligned}\frac{\partial \ell}{\partial z_j} &= \frac{e^{z_j}}{\sum_r e^{z_r}} - \frac{\partial}{\partial z_j} \sum_k y_k z_k \\ &= p_j - y_j.\end{aligned}$$

Collecting coordinates gives $\nabla_z \ell = p - y$. □

The simplicity of the derivative is not a reason to split softmax and loss in software. A fused operation states that its inputs are logits, avoids the logarithm of a rounded zero probability, and can reuse stable intermediates.

18.7 Backpropagation for a mini-batch

Let the objective be the mean of m example losses. The output sensitivity is

$$\Delta^2 = \frac{P - Y}{m}.$$

The division by m appears exactly once. If the loss is a mean but the derivative is treated as a sum, changing batch size silently changes the effective learning rate. Dividing once in the output sensitivity makes all subsequent matrix products derivatives of the stated mean loss.

The output parameter derivatives are

$$\nabla_{W^2} L = (A^1)^\top \Delta^2, \qquad \nabla_{b^2} L = (\Delta^2)^\top \mathbf{1}.$$

Propagate sensitivity through W^2 and apply the ReLU derivative:

$$\Delta^1 = \left(\Delta^2 (W^2)^\top\right) \odot \mathbf{1}[Z^1 > 0].$$

Then

$$\nabla_{W^1} L = (A^0)^\top \Delta^1, \qquad \nabla_{b^1} L = (\Delta^1)^\top \mathbf{1}.$$

Every shape can be audited:

quantity	shape
A^0	$m \times 784$
Z^1, A^1, Δ^1	$m \times 64$
$W^1, \nabla_{W^1} L$	784×64
Z^2, P, Y, Δ^2	$m \times 10$
$W^2, \nabla_{W^2} L$	$64 \times 10.$

These shapes explain the transposes. $(A^1)^\top$ has shape $64 \times m$ and Δ^2 has shape $m \times 10$, so their product matches W^2. Likewise, $\Delta^2(W^2)^\top$ maps ten output sensitivities back to 64 hidden sensitivities per observation. A transpose should be justified by this linear map, not inserted until NumPy accepts the multiplication.

All gradients must be computed from one parameter state before any parameter is updated. Otherwise an early update changes quantities needed to calculate a later derivative. Finite-difference checks on a tiny deterministic example test the analytical implementation independently.

18.8 Mini-batch gradient descent

Full-batch descent uses every training observation for one update. Stochastic descent uses one. A mini-batch provides a noisy estimate of the full gradient while exposing matrix operations large enough for efficient numerical kernels. For batch B_t and learning rate η,

$$\theta_{t+1} = \theta_t - \eta \nabla_\theta \left(\frac{1}{|B_t|} \sum_{i \in B_t} \ell_i(\theta_t) \right).$$

An epoch visits every training observation once after a random permutation. The random seed, permutation generator, batch size, incomplete final-batch policy, learning rate, dtype, and initialization are parts of the experimental record. A seed does not make floating-point computation universally identical across all hardware, but it removes an important source of uncontrolled variation.

With $n = 2400$ and batch size 64, one epoch contains $\lceil 2400/64 \rceil = 38$ updates; the final batch contains 32 observations. Discarding that batch would systematically omit data unless row order were reshuffled and coverage explicitly managed. Keeping it is simpler, and the mean-loss gradient makes its update scale comparable to the full batches.

Training loss is *optimization evidence*: it shows whether the procedure reduces its stated objective on fitting data. Validation or held-out accuracy is *decision evidence*: it estimates a decision property on unseen data. Neither alone establishes probability calibration, population transport, or operational utility.

An epoch-level history is deliberately an aggregate. Batch-level loss is noisier and can diagnose update instability, while epoch-level loss is easier to interpret. A production training run should log both only when the added volume has a stated diagnostic purpose; logging every tensor or observation can be expensive and can expose sensitive data.

Worked example: A bounded handwritten-digit experiment

The course implementation trains a 784–64–10 ReLU network for eight epochs with batches of 64. Inputs are scaled once, parameters use He and Xavier initialization under a recorded seed, and a stable fused loss consumes logits.

The experiment first asserts all tensor shapes and verifies that initial logits are finite. During training it records mean cross-entropy, training accuracy, and held-out accuracy. After parameters are frozen, it calculates a ten-by-ten confusion matrix, per-class precision and recall, and a gallery of high-confidence errors. This sequence answers more than "what score did the model get?" It asks which distinctions remain difficult and whether apparent confidence agrees with the images a person sees.

The held-out partition is observed during the teaching run to illustrate a curve. In a genuine model-selection study, that role belongs to a validation partition; the test set is exposed only after architecture, learning rate, and stopping policy are frozen.

18.9 Confusion is part of the scientific result

Accuracy is

$$\frac{1}{n_{\text{test}}} \sum_i \mathbf{1}[\widehat{y}_i = y_i].$$

For class k, define

$$\text{precision}_k = \frac{\text{TP}_k}{\text{TP}_k + \text{FP}_k}, \qquad \text{recall}_k = \frac{\text{TP}_k}{\text{TP}_k + \text{FN}_k},$$

and

$$F_{1,k} = \frac{2\,\text{precision}_k\,\text{recall}_k}{\text{precision}_k + \text{recall}_k}.$$

Precision conditions on the model's class-k decisions; recall conditions on the true class-k observations. They answer different operational questions and neither is recovered from overall accuracy alone.

A confusion matrix retains which true digit became which predicted digit. Rows normalized to sum to one estimate class-conditional recall patterns; integer counts quantify actual sample evidence. They answer different questions.

Inspect individual errors after aggregate metrics. A high-confidence mistake can indicate ambiguous handwriting, an annotation problem, an unusual translation or stroke, or model overconfidence. Examining only convenient correct predictions hides failure structure. Examining only the ten worst examples without aggregate context can exaggerate rare cases. Professional analysis uses both.

Prediction confidence $\max_k p_k$ is not proof of calibration. Calibration asks whether events assigned probability near q occur approximately a fraction q of the time under the relevant distribution. It needs a separate reliability analysis and enough observations.

The highest-confidence mistakes are a diagnostic sample, not an unbiased summary of failure frequency. They are chosen precisely because the model was most certain. Use them to generate hypotheses, then test those hypotheses on a defined population rather than generalizing from an error gallery.

Professional practice

The notebook is an experimental narrative; reusable computations belong in a tested package. Record data provenance, split identity, code revision, preprocessing, class order, architecture, initializer, learning rate, batch size, seed, metrics, and known limitations. A released artifact must reproduce the same flattening and scaling before applying the learned parameters.
Serialization should package or reference all inference state: parameter arrays, architecture, dtype, feature ordering, scaling rule, and class order. A fresh-process test should load the artifact, transform a versioned fixture, and reproduce a stored probability vector within an explicit tolerance.

18.10 Failure modes and diagnostic tests

When loss becomes nonfinite, inspect scaled feature range, logits, learning rate, log-sum-exp stability, parameter norms, and gradients. Accuracy near 0.1 suggests a broken ten-class pipeline: verify label alignment, output width, class order, and whether updates change weights. Falling training loss with stagnant held-out performance suggests a generalization problem rather than a derivative failure.

Useful automated tests include:

- one-hot rows sum to one and recover their integer labels;
- softmax remains finite for large logits and is invariant to a common additive shift;
- softmax probabilities sum to one;
- analytical output and layer gradients match central differences;
- initialization standard deviations approximate their fan-in targets;
- all parameter and gradient shapes agree; and
- a small deterministic multiclass problem can be learned.

These tests catch mathematical and interface regressions. They do not establish that labels measure the intended construct or that a deployment population matches MNIST.

18.11 Exercises

1. Prove that flattening followed by reshaping is invertible when the ordering convention and original dimensions are retained. State what the dense architecture still fails to encode.
2. For a 784–128–64–10 network, write every parameter shape and count the trainable scalars.
3. Derive the softmax Jacobian $\partial p_k/\partial z_j = p_k(\mathbf{1}[k = j] - p_j)$, then recover the fused cross-entropy gradient.
4. Suppose all first-layer weights are sampled from $N(0, 1)$. Estimate the initial preactivation variance under independent unit-variance inputs and compare it with He initialization.
5. Add a second hidden ReLU layer to the course implementation. Supply gradient checks, shape tests, and a controlled comparison that changes only depth.
6. Replace accuracy with a cost matrix in which mistaking 1 for 7 is five times as costly as most other errors. Derive the empirical decision cost and explain whether retraining is required to change the decision rule.
7. Reproduce the full study on Fashion-MNIST. Use a validation partition for architecture choices, preserve the test set, report per-class evidence, and analyze visually plausible confusions such as shirts and pullovers.
8. Write a pull request adding serialization and a fresh-process inference test. The saved contract must include feature shape, class order, scaling, architecture, and parameter arrays.

Chapter review

An image becomes a dense-network input by an explicit flatten-and-scale contract. One-hot vectors encode fixed categorical identity; logits are unconstrained scores; softmax assigns one joint distribution. Pairing logits with stable cross-entropy gives the output gradient $P - Y$, while vectorized backpropagation transports that sensitivity through ReLU layers. He and Xavier random-normal initialization account for fan-in rather than applying arbitrary noise. Mini-batches make updates practical, but training curves remain optimization evidence. Held-out confusion patterns and inspected errors turn a score into a scientific analysis. The manual implementation makes each of these decisions visible before a framework automates their execution.

Executable companion

Lecture 12 notebook 02 performs the complete authentic-MNIST experiment with a tested NumPy implementation. It visualizes flattening, audits initialization, derives and checks the fused loss, trains with mini-batches, studies confusion patterns, compares hidden widths, and leaves Fashion-MNIST as an independent applied investigation.

CHAPTER 19

TensorFlow, convolution, and observable training

Learning objectives

After this chapter, you should be able to:

- distinguish tensors, variables, automatic differentiation, Keras, and TensorBoard as separate parts of a learning system;
- translate a scientific modeling contract into the Keras model lifecycle;
- explain mathematically why convolution respects image structure;
- calculate convolution output shapes and receptive fields;
- distinguish the full-data MNIST experiment from its bounded, offline CI smoke test and design a defensible cats-versus-dogs study; and
- select optimization, generalization, data, and system telemetry that makes training diagnosable.

Where this chapter fits

Chapter 17 constructed a neural network from literal neurons and derived reverse-mode differentiation. The preceding MNIST lesson then implemented the same mechanism directly. We now cross the framework boundary. TensorFlow automates tensor execution and derivatives, while Keras provides a higher-level model lifecycle. Neither removes the need to specify data provenance, output semantics, held-out evidence, or operational diagnostics.

19.1 A framework is a stack of contracts

TensorFlow was released as open-source software in November 2015. Its original white paper described both an interface for expressing machine-learning algorithms and an implementation capable of executing computations across heterogeneous systems.[1] TensorFlow 2 made eager execution the normal interactive experience and standardized on Keras as its high-level interface. Modern Keras is a multi-backend deep-learning API; this chapter uses its TensorFlow backend.

The names are related but not interchangeable:

Tensor. A typed multidimensional value with a shape and an execution device. A tensor is immutable.

Variable. Mutable state, ordinarily a model parameter, tracked for differentiation and checkpointing.

Operation. A transformation such as matrix multiplication, convolution, reduction, or activation.

[1] M. Abadi et al., *TensorFlow: Large-Scale Machine Learning on Heterogeneous Distributed Systems*, 2015, https://www.tensorflow.org/static/extras/tensorflow-whitepaper2015.pdf.

Automatic differentiation. A system that records differentiable operations and applies their local derivative rules in reverse.

Keras layer. A reusable parameterized transformation with explicit input and output shapes.

Keras model. A connected collection of layers with training, evaluation, inference, and serialization interfaces.

Callback. A hook invoked at defined lifecycle events, for example to write telemetry, save a checkpoint, or stop training.

TensorBoard. A separate application that reads event files and displays scalar series, histograms, images, graphs, and performance traces.

Figure 19.1 places these responsibilities in one system.




Figure 19.1: The framework occupies the computational middle of a larger scientific system. It can calculate derivatives and execute kernels; it cannot make the target valid or the evidence relevant. Observability connects the running computation to human diagnosis.

Common misconception

"Keras trained the model" is not a complete experimental description. A reproducible claim also needs the data version and sampling unit, split policy, preprocessing fit boundary, architecture, initializers, objective, optimizer, randomness policy, stopping rule, checkpoint-selection rule, metrics, software versions, and final artifact identity.

19.2 Tensors and automatic differentiation

A batch of grayscale images commonly has shape

$$(n, h, w, 1),$$

where n is batch size, h and w are spatial dimensions, and the last coordinate is the channel. A color image normally has three input channels. The channel dimension is semantic; silently transposing channel and spatial axes changes the represented computation.

Let $L(\theta)$ be a scalar loss. Inside a `GradientTape`, TensorFlow records relevant primitive operations. A call to `gradient` traverses that recorded graph backward to compute $\nabla_\theta L$. This is the same chain rule derived in Chapter 17. The framework maintains the graph and supplies derivative implementations for supported operations.

Definition: automatic differentiation is not symbolic or numerical differentiation

Automatic differentiation evaluates exact chain-rule compositions of the program's primitive derivative rules, up to floating-point arithmetic. It does not manipulate a symbolic expression into a closed form, and it does not approximate every coordinate by finite differences. Finite differences remain valuable as an independent check on a small deterministic calculation.

The tape ordinarily watches trainable variables automatically. Constants must be watched explicitly when derivatives with respect to them are required. Integer-valued computations are not differentiable in this sense, stateful updates can stop a gradient path, and persistent tapes retain more intermediate state.[2]

Concept check. A tape returns `None` for one parameter. Give three distinct hypotheses: one involving connectivity, one involving dtype, and one involving state. What evidence would distinguish them?

19.3 The Keras lifecycle is an executable argument

A routine experiment passes through six stages:

$$\texttt{build} \longrightarrow \texttt{compile} \longrightarrow \texttt{fit} \longrightarrow \texttt{evaluate} \longrightarrow \texttt{predict} \longrightarrow \texttt{save}.$$

Each verb answers a different question.

1. **Build** establishes transformations, shapes, parameters, and output semantics.
2. **Compile** binds an optimizer, loss, and reported metrics. These are not interchangeable: the loss supplies gradients, whereas a metric may be nondifferentiable.
3. **Fit** updates parameters using training batches. Validation data may guide stopping or checkpoint selection but receives no gradient update.
4. **Evaluate** computes declared metrics without parameter updates. The final test partition is used once after choices are frozen.
5. **Predict** runs inference and must reproduce the training-time feature and preprocessing contract.
6. **Save** preserves the chosen artifact. A fresh-process reload test verifies that serialization is operational, not merely promised.

Keras supports a simple `Sequential` stack, a Functional API for graphs with branches or shared layers, and model subclassing for custom behavior. Use the least flexible interface that expresses the intended graph clearly. Progressive disclosure is a virtue: a three-layer sequential model should not be hidden inside a custom training architecture without a reason.

19.4 MNIST: concise code, explicit semantics

MNIST observations are 28×28 grayscale images of handwritten digits. A dense baseline reshapes each image into

$$x \in \mathbb{R}^{784}.$$

[2] TensorFlow, "Introduction to gradients and automatic differentiation," https://www.tensorflow.org/guide/autodiff.

Flattening changes the view, not the values. It also erases the explicit two-dimensional neighborhood relation. Dividing integer intensities by 255 maps them to $[0, 1]$ and makes the numerical range explicit.

For ten mutually exclusive classes, the model emits logits $z \in \mathbb{R}^{10}$. With class index y, sparse categorical cross-entropy is

$$\ell(z, y) = -z_y + \log\left(\sum_{k=0}^{9} \exp z_k\right).$$

With a one-hot vector e_y, the same quantity can be written

$$-\sum_{k=0}^{9} (e_y)_k \log p_k, \qquad p_k = \frac{\exp z_k}{\sum_r \exp z_r}.$$

Sparse and one-hot targets encode the same class but require different loss interfaces. If a model emits raw logits, the loss must be told that its inputs are logits. Applying softmax in the model and then configuring a logits loss applies the wrong contract.

19.4.1 Acquire data without hiding provenance

The executable lesson has two routes with different evidential purposes. During normal student work, `tf.keras.datasets.mnist.load_data()` obtains the full official training and test arrays. On the first call, Keras downloads its MNIST archive to the user's Keras cache; later calls ordinarily reuse the cached file. A cache improves performance and supports repeated local work, but it is not a complete provenance record. A professional experiment records the source, version or checksum, license, sampling unit, and meaning of the supplied split.

Continuous integration cannot safely depend on network availability or repeat a full scientific experiment for every commit. It therefore sets a documented environment flag and loads a small, versioned repository fixture made from authentic MNIST observations. This route exercises loading, representation checks, model construction, fitting, evaluation, and telemetry. Its metrics are *software evidence only*. They must not be presented as the empirical result of the full-data lesson.

Definition: experiment versus smoke test

An experiment estimates or compares scientifically relevant quantities under a declared design. A smoke test asks whether a bounded execution path still runs and satisfies basic contracts. Using real observations makes a smoke test representative of data shape and dtype; it does not give the sample the scope or statistical meaning of the full experiment.

19.4.2 Validate first, then transform

The acquired image arrays have shape $(n, 28, 28)$ and unsigned eight-bit pixel values in $[0, 255]$. Before training, the notebook checks image rank and shape, label alignment, class vocabulary, and dtype. It then converts pixels to `float32` and divides by 255, producing values in $[0, 1]$. This scale factor is a fixed representation convention; unlike a fitted mean or standard deviation, it does not estimate state from either partition.

The flattening operation remains inside the model. Thus an input batch with shape $(n, 28, 28)$ becomes $(n, 784)$ at a named model layer, and the serialized model retains that shape transformation. Data validation belongs at the boundary, while deterministic transformations may belong in the model artifact when they must accompany inference.

Worked example: a full-data MNIST baseline with a bounded CI analogue

On the normal route, reserve the official test partition before modeling. Fit a model containing `Flatten`, a 64-unit ReLU layer, and a ten-logit output. The parameter count is

$$(784 \cdot 64 + 64) + (64 \cdot 10 + 10) = 50{,}890.$$

Use a declared seed, Adam with learning rate 10^{-3}, sparse categorical cross-entropy, and a maximum of two epochs for the live demonstration. Keras reserves the last ten percent of the supplied training array as validation data. This is transparent for the lesson; a research system should persist an explicit split, especially when observations contain repeated subjects, groups, or time order.

After architecture and training choices are frozen, report one official-test loss and accuracy together with a row-true, column-predicted confusion matrix. During CI, run the same interfaces against the bounded authentic-MNIST fixture only to verify that the pipeline remains executable.

The result is a baseline, not a deployment claim. The experiment must also record data source, counts, preprocessing range, parameter count, runtime, and artifact identity. A bounded epoch budget is preferable in lecture; a longer study belongs in an explicitly configured experiment, not in an import or notebook-open side effect. CI remains bounded in observations as well as epochs.

19.4.3 The API lifecycle marks changes of state

Building establishes the forward computation and shapes. Compiling binds the optimizer, differentiable objective, and reported metrics but changes no parameter. Fitting updates parameters using training batches and evaluates the declared validation partition after each epoch. The returned `History` is in-memory telemetry, not the trained artifact itself.

Evaluation runs a frozen model without updates. Prediction returns ten logits per observation; an `argmax` produces the displayed class. If an application requires probabilities, it must apply the declared link function and test calibration rather than calling arbitrary scores probabilities. The confusion matrix then localizes which true digits become which predicted digits, exposing error structure hidden by aggregate accuracy.

19.5 Convolution preserves a spatial hypothesis

A fully connected unit has an independent weight for every incoming pixel. A convolution instead assumes that useful local patterns may recur at different locations. It uses the same small kernel across the grid. This combines two inductive biases:

- *local connectivity*: one activation initially sees a small neighborhood; and
- *parameter sharing*: the same detector is applied at every eligible location.

For one input channel and kernel $K \in \mathbb{R}^{k_h \times k_w}$, the operation called convolution in deep-learning libraries is ordinarily cross-correlation:

$$z_{i,j} = b + \sum_{u=0}^{k_h-1} \sum_{v=0}^{k_w-1} K_{u,v} x_{i+u,j+v}.$$

The mathematical convolution would reverse the kernel. The naming convention does not impair learning because the kernel entries are learned, but the distinction matters when reproducing a hand calculation.

For input size n, symmetric padding p, kernel size k, and stride s, an output side has length

$$n_{\text{out}} = \left\lfloor \frac{n + 2p - k}{s} \right\rfloor + 1.$$

"Valid" padding means $p = 0$. "Same" padding is chosen to preserve spatial size for stride one. A stride larger than one skips positions and reduces resolution.




Figure 19.2: One convolution location. Every output value is an inner product between a local patch and the same learned kernel, plus a bias.

19.5.1 Channels and filters

For c_{in} input channels, a filter has shape $k_h \times k_w \times c_{\text{in}}$. It spans every input channel and produces one output channel. With c_{out} filters, the kernel tensor contains

$$k_h k_w c_{\text{in}} c_{\text{out}}$$

weights, plus c_{out} biases. The output channels are learned feature maps, not copies of RGB.

The notebook's inspectable CNN therefore follows

$$(28, 28, 1) \to (28, 28, 16) \to (14, 14, 16) \to (14, 14, 32) \to (7, 7, 32) \to 32 \to 10.$$

The two max-pooling layers have no trainable parameters, and global average pooling replaces each 7×7 feature map by its mean. The parameter count is

$$16(3 \cdot 3 \cdot 1 + 1) + 32(3 \cdot 3 \cdot 16 + 1) + 10(32 + 1) = 5{,}130.$$

Writing this calculation before calling `count_params()` turns the API result into a checked prediction rather than an unexplained number.

19.5.2 Pooling and receptive fields

Max pooling reports the largest value in each local window; average pooling reports the mean. Pooling reduces spatial resolution and can produce limited local invariance, but it also discards information. Strided convolution is an alternative learned downsampling mechanism.

The *receptive field* of a unit is the region of the original input that can influence it. Two stride-one 3×3 convolutions yield a 5×5 effective field; three yield 7×7. In general, if layer ℓ has kernel k_ℓ and stride s_ℓ, define the jump between adjacent units in input coordinates by

$$j_0 = 1, \qquad j_\ell = j_{\ell-1} s_\ell,$$

and receptive-field width by

$$r_0 = 1, \qquad r_\ell = r_{\ell-1} + (k_\ell - 1) j_{\ell-1}.$$

This recurrence exposes why pooling and stride make the field grow faster.




Figure 19.3: A small convolutional classifier gradually trades spatial resolution for more learned channels and a wider effective receptive field. Exact shapes must be computed rather than inferred from the drawing.

Concept check. A 28×28 input receives a 5×5 valid convolution with stride two. Compute the output side length. Then compute the parameter count for 16 filters when the input has one channel and when it has three.

19.6 From MNIST to cats and dogs

MNIST is valuable because the data and computation are bounded. It is not a template for every image claim. A real cats-versus-dogs study introduces nuisance variables: backgrounds, photographers, compression, duplicate animals, breed distribution, pose, occlusion, and label ambiguity. A model may appear accurate after learning grass versus furniture.

A defensible pathway is:

1. record source, license, checksum, and stable sample identifier;
2. identify the independent sampling unit—preferably animal rather than image—and split groups before augmentation;
3. validate decoding, shape, channel order, label vocabulary, and duplicates;
4. establish a small CNN baseline under a bounded budget;
5. compare transfer learning under the same split and selection rule;
6. inspect confusion counts, per-class metrics, confidence, subgroup slices, and representative errors; and
7. save and reload the selected artifact before reporting final test evidence.

The official TensorFlow transfer-learning tutorial provides a reproducible starting point for the mechanics.[3] The course notebook uses a tiny programmatic image fixture only to explain kernels. It never presents the fixture as evidence about animal classification and does not make CI depend on a large network download.

Professional practice

Augmentation belongs inside the training boundary. Apply only transformations that preserve the label in the intended operating domain. Never augment first and then split: near-duplicate transformed images can leak across partitions. Record the transform distribution because it is part of the model specification.

[3] TensorFlow, "Transfer learning and fine-tuning," https://www.tensorflow.org/tutorials/images/transfer_learning.

19.7 Observable training

Training is a running software process. When it behaves unexpectedly, a final accuracy number cannot explain whether the failure came from data, numerical optimization, the device pipeline, or the evaluation contract. Observability provides structured evidence.

Python logging and TensorBoard serve complementary purposes:

Application logs record discrete events and context: configuration identity, data counts, warnings, exceptions, checkpoint paths, and final artifact identity.

TensorBoard summaries record measurements indexed by step or time: losses, task metrics, learning rate, distributions, images, and selected performance traces.

Useful measurements have a diagnostic question attached:

Boundary	Evidence to record
Optimization	training loss, learning rate, gradient norm, nonfinite count
Generalization	validation loss, task metrics, train–validation gap
Data	class counts, corrupt records, observed ranges, augmentation rate
System	batch latency, examples per second, device/memory use when profiled
Release	frozen-test metrics, artifact hash, reload result, inference latency

Metrics create overhead and risk. Histograms are larger than scalars; profiling can materially slow execution; images can reveal private data; and high-cardinality identifiers make logs expensive and difficult to aggregate. Collect the least evidence that answers a defined diagnostic question.

Worked example: diagnosing overfitting rather than naming it

Training accuracy rises from 0.91 to 0.999, while validation loss reaches a minimum in epoch four and then rises. TensorBoard makes the divergence visible, but it does not prescribe a remedy. The team first verifies that the split unit and preprocessing boundary are correct. It restores the epoch-four checkpoint, compares class-specific errors, and repeats the experiment across seeds. Only then does it evaluate regularization, augmentation, model capacity, or more representative data. The plot begins an investigation; it does not complete one.

The Keras TensorBoard callback writes event data at selected lifecycle points. The normal full-MNIST route attaches this callback and records epoch-level loss and accuracy for training and validation. The CI route deliberately attaches no TensorBoard callback: it checks that the dependency and log-directory configuration exist, but avoids creating an event writer whose startup and filesystem costs could dominate a one-epoch smoke test. Different execution budgets are legitimate only when their purposes and evidence claims remain explicit. The local viewer is launched from the repository root with

```
uv run tensorboard --logdir output/tensorboard/lecture-12 --port 6006.
```

The viewer should bind locally unless exposure is explicitly authorized. Stop it with `Ctrl+C`. A different port resolves a local collision. The official Keras guide documents the callback and managed training lifecycle.[4]

[4]TensorFlow, "Training & evaluation with the built-in methods," https://www.tensorflow.org/guide/keras/training_with_

19.8 Debugging framework experiments

Several failures recur often enough to treat them as tests:

1. **Wrong kernel.** Installation succeeded in one interpreter but the notebook kernel points elsewhere. Inspect `sys.executable` and select Rice DSM.
2. **Wrong rank or channel order.** Assert batch shapes at the data boundary and after the first batch.
3. **Loss/output mismatch.** Test that a logits loss receives logits, and that sparse versus one-hot target encoding matches the selected loss.
4. **Training/evaluation mode mismatch.** Dropout and batch normalization behave differently by mode. Reload in a fresh process and test inference explicitly.
5. **Leakage.** Test the group split and ensure normalization or augmentation state is fitted only within the training boundary.
6. **Empty telemetry.** Verify that the callback log directory and TensorBoard command resolve to the same absolute location.
7. **Nondeterministic evidence.** Record seeds and deterministic options, then report variation across repeats rather than promising bitwise identity across all hardware.

Common misconception

A high validation accuracy is not an observability strategy. Validation accuracy summarizes one outcome on one partition. Logs and telemetry help explain the process that produced it; class-specific and operational evidence determine whether it is fit for a decision.

19.9 Exercises

1. Draw the framework stack in Figure 19.1 from memory and give one failure that belongs at each boundary.
2. Derive the gradient of softmax cross-entropy with respect to each logit. Explain why a fused implementation is numerically preferable.
3. Calculate every intermediate shape and parameter count in Figure 19.3 under valid and same padding.
4. Prove the receptive-field recurrence and apply it to two convolution–pool blocks.
5. Construct a 3×3 vertical-edge kernel and perform one complete patch calculation by hand. Explain why the operation is cross-correlation.
6. Design a test that catches sparse versus one-hot loss mismatch before training begins.
7. Compare a dense MNIST baseline with a small CNN under the same budget. Report parameter count, seed variation, error pairs, and runtime as well as accuracy.
8. Design a group-aware cats-versus-dogs manifest. State which fields protect against duplication and leakage.
9. Select no more than eight TensorBoard measurements for an MNIST run. For each, state the failure hypothesis it helps test.
10. Extend the experiment to Fashion-MNIST. Frame a question about visual ambiguity between garment classes, then write a model-card limitation based on observed errors.

Chapter review

TensorFlow supplies tensor execution, mutable variables, automatic differentiation, and optimized device kernels. Keras organizes these capabilities into layers, models, objectives, optimizers, metrics, callbacks,

`built_in_methods`.

and a managed lifecycle. Concise framework code does not make the modeling argument concise: shapes, label semantics, split boundaries, checkpoints, and artifacts remain explicit contracts. Convolution fits image data by combining local connectivity with parameter sharing. Channels represent learned feature maps, stride and padding determine spatial shape, pooling downsamples, and composition expands receptive fields. Python logging and TensorBoard make a running experiment diagnosable when each measurement is tied to a concrete question. They supplement rather than replace held-out decision evidence.

Executable companion

Lecture 12 notebook 03 introduces the TensorFlow/Keras API, verifies automatic differentiation against a hand calculation, and downloads the full official MNIST dataset through Keras for the normal student analysis. CI explicitly selects the repository's bounded authentic-MNIST sample as a software smoke test. The notebook visualizes convolution mechanics, gives exact local TensorBoard commands, and develops a real-data cats-versus-dogs extension with provenance, licensing, and group-aware splitting requirements.

CHAPTER 20

Text, tokenization, and sentiment systems

Learning objectives

After this chapter, you should be able to:

- formulate sentiment analysis as a supervised prediction problem while stating what the label does and does not mean;
- distinguish text normalization, tokenization, vocabulary construction, integerization, padding, masking, and out-of-vocabulary handling;
- prevent preprocessing leakage by fitting a vocabulary on training data alone;
- explain embeddings, pooled text representations, binary logits, and cross-entropy mathematically;
- evaluate thresholded decisions with error-specific metrics and direct inspection of held-out failures; and
- specify the artifacts and monitoring signals required for a reliable text-classification system.

Where this chapter fits

The preceding chapters built nonlinear predictors from affine maps, activations, objectives, and backpropagation. Text presents a new difficulty: an observation is a variable-length sequence of symbols rather than a fixed vector of measured real numbers. TensorFlow can differentiate and execute the resulting model, but first we must define how language becomes tensors without leaking held-out information or erasing important structure.

20.1 A scientific question before an architecture

Consider a movie review x and a binary label y, where $y = 1$ denotes a positive rating and $y = 0$ denotes a negative rating. We seek a function whose output supports the conditional probability claim

$$p_\theta(y = 1 \mid x).$$

This is a supervised binary-classification problem. It is not a measurement of an author's complete emotional state and it is not a universal definition of positive language. The label inherits the data creator's rating threshold, sampling decisions, time period, platform, and population.

The Stanford Large Movie Review Dataset is an instructive case. It contains 25,000 labeled reviews for training and 25,000 for testing, with balanced positive and negative classes. Reviews with intermediate ratings are excluded. That design makes a clean educational benchmark, but it also removes much of the ambiguity that a deployed sentiment system would encounter.

Definition: prediction contract for sentiment

A sentiment prediction contract names the unit of analysis, label-construction rule, represented population, information available at prediction time, output semantics, decision threshold, error costs, and conditions under which the model should abstain or defer to a person.

The first baseline need not be a neural network. A bag-of-words or TF–IDF representation followed by logistic regression is fast, auditable, and often competitive. A neural model should earn its added complexity through held-out evidence or through a requirement—such as reusable learned representations or sequence-sensitive prediction—that the baseline cannot satisfy.

20.2 Data acquisition is part of the experiment

The notebook obtains the archive from Stanford through Keras's cache-aware `get_file` utility. On the first student run, the utility downloads and extracts the publisher's archive. Later runs reuse the local cache. An explicit environment variable may instead identify an existing extracted `aclImdb` directory. These are acquisition mechanisms, not alternative datasets: both must resolve to the publisher's directory structure.

The path alone is insufficient provenance. An experiment record should retain the publisher URL, retrieval date, archive checksum when available, local manifest, class-selection rule, and sample limit. The lecture pipeline selects the first fixed number of lexicographically sorted files in each class. This makes membership deterministic across supported operating systems and balances the classes, but the limit changes sampling uncertainty and therefore belongs in every reported result.

IMDB supplies distinct `train` and `test` directories. We preserve that boundary and create a validation split only from publisher-designated training reviews:

$$D_{\text{publisher train}} = D_{\text{optimization}} \dot{\cup} D_{\text{validation}}, \qquad D_{\text{test}} \text{ remains untouched.}$$

Stratification preserves class proportions, while a fixed split seed makes membership reproducible. The optimization subset fits parameters and preprocessing state. Validation data selects checkpoints, architectures, and decision policy. Test data estimates the frozen procedure once.

Professional practice

The automated test suite sets an explicit CI flag and replaces the download with locally authored sentences. That fixture answers "does the pipeline still execute and obey its shape contracts?" It cannot answer "does this model classify movie reviews?" Outside CI, acquisition failure must raise an error rather than silently substitute the fixture and change the scientific question.

20.3 How text models developed

Early automatic text classifiers commonly combined manually constructed lexicons with counts of words or short word sequences. Statistical language models and linear classifiers made these counts trainable and testable. Distributed representations later replaced one coordinate per vocabulary word with compact learned vectors. Convolutional networks detected local phrase patterns, while recurrent networks propagated state across a sequence. Attention mechanisms then allowed representations to combine information from distant positions more directly, and large pretrained transformers made it possible to adapt representations learned from vast corpora.

This history is not a sequence in which every new method makes earlier methods obsolete. Count-based linear models remain valuable baselines. Small embedding models can be appropriate when latency, energy, privacy, or data volume rule out a large pretrained model. Every approach still depends on data provenance, split integrity, metric choice, error analysis, and operational monitoring.

20.4 The representation pipeline

A raw string must cross several conceptually different boundaries before it can enter a dense neural network:

$$\text{raw review} \longrightarrow \text{normalized text} \longrightarrow \text{tokens} \longrightarrow \text{integer IDs} \longrightarrow \text{embeddings} \longrightarrow \text{review vector}.$$

Collapsing these steps under the word "tokenization" hides important modeling decisions.

In TensorFlow, `TextVectorization` is a stateful preprocessing layer. Its `adapt` method counts tokens and constructs a vocabulary; calling the layer applies the frozen mapping. The distinction is analogous to `fit` versus `transform` in a tabular pipeline. Only optimization text may enter `adapt`. Validation, test, and future text call the already adapted layer.

Keeping this layer inside the Keras model makes the deployed input contract a batch of strings rather than a batch of unexplained integers. It also packages normalization rules and vocabulary order with the fitted network. A parity test should confirm that a saved and reloaded model returns the same logits for versioned review fixtures.

Common misconception

token IDs are not numerical measurements Assigning the word *excellent* ID 200 and *awful* ID 100 does not make the first word twice the second. The IDs are addresses in a vocabulary. A trainable embedding converts those addresses into vectors whose geometry is learned from the training objective; treating raw IDs as scalar features would invent an ordering and distance that language does not possess.

20.4.1 Normalization

Normalization may lowercase text, standardize Unicode, remove markup, or strip punctuation. Each transformation encodes an assumption. Exclamation marks, capitalization, emoji, spelling variants, and repeated characters can carry sentiment. A default that is sensible for movie reviews may be destructive for clinical notes, source code, or multilingual messages.

A normalization function should be deterministic, versioned, and identical in training and inference. It should also be tested on empty strings, unusual Unicode, markup, and adversarially long inputs.

20.4.2 Tokens and vocabularies

A tokenizer divides normalized text into units. Word tokenization is intuitive but creates rare and unseen words. Character tokenization has a small vocabulary but produces long sequences. Subword methods construct reusable pieces, allowing an unfamiliar word to share structure with familiar ones.

Let the training vocabulary be

$$\mathcal{V} = (v_0, v_1, \ldots, v_{V-1}).$$

An integerizer maps a token to its index in $\mathcal{V}$. These integers are identifiers, not quantitative measurements: token 200 is not twice token 100. A typical contract reserves index zero for padding and index one for an out-of-vocabulary token, often displayed as `[UNK]`.

If n_{OOV} observed training tokens map to ID one and n_{observed} excludes padding, then

$$r_{\mathrm{OOV}} = \frac{n_{\mathrm{OOV}}}{n_{\mathrm{observed}}}$$

is a useful representation diagnostic. It is not a performance metric. A high rate may indicate an undersized vocabulary, unexpected language, or domain shift. Enlarging the vocabulary increases memory and can admit rare noisy features, so the response should follow diagnosis rather than a fixed rule.

Proposition 20.1. *If a vocabulary is selected using validation or test documents, then the evaluation pipeline is not independent of those held-out documents.*

Proof. Vocabulary selection is a learned transformation because the selected tokens and their indices depend on observed token frequencies. If held-out documents contribute to those frequencies, then the representation function supplied to the estimator is a function of the held-out inputs. Consequently the fitted pipeline has received information about the evaluation distribution before evaluation, even if it has not received the held-out labels. The evaluation no longer estimates a pipeline constructed from training data alone. □

This leakage may appear weak because labels are absent, but it breaks the experimental contract. Split observations first. Fit normalization state, vocabulary, and any other learned preprocessing using only the training partition. Apply the frozen transformation to validation, test, and production text.

20.4.3 Padding, truncation, and masking

Reviews have different lengths. A tensor batch is usually rectangular, so a pipeline selects a sequence length L. Short sequences receive padding; tokens beyond L are truncated. These operations are not harmless bookkeeping. A small L may remove a final conclusion that reverses earlier language. A large L increases memory and computation.

A mask is a Boolean tensor marking positions that contain actual tokens rather than padding. A compatible embedding or sequence layer uses the mask so that padding does not contribute to a pooled representation or recurrent state. Without masking, document length can become an unintended predictive feature.

Before choosing L, examine the training length distribution and state the truncation rate. In deployment, monitor this rate because longer documents can signal distribution shift or an input-contract violation.

For a batch of B reviews, the representation shapes are

$$\begin{aligned}
\text{raw strings} &: (B),\\
\text{token IDs} &: (B, L),\\
\text{embedding vectors} &: (B, L, d),\\
\text{padding mask} &: (B, L),\\
\text{pooled review vectors} &: (B, d),\\
\text{binary logits} &: (B, 1).
\end{aligned}$$

Shape assertions make these interfaces executable. They catch accidental scalar inputs, missing batch dimensions, wrong output width, and incompatible label tensors before a long training run.

20.5 Embeddings are trainable lookup tables

Let V denote vocabulary size and d embedding dimension. An embedding layer stores

$$E \in \mathbb{R}^{V \times d}.$$

For token ID i, the layer returns row $E_{i,:}$. A length-L sequence thus becomes a matrix in $\mathbb{R}^{L \times d}$. The rows of E begin from an initializer and are updated by backpropagation because they participate in the classification loss.

An embedding coordinate does not come with a fixed linguistic interpretation. If two tokens acquire nearby vectors, they were useful in similar predictive contexts under this corpus, objective, model, and training run. That geometry does not establish causal, psychological, or universal semantic equivalence.

20.5.1 Pooling a sequence

The simplest fixed-width representation is a masked average. Let $m_t = \mathbf{1}[i_t \neq 0]$ indicate a non-padding token. Define

$$h(x) = \frac{\sum_{t=1}^{L} m_t E_{i_t,:}}{\sum_{t=1}^{L} m_t}.$$

This formula assumes at least one observed token. The input contract must reject, abstain on, or deliberately represent an empty normalized input rather than letting a zero denominator produce an undefined result. For an admissible review it produces $h(x) \in \mathbb{R}^d$ regardless of review length. A hidden layer and output logit can then compute

$$r = \mathrm{ReLU}(W_h h(x) + b_h), \qquad z = w_o^\top r + b_o.$$

Mean pooling is fast and makes tensor shapes transparent. It also largely discards order. The phrases "not painfully slow" and "not moving, painfully slow" can contain similar tokens but express different judgments. A one-dimensional convolution can detect local patterns; a recurrent network can propagate ordered state; and attention can form context-dependent combinations across positions. The added structure should be justified with a controlled comparison rather than assumed to help.

In Keras, `Embedding(mask_zero=True)` constructs the Boolean mask and a compatible `GlobalAveragePooling1D` consumes it. Padding ID zero is ignored; OOV ID one is not. The latter represents observed but unresolved language and should therefore contribute its learned OOV vector.

20.6 A binary logit and a stable objective

The model emits a logit $z \in \mathbb{R}$. The sigmoid converts this unrestricted score to a value in $(0, 1)$:

$$p_\theta(y = 1 \mid x) = \sigma(z) = \frac{1}{1 + \exp(-z)}.$$

For $y \in \{0, 1\}$, binary cross-entropy is

$$\ell(z, y) = -y \log \sigma(z) - (1 - y) \log(1 - \sigma(z)).$$

Mature frameworks should consume logits directly because a stable implementation avoids first forming probabilities that round to exactly zero or one.

Proposition 20.2. *The derivative of binary cross-entropy with respect to its logit is*

$$\frac{\partial \ell}{\partial z} = \sigma(z) - y.$$

Proof. Let $p = \sigma(z)$. Since $dp/dz = p(1-p)$,

$$\begin{aligned}\frac{\partial \ell}{\partial z} &= \left(-\frac{y}{p} + \frac{1-y}{1-p}\right) p(1-p) \\ &= -y(1-p) + (1-y)p \\ &= p - y.\end{aligned}$$

□

The expression is the familiar prediction-minus-target error from logistic regression. The difference is that $z = f_\theta(x)$ now depends on vectorization, embedding lookup, pooling, and hidden layers. Automatic differentiation applies the chain rule from $p - y$ through this graph.

The output and loss form one contract. A final dense layer with no activation emits logits and must pair with `BinaryCrossentropy(from_logits=True)`. If the model instead emits $\sigma(z)$, the loss must be configured for probabilities. Applying sigmoid twice changes the objective and weakens gradients. Before fitting, evaluate one batch and assert that the logit shape is $(B, 1)$ and the loss is finite.

Keras's binary-accuracy threshold is expressed in the coordinate system of its input. When the metric receives logits, threshold zero corresponds to $\sigma(0) = 0.5$. Confusing a logit threshold of zero with a probability threshold of zero can make an apparently reasonable metric configuration meaningless.

Worked example: a TensorFlow sentiment pipeline

A reproducible first model has the following explicit contract:

1. preserve the publisher's train/test partition and reserve validation observations from the training partition;
2. adapt a `TextVectorization` layer on training reviews only;
3. output a fixed-length integer sequence with documented padding, OOV, vocabulary-size, and truncation policies;
4. map IDs through an `Embedding` layer with masking enabled;
5. use masked global-average pooling, a small ReLU hidden layer, and one output logit;
6. optimize logits-based binary cross-entropy with Adam;
7. select checkpoints and any threshold using validation data; and
8. evaluate the frozen candidate once on test data.

The baseline should record its seed, package versions, vocabulary, sequence length, parameter count, epoch times, loss curves, and evaluation metrics. The vectorizer belongs inside or beside the saved model artifact so that training and serving cannot silently disagree about integer IDs.

20.7 Thresholds turn modeled probabilities into decisions

The conventional classifier

$$\widehat{y} = \mathbf{1}[\sigma(z) \geq 0.5]$$

is equivalently $\mathbf{1}[z \geq 0]$. Neither threshold is mandated by cross-entropy. A threshold encodes an operational tradeoff.

For the positive class, precision and recall are

$$\text{precision} = \frac{TP}{TP + FP}, \qquad \text{recall} = \frac{TP}{TP + FN}.$$

If falsely promoting an unfavorable review is costly, precision may matter. If missing critical feedback is costly, recall may matter. A confusion matrix retains all four error counts; accuracy alone collapses them.

Threshold selection belongs on validation data and should reflect a stated cost or capacity constraint. Repeatedly choosing a threshold after examining test results converts the test set into another validation set. Probability calibration should also be checked when consumers interpret scores as probabilities rather than ranks.

A valid sequence is therefore:

1. fit parameters on optimization data;
2. select the checkpoint from validation loss;
3. inspect validation precision–recall tradeoffs and freeze a threshold;
4. compute test logits once, transform them with sigmoid, and apply that frozen threshold; and
5. report the confusion counts, metrics, sample size, and uncertainty.

For the classroom example no real operating cost is supplied, so the notebook predeclares 0.5 instead of reverse-engineering a favorable threshold. A real application must elicit costs, capacity, or a target constraint from its decision context.

Concept check. Suppose a team chooses a threshold after repeatedly inspecting test-set recall. Which experimental boundary has been broken, and what data should the team use to choose the threshold instead?

20.8 Error analysis is part of modeling

Inspect false positives, false negatives, and low-margin correct predictions. Useful error categories include:

- negation and contrast, such as “slow at first, but not disappointing”;
- sarcasm or rhetorical language;
- mixed evaluations of acting, direction, and plot;
- names, genres, or years used as shortcuts;
- influential tokens mapped to OOV;
- decisive evidence removed by truncation; and
- disagreement or ambiguity in the original rating rule.

An error category suggests an experiment. Negation may motivate order-sensitive features. Truncation errors may motivate a larger L or hierarchical model. Genre shortcuts may require stratified evaluation. Ambiguous labels may place an upper limit on meaningful performance. A larger architecture is not the automatic response to every error.

Professional practice

An error audit should retain the true label, frozen-model probability, decision, error type, retained-token count, OOV count, and a bounded review excerpt when the data policy permits inspection. Assign a hypothesized category before changing the model. Then propose a controlled experiment and a result that would falsify the hypothesis. Error browsing without a coding scheme easily becomes anecdotal model tuning.

20.9 Responsible use and deployment

A movie-review classifier is a bounded educational task. Sentiment models are often redeployed to employee messages, student writing, clinical narratives, or customer support. That transfer changes the population, language, privacy risk, and consequences. Performance on IMDB does not justify such use.

Potential failures include dialect-dependent error rates, changing slang, spurious correlations with identity terms, forced binary predictions on mixed sentiment, and exposure of personal text through logs. Evaluation should be sliced by relevant, ethically supportable groups and linguistic phenomena, with uncertainty reported for small samples. High-impact uses require human review, appeal paths, access controls, retention limits, and possibly a decision not to deploy.

A released text system should version together:

- a data manifest and split identifiers;
- normalization and tokenization code;
- vocabulary order, OOV policy, and sequence length;
- architecture, parameters, optimizer state when resuming, and framework versions;
- class order, logit/probability contract, and decision threshold;
- validation and test evidence; and
- a model card describing intended use and known limitations.

Production monitoring should include request validity, empty-input frequency, token length, truncation rate, OOV rate, score and decision distributions, latency, failures, and delayed outcome metrics when legitimate labels arrive. Raw user text should not appear in general logs. Aggregate diagnostics or carefully controlled examples reduce privacy and security exposure.

20.10 Exercises

1. Give separate definitions of normalization, tokenization, integerization, padding, masking, and embedding. For each, name one failure mode.
2. Explain why adapting a vocabulary on unlabeled test text is still leakage. Construct a small example in which the selected vocabulary changes.
3. For a vocabulary of size 8,000, embedding dimension 48, sequence length 200, and batch size 32, compute the embedding parameter count and output-tensor shape.
4. Derive the binary-cross-entropy logit gradient. Explain why using a sigmoid output with a loss configured for logits is incorrect.
5. Compare masked mean pooling with a one-dimensional convolution while holding the split, vocabulary, sequence length, and evaluation protocol fixed. Report parameter count, runtime, validation loss, and error categories.
6. Evaluate sequence lengths 100, 250, and 500. Plot truncation rate, runtime, and negative-class recall. Recommend a length using evidence rather than accuracy alone.
7. Choose an operational setting for which false positives and false negatives have different costs. Define a threshold-selection rule without touching the test set.
8. Conduct a ten-example error audit. Propose one data change and one model change, and state what result would falsify each proposed improvement.
9. Write tests verifying reserved token IDs, output shape, finite logits, deterministic inference, empty-string handling, artifact reload, and parity between batch and single-review predictions.
10. Draft a monitoring plan that detects changing review length, OOV rate, score distribution, and delayed

accuracy without logging raw reviews.

Chapter review

Text classification begins with a construct and data contract, not an architecture. Normalization, tokenization, vocabulary construction, padding, and masking determine what evidence a model can use. Learned preprocessing must fit the training partition alone. Embeddings replace arbitrary integer identifiers with trainable vectors, while pooling or sequence layers produce a fixed representation. A binary logit trained by cross-entropy retains the logistic-regression error $\sigma(z) - y$; backpropagation distributes that error through the text representation. Threshold metrics, direct error inspection, artifact versioning, privacy-conscious monitoring, and responsible scope are part of the model, not postscript engineering.

Executable companion

Lecture 12 notebook 04 executes this full pipeline. The normal student route downloads the genuine Stanford IMDB corpus from its publisher through Keras's cache-aware data API. Only the automated CI route selects a bounded locally authored fixture, and its results are explicitly excluded from substantive analysis. Students inspect length and label distributions, fit a training-only vocabulary, trace tensor shapes, train an embedding classifier, vary thresholds, and audit held-out errors.

CHAPTER 21

Nearest neighbors: local prediction, retrieval, and engineering

Learning objectives

After this chapter, you should be able to:

- define nearest-neighbor classification and regression from a metric, neighborhood, weighting rule, and aggregation rule;
- explain how representation, scaling, dimension, and k determine a local model's statistical behavior;
- construct an item-item collaborative-filtering recommender and state what its offline evidence can and cannot establish;
- implement nearest-neighbor estimators as typed, tested package code rather than notebook-only functions; and
- place data, fixtures, algorithms, tests, experiments, and operational evidence in defensible repository boundaries.

Where this chapter fits

The preceding chapters learned affine scores, margins, compositions, and dense representations. Nearest neighbors takes a different position: retain the training observations and answer a query from nearby evidence. The fitted object has few numerical coefficients, but it has strong assumptions. A representation defines which differences are visible; a metric defines closeness; k defines locality; an aggregation rule turns neighbors into an answer; and a system must store and search the resulting evidence under latency, memory, privacy, and update constraints.

21.1 A local principle with a long history

Nearest-neighbor methods formalize a simple proposition: observations that are near one another in a defensible representation should have related responses. Fix and Hodges studied nearest-neighbor discrimination in 1951. Cover and Hart's 1967 analysis made the one-nearest-neighbor rule a foundational result in statistical pattern recognition. The method remains useful because it is both a model and a diagnostic. It supplies a transparent nonlinear baseline, exposes whether a representation creates coherent neighborhoods, and provides the retrieval operation beneath recommendation, similarity search, and some anomaly systems.

Calling kNN *nonparametric* does not mean that it has no choices, performs no fitting, or automatically ignores irrelevant variables. It means that the model is not confined to a fixed finite-dimensional parameter vector as the sample grows. Training observations themselves are fitted state. The method has hyperparameters—metric, k, weights, preprocessing, search strategy—and its effective complexity can grow with the data.

Common misconception

Misconception: nonparametric methods accept every available feature and ignore useless ones. **Correction:** every included coordinate can change distance and therefore neighbor identity. Independent noise dimensions may overwhelm useful local structure. Representation selection is part of the model.

21.2 The mathematical object: a neighborhood

Let

$$D = \{(x_i, y_i)\}_{i=1}^{n}, \qquad x_i \in \mathcal{X},$$

be a supervised training set. The response y_i is numerical for regression and belongs to a finite class set C for classification. A metric $d : \mathcal{X} \times \mathcal{X} \to [0, \infty)$ satisfies

$$\begin{aligned} &d(x, z) \geq 0, && d(x, z) = 0 \iff x = z, \\ &d(x, z) = d(z, x), && d(x, z) \leq d(x, u) + d(u, z). \end{aligned}$$

For a query x, write $N_k(x)$ for the indices of the k training observations with smallest $d(x, x_i)$. A complete implementation also declares how exact distance ties are ordered.

For vectors in $\mathbb{R}^p$, the Minkowski family is

$$d_q(x, z) = \left(\sum_{j=1}^{p} |x_j - z_j|^q \right)^{1/q}, \qquad q \geq 1.$$

$q = 1$ is Manhattan distance and $q = 2$ is Euclidean distance. Other domains need other structures: angular similarity for direction, Hamming distance for binary attributes, geodesic distance on a sphere, edit distance for sequences, or a domain-specific combination of continuous and categorical differences. A formula is not defensible merely because software provides it.

Concept check. Suppose a dataset records temperature in degrees Celsius and annual income in dollars. Which coordinate is likely to dominate raw Euclidean distance? Why does standardization address numerical scale without proving that one standard deviation has equal scientific meaning in both variables?

21.2.1 Classification by local vote

Uniform kNN estimates a class probability by a local frequency:

$$\widehat{P}_k(Y = c \mid X = x) = \frac{1}{k} \sum_{i \in N_k(x)} \mathbf{1}\{y_i = c\},$$

and predicts

$$\widehat{g}_k(x) = \arg\max_{c \in C} \widehat{P}_k(Y = c \mid X = x).$$

The vote vector sums to one, but it is not automatically a calibrated probability vector. The neighborhood is data-dependent, classes may be imbalanced, and k may have been selected for a metric other than calibration. A deterministic class-tie policy belongs in the public contract.

21.2.2 Regression by local averaging

Uniform kNN regression estimates a local conditional mean:

$$\widehat{f}_k(x) = \frac{1}{k} \sum_{i \in N_k(x)} y_i.$$

It is piecewise constant under a fixed training set. It interpolates local evidence rather than extending a global trend, so it can behave poorly outside training support even though it always returns a number.

21.2.3 Distance-weighted aggregation

A weighted rule replaces equal contributions with nonnegative weights:

$$\widehat{f}(x) = \frac{\sum_{i \in N_k(x)} w_i(x) y_i}{\sum_{i \in N_k(x)} w_i(x)}, \qquad w_i(x) = \frac{1}{d(x, x_i)}.$$

Classification replaces y_i with class indicators. Exact matches require an explicit zero-distance policy. A common contract assigns vote mass only to exact matches, preventing division by zero and preventing distant observations from diluting identical inputs. Conflicting labels at identical inputs should also trigger a data-quality investigation.




Figure 21.1: The neighbor search is shared, while the target contract determines aggregation. Classification votes over labels; regression averages numerical responses. The query's three selected neighbors are drawn explicitly.

Worked example: one search, two prediction tasks

Let training features be

$$(0, 0),\ (1, 1),\ (3, 1),\ (4, 3)$$

and let the query be $x = (2.5, 1.5)$. The Euclidean distances are approximately 2.92, 1.58, 0.71, and 2.12. Thus the three-neighbor index set contains rows 3, 2, and 4 when rows are numbered from one.

If their class labels are B, A, and B, then the class vote is two-thirds B. If their numerical responses are 3.5, 1.5, and 4.0, the regression estimate is

$$(3.5 + 1.5 + 4.0)/3 = 3.0.$$

The calculation is elementary enough to become a unit test. That is a virtue: an analytic case verifies the implementation before a realistic dataset adds preprocessing, splitting, and domain uncertainty.

21.3 Why the neighbor count changes the model

At $k = 1$, the prediction can follow individual observations. The method has small local smoothing bias and potentially high variance. As k increases, neighborhoods grow, predictions smooth, and variance often falls while local bias rises. Very large k drives classification toward the dominant class and regression toward a broad average.

k is selected using validation evidence, not the final test set. The phrase "choose the k with smallest error" is incomplete unless it specifies which data generated that error, which metric corresponds to the task, and how ties or repeated splits are handled. An odd k does not eliminate multiclass ties, and distance weighting can create ties for any k.

21.3.1 A consistency theorem

The statistical appeal of kNN is not limited to intuition. Under regularity conditions, increasing the neighborhood count while shrinking its fraction of the sample yields a consistent local estimate.

Theorem 21.1 (informal universal consistency of kNN)**.** *For iid observations in a finite-dimensional Euclidean space, suppose $k = k_n$ satisfies*

$$k_n \longrightarrow \infty, \qquad \frac{k_n}{n} \longrightarrow 0.$$

Under standard measurability and integrability conditions, kNN classification risk approaches Bayes risk; for squared-error regression, the kNN estimate approaches the conditional mean in the corresponding risk sense.

Proof sketch. The neighborhood must solve two competing problems. Because $k_n \to \infty$, the average contains enough responses for sampling variation to vanish. Because $k_n/n \to 0$, the radius needed to capture those k_n observations shrinks in regions of positive probability, so the average becomes local rather than a global mixture. A differentiation argument connects the local average to the conditional response. Classification then chooses the largest conditional class probability, and regression estimates the conditional mean. The theorem does not say that a finite dataset supplies good neighborhoods, that every metric is scientifically valid, or that convergence is fast in high dimension. □

Cover and Hart also showed a striking asymptotic bound for one-nearest-neighbor classification: under appropriate continuity conditions, its limiting error is no more than twice the Bayes error in the small-error regime (more precisely, the classical bound is $R_{1NN} \leq 2R^*(1 - R^*)$ for binary classification). This result explains why an extremely local rule can be competitive, but it is not a guarantee for arbitrary finite, shifted, dependent, or poorly represented data.

21.4 Scaling, representation, and leakage

Euclidean distance is sensitive to units. If one column ranges over thousands and another over tenths, the first can dominate neighbor identity. A standard scaler learns training means μ_j and standard deviations s_j and maps

$$x_j \mapsto \frac{x_j - \mu_j}{s_j}.$$

The fitted scaler and ordered feature schema are part of the model artifact. Fitting the scaler on all observations before validation leaks held-out distribution information even though no targets enter the calculation.

A correct development boundary is:

1. reserve the test set;
2. split development data into training and validation, or define inner cross-validation;
3. fit preprocessing on training folds only;
4. select k, weights, metric, and representation from validation evidence;
5. freeze the configuration, refit on development data, and evaluate the test set once.

Standardization is not universally correct. It encodes the proposition that a one-training-standard-deviation displacement is comparable across features. Robust scaling, transformations, learned representations, or a domain metric may better match the scientific question. A pipeline owns that decision so training and inference cannot silently disagree.

Concept check. Why can adding an independent Gaussian noise column change a kNN prediction even though the column contains no target information? Why might a linear model with strong regularization react differently?

21.5 Dimension and the loss of locality

In high dimension, local coverage requires rapidly increasing sample size. A unit interval has length one; a unit square needs a fine two-dimensional grid; a unit cube needs that resolution along three axes. Repeating this argument produces exponential growth in the number of cells. This is one expression of the *curse of dimensionality*.

Distances may also concentrate. For many high-dimensional distributions, the ratio of nearest to farthest distance approaches one. “Nearest” then provides weak contrast. Irrelevant coordinates worsen the problem by adding variation that does not correspond to the response. Dimensionality reduction can help only when the retained representation preserves task-relevant neighborhoods and is fitted within the validation boundary.

21.6 A real classification workflow: wine chemistry

The Lecture 13 laboratory queries the versioned wine-recognition table. One row is one Italian wine sample, thirteen features are chemical measurements, and the target is one of three cultivar classes. Before modeling, the analysis reads the dataset catalog, verifies identifier uniqueness and missingness, inspects class counts, and plots scale differences.

The development pipeline compares uniform and inverse-distance votes across a declared grid of odd k values. Validation accuracy selects a candidate; the test labels remain hidden. After freezing the configuration, the pipeline refits the scaler and kNN state on combined development data and reports a majority-class baseline,




Figure 21.2: Left and center: k changes the smoothness of a local classifier. Right: independent coordinates reduce nearest-versus-farthest distance contrast in one reproducible simulation. The simulation isolates geometry; it is not population evidence.

held-out accuracy, and a confusion matrix. The confusion matrix matters because an average can conceal one cultivar's repeated errors.

This is a complete evaluation contract but a bounded scientific claim. The sample is small, its collection context limits generalization, and prediction does not establish that cultivar caused every measured chemical difference.

21.7 A real regression workflow: disease progression

The regression laboratory uses baseline measurements for 442 patients and a quantitative disease-progression response measured one year later. It chooses k and weight mode using validation MAE, then reports both MAE and RMSE on the held-out test data beside a training-mean baseline.

MAE answers the expected absolute target-unit error. RMSE penalizes large errors more heavily. A residual-versus-prediction plot asks whether errors change over the response range; inspecting the neighbors of the largest residual asks whether the query had coherent local support. Feature meanings are incompletely documented, the sample is small, and no classroom score establishes clinical utility. The limitation is part of the result.

Common misconception

Misconception: because kNN is interpretable, a prediction is explained by listing its neighbors. **Correction:** neighbor identities reveal the model's local evidence, but the metric, sampling process, omitted variables, label quality, and support determine whether those neighbors are meaningful. An example-based explanation does not validate the underlying similarity.

21.8 Recommendation as neighbor retrieval

A recommender does not merely assign a class. It retrieves and ranks unseen items from incomplete behavioral evidence. The Lecture 13 laboratory uses an authentic, deterministic subset of GroupLens MovieLens data: 13,817 rating events for the 80 most-rated movies in the `ml-latest-small` development dataset. The selection makes class execution reliable but intensifies popularity bias. It is not a stable research benchmark.

21.8.1 Content versus collaborative similarity

A content-based system compares item attributes such as genres or measured properties. A collaborative system compares patterns of interaction. Let r_{ui} be user u's rating of item i, and let $\bar{r}_u$ be that user's mean observed rating. For users U_{ij} who rated both items i and j, an adjusted cosine similarity is

$$s(i,j) = \frac{\sum_{u \in U_{ij}} (r_{ui} - \bar{r}_u)(r_{uj} - \bar{r}_u)}{\sqrt{\sum_{u \in U_{ij}} (r_{ui} - \bar{r}_u)^2} \sqrt{\sum_{u \in U_{ij}} (r_{uj} - \bar{r}_u)^2}}.$$

User centering partially separates item preference from generous-versus-strict rating habits. A minimum co-rating count prevents a single pair of events from creating apparently perfect similarity.

For user u and unseen item j, let $N_k(j;u)$ contain the up-to-k most positively similar items that the user has rated. A transparent score is

$$\widehat{r}_{uj} = \bar{r}_u + \frac{\sum_{i \in N_k(j;u)} s(j,i)(r_{ui} - \bar{r}_u)}{\sum_{i \in N_k(j;u)} |s(j,i)|}.$$

The implementation excludes already-seen items and declines candidates with no positive supported neighbor. Those are testable product rules.

21.8.2 Offline evaluation is limited evidence

A temporal holdout may hide each eligible user's latest positive interaction, fit on earlier events, and ask whether the hidden item appears in the top-N list. Recall@N or hit rate then measures retrieval of known events. It does not measure satisfaction for every unseen item because exposure is missing not at random: an unrated movie may be unknown rather than disliked.

Always compare with a popularity baseline. Also report catalog coverage, list concentration, novelty or diversity where defensible, and latency. A system can achieve plausible recall by recommending the same popular items to everyone. Production evaluation eventually needs user outcomes and guarded experiments, with explicit protections against feedback loops and harm.

Worked example: why missing does not mean negative

Suppose user A rated two science-fiction movies five stars and never rated a documentary. Encoding the missing documentary rating as zero asserts dislike, although the user may never have encountered it. A collaborative similarity calculation therefore operates on co-rated entries and records the overlap count. A ranking evaluation hides an observed event; it does not manufacture negative labels from every unobserved pair. This distinction is essential for both mathematics and data engineering.

21.9 Software design: from formula to package

The course implementation separates three public estimators:

- `KNearestNeighborsClassifier` stores feature rows and class labels, exposes neighbor indices and distances, and predicts normalized vote mass;
- `KNearestNeighborsRegressor` reuses search while enforcing finite numerical responses and local weighted averaging; and




Figure 21.3: Recommendation is an end-to-end data path. Each transition owns a contract: event provenance, missingness semantics, similarity support, seen-item exclusion, ranking, and operational evaluation.

- `ItemKNNRecommender` validates rating events, builds a sparse-in-meaning user-item matrix, fits item similarities, excludes seen items, and ranks supported unseen candidates.

Hyperparameters are constructor inputs. `fit` validates and stores learned state. `predict`, `similar_items`, and `recommend` refuse use before fitting. Input shape, finite-value policy, exact matches, tie ordering, unknown IDs, and duplicate events have explicit behavior. NumPy-style docstrings and type hints make the interface reviewable, while exceptions help users locate violated contracts.

The implementation deliberately uses readable brute-force NumPy. For n training rows and p features, storage is $O(np)$ and one query costs roughly $O(np)$ before selecting neighbors. A full item-item matrix for m items costs $O(m^2)$ storage. Larger systems consider sparse operations, tree indexes in favorable low dimension, or approximate nearest-neighbor methods. Approximation adds retrieval recall as another evaluated quantity.

21.9.1 Tests as executable mathematics

A serious test suite includes:

1. a 3–4–5 distance test;
2. hand-computable class votes and regression means;
3. properties such as nondecreasing returned distances and probability sums;
4. exact-match behavior under inverse-distance weighting;
5. invalid k, nonfinite input, shape mismatch, and pre-fit use;
6. differential agreement with a trusted library under matched conventions;
7. recommendation invariants, including no already-seen item; and
8. clean-kernel execution importing the installed package.

Tests protect public behavior, not private helper names. A useful failure tells a teammate which mathematical or user-facing contract changed.

21.10 The student project handoff

The companion project template supplies a working production shell. Students add scientific and product substance without collapsing everything into a notebook. For a nearest-neighbor contribution, the intended map is

```
data/local/your_dataset/                 ignored full or private data
data/fixtures/neighbors/                 small lawful CI fixture
docs/DATASET_CARD.md                     source, license, row meaning, limits
configs/student.toml                     ignored local paths and task config
scripts/fetch_or_validate_your_data.py   reproducible access and validation
src/dsm_project/algorithms/student/neighbors.py
src/dsm_project/algorithms/registry.py   explicit registration
tests/test_student_neighbors.py          executable contracts
notebooks/NN-your-question.ipynb         applied investigation and evidence
```

"Upload the data" is not an instruction to commit an arbitrary downloaded file. License, privacy, size, provenance, and reproducibility determine whether the repository contains a small fixture, a reviewed database snapshot, retrieval code plus a checksum, or metadata only. Full local data belongs under an ignored boundary when redistribution is not justified.

The notebook is named for its question, not merely `knn.ipynb`. It imports student package code, identifies the observation and prediction units, explores assumptions, compares a baseline, selects on validation evidence, analyzes failures, and states what can and cannot be concluded. It does not redefine the estimator, metric, or reusable evaluation function in hidden cells.

Worked example: a focused student pull request

A team investigates whether chemical measurements can retrieve wines with similar sensory profiles. They first open an issue defining the data license, observation unit, response, distance, scaling rule, split, baseline, and latency envelope. On a feature branch they add a validated data adapter, a tiny public fixture, a NumPy-style documented estimator, analytic and failure tests, registry entry, and question-led notebook. They run Ruff and pytest locally, push the branch, and open a pull request that links the issue and interprets the evidence. Review examines both scientific similarity and software behavior. Only reviewed package code becomes a candidate for product promotion.

21.11 Failure modes and operational evidence

Common symptoms have diagnostic meaning:

Majority predictions everywhere. k may be too large, class imbalance may dominate, or the representation may lack local signal.

Unit conversion changes results. Preprocessing is absent or not owned by the fitted pipeline.

Excellent validation, weak deployment. The split may not reproduce time, group, geography, or acquisition shift.

Fast fit, slow API. Exact search deferred computation to inference. Measure batch size and tail latency.

Empty recommendation lists. Co-rating overlap or positive similarity is insufficient. Define a safe fallback rather than lowering safeguards silently.

Same recommendations for everyone. Popularity dominates. Measure coverage and concentration beside recall.

A serialized kNN artifact may contain training features, labels, identifiers, or user histories. Artifact governance must address access, retention, deletion, encryption, provenance, and retraining. Monitoring can track query distance, empty-neighborhood rate, latency, feature-schema failures, catalog coverage, popularity concentration, and delayed outcomes. Logs should identify model and data versions without exposing sensitive raw records.

21.12 Exercises

Intuition and interpretation

1. Construct two changes of units that reverse the nearest of two points. State which units are scientifically defensible.
2. Explain why a five-of-seven class vote is not necessarily a calibrated probability of $5/7$.
3. Describe a setting where a farthest-neighbor diagnostic is more useful than the kNN prediction itself.
4. Explain why an unrated item is not a negative recommendation label.

Mathematics

5. For query $x = (1, 2)$ and training points $(0, 0)$, $(2, 2)$, $(4, 1)$, compute Euclidean and Manhattan neighbor orderings.
6. Derive the inverse-distance regression prediction for targets 0 and 4 at distances 1.5 and 0.5.
7. Prove that the uniform kNN class vote vector sums to one. State the assumption needed about k.
8. In your own words, explain why both $k_n \to \infty$ and $k_n/n \to 0$ are needed for consistency.
9. Show that multiplying every coordinate by the same positive constant preserves all Euclidean neighbor identities. Give a coordinate-wise scaling that does not.

Engineering and contribution

10. Add a test for conflicting labels at zero distance and propose a public policy before implementing it.
11. Benchmark prediction latency for batch sizes 1, 8, 64, and 256. Report median and tail behavior and identify the service implication.
12. Create a temporal recommender split and compare item kNN with a popularity baseline using recall@10 and catalog coverage.
13. In the project template, open an issue for a domain-aware distance. Specify units, invariances, missingness, scaling, analytic tests, and a trusted comparison. Implement it only after review of the contract.
14. Write a dataset-card section explaining whether full data, a CI fixture, retrieval code, or metadata may be committed. Support the decision with the source terms and privacy boundary.

Chapter review

Nearest neighbors turns similarity into a local prediction or retrieval rule. Classification votes, regression averages, and collaborative recommendation ranks supported unseen items. The apparent simplicity does not remove modeling or engineering decisions: representation, metric, scaling, k, weighting, validation, support, dimension, latency, storage, privacy, and update behavior all belong to the system contract. A professional implementation lives in a typed package, is protected by analytic and failure tests, is exercised through real-data notebooks, and enters a product only through reviewed evidence.

Executable companion

Lecture 13 notebook 00 derives neighbor geometry and the package API. Lecture 13 notebook 01 builds leakage-safe classification and regression pipelines on real wine-chemistry and diabetes-progression data. Lecture 13 notebook 02 uses authentic MovieLens events for collaborative recommendation and maps data, fixtures, code, tests, notebooks, and pull-request evidence into the companion student project template.

CHAPTER 22

Classification and regression trees

Learning objectives

After this chapter, you should be able to:

- interpret a tree as a recursive partition and a piecewise-constant prediction rule;
- derive classification impurity and regression squared-error reduction;
- explain greedy split search, structural constraints, and cost-complexity pruning;
- design leakage-safe classification and regression evaluations;
- audit instability, threshold, extrapolation, missingness, and interpretation failures; and
- separate an applied notebook from reusable package code and executable behavior contracts.

Where this chapter fits

Nearest neighbors let nearby observations vote or average. A decision tree learns the neighborhood itself: a sequence of binary questions creates axis-aligned regions, and each terminal region returns a class distribution or a response mean. This representation captures nonlinearities and interactions without feature scaling. Its greedy construction is also unstable. That instability motivates the ensembles in the next chapter.

22.1 From questions to a prediction function

An internal node asks whether feature x_j is at most threshold t. The answer routes an observation left or right. Repeating this operation partitions feature space into disjoint rectangular regions $R_1, \ldots, R_M$. The resulting predictor has the form

$$\widehat{f}(x) = \sum_{m=1}^{M} c_m \, \mathbf{1}\{x \in R_m\},$$

where c_m is a class decision, a class-probability vector, or a numerical response. The model is piecewise constant: inputs can move within a leaf without changing the prediction, then cross one threshold and jump abruptly.

Figure 22.1 shows how a root question and two child questions create four possible regions. The tree diagram and the feature-space partition are two views of the same mathematical object.

The representation is locally interpretable in a narrow sense. A root-to-leaf path exactly states which conditions in this fitted artifact produced an output. It does not identify a biological mechanism, a causal effect, or a stable population law.




Figure 22.1: Recursive binary questions create axis-aligned regions. The root split extends across the full domain; each child split applies only inside the region inherited from its parent.

22.2 Classification trees estimate local class distributions

Suppose node S contains n observations from K classes. Let n_k be the class-k count and $p_k = n_k/n$. Two common impurity measures are

$$G(S) = 1 - \sum_{k=1}^{K} p_k^2, \qquad H(S) = -\sum_{k:p_k>0} p_k \log_2 p_k.$$

Gini impurity is zero for a pure node and largest when class mass is evenly distributed. To see why it is meaningful, draw two labels Y and Y' independently from the node proportions. Then

$$\Pr(Y \neq Y') = 1 - \Pr(Y = Y') = 1 - \sum_k p_k^2 = G(S).$$

Gini impurity is therefore the probability of label disagreement under the node's empirical distribution. It is not the fraction currently misclassified.

Entropy is the expected surprise of a label:

$$H(S) = \mathbb{E}[-\log_2 p_Y].$$

An event assigned probability $1/2$ carries one bit of surprise; a rare event carries more. Entropy is zero when the next label is already known and is largest when the classes are equally plausible. For two classes with class-1 proportion p, Gini is $2p(1-p)$ and entropy is $-p\log_2 p - (1-p)\log_2(1-p)$. Both rise smoothly from zero to their maximum at $p = 1/2$.

A third quantity is majority-class error,

$$E(S) = 1 - \max_k p_k.$$

It answers how many node observations the majority prediction misses. It is less sensitive to changes in class composition, so Gini and entropy usually provide a stronger signal while searching for splits. These measures have different scales and meanings:

Measure	Interpretation	Role
Gini	probability that two node labels disagree	fast split-search criterion
Entropy	average label surprise in bits	information-gain criterion
Class error	error of the node's majority decision	intuitive leaf summary

None of these is a deployment loss. The cost of a false negative, delayed decision, or unnecessary intervention must be defined from the application.

A candidate question $x_j \le t$ divides the node into S_L and S_R. Its impurity reduction is

$$\Delta I = I(S) - \frac{|S_L|}{|S|} I(S_L) - \frac{|S_R|}{|S|} I(S_R).$$

The child terms must be weighted by child sample counts. Otherwise a tiny pure leaf and a large mixed leaf would receive the same influence, rewarding fragmentation for the wrong reason. More precisely, after applying the split, a uniformly sampled parent observation reaches the left child with probability $|S_L|/|S|$ and the right child with probability $|S_R|/|S|$. The weighted child expression is therefore the expected remaining impurity. The gain ΔI is the immediate uncertainty removed by asking the question.

Worked example: a hand-computable Gini split

A parent contains four observations from each of two classes, so its Gini impurity is $1-(1/2)^2-(1/2)^2 = 0.5$. A candidate split produces left counts $(4, 1)$ and right counts $(0, 3)$. The left impurity is $1-(4/5)^2-(1/5)^2 = 0.32$ and the right impurity is zero. Therefore

$$I_{\text{children}} = \frac{5}{8}(0.32) + \frac{3}{8}(0) = 0.20, \qquad \Delta I = 0.30.$$

This calculation is small enough to become an analytic unit test. A trusted implementation must agree before it is evaluated on hundreds of observations.

At a classification leaf, empirical probabilities are $\widehat{p}_k = n_k/n$. The class prediction usually selects the largest probability, but class ordering and tie policy are part of the interface. The decision threshold need not be the largest-probability rule when errors have different consequences. Small-leaf probabilities can also be poorly calibrated even when the class decisions are useful.

Concept check. A leaf contains one malignant and nine benign training observations. What probability vector does the tree return? What additional evidence would be required before treating that vector as a calibrated clinical probability?

22.3 Regression trees estimate local conditional means

For numerical responses in a node S, consider a constant prediction c. The within-node squared-error loss is

$$L_S(c) = \sum_{i \in S} (y_i - c)^2.$$

Theorem 22.1 (the leaf mean minimizes squared error)**.** *For a nonempty node S, the unique minimizer of $L_S(c)$ is the sample mean $\bar{y}_S$.*

Proof. Differentiate with respect to c:

$$\frac{d}{dc} L_S(c) = -2 \sum_{i \in S} (y_i - c) = -2 \sum_{i \in S} y_i + 2|S|c.$$

Setting the derivative to zero gives $c = |S|^{-1} \sum_{i \in S} y_i = \bar{y}_S$. The second derivative is $2|S| > 0$, so this stationary point is the unique minimum. □

Consequently a regression leaf returns a local target mean. A split is scored by squared-error reduction

$$\Delta\mathrm{SSE} = \mathrm{SSE}(S) - \mathrm{SSE}(S_L) - \mathrm{SSE}(S_R),$$

where $\mathrm{SSE}(A) = \sum_{i \in A} (y_i - \bar{y}_A)^2$. Maximizing this reduction is equivalent to minimizing total child SSE.

Regression impurity is often reported as

$$I_{\mathrm{MSE}}(S) = \frac{1}{|S|} \mathrm{SSE}(S).$$

It is the average squared distance from the node mean: unresolved response variation inside that region. Squaring prevents positive and negative residuals from canceling and penalizes large deviations strongly. It also selects the mean; absolute error would select a median instead. Thus the split criterion and leaf prediction must be designed together.

The meaning of SSE reduction follows from the variance decomposition

$$\begin{aligned} \mathrm{SSE}(S) = \mathrm{SSE}(S_L) + \mathrm{SSE}(S_R) \\ + |S_L|(\bar{y}_L - \bar{y}_S)^2 + |S_R|(\bar{y}_R - \bar{y}_S)^2. \end{aligned}$$

The first two terms are variation left within the children. The last two terms are variation explained by separating their means. Maximizing SSE reduction therefore searches for children whose responses are internally coherent and whose means differ. As in classification, adding child SSE is equivalent to weighting child MSE by child size; tiny leaves must not receive equal influence with large leaves.

Worked example: a regression stump

For ordered feature values $(1, 2, 3, 5, 8, 9)$ and responses $(2, 3, 2, 8, 9, 10)$, candidate thresholds are adjacent midpoints. The threshold 4 separates response means $7/3$ and 9. A depth-one regression tree returns those two constants. Its fit is nonlinear and discontinuous even though every leaf calculation is only an average.

Figure 22.2 makes the two prediction contracts explicit. An internal node stores a question and evidence about the observations reaching it. A classification leaf stores class counts and returns an empirical class distribution; a regression leaf stores a target mean. The arrows labeled "yes" implement $x_j \le t$, including equality, while "no" implements $x_j > t$.

The left panel of Figure 22.3 contrasts a smooth data-generating signal with a tree's step function. A tree cannot extrapolate a trend: outside the training range, it still returns one of its learned leaf means.




Figure 22.2: The anatomy of fitted classification and regression trees. The recursive question structure is shared, but node evidence and leaf prediction semantics differ. Each diagram describes one fitted artifact, not a causal mechanism.

22.4 Greedy growth is a computational compromise

Searching all possible tree structures is combinatorial. Standard algorithms therefore grow a tree greedily:

1. at the current node, sort each feature's observed values;
2. consider thresholds between distinct adjacent values;
3. compute the weighted classification impurity or regression SSE;
4. choose the feature-threshold pair with the largest immediate reduction;
5. partition the observations and recurse; and
6. stop when a declared structural or impurity condition is reached.

A locally best split need not appear in the globally best tree. Deterministic implementations must also define how equal gains, repeated feature values, and class ties are resolved. Those choices can change structure without materially changing aggregate performance.

Depth, minimum samples per split, minimum samples per leaf, maximum leaf count, and minimum impurity decrease constrain growth. These are statistical regularizers as well as software parameters. A leaf with one regression target has zero training impurity but is usually a high-variance estimate of its region's conditional mean.

22.5 Pruning trades fit for structural complexity

An alternative strategy grows a larger tree and prunes it. Cost-complexity pruning studies

$$R_\alpha(T) = R(T) + \alpha|\widetilde{T}|,$$

where $R(T)$ is the sum of terminal-node losses and $|\widetilde{T}|$ is the number of leaves. Larger α favors smaller trees. Weakest-link pruning produces a nested sequence of candidate subtrees rather than searching every possible subtree independently.

The pruning path is estimated from training data. The value of α is a hyperparameter and belongs to the validation boundary. Choosing the tree with the smallest test error leaks final evidence into model selection.




Figure 22.3: Left: a regression tree approximates a smooth relationship with local constants. Right: training error usually decreases as leaves are added, while validation error can reach a minimum and then rise. The curves are schematic; a real report includes resampling uncertainty.

The right panel of Figure 22.3 illustrates the bias-variance tradeoff. A one-standard-error rule can prefer a smaller tree whose validation estimate is statistically indistinguishable from the observed minimum. Simplicity is not automatically correctness, but unnecessary leaves increase variance, operational surface area, and explanation burden.

22.6 Classification evidence is decision evidence

The Wisconsin Diagnostic Breast Cancer laboratory uses a versioned SQL table rather than a hidden loader call. Before fitting, the analysis verifies the observational unit, target encoding, missingness, duplicate identity, class support, and feature ranges. The target contract explicitly records that zero means malignant and one means benign.

Training observations estimate thresholds and leaf proportions. Validation observations choose criterion, depth, leaf size, and pruning. Test observations are evaluated once after these choices are frozen. Stratification preserves class support, but a random split remains an assumption about exchangeability. Patient, site, batch, or temporal dependence would require grouped or temporal validation instead.

A professional classification report includes a dummy baseline, class support, balanced accuracy, class-specific precision and recall, a confusion matrix, and a probability metric when probabilities are claimed. False negatives and false positives must be interpreted in the problem's encoding and decision context. The instructional analysis is not evidence of clinical utility.

Common misconception

Misconception: a shallow classification tree is objective because its questions can be read. **Correction:** feature construction, target encoding, missingness policy, class support, split criterion, validation design, pruning, and decision threshold all encode choices. Readability does not establish stability, fairness, calibration, or causality.

22.7 Regression evidence includes residual structure

The diabetes-progression laboratory compares the fitted tree with a mean baseline. Mean absolute error measures a typical absolute miss in target units; root mean squared error emphasizes large misses. Scalar metrics are followed by predicted-versus-observed and residual-versus-predicted plots. Residual pattern, heteroscedasticity, and extreme errors can reveal failures hidden by an average.

The dataset contains ten baseline variables and a response measured one year later, but several feature meanings are incompletely documented. This limits scientific interpretation. A random split is used as an instructional baseline because no grouping or time variable is supplied; a serious clinical study would need a validation design aligned with collection sites, patient dependence, and intended deployment.

Tree-specific regression checks include:

- comparing the prediction range with the observed training response range to expose non-extrapolation;
- inspecting leaf sample counts and target dispersion;
- evaluating inputs immediately below, equal to, and above important thresholds;
- refitting across resamples to measure root-variable and threshold instability; and
- monitoring reached-leaf frequencies after release.

22.8 Instability is a defining property

A small perturbation can change an early split and therefore the entire downstream partition. Two trees can have similar predictive performance and very different structures. Bootstrap refits can compare prediction variation, root-feature frequency, threshold dispersion, and subgroup error. A displayed tree is an exact account of one artifact, not necessarily a stable account of the population.

Feature importance needs the same restraint. Impurity importance allocates training impurity reduction to split variables. It can favor variables with many candidate thresholds and distribute credit unreliably among correlated features. Held-out permutation importance asks how prediction deteriorates under a particular perturbation; dependent features can make that perturbation unrealistic. Every interpretation must name the model, population, perturbation, and uncertainty.

Concept check. Two bootstrap trees achieve nearly identical validation RMSE but choose different root features. Which claim about predictive performance may still be supported, and which structural interpretation has become weaker?

22.9 Thresholds, missingness, and schema are contracts

The conventional numerical rule routes equality left: $x_j \le t$. A boundary test should include nextafter$(t, -\infty)$, t, and nextafter$(t, +\infty)$. Unit conversion, rounding, or feature reordering can otherwise change paths silently.

Missingness requires a declared policy: reject, impute inside the fitted pipeline, learn a default direction, or use a native missing-value mechanism. Missingness may encode collection behavior that changes after deployment. Categorical variables likewise need a stable vocabulary and unknown-category policy.

Professional practice

Export the exact feature names and order, units, preprocessing, class ordering, missing-value policy, library and artifact versions, and decision policy with a tree. At every release, run analytic split tests, fit-before-predict and invalid input tests, threshold boundary tests, golden prediction tests, and a trusted-library differential check on a fixed fixture.

22.10 From notebook experiment to maintained package

The course implementation places impurity functions, node representation, classifier, regressor, rule export, tree visualization, and pruning behavior in `src/rice_dsm/ml/trees.py`. The notebooks import that implementation; they do not maintain private copies. Tests specify hand-computable impurities, split thresholds, equality routing, probability ordering, local means, pruning, invalid inputs, and reference-library agreement.

The companion student project follows the same boundary:

- `src/dsm_project/algorithms/student/trees.py` contains the reusable estimator;
- `tests/test_student_trees.py` contains analytic, failure, boundary, and differential contracts;
- `data/local/` contains private or large data that cannot be committed;
- `data/fixtures/` contains a small lawful CI fixture; and
- a question-led notebook imports the package and presents data, validation, evidence, and limitations.

Begin from a clean `main` branch in the companion template at https://github.com/RandyRDavila/Data-Science-Machine-Learning-Project-Template:

```
git switch main
git pull --ff-only
git switch -c YOUR-GITHUB-USERNAME/decision-trees
uv sync --locked
```

The implementation sequence is issue first, test first, then analysis:

1. open an issue defining the observation, target, split policy, baseline, data license, and intended decision;
2. write hand-computable impurity, leaf-prediction, and threshold-boundary tests;
3. implement one public behavior at a time under `src/` and register it explicitly;
4. put only lawful, small CI data under `data/fixtures/`;
5. write a self-contained applied notebook that imports the package; and
6. run the complete quality gate before opening a pull request.

```
uv run ruff check src tests scripts
uv run pytest -q
git status --short
git add src tests notebooks docs data/fixtures
git commit -m "Add decision-tree case study"
git push -u origin YOUR-GITHUB-USERNAME/decision-trees
```

The minimum analytic test suite checks Gini and entropy on known class counts, the regression leaf mean, a hand-computable best threshold, equality routing to the left child, class-probability ordering, no-extrapolation behavior, invalid inputs, prediction before fitting, and agreement with a trusted implementation under a fixed configuration. Notebook execution in a clean kernel is an integration test; it is not a substitute for the smaller mathematical tests.

The pull request records the issue, dataset provenance and license, observational unit, target timing, split policy, baseline, selected metrics, tests, limitations, and one investigated failure. This is the difference between demonstrating an algorithm and maintaining a reviewable data-science artifact.

Worked example: a brittle degradation rule

A depth-three regression tree places resistance change at its root and performs well on a held-out random split. When evaluation instead holds out later manufacturing batches, performance falls. Repeated fits also move the root threshold substantially.
Investigation shows that instrument calibration changed between batches. The tree learned a separator tied to measurement context. The team retains it as a baseline, documents threshold instability, adds batch-aware validation, and rejects causal language about resistance. The failure provides useful evidence about the data-generating system.

22.11 Operational evidence after release

Before outcomes arrive, monitor schema violations, missingness, feature ranges, category novelty, reached-leaf distribution, prediction distribution, and latency. A sudden shift into rarely visited leaves can signal acquisition or population change. After delayed outcomes arrive, join them to identified predictions and recompute

class-conditional errors or residual metrics by time, site, and relevant subgroup.

Logs must identify model version, schema version, request or batch identity, decision policy, and failure category without exposing prohibited sensitive data. Alerts require a governed response: investigate, mitigate, roll back, retrain, or document why no action is warranted. Monitoring does not repair a model; it creates evidence for a decision.

22.12 Exercises

1. Compute Gini impurity and entropy for class counts $(6, 2, 2)$. Then compute weighted impurity after a proposed split and state whether impurity decreases.
2. Prove the leaf-mean theorem by completing the square rather than using derivatives.
3. Enumerate every midpoint threshold for feature values $(1, 2, 4, 7)$ and responses $(1, 2, 8, 9)$. Identify the regression-stump split.
4. Construct a classification example where an unweighted average of child impurities ranks two splits incorrectly.
5. Explain why strictly increasing feature rescaling preserves candidate partitions but does not prevent preprocessing leakage.
6. Design threshold tests at $t = 0.2$ for equality, adjacent floating-point values, missing input, infinity, and a unit-converted input.
7. Compare two bootstrap trees. Report predictive agreement, root-feature frequency, threshold dispersion, and one interpretation that is no longer defensible.
8. Design a validation protocol for repeated measurements from patients collected at four hospitals over three years.
9. Add a classification-tree module and analytic test to the companion project. Document class ordering and tie behavior in its NumPy-style docstring.
10. Add a regression-tree analysis on a real dataset. Include a baseline, residual plot, pruning evidence, extrapolation test, and dataset card.
11. Propose a production monitoring panel separating label-free signals from metrics that require delayed outcomes.
12. Review a peer pull request for duplicated notebook logic, test leakage, unstable feature order, and unsupported causal language.

Chapter review

Classification and regression trees construct piecewise-constant predictions through greedy recursive partitioning. Classification splits reduce weighted class impurity; regression splits reduce within-leaf squared error, whose optimal constant is the leaf mean. Depth, leaf size, impurity constraints, and cost-complexity pruning regularize the model. Trees capture nonlinear interactions naturally, but they are discontinuous, non-extrapolating, and often unstable. Their paths describe one fitted artifact within a declared schema and validation design; they do not establish causality. Professional work places reusable code and tests in a package, uses notebooks for evidence, and monitors the released artifact with explicit operational contracts.

Executable companion

Lecture 14 notebook 00 develops classification trees from Gini and entropy calculations through clinical decision evidence, pruning, stability, threshold tests, and project packaging. Lecture 14 notebook 01

derives regression-tree local means and develops residual, pruning, discontinuity, extrapolation, stability, interpretation, and monitoring evidence.

CHAPTER 23

Ensemble learning: forests, boosting, and model combination

Learning objectives

After this chapter, you should be able to:

- distinguish bagging, random forests, extra trees, boosting, voting, and stacking by the mechanism that creates and combines learners;
- derive the variance of an average under correlated member errors and explain why diversity matters;
- derive squared-error gradient boosting as stagewise residual fitting;
- construct out-of-fold features for leakage-safe stacking;
- evaluate discrimination, probability quality, stability, interpretation, and resource cost; and
- design reusable ensemble code, behavior tests, and a defensible champion–challenger promotion gate.

Where this chapter fits

A decision tree learns nonlinear interactions and an interpretable partition, but small changes in its training observations can produce different early splits and a different tree. Ensemble learning turns variation among fitted learners into a design variable. Bagging and random forests average perturbed learners to reduce variance. Boosting constructs a sequence of corrections to reduce loss. Voting and stacking combine heterogeneous inductive biases. These mechanisms share multiple members, but not the same mathematics, data flow, or failure modes.

23.1 The organizing question: where does useful diversity come from?

An ensemble produces a prediction from member functions $F_1, \ldots, F_M$. Its benefit cannot follow from member count alone. If every member makes the same error, repeating it changes nothing. If members are independent but useless, their average remains useless. A successful ensemble requires two properties:

1. *competence*: members carry information about the target; and
2. *diversity*: members do not reproduce exactly the same error.

Different methods create diversity differently. Bagging perturbs observations. Random forests perturb observations and candidate features. Extra trees also randomize thresholds. Boosting changes the pseudo-response or example weights at every stage. Voting and stacking combine model families with different representations. Evaluation must identify which mechanism is being used rather than calling all of them "many models."

Historically, ensemble learning joins ideas from statistics, computational learning theory, and numerical optimization. Breiman introduced bootstrap aggregating, or *bagging*, in 1996 and random forests in 2001. Ho developed random-subspace methods in the 1990s. Schapire showed that weak learnability can imply strong learnability; Freund and Schapire's AdaBoost made sequential reweighting practical. Friedman later formulated

gradient boosting as optimization over functions. Wolpert's stacked generalization combines heterogeneous models using a learned second level. The chronology matters because these algorithms solve different problems, not because newer always means better.

23.2 Why averaging can reduce variance

Let $E_m = F_m(X) - Y$ denote member m's prediction error. Suppose, as a simplifying model, that

$$\operatorname{Var}(E_m) = \sigma^2, \qquad \operatorname{Corr}(E_m, E_\ell) = \rho \quad (m \neq \ell).$$

Theorem 23.1 (variance of an equally weighted correlated ensemble)**.** *Under the equal-variance, equal-correlation assumptions above, the error* $\overline{E} = M^{-1}\sum_{m=1}^{M} E_m$ *satisfies*

$$\operatorname{Var}(\overline{E}) = \rho\sigma^2 + \frac{1-\rho}{M}\sigma^2.$$

Proof. Variance is bilinear in covariance, so

$$\begin{aligned}\operatorname{Var}(\overline{E}) &= \frac{1}{M^2}\sum_{m=1}^{M}\sum_{\ell=1}^{M}\operatorname{Cov}(E_m, E_\ell)\\ &= \frac{1}{M^2}\left(M\sigma^2 + M(M-1)\rho\sigma^2\right)\\ &= \frac{\sigma^2}{M} + \frac{M-1}{M}\rho\sigma^2 = \rho\sigma^2 + \frac{1-\rho}{M}\sigma^2.\end{aligned}$$

The first sum contains M diagonal variances; the second contains $M(M-1)$ ordered off-diagonal covariances. □

The independent component shrinks like $1/M$. The shared component approaches $\rho\sigma^2$ and remains no matter how many members are added. Figure 23.1 shows this correlation floor. When $\rho = 0$, variance approaches zero in this simplified model. When $\rho = 1$, averaging does not reduce variance at all.

The theorem is a model, not a guarantee. Real members can have different variances, correlations, and biases. Averaging primarily targets variance; it does not automatically remove shared bias or data leakage.

Common misconception

Misconception: any diverse collection improves prediction. **Correction:** deliberately bad members can be diverse and still damage an ensemble. Diversity is useful only together with competence, and the gain must survive held-out evaluation under the intended dependence structure.

Concept check. Two ensembles contain equally accurate members. The first has pairwise error correlation 0.15 and the second 0.80. Under the theorem's assumptions, which has the lower limiting variance as $M \to \infty$, and what does that say about adding more nearly identical members?

23.3 Bootstrap sampling and bagging

Given observations indexed by $1, \ldots, n$, a bootstrap sample draws n indices independently and uniformly *with replacement*. Repeated and omitted observations are expected. For any row i,

$$\Pr(i \text{ is omitted}) = \left(1 - \frac{1}{n}\right)^n \longrightarrow e^{-1} \approx 0.368.$$




Figure 23.1: Relative variance of an equally weighted ensemble under the equal-correlation model. Member count suppresses independent variation but cannot remove error shared by all members.

Thus a large bootstrap sample contains approximately 63.2%, or $1 - e^{-1} \approx 0.632$, of the distinct training observations.

Bagging fits a base learner F_m to each bootstrap sample and aggregates. For regression,

$$\widehat{F}_{\mathrm{bag}}(x) = \frac{1}{M} \sum_{m=1}^{M} F_m(x).$$

For classification, members may vote on labels or, preferably when available, average aligned class probabilities. Deep trees are natural members because they are competent and unstable: bootstrap perturbation produces meaningfully different partitions, while averaging suppresses some of that variation.

The bootstrap creates no new scientific information. It approximates repeated sampling from the empirical distribution and perturbs the fitted algorithm. If rows are clustered by patient, site, instrument, or time, ordinary row bootstrap sampling may destroy the dependence structure. The resampling unit must match the population and deployment question.

23.3.1 Out-of-bag evidence

Observation i is *out of bag* for member m when the mth bootstrap sample omitted it. An OOB prediction for i aggregates only members that did not train on i:

$$\widehat{F}_{\mathrm{OOB}}(x_i) = \frac{1}{|\mathcal{M}_i|} \sum_{m \in \mathcal{M}_i} F_m(x_i), \qquad \mathcal{M}_i = \{m : i \text{ is OOB for } m\}.$$

This provides economical internal evidence for debugging and rough selection. It does not replace a final audit, repair grouped or temporal leakage, or simulate a future population shift.

Worked example: why an unstable tree can benefit from bagging

Suppose two nearly tied root splits exist. A few changed rows make a single tree choose one or the other, producing large downstream differences. Across bootstrap samples both structures appear. If their held-out errors are not perfectly aligned, probability averaging can be more stable than either structure. A shallow, highly constrained tree may vary less and therefore gain less from bagging. The observation "bagging helps unstable learners" follows from a mechanism that can be measured, not from a model-name rule.

23.4 Random forests: decorrelate the trees

A random forest adds feature randomization to bootstrap aggregation. At each split, a tree considers only a random subset of the p predictors. A common classification default is roughly $\sqrt{p}$ candidate features, but the value is a hyperparameter, not a law.

If one strong predictor is available to every split, many bagged trees may ask the same root question and remain highly correlated. Feature subsampling forces some trees to discover alternative predictive structure. This can weaken an individual tree while improving the average by reducing member-error correlation. Figure 23.2 separates row perturbation, feature perturbation, and aggregation.




Figure 23.2: A random forest draws bootstrap rows, grows trees with random candidate features at their splits, and averages aligned class probabilities. Rows omitted from a member's draw support OOB evidence.

Extremely randomized trees, or extra trees, inject additional randomness into candidate thresholds and may use the full sample rather than bootstrap rows. They can reduce correlation and computation while increasing bias. The proper question is not which name sounds most advanced, but how bias, variance, stability, probability quality, and resource cost change under a frozen evaluation design.

More trees usually stabilize a forest average rather than overfit in the same way as increasing single-tree depth. Nevertheless, depth, leaf size, feature sampling, class weighting, bootstrap policy, and threshold choice still change the learned function. Member count also increases fit cost, artifact size, memory, and inference work.

23.4.1 Probability aggregation is an interface contract

For classes $C = (c_1, \dots, c_K)$, let member m return $p_{mk}(x)$. The forest probability is

$$\overline{p}_k(x) = \frac{1}{M} \sum_{m=1}^{M} p_{mk}(x).$$

Every vector must use the same class order. A bootstrap member may observe no examples of a rare class; implementation code must insert a zero column in the correct location rather than silently shifting columns. Tests should assert shape, class order, finite values, range, and row sums.

The class decision $\arg\max_k \overline{p}_k(x)$ is separate from probability quality. For a binary task, ROC AUC evaluates ranking; log loss and Brier score evaluate probabilities; a decision threshold encodes consequences. A forest can rank well and still be poorly calibrated.

23.4.2 Feature importance does not identify scientific mechanism

Mean decrease in impurity accumulates split improvements attributed to each feature. It is fast but can favor variables with many candidate thresholds and divide credit unpredictably among correlated predictors. Permutation importance measures held-out degradation after shuffling a feature under a specified perturbation. Correlated substitutes can conceal one another, and unrealistic permutations can leave the data manifold. Neither method turns association into causation.

Interpretation should therefore be scoped: "this fitted artifact relied on this feature under this perturbation and evaluation distribution." Stability across folds, seeds, batches, and plausible perturbations is useful evidence.

23.5 Boosting builds an additive model sequentially

Bagging members can be fitted independently. Boosting constructs a sequence:

$$F_M(x) = F_0(x) + \sum_{m=1}^{M} \nu h_m(x),$$

where h_m is usually a shallow tree and $0 < \nu \leq 1$ is a learning rate or *shrinkage*. Each stage depends on the current model. Parallelizing this dependency is fundamentally different from parallelizing a forest.

For empirical risk

$$\mathcal{R}(F) = \frac{1}{n} \sum_{i=1}^{n} L(y_i, F(x_i)),$$

define the negative gradient at stage m by

$$r_{im} = - \left. \frac{\partial L(y_i, f)}{\partial f} \right|_{f = F_{m-1}(x_i)}.$$

The base learner is fitted so that $h_m(x_i) \approx r_{im}$, and the model updates to $F_m = F_{m-1} + \nu h_m$. This is gradient descent in a space of functions, restricted to directions representable by the base learner.

Theorem 23.2 (squared-error boosting fits residuals)**.** *For half squared-error loss $L(y, f) = \frac{1}{2}(y - f)^2$, the negative gradient with respect to the prediction f is the residual $y - f$.*

Proof. Differentiation gives

$$\frac{\partial}{\partial f}\frac{1}{2}(y - f)^2 = f - y.$$

Negating this derivative gives $y - f$. Evaluating at $f = F_{m-1}(x_i)$ yields $r_{im} = y_i - F_{m-1}(x_i)$. □

The best constant initializer for squared error is the training-target mean. The first tree fits residuals from that mean; the next fits residuals from the updated additive model. Figure 23.3 depicts successive corrections.




Figure 23.3: A boosted model begins with a simple function and adds restricted learners toward current negative gradients. The shaded discrepancy changes after every stage.

23.5.1 Classification gradients

For a binary logit F, probability $p = \sigma(F)$, and cross-entropy

$$L(y, F) = \log(1 + e^F) - yF,$$

the derivative is $p - y$, so the negative gradient is $y - p$. Each new learner approximates a correction related to probability residuals. Numerical implementations also optimize leaf values and apply regularization; the phrase "fit residuals" must always be interpreted relative to the chosen loss.

AdaBoost follows a related but distinct route. With labels and weak predictions in $\{-1, +1\}$, weighted error is

$$\epsilon_m = \sum_i w_i \mathbf{1}\{y_i \neq h_m(x_i)\}.$$

When $\epsilon_m < 1/2$, define

$$\alpha_m = \frac{1}{2}\log\frac{1 - \epsilon_m}{\epsilon_m}, \qquad w_i \leftarrow \frac{w_i \exp(-\alpha_m y_i h_m(x_i))}{Z_m}.$$

Misclassified observations gain relative weight. The final score is a weighted vote. Hard or mislabeled observations can consequently receive increasing attention, making data auditing essential.

23.5.2 Shrinkage, depth, and stopping

Learning rate and stage count interact. Small ν takes conservative steps and generally requires more stages. It is not free regularization: additional stages increase fit time, prediction time, and artifact size. Tree depth controls the interaction order available in one correction. Stumps represent main effects; deeper trees represent higher-order interactions but can chase noise more readily.

Early stopping monitors a validation trace and halts after improvement ceases. The monitoring data must remain inside the training boundary. If final test data determine the stopping stage, they are no longer an honest final audit. Nested selection may be required when comparing many losses, depths, learning rates, and stage budgets.

Histogram-based implementations bin feature values to accelerate split search. XGBoost, LightGBM, CatBoost, and scikit-learn's histogram estimators differ in category handling, missing-value routing, regularization, distributed or GPU execution, determinism, and serialization. A library is a versioned dependency with a behavioral contract, not merely an import.

Worked example: a regression booster as an auditable sequence

Begin with $F_0 = \overline{y}$. Store the stage-one residuals, fitted tree, and updated predictions. Repeat while recording training and validation loss after each stage. A behavior test uses a hand-computable piecewise-constant target and verifies the initializer, staged prediction count, and decreasing training loss. A production comparison then checks a trusted histogram booster on the same split. This separates mechanism verification from optimized implementation evaluation.

Concept check. Why can adding more trees to a random forest and adding more stages to a boosted ensemble have different overfitting behavior? Identify the parallel averaging mechanism in the first and the adaptive optimization path in the second.

23.6 Leakage-safe out-of-fold stacking and voting

Hard voting returns the modal class label and discards confidence. Soft voting averages class probabilities, optionally with validation-selected weights. Soft voting requires aligned class orders and probabilities whose calibration is sufficiently comparable. A confidently wrong member can dominate an unweighted mean.

Stacking learns a meta-model from base-model outputs. The tempting procedure fits each base learner on all training rows, predicts those same rows, and fits the meta-model on the resulting predictions. Those in-sample predictions are optimistically biased: the meta-model learns from information unavailable at future inference.

Correct stacking constructs out-of-fold (OOF) features. Partition training rows into folds. For each fold, fit base models on the remaining folds and predict the reserved fold. Every training row's meta-features then come from base models that did not train on that row. Refit base models on all training data only after the meta-model has been trained. Figure 23.4 contrasts the two data flows.

If there are B base learners and K classes, raw probability meta-features have BK columns. Every block should be finite, lie in $[0, 1]$, sum to one, and follow a tested class order. Preprocessing must be fitted inside every base fold. The folds must also preserve groups, time, or other dependence from the original problem.




Figure 23.4: In-sample base predictions leak fitted-row performance into the meta-model. Out-of-fold construction preserves a training-row information boundary: each row is predicted by a base model that did not fit it.

Failure mode

Out-of-fold does not automatically mean leakage-safe. Shuffled row folds remain wrong when multiple rows describe the same patient, when future observations predict the past, or when preprocessing was fitted globally. The stacking split must inherit the original information and dependence boundaries at every level.

23.7 Evaluation is a systems comparison

An ensemble may improve one predictive metric while harming probability quality, class-specific performance, latency, memory, energy, portability, or maintainability. Compare candidates under a common evidence contract:

Evidence family	Questions
Predictive	Which loss and metrics match the decision? What is uncertainty in the difference?
Probability	Are probabilities calibrated overall and where decisions are made? Are class orders and thresholds correct?
Stability	Do conclusions survive seeds, folds, batches, subgroups, and plausible perturbations?
Operational	What are fit cost, batch throughput, tail latency, memory, serialized size, and energy where material?
Governance	Can the complete artifact be rebuilt, tested, owned, monitored, rolled back, and explained at an appropriate scope?

The *champion* is the approved artifact currently serving the contract. A *challenger* is evaluated under the same

split, preprocessing, metrics, calibration procedure, and resource budget. Promotion should require a practically meaningful gain and no unacceptable regression, not merely the largest point estimate among many trials.

Worked example: forest and boosting challengers

For future-batch degradation prediction, a calibrated logistic champion is compared with a random forest and a histogram gradient booster. Hyperparameters and early stopping use earlier batches only. The final batch is audited once.

The booster improves average precision but overstates event probability. A calibrator is fitted without touching the final batch. The promotion report compares decision cost, calibration, batch uncertainty, artifact size, and prediction latency. Promotion is withheld when the gain disappears on the newest batch. That is a successful evaluation: it prevented unjustified system complexity.

23.8 Software engineering contracts for ensembles

Reusable code belongs in a module, not duplicated across notebooks. An inspectable forest should expose fitted members, bootstrap indices, seeds, OOB counts and probabilities, classes, feature count, and importances. An inspectable booster should expose the initializer, ordered stage learners, learning rate, staged predictions, and loss trace.

Tests should include:

- hand-computable bootstrap and additive-update examples;
- deterministic reconstruction under a fixed seed;
- probability shape, range, class order, and row sums;
- OOB coverage and exclusion of in-bag predictions;
- initializer and staged-loss behavior for squared-error boosting;
- prediction-before-fit, dimensional mismatch, nonfinite data, and invalid hyperparameters;
- differential checks against a trusted library on unambiguous fixtures;
- serialization, schema, and supported-runtime smoke tests; and
- an explicit test that rejects leaky stacking features.

CI uses small lawful fixtures. Full student-supplied data belongs outside Git when license, privacy, or size demands it; provenance, schema, checksum, and retrieval instructions remain versioned. Applied notebooks import the package, state a question, and present evidence. They are not a second implementation of the algorithm.

Common misconception

Misconception: the most accurate ensemble is the most professional model. **Correction:** professional quality is conditional on the system contract. A smaller calibrated model may be superior when the ensemble's point gain is unstable, operationally expensive, difficult to monitor, or unsupported in the deployment runtime.

23.9 Exercises

1. Derive the equal-correlation variance theorem without assuming equal means. State why means do not enter the variance calculation.

2. For $n = 5$, compute the exact probability that a specified observation is OOB from a size-five bootstrap sample. Compare it with e^{-1}.
3. Design an experiment that separates member competence from member-error correlation for bagging and random forests.
4. Prove that the mean is the constant minimizing squared-error loss and connect this result to the gradient booster's initializer.
5. Derive the negative gradient of binary cross-entropy written as $\log(1 + e^F) - yF$.
6. Explain why learning rate, stage count, and tree depth cannot be tuned independently of the validation design.
7. Draw the data flow for five-fold stacking with three base learners and three classes. Label every fit and prediction boundary.
8. Construct a test that fails for in-sample stacking features but passes for correct OOF features.
9. Compare impurity and permutation importance under two strongly correlated predictors. Explain why disagreement need not be a bug.
10. Write a champion–challenger gate covering predictive quality, calibration, class-specific regressions, artifact size, latency, and deterministic rebuild.
11. In the companion student project, contribute one ensemble component with package code, analytic and failure tests, a lawful CI fixture, and a question-led notebook using student-supplied data. Your pull request must explain added operational cost and one reason not to promote the model.

Chapter review

Ensembles improve learning through structured diversity, not member count alone. Bagging perturbs observations and averages unstable learners. Random forests also randomize candidate features to lower member correlation; OOB predictions provide useful internal evidence with important limits. Boosting constructs an additive sequence guided by negative loss gradients; for squared error, those gradients are residuals. Voting combines decisions or probabilities, while stacking requires out-of-fold meta-features and tested class alignment. Any predictive gain must survive probability, dependence, stability, interpretation, software, and resource evidence before promotion.

Executable companion

Lecture 15 notebook 00 derives bagging and random forests on the Wisconsin Diagnostic Breast Cancer data. Lecture 15 notebook 01 derives residual and gradient boosting on diabetes-progression data and compares production estimators. Lecture 15 notebook 02 constructs leakage-safe voting and stacking on UCI Wine data and closes with a champion–challenger promotion gate. Each laboratory includes the exact companion-project code, test, data, and pull- request boundary.

CHAPTER 24

Model selection and honest evaluation

Learning objectives

After this chapter, you should be able to:
- state what an evaluation design estimates;
- use cross-validation without crossing preprocessing or dependence boundaries;
- separate model selection from final performance estimation; and
- make a promotion decision with uncertainty and error analysis.

Where this chapter fits

Part II has introduced several plausible learners. Choosing among them is itself an adaptive statistical procedure. This chapter treats the evaluation protocol as an estimator and the promotion decision as a versioned result, not as a contest for the largest displayed score.

24.1 Name the estimand before the splitter

An evaluation score estimates performance under a hypothetical repetition. In ordinary K-fold cross-validation, rows are partitioned into folds; each fold is predicted by a model trained on the others. The resulting estimate concerns training sets somewhat smaller than the full sample and a population represented by the fold construction.

Grouped folds estimate transfer to held-out groups. Forward or rolling temporal splits estimate transfer from past training windows to later periods. Spatial or domain splits can estimate transfer across sites. A convenient splitter cannot repair an unclear deployment claim.

24.2 A pipeline owns every fitted transformation

Within each fold, fit imputation, scaling, category handling, feature selection, dimensionality reduction, calibration, and the predictor using only the fold's training portion. Apply the fitted sequence to its validation portion. A pipeline makes this boundary executable and ensures that the same transformations travel with the final artifact.

Static operations that use no sample information can be defined outside, but their schemas and versions still belong to the contract. The test is not whether an operation is called "preprocessing"; it is whether it learns from observations.

24.3 Selection creates optimism

Suppose many noisy performance estimates are compared and the largest is reported. Even when every estimate is individually unbiased, the maximum tends to be optimistic. Hyperparameter search, feature choice, threshold selection, and repeated manual notebook experiments all consume validation information.

Nested evaluation separates these roles. Inner folds choose the candidate; outer folds estimate the entire selection procedure on observations hidden from that choice. A final locked test set can provide a single additional estimate after development stops. It must not become a repeatedly queried leaderboard.

Concept check. If the test set influences one feature choice, what has become the new test set, and what evidence has been lost?

24.4 Search should express prior structure and budget

A grid is useful for a small structured set. Random search often covers high-dimensional spaces more efficiently when only some dimensions matter. Adaptive search uses prior trials to choose later trials and must be included in the selection boundary.

Search ranges should be expressed on natural scales, such as logarithmic ranges for regularization strengths. Invalid combinations should be excluded by construction. Record every trial, seed, split identifier, duration, failure, metric, and artifact reference. A failed run is data about the process, not a row to delete silently.

Professional practice

Specify a compute budget and stopping rule before search. Reproducibility means another run can reconstruct data, folds, code, configuration, and selection logic; it does not require pretending that parallel floating-point execution is bitwise identical on every device.

24.5 Uncertainty and dependence

Fold scores are not independent replicates because training sets overlap. Reporting their standard deviation as if it were a simple standard error can be misleading. Bootstrap methods must resample at the independent unit: cell, patient, site, or time block rather than row when dependence lives at that level.

Uncertainty should match the decision. A confidence interval for mean loss does not bound every subgroup or future shift. Report point estimates alongside sample counts, variation by relevant group or period, and sensitivity to design choices. Practical equivalence may matter more than a tiny nominal difference.

24.6 Error analysis is structured, not anecdotal

After obtaining held-out predictions, stratify errors by target range, feature support, group, time, missingness, and operational context. Inspect examples to form hypotheses, then test those hypotheses on data not used to invent them when possible. Do not remove inconvenient cases without a protocol.

Learning curves compare performance as training size grows. A persistent gap between training and validation behavior suggests variance or shift; uniformly poor behavior suggests limited signal, representation, or

misspecification. These are diagnostic patterns, not universal proofs.

Common misconception

Misconception: cross-validation eliminates overfitting. **Correction:** it estimates a procedure under its split assumptions. Repeatedly adapting to its results can overfit the validation process, and an inappropriate fold structure can estimate the wrong use setting precisely.

Worked example: a promotion decision, not a leaderboard

Four candidate families are evaluated for capacity regression. Inner grouped temporal folds choose transformations and hyperparameters. Outer future-batch folds estimate the complete choice procedure. The ensemble has the lowest mean error, but the interval overlaps the ridge model and its tail latency exceeds the batch-service budget.

The evaluation report promotes ridge because it beats the baseline by the prespecified practical margin, satisfies batch-level regression limits, and has stable resource use. The ensemble remains a challenger. The report includes split hashes, data and code versions, candidate search spaces, all failed trials, and a signed decision rationale.

24.7 Exercises

1. Design splits for unseen cells, future batches, and a new laboratory. State the estimand for each.
2. Draw nested cross-validation including preprocessing and threshold selection.
3. Explain why trial deletion and repeated seed selection can bias a report.
4. Write promotion criteria containing a baseline margin, uncertainty, subgroup limits, latency, artifact size, and rollback readiness.

Chapter review

Evaluation estimates a named future use under a split design. Pipelines preserve fold boundaries for every learned transformation. Selection creates optimism, so nested or locked evaluation must separate choosing from estimating. Search has a budget and provenance; uncertainty respects independent units; and a promotion gate combines predictive, subgroup, and operational evidence.

Executable companion

Lecture 16 notebook 00 treats selection as estimation. Companion laboratories implement nested pipelines, bounded search, error analysis, uncertainty, and a versioned promotion report.

CHAPTER 25

Reliable supervised-learning systems

Learning objectives

After this chapter, you should be able to:


- separate training, prediction, and feedback paths;
- define a versioned model artifact and feature contract;
- monitor service behavior, input shift, predictions, and delayed outcomes; and
- design promotion, rollback, and retraining as governed operations.

Where this chapter fits

The preceding chapters developed candidate estimators and honest selection. This Part II synthesis places an approved artifact inside the end-to-end architecture of Chapter 9. A prediction system is incomplete until future outcomes can test its claims and operators can respond safely.

25.1 Three paths define the operated system

The **training path** validates a data snapshot, constructs split and features, fits candidates, evaluates them, and promotes an immutable artifact. The **prediction path** validates a request or batch, applies the exact feature transformation and approved artifact, and records output context. The **feedback path** joins predictions to outcomes after the target horizon and produces evidence for continuation, investigation, rollback, or retraining.



Each arrow requires identity, schema, version, time, error, retry, access, and retention semantics. The paths may run at different cadences and on different infrastructure, but their contracts must agree.

25.2 A model artifact is more than parameters

An approved artifact binds together a feature schema and order, fitted transformations, model state, class or output semantics, supported runtime, training-data and code references, evaluation report, and model card. A registry records lifecycle state such as candidate, approved, superseded, or withdrawn.

Never load arbitrary serialized objects from untrusted sources. Many Python serialization formats can execute code. Control provenance, integrity, access, and runtime compatibility. Prefer constrained formats when they

represent the needed operations faithfully.

25.3 Offline and online features must agree

Training-serving skew occurs when feature computation differs between historical training and live prediction. Causes include time-zone handling, category vocabularies, window boundaries, late data, default values, code versions, and units. Reuse package code where possible, and test representative raw records through both paths.

Point-in-time correctness is essential: a historical feature must use only information available at its historical prediction time. Recomputing it from a current database can accidentally include future corrections or outcomes.

Concept check. A live feature has the same name, dtype, and range as its training counterpart. Give two ways it can still have different semantics.

25.4 Prediction interfaces fail explicitly

Batch inference favors throughput, snapshot lineage, restartable partitions, and idempotent outputs. Online inference adds latency, concurrency, admission control, timeout, and availability responsibilities. Both validate schemas, bound resources, record artifact identity, and reject incompatible requests.

The interface should define behavior for missing, unknown, infinite, or out-of- support inputs. Abstention or routing to human review can be safer than a forced prediction. Error responses must not leak secrets or silently substitute a different model.

25.5 Operating evidence is part of the model contract

Offline evaluation estimates behavior under a stated sampling and measurement process. Release changes the question. The team must now determine what code, data, model, policy, and dependencies actually served clients; whether the system met its operational objectives; and whether later outcomes support the original predictive claim. Source code alone cannot answer those questions.

Four terms should be separated. **Telemetry** is evidence emitted by a running system. **Monitoring** repeatedly checks selected evidence and conditions. **Observability** is the property that permits investigators to infer useful internal behavior from available evidence. **Model monitoring** concerns feature validity, populations, scores, decisions, slices, and outcomes for a learned component. Installing a dashboard product does not make an uninstrumented or semantically ambiguous system observable.

The first design question is not “What can this tool display?” It is “Which failure must an operator distinguish, and what evidence would separate its competing causes?” Instrumentation follows the diagnostic question.

25.6 Failure layers require different evidence

An HTTP 200 response proves that an endpoint produced a response under its transport contract. It does not prove that the request used the intended units, feature meanings, model, decision policy, or population. Conversely, an accurate model is not useful when its service is unavailable. Reliability therefore has several causal layers.

Layer	Representative failure	Evidence needed
Service	process unavailable, slow dependency, exhausted worker pool	request rate, status, latency distribution, saturation, dependency spans
Data contract	missing field, unit mismatch, stale feature, new category	schema rejection, feature lineage, safe summaries, producer version
Artifact	wrong or incompatible model loaded	artifact digest, model version, feature-contract version, load event
Population	input or prevalence distribution changes	reference and current windows, slices, missingness, score and decision distributions
Decision policy	threshold, abstention, or routing rule changes	policy version, action counts, cost and constraint evidence
Outcome	calibration or predictive performance degrades	prediction-outcome join, target horizon, sample size, loss and slice estimates
Client	response cannot be used or rendered	client event, synthetic journey, support report, release identity

The layers interact. A sensor firmware change can look like population shift; a unit conversion defect can look like model decay; a failed outcome join can make quality appear stable because the hardest cases disappear. An alert should therefore initiate diagnosis, not name a cause prematurely.

Concept check. Every prediction request is fast and returns HTTP 200, but the fraction routed to human review falls by half. Give three causes at different layers and one observation that would distinguish each cause.

25.7 Logs, metrics, and traces answer different questions

A **structured log** records one discrete event as named fields: timestamp, event type, severity, request or prediction identifier, model and release versions, and approved diagnostic context. It should not serialize arbitrary arguments or complete feature vectors. Logs otherwise become an ungoverned copy of sensitive inputs, credentials, or proprietary data. Field policy, access, retention, and deletion are part of logging design.

A **metric** is a numeric time series. Request count, error count, duration, queue depth, rejected-input count, score histogram, and joined-outcome count can be aggregated over time and across replicas. Labels define groups, so their value sets must remain bounded. Route, status class, risk band, and deployed model version may be controlled labels. Request IDs, prediction IDs, raw error messages, users, and timestamps are not: they can create an effectively unbounded number of time series. This **cardinality** failure can exhaust a monitoring system during the incident when it is most needed.

A **trace** follows one unit of work through nested spans. An HTTP request may contain spans for schema transformation, feature lookup, model execution, database write, and downstream calls. Metrics establish scope; a sampled trace localizes representative work; logs explain selected events. A request ID is an application correlation identifier, while a trace ID belongs to the tracing system. Recording both can connect evidence without using either as a metric label.

Diagnostic order. Begin with the client-visible symptom. Use metrics to determine scope, traces to locate work, and logs to inspect relevant events. Scrolling through all logs is not an investigation strategy, and absence of error logs is not proof of correctness.

The common service summary called RED records request **rate**, **errors**, and **duration**. Saturation and

dependency health add capacity context. These signals remain necessary for a model service, but they cannot establish feature meaning or predictive quality.

25.8 Model monitoring needs a feedback path

Operational monitoring covers rate, latency, errors, saturation, artifact load, and dependency health. Data-quality monitoring covers schema, missingness, range, category, freshness, units, and joins. Distribution monitoring compares feature, score, and decision summaries with explicit reference windows.

Covariate shift means the distribution of X changes. Prior shift changes class prevalence. Concept shift changes the relationship between X and Y. Unlabeled inputs can reveal aspects of the first and sometimes the second; they cannot by themselves measure predictive error or identify the third. A prediction record therefore needs a stable join key, prediction time, target horizon, score or action, model and policy identity, and lawful retention. When the outcome arrives, the feedback path validates and joins it to the original prediction rather than recomputing history from mutable current data.

Report quality estimates with their denominators, time windows, and slice definitions. A Brier score computed from eight convenient outcomes is not equivalent evidence to one computed from a representative sample of eight thousand. Monitor slices defined before release and investigate emerging slices carefully; repeated searching can turn random variation into an apparent incident.

There are three important clocks: request time, outcome-availability time, and monitor-computation time. A system can detect schema rejection immediately, score shift after a monitoring window, and outcome degradation only after the target horizon. Alert policy must respect these information delays.

Reference and current windows must name their populations, measurement processes, missingness, and sample sizes. A divergence statistic or a two-sample test does not identify a cause and does not by itself quantify decision harm. Large samples can make negligible changes detectable; repeated slice searches can turn random variation into an apparent incident. Predeclare consequential slices, report uncertainty, and examine whether outcomes are selectively missing or delayed.

Common misconception

Misconception: feature drift means the model must be retrained.
Correction: drift is evidence to investigate. A producer change, failed transformation, selection effect, or real population change may produce the same summary. Retraining can preserve the defect, learn from corrupted labels, or degrade important groups. Action depends on outcomes, cause, severity, and the validated response policy.

25.9 Alerts connect objectives to owned action

A **service-level indicator** (SLI) is a measured quantity such as the fraction of eligible prediction requests completed successfully within 250 ms. A **service-level objective** (SLO) states a target over a window, for example at least 99.5% over 28 days. The objective should reflect a client outcome and exclude only cases justified by the contract.

An alert is useful when it detects a meaningful symptom early enough for an owner to act. Every alert needs a condition, evaluation window, urgency, owner, runbook, evidence links, duplicate suppression, and recovery condition. Page on sustained user impact or rapid consumption of an error budget, not every log line.

Model-quality alerts often require longer windows, minimum sample sizes, and human review because their estimates are noisy and delayed.

An alert rule has temporal state. It is *inactive* while its expression is false, *pending* while the expression is true but has not satisfied its required duration, and *firing* only after that duration. This delay reduces reactions to isolated noise, but it also makes evaluation interval, traffic rate, and window length part of the alert contract. The production monitoring laboratory makes these states executable through Prometheus rules; notification routing remains deliberately outside the local teaching stack.

A dashboard without a response policy is visualization, not operational control. A runbook should state safe first checks, authority limits, reversible mitigations, escalation contacts, and verification. It should never instruct an operator to delete evidence, expose data, or retrain reflexively.

25.10 Incident diagnosis is disciplined inference

An incident response can be organized as a sequence of falsifiable decisions:

1. state the exact client symptom and time interval;
2. preserve release, model, data, configuration, and deployment identity;
3. form at least two competing hypotheses;
4. use aggregate metrics to establish scope;
5. select a representative trace to localize work;
6. inspect correlated structured events rather than the entire log stream;
7. examine feature, score, decision, slice, and outcome evidence as needed;
8. apply the safest reversible mitigation within the responder's authority;
9. repeat the original client action and verify recovery; and
10. record the timeline, cause, impact, repair, and preventive controls.

Restarting first can destroy diagnostic state. Changing several components at once prevents causal attribution. A useful post-incident review separates facts known at the time from later conclusions and assigns follow-up actions with owners and verifiable completion criteria.

Worked example: one application, two very different incidents

The repository's production monitoring laboratory operates a FastAPI battery- risk service backed by package modules and SQLite prediction lineage. A traffic script acts as the client. Prometheus stores metrics, Loki stores structured events, Tempo stores OpenTelemetry traces, and Grafana presents a provisioned dashboard. No notebook is part of the runtime.

First, an instructor introduces delay in the feature-contract operation. The request-rate panel remains stable, the error ratio remains near zero, and the 95th-percentile latency rises. A representative trace assigns most of the duration to `feature_contract.apply`. The team restores the healthy configuration and verifies the original latency symptom with new traffic.

Second, the service remains fast and returns HTTP 200, but the temperature transformation assumes Fahrenheit for inputs contracted as Celsius. Service health remains green while score and risk-band distributions shift. A `prediction_completed` event records the model and release identities and the approved unit-assumption field; the correlated transformation span confirms where semantics changed. Retraining would not repair this defect. The correct response restores the feature contract, tests the unit boundary, and evaluates the affected predictions and later outcomes.

The exercise makes a central distinction observable: software availability and model validity are related

operational responsibilities, not the same claim.

The lab manual, scripts, configurations, runbook, and tests live under `projects/production-monitoring-lab`. The application implementation lives under `src/rice_dsm/monitoring_lab`. This separation is intentional: modules implement the system; scripts operate it; configuration connects processes; tests preserve contracts; notebooks remain live computational laboratories.

25.11 Retraining is a release, not a reflex

A retraining trigger begins a candidate-building workflow. The candidate must pass data validation, tests, evaluation, subgroup and resource gates, and approval. Automatic promotion is appropriate only when those gates and rollback controls match the consequence of failure.

Rollback requires a previously known artifact, compatible feature interface, and a procedure tested before the incident. Some shifts make rollback insufficient because the old artifact faces the same new population. A safe fallback may be a baseline, abstention, reduced scope, or human review.

Professional practice

Separate the decision to recompute a candidate from the decision to release it. Schedule-driven retraining is an opportunity to evaluate new evidence, not a guarantee that the newest artifact is better.

25.12 The release dossier

A defensible release records the prediction contract, data and feature lineage, split specification, candidate search, final evaluation, known limitations, model and policy versions, security review, test evidence, monitoring plan, owner, rollback plan, and expiration or review date. CI verifies reproducible software properties; human review owns scientific and operational judgment that cannot be reduced to one test.

Worked example: an incident closes the evidence loop

After release, the degradation service remains fast and error-free, but a new batch produces higher scores and more out-of-support warnings. Outcomes will not arrive for 100 cycles. The runbook narrows automated use and routes affected cells to review rather than immediately retraining.
Investigation finds a sensor firmware change that altered one summary feature. The team reconstructs the feature with point-in-time data, evaluates both the approved artifact and a candidate on the corrected representation, and records the incident. A compatibility adapter restores the defined unit; the model is not changed. Operational evidence prevented a data-interface defect from being misdiagnosed as concept drift.

25.13 Exercises

1. Draw training, prediction, and feedback paths for batch inference. Mark every durable artifact and join key.
2. Specify a feature-parity test involving time windows, late records, unknown categories, and units.

3. Design monitoring that distinguishes service failure, input shift, score shift, calibration change, and outcome degradation.
4. Write a rollback rehearsal and explain one shift for which rollback would not restore acceptable behavior.

Chapter review

A reliable supervised-learning system joins three paths. Training creates and promotes versioned evidence; prediction applies an approved artifact through a validated interface; feedback connects outputs to delayed outcomes. Monitoring must cover operations, data, scores, slices, and eventual performance. Drift prompts investigation, while retraining and rollback remain governed releases.

Executable companion

Lecture 17 notebook 00 maps the three system paths; later notebooks analyze drift and outcome evidence. The operated, module-based exercise is `projects/production-monitoring-lab`; scripts operate it, tests preserve its contracts, and notebooks neither serve nor orchestrate it.

APPENDIX A

Course setup reference

This appendix is a compact operational reference. Chapter 2 explains why the steps work.

A.1 Initial setup

1. Install uv using its current official instructions.
2. Clone or download the course repository.
3. Open the repository folder in VS Code.
4. Open VS Code's integrated terminal at the repository root.
5. Run:

```
uv run python scripts/setup_course.py
```

Open a notebook and select the **Rice DSM** kernel. The setup command does not launch JupyterLab.

A.2 One-command refresh after main changes

After the initial setup, use the same command in macOS or Linux shells and in Windows PowerShell:

```
uv run --locked python scripts/refresh_course.py
```

On a clean local `main`, this command fast-forwards from `upstream/main` when that remote exists and otherwise from `origin/main`. It then synchronizes the exact lockfile environment, verifies course resources, and repairs the Rice DSM kernel. It refuses to run on another branch or over uncommitted work.

A.3 Verify the active notebook process

```
import sys
from pathlib import Path
import rice_dsm

print("Python:", sys.version.split()[0])
print("Executable:", Path(sys.executable))
print("Package:", Path(rice_dsm.__file__))
print("Version:", rice_dsm.__version__)
```

The executable should belong to the repository's `.venv`, and the package should resolve to this repository's `src/rice_dsm` tree.

A.4 Run checks

```
uv run pytest
uv run ruff check src tests scripts
```

The test suite includes package behavior, repository contracts, instructional standards, and execution of every notebook from top to bottom.

A.5 Build this textbook

With a LaTeX distribution and `latexmk` installed:

```
make -C textbook
```

The compiled book is written to `output/pdf/data-science-machine-learning-textbook.pdf`.

A.6 First diagnostic questions

1. Am I at the repository root?
2. Which executable does `sys.executable` report?
3. Which kernel is selected in VS Code?
4. Does `rice_dsm.__file__` point into this repository?
5. Did I restart the kernel after changing the environment?
6. Does the complete setup output identify an earlier failure?

APPENDIX B

Git and GitHub: evidence, collaboration, and recovery

Git is sometimes introduced as a place to save code and GitHub as a place to upload it. Both descriptions are too weak. A professional data project changes continuously: code is revised, datasets acquire new versions, notebooks are rerun, assumptions are corrected, and several people may work at once. Without an inspectable history, the team cannot reliably answer which change produced a result, why a decision was made, whether two analyses used the same source, or how to return to the last known good state.

Git makes coherent project states identifiable and comparable. GitHub adds a shared location and collaboration system around that history. Together they support review, attribution, automation, release, and recovery. They do not replace backups, data governance, testing, or scientific records; they connect those practices to concrete versions of the project.

Learning objectives

After working through this appendix, you should be able to:

- distinguish Git, GitHub, a repository, a commit, a branch, a remote, and a pull request;
- explain the working tree, staging area, local repository, and remote repository without relying on memorized commands;
- inspect, stage, commit, compare, and recover changes deliberately;
- use a branch-based GitHub workflow for a small reviewed change;
- synchronize with collaborators and resolve a simple merge conflict;
- protect secrets, large data, environments, and generated artifacts;
- interpret a GitHub Actions workflow and use CI evidence during review; and
- follow a conservative daily workflow that works in VS Code on Windows, macOS, and Linux.

Where this chapter fits

Version control is part of the professional-practice spine, not an isolated tool. It identifies the code and documentation used by notebooks, packages, tests, data pipelines, models, APIs, and deployments. Chapter 5 develops tests and CI; this appendix supplies the history and review workflow that make those checks useful during change.

B.1 Why version control matters in data science

A data-science result is rarely produced by one immutable script. Exploration creates alternatives; cleaning rules evolve; features are redefined; model parameters change; plots are revised; and conclusions are challenged. The history matters for at least six reasons.

Reproducibility. A result can name the exact source revision that produced it rather than “the code from last

month."

Review. A collaborator can inspect the proposed difference instead of rereading the entire project and guessing what changed.

Attribution. Commits record authorship, time, and intent. They help a team locate the person or discussion with relevant context; they are not a measure of individual productivity.

Parallel work. Branches allow independent changes to proceed without continuously overwriting one shared directory.

Recovery. Recorded snapshots provide known states to compare, restore, or counteract when an experiment or release fails.

Automation. CI systems can test the precise revision proposed for integration and attach the evidence to its review.

Version control is evidence about artifacts and decisions. It does not prove that the data was valid, the analysis was unbiased, or the conclusion was true. A perfectly versioned invalid experiment remains invalid. The value of Git is that the exact artifact can be examined, challenged, and connected to other evidence.

Common misconception

Misconception: Git is useful only when several programmers collaborate.
Correction: a solo researcher also changes assumptions, revisits old results, makes mistakes, and needs to communicate with a future version of themself. Small coherent commits make that reasoning inspectable before a second person joins the project.

B.2 Git and GitHub are different systems

Git is an open-source distributed version-control system that runs on your computer. Most Git operations, including commits, branches, comparisons, and history inspection, do not require a network connection. A clone contains a project history and can create new history locally.

GitHub is a hosted collaboration platform built around Git repositories. It provides remote hosting, accounts and permissions, pull requests, reviews, issues, releases, Actions, and other services. GitHub is not required to use Git, and Git can communicate with hosting services other than GitHub.

Question	Git	GitHub
Where does it operate?	Primarily in a local repository on your computer	As a network service containing hosted repositories and collaboration records
What does it identify?	Snapshots, commits, branches, tags, and relationships between them	Accounts, repositories, pull requests, reviews, issues, workflow runs, releases, and permissions
Does it require the internet?	Not for ordinary local history operations	Yes for interacting with the hosted service
Typical commands or actions	`status`, `diff`, `add`, `commit`, `switch`, `merge`, `log`	Open a pull request, review files, inspect checks, manage an issue, merge an approved change
What does "save" mean?	Writing a file is separate from committing a staged snapshot	Pushing transfers local commits; the GitHub copy is not updated by a local save or commit alone

VS Code supplies a graphical Source Control view for many Git operations, but the underlying states are the same. This appendix shows commands because they make inputs and effects explicit and transfer across operating systems. You may use the graphical interface after you can predict which Git state it will change.


Worked example: Saved is not committed, and committed is not shared

A student edits `analysis.py` in VS Code and saves it. The file is now on disk in the working tree, but no Git history contains the edit. The student runs `git add analysis.py`; the current contents enter the staging area, but no commit exists yet. After `git commit`, the snapshot exists in the local repository. A collaborator still cannot see it on GitHub until the containing branch is pushed to a remote the collaborator can access.

Each claim has distinct evidence: the editor or filesystem shows the saved file; `git diff` and `git status` show the working change; `git diff --staged` shows the proposed snapshot; `git log` shows the local commit; and the GitHub branch or a fetch from the remote shows that the commit was shared. Saying "I saved it" leaves all but the first state unknown.

B.3 The four-state mental model

Most beginner confusion disappears when four locations are kept distinct.



`git add`: working tree → staging `git commit`: staging → local repository

`git push`: local → remote `git fetch`: remote → local

The working tree is the checked-out directory visible in VS Code. Saving a file changes the working tree, not Git history.

The staging area, also called the index, is Git's proposed content for the next commit. Staging is selection, not a permanent save. If a staged file is edited again, one version can be staged while newer edits remain unstaged.

The local repository is the history stored under the hidden `.git` directory. A commit records the staged project snapshot, metadata, a message, and parent commit. It does not automatically appear on GitHub.

A remote repository is another repository reachable through a named network location. `origin` is a conventional local nickname for the remote used when cloning; it is not a special server or a branch.


These locations explain common surprises. `git diff` normally shows unstaged working-tree changes. `git diff --staged` shows what the next commit would contain. A clean working tree says that tracked local files match the current commit; it does not say the branch has been pushed or is current with GitHub.

Professional practice

Use `git status` before and after every unfamiliar Git command. Read its output as evidence: current branch, relationship to its upstream branch, staged changes, unstaged changes, and untracked files. Do not treat status as an error message to dismiss.

B.4 Commits, branches, and HEAD

Git stores project snapshots as commits connected to parent commits. The resulting history is a directed graph. A branch is a movable name pointing to a commit; creating one does not duplicate the entire project. `HEAD` normally refers to the branch currently checked out.



In this graph, both branches share commits A through C. Work on `main` produced D; work on `feature` produced E. A later merge can integrate the histories. Switching branches moves `HEAD` and updates the working tree to the selected snapshot. Git may refuse to switch when uncommitted changes would be overwritten; that refusal protects evidence.

Commit identifiers are content-derived hexadecimal names, usually displayed in abbreviated form. A branch name is convenient and movable; a commit identifier names one historical state. Results that require durable reproducibility should record a commit identifier or release tag, not only "main," because `main` will move.

B.5 First-time setup

Install Git using the current instructions for your operating system, then open the repository folder in VS Code and use **Terminal: New Terminal**. The integrated terminal may be PowerShell on Windows and a shell such as zsh or bash on macOS or Linux. The Git commands in this appendix are the same in each; we avoid shell-specific commands for creating or editing files.

Verify Git and set the identity written into future commits:

```
git --version
git config --global user.name "Your Name"
```

```
git config --global user.email "you@example.edu"
git config --global init.defaultBranch main
git config --global --list
```

The name and email are commit metadata, not GitHub authentication. They should identify your work accurately. If email privacy matters, use the no-reply address provided by your GitHub account and follow the account's current email settings. Repository-specific settings can override global settings by omitting `-global` while inside that repository.

Authentication is a separate boundary. GitHub supports HTTPS and SSH remote URLs. For HTTPS, a credential manager or `gh auth login` can complete a browser-based sign-in; account passwords are not used as Git credentials. SSH uses a private key on your computer and a corresponding public key registered with GitHub. Follow GitHub's current setup instructions rather than pasting a token into a command, file, notebook, or remote URL.

Failure mode

Never commit a password, API key, access token, private SSH key, database URL, or credential file. Deleting it in a later commit does not remove it from earlier history. Revoke or rotate an exposed credential immediately, then follow the repository owner's incident and history-cleanup process.

B.6 Worked lesson 1: build a local history

This lesson requires no GitHub account and makes no network changes. Create an empty folder named `git-practice` outside the course repository, open that folder in a separate VS Code window, and open its integrated terminal.

Step 1: initialize and inspect

```
git init -b main
git status
```

`git init` creates the hidden local repository. The `-b main` option names the initial branch. No project snapshot exists until the first commit.

Step 2: create the first artifact

In VS Code, create `README.md` containing:

```
# Probability experiment

This project records a small reproducible experiment.
```

Save the file, then inspect and stage it:

```
git status
git diff -- README.md
```

```
git add README.md
git status
git diff --staged
```

Before `git add`, the file is untracked, so ordinary `git diff` may not display its contents. After staging, `git diff -staged` shows the exact snapshot proposed for the commit.

Step 3: make and inspect a commit

```
git commit -m "Document the probability experiment"
git status
git log --oneline --decorate
git show --stat --oneline HEAD
```

The commit message completes the sentence "If applied, this commit will..." with a concise action. `HEAD` refers to the current commit. A clean status now means the working tree and staging area match that commit.

Step 4: separate two changes

Create `experiment.py` in VS Code:

```
outcomes = [True, False, True, True, False]
estimated_probability = sum(outcomes) / len(outcomes)
print(estimated_probability)
```

Also add a sentence to `README.md` explaining that the estimate is the fraction of observed successes. Save both files and run:

```
git status --short
git diff
git add experiment.py
git diff --staged
git commit -m "Add a Bernoulli probability estimate"
git status --short
```

Only `experiment.py` entered that commit. The README edit remains in the working tree. Now review, stage, and commit it separately:

```
git diff -- README.md
git add README.md
git diff --staged
git commit -m "Explain the probability estimate"
git log --oneline --decorate --graph --all
```

This is the purpose of staging: construct one reviewable snapshot from selected work. `git add .` is convenient but broad; named paths make intent visible and reduce accidental inclusion.

Checkpoint

Edit `experiment.py`, stage it, and then edit it again. Use `git status`, `git diff`, and `git diff --staged` to identify which version is in each state. Explain what a commit would record before running any commit command.

B.7 Design coherent commits

A useful commit is a review and recovery unit. It should express one coherent intent, include the tests and documentation required by that intent, and avoid unrelated formatting or generated noise. "One intent" does not mean one file: a feature may properly change source, tests, documentation, and configuration together.

Before committing, ask:

- Can I state the purpose in one specific sentence?
- Does every staged line contribute to that purpose?
- Did I include tests, documentation, schema, or migration changes needed for the contract?
- Did I inspect both unstaged and staged differences?
- Did I run the relevant checks from the intended environment?
- Is any secret, private data, large generated file, or local path present?

Prefer an imperative subject such as "Validate probability bounds" over "changes," "updates," or "worked on notebook." The body of a larger commit can explain why the change is needed, important constraints, and consequences that are not obvious from the diff. A commit message should explain intent; it should not repeat filenames already visible in the snapshot.

B.8 Ignore local and generated state deliberately

A `.gitignore` file names untracked paths that Git should normally omit from status and staging. This repository ignores the project virtual environment, Python caches, notebook checkpoints, LaTeX intermediates, editor state, local secrets, and most local data. That policy keeps the repository small and prevents machine-specific artifacts from obscuring meaningful change.

```
.venv/
__pycache__/
.ipynb_checkpoints/
.env
data/raw/*
data/processed/*
```

Ignoring is not security. It reduces accidental staging but does not protect a file that was already tracked, explicitly forced into staging, copied elsewhere, or exposed outside Git. Use `git check-ignore -v PATH` to determine which rule ignores a path. Use `git ls-files PATH` to determine whether Git already tracks it.

Git is optimized for source-like artifacts, not arbitrary data storage. Do not commit virtual environments, dependency downloads, database files, model checkpoints, or large raw datasets merely for convenience. Store reproducible instructions, schemas, small teaching fixtures, checksums, and controlled references instead. When a project genuinely requires versioned large binaries, choose an approved artifact store or Git LFS and document the retrieval and retention policy. GitHub currently warns for regular Git files above 50 MiB and

blocks files above 100 MiB; institutional and repository policies may be stricter.

B.9 Worked lesson 2: branches isolate change

Return to `git-practice` with a clean working tree. Create and switch to a branch in one command:

```
git status
git switch -c feature/validate-probabilities
git branch --show-current
git log --oneline --decorate --graph --all
```

Edit `experiment.py` so that invalid values are rejected. One possible version is:

```
def mean_probability(values: list[float]) -> float:
    if not values:
        raise ValueError("values must not be empty")
    if any(value < 0 or value > 1 for value in values):
        raise ValueError("probabilities must lie in [0, 1]")
    return sum(values) / len(values)


print(mean_probability([1.0, 0.0, 1.0, 1.0, 0.0]))
```

Review and commit:

```
git diff --check
git diff -- experiment.py
git add experiment.py
git diff --staged
git commit -m "Validate probability inputs"
git log --oneline --decorate --graph --all
```

Switch to the main branch and inspect the file:

```
git switch main
git log --oneline --decorate --graph --all
git switch feature/validate-probabilities
```

The function disappears on `main` and returns on the feature branch because the working tree follows `HEAD`. No work was lost. The branch names point to different commits.

To integrate the completed branch locally:

```
git switch main
git merge --ff-only feature/validate-probabilities
git log --oneline --decorate --graph --all
git branch -d feature/validate-probabilities
```

A fast-forward moves `main` to the descendant commit without creating a merge commit. Deleting the merged branch removes a movable name, not the commits now reachable from `main`. In a shared GitHub repository,

integration normally happens through a reviewed pull request instead of a local merge.

B.10 Connect a repository to GitHub

There are two common starting paths.

Clone an existing repository. On GitHub, copy the HTTPS or SSH URL from the repository's Code menu. In a parent directory, run:

```
git clone <repository-url>
cd <repository-directory>
git remote -v
git status
```

Cloning creates a new directory, copies reachable history, checks out a branch, and records the source remote as `origin`. Angle-bracketed names above are placeholders; replace them, including the brackets, with actual values.

Publish an existing local repository. First create an empty GitHub repository without an automatically generated README or license, then connect the local history:

```
git remote add origin <repository-url>
git remote -v
git push -u origin main
```

The `-u` option records `origin/main` as the upstream for local `main`, allowing later `git push` and status comparisons to infer the destination. Pushing transfers commits and branch references; it does not upload uncommitted files.

If you lack write permission to a repository, GitHub's fork model can create a repository under your account from which you propose a pull request. A fork is a GitHub repository relationship, not the same concept as a local branch.

B.11 The daily branch and pull-request workflow

GitHub flow is a lightweight branch-based workflow. For this course, use the following conservative sequence unless an assignment specifies otherwise.

1. Begin from an inspected, current base

```
git status
git switch main
git fetch origin
git status -sb
git pull --ff-only
```

`git fetch` downloads remote commits and updates remote-tracking names such as `origin/main`; it does not rewrite your working files. Inspect before integrating. `git pull --ff-only` permits only an unambiguous fast-forward and stops if local and remote history diverged.

2. Create one purpose-specific branch

```
git switch -c feature/add-calibration-check
```

Use a short descriptive name. Separate unrelated work into separate branches so review, delay, or rejection of one change does not entangle another.

3. Work in small verified steps

Edit in VS Code. Frequently inspect:

```
git status --short
git diff
uv run pytest -q
uv run ruff check src tests scripts
```

Stage explicit paths and review the proposed commit:

```
git add src/rice_dsm tests
git diff --staged --check
git diff --staged
git commit -m "Validate calibration ranges"
```

4. Publish the branch

```
git push -u origin feature/add-calibration-check
```

The feature branch now exists locally and on GitHub. Future commits pushed to that branch automatically update its pull request.

5. Open a pull request

On GitHub, choose the feature branch as the compare branch and `main` as the base branch. The pull request asks to integrate the feature history into the base; it is not merely a notification that coding is finished. A strong description answers:

- What problem or scientific need does this change address?
- What behavior, assumptions, data, or interfaces changed?
- What evidence was run, and what does it not prove?
- What should the reviewer inspect especially carefully?
- What could fail, and how would the team recover?

Use a draft pull request when the design or evidence needs early discussion. Read the Files changed tab as the integrated proposal, not merely commit by commit. Inspect automated checks and respond to review with additional commits; do not resolve a conversation until the concern is actually addressed or moved to an explicit follow-up issue.

6. Merge and clean up

After required review and checks pass, use the repository's selected merge strategy. GitHub may offer merge commits, squash merging, or rebasing; the team should choose deliberately and consistently. Delete the merged remote branch, then synchronize locally:

```
git switch main
git pull --ff-only
git branch -d feature/add-calibration-check
```

Professional practice

Never push directly to a protected default branch simply because you have permission. Branch protection, review, and required checks make integration a visible decision. Administrator ability is not evidence that bypassing the process is appropriate.

B.12 Course contribution practicum: textbook problem to pull request

This section is the exact course procedure for turning a contribution-studio problem into a reviewed change. It specializes the general workflow above to a student fork. In this model, `origin` is the student's GitHub fork and `upstream` is the instructor-maintained course repository. Confusing those two names is a common source of failed pushes and stale branches.

Step 0: preserve the problem identity

Contribution problems have stable identifiers such as **MLF-PR1**, **SLC-PR2**, **LR-PR3**, and **GD-PR1**. The identifier connects the mathematical prompt to public design and review evidence. Use it in all of the following places:

- issue title: `[GD-PR1] Add optimizer result records`;
- issue field: `Textbook problem ID = GD-PR1`;
- branch: `student/gd-pr1-optimizer-records`;
- pull-request title: `[GD-PR1] Add optimizer result records`; and
- pull-request description: `Textbook problem: GD-PR1` and `Closes #123`.

The identifier does not imply that every student must produce the same design. The issue records the student's proposed scope, public interface, mathematical contract, evidence, and limitations. Search open and closed issues for both the problem ID and proposed package slug before opening a duplicate.

Use the GitHub **Student package contribution** issue form. Do not put a grade, student ID, accommodation, private communication, credential, restricted data, or identifiable student record in any public field. Wait for the issue's scope and unique package slug to be approved before implementing the full change. If the instructor has enabled generated course tasks, use `/claim` only on a ready task and `/release` if you cannot continue.

Step 1: open a terminal in the repository root

The Git and `uv` commands in this procedure are the same on Windows, macOS, and Linux. Only navigation and directory-listing syntax differs. The recommended route is **VS Code → Terminal → New Terminal** after

opening the repository folder.

Platform	Recommended shell	Root check
Windows	PowerShell in VS Code	`Get-Location`; `Get-ChildItem README.md, pyproject.toml`
macOS	zsh in VS Code	`pwd`; `ls README.md pyproject.toml`
Linux	bash in VS Code	`pwd`; `ls README.md pyproject.toml`

On Windows PowerShell, navigate with:

```
Set-Location "C:\path\to\Data-Science-Machine-Learning-Fall-2026"
Get-Location
Get-ChildItem README.md, pyproject.toml
git --version
uv --version
```

On macOS or Linux, navigate with:

```
cd "/path/to/Data-Science-Machine-Learning-Fall-2026"
pwd
ls README.md pyproject.toml
git --version
uv --version
```

Stop if both `README.md` and `pyproject.toml` are not visible. Do not run setup, scaffold, or Git mutation commands from an arbitrary parent folder.

Step 2: fork, clone, and configure remotes once

On GitHub, fork `RandyRDavila/Data-Science-Machine-Learning-Fall-2026` into your account. Then run the following in the parent directory where the course folder should live. Replace `YOUR-GITHUB-NAME`; do not type the placeholder literally.

```
git clone https://github.com/YOUR-GITHUB-NAME/Data-Science-Machine-Learning-Fall-2026.git
cd Data-Science-Machine-Learning-Fall-2026
git remote add upstream https://github.com/RandyRDavila/Data-Science-Machine-Learning-Fall-2026.git
git remote -v
```

The output must show `origin` pointing to the student's fork and `upstream` pointing to the course repository, each with fetch and push URLs. Students fetch accepted class work from `upstream` and push their own branches to `origin`. If an existing clone has different remotes, do not delete the clone or uncommitted work. Stop and ask for help reassigning the remote names safely.

Prepare and verify the environment:

```
uv run python scripts/setup_course.py
uv run pytest tests/test_course_setup.py tests/test_repository.py -q
```

On the first run, `uv` may install the project Python and dependencies. Later runs reconcile the environment

with the committed lockfile. Students should not edit `pyproject.toml` or `uv.lock` for a contribution unless the approved issue explicitly requires a shared dependency change.

Step 3: synchronize `main` before every new branch

First inspect the working tree:

```
git status --short
```

The command should print nothing. If it prints paths, preserve and understand that work before switching branches. A new task does not authorize discarding old work. With a clean tree, synchronize exactly:

```
git switch main
git fetch upstream
git merge --ff-only upstream/main
git push origin main
git status -sb
git rev-parse main
git rev-parse upstream/main
```

The two final commit identifiers must match. The status line should identify `main` and should not report modified files. A failed `-ff-only` merge means local `main` has diverged; stop rather than using force, reset, or an improvised merge.

Create one branch from this verified base. Use lowercase in the branch name:

```
git switch -c student/gd-pr1-optimizer-records
git branch --show-current
git status -sb
```

Replace the example ID and description with the approved problem. Never reuse a merged branch for a new problem. One problem, one branch, one primary issue, and one pull request make scope and recovery visible.

Step 4: scaffold the approved contribution

For an incubating package, use the approved lowercase slug:

```
uv run python scripts/scaffold_student_package.py optimizer_records
git status --short
uv run pytest tests/contrib/optimizer_records -q
```

The scaffold creates source, test, and README boundaries. It refuses to overwrite an existing package. A collision is a coordination problem, not a reason to delete someone else's directory. Put reusable behavior under `src/rice_dsm/contrib/optimizer_records/`, tests under the matching `tests/contrib/optimizer_records/`, and experiments in notebooks only when interactive investigation is useful. The reusable implementation must not exist only in notebook state.

Before substantial implementation, write failing or incomplete tests from the approved contract: an ordinary case, a mathematical property, a boundary, and an expected failure. Develop in small steps and repeatedly inspect `git diff`.

Step 5: validate, stage explicit paths, and commit

Run narrow checks first and the broad gate second:

```
git status --short
git diff --check
git diff
uv run pytest tests/contrib/optimizer_records -q
uv run ruff check src tests scripts
uv run pytest -q
```

If a check fails, read the first causal error. Do not weaken a test, delete a platform case, or change an expected result merely to obtain green status. Decide whether the implementation, test, mathematical contract, documentation, or environment is wrong.

Stage only the intended contribution and inspect the exact proposed snapshot:

```
git add src/rice_dsm/contrib/optimizer_records
git add tests/contrib/optimizer_records
git diff --staged --check
git diff --staged
git commit -m "Add GD-PR1 optimizer result records"
git show --stat --oneline HEAD
git status -sb
```

Add documentation or another approved path explicitly when needed. Do not use an uninspected `git add .`. Never stage `.venv`, caches, credentials, private data, restricted datasets, or sensitive notebook output.

Step 6: incorporate accepted upstream work while the PR is open

If `main` changes before the contribution merges, preserve a clean feature branch, then merge current upstream into it:

```
git status --short
git fetch upstream
git merge upstream/main
uv run pytest tests/contrib/optimizer_records -q
uv run ruff check src tests scripts
uv run pytest -q
```

If Git reports a conflict, read each marked region and resolve the intended combined behavior; do not automatically choose "ours" or "theirs." Then stage the resolved paths, run the tests, and commit the merge. If the resolution becomes unclear, `git merge --abort` safely returns to the pre-merge state. Do not rebase a branch another student may have checked out unless the team has explicitly coordinated the history rewrite.

Step 7: push and open the pull request

Publish the named branch to the student's fork:

```
git push -u origin student/gd-pr1-optimizer-records
```

On GitHub, verify all four endpoints before submitting:

```
base repository: RandyRDavila/Data-Science-Machine-Learning-Fall-2026
base branch:     main
head repository: YOUR-GITHUB-NAME/Data-Science-Machine-Learning-Fall-2026
compare branch: student/gd-pr1-optimizer-records
```

Complete the pull-request template. State the textbook problem ID, public contract, mathematical assumptions, limitations, affected paths, and exact validation commands with results. Use `Closes #ISSUE-NUMBER`, not only a bare issue link, so an accepted merge closes the design issue. Open a draft PR when early interface review would prevent wasted implementation.

CI may require maintainer approval for a first-time fork. Once it runs, inspect the first failing job and first causal error. The Linux, macOS, and Windows matrix is evidence of encoded contracts on those runners; it does not prove the scientific problem is meaningful or the public interface is well designed.

Step 8: review, revise, and finish

When coordination is enabled, two eligible classmates are requested. Reviewers inspect mathematics, types and units, failure behavior, provenance, tests, documentation, and scope. Respond to every substantive comment with a change, evidence, or reasoned disagreement. Push follow-up commits to the same branch:

```
git add PATHS-CHANGED-AFTER-REVIEW
git diff --staged
git commit -m "Address optimizer record review"
git push
```

The existing pull request updates automatically. Do not open a new PR for each review revision. After maintainer merge, synchronize and clean up:

```
git switch main
git fetch upstream
git merge --ff-only upstream/main
git push origin main
git branch -d student/gd-pr1-optimizer-records
git status -sb
```

The merged history retains authorship, review, CI, and issue linkage. A merged component also creates maintenance responsibility: help investigate later integration failures or clarify limitations when asked.

Failure mode

Stop and ask before proceeding when status shows unexplained work, remotes do not match the fork model, `main` cannot fast-forward, a package path already exists, a command would require `-force`, a merge resolution is unclear, or a secret may have entered history. If a secret was exposed, revoke or rotate it immediately and use the private route in `SECURITY.md`; deleting the visible line is not sufficient.

B.13 Review is a technical skill

A reviewer is not a final syntax checker. Review challenges the change at several levels.

Lens	Reviewer question	Possible evidence
Intent	Does the diff solve the stated problem without unrelated change?	Issue, pull-request description, coherent commits
Contract	Are inputs, outputs, errors, schemas, units, and compatibility clear?	Types, docstrings, validation, interface tests
Correctness	Does behavior hold for ordinary, boundary, and failure cases?	Focused tests, properties, independent calculation
Data and science	Are provenance, leakage, uncertainty, and interpretation addressed?	Data checks, split design, evaluation, domain review
Operations	Can the change be observed, bounded, secured, and recovered?	Logs, limits, permissions, migration and rollback plan
Maintainability	Can a future contributor understand and safely change it?	Names, structure, documentation, small diff

Review comments should identify the observation and its consequence. Prefer "This parser accepts a missing unit, so Celsius and Fahrenheit records can become indistinguishable; could validation reject an absent unit?" over "This looks wrong." Ask questions when context is missing. Mark nonblocking suggestions as such. Authors should explain disagreement with evidence rather than silently obeying or dismissing feedback.

B.14 Synchronize without guessing

Three commands are often confused:

`git fetch origin` Downloads remote objects and updates local remote-tracking references. It does not integrate them into the current branch.

`git merge origin/main` Integrates the fetched `origin/main` history into the current branch, possibly by fast-forward or merge commit.

`git pull` Fetches and then integrates according to configuration and options. Because it combines steps, inspect status and use an explicit policy such as `--ff-only` when that is the intended result.

Useful comparisons after fetching include:

```
git status -sb
git log --oneline --decorate --graph --all -n 20
git log main..origin/main --oneline
git diff main...origin/main
```

The two-dot log above asks which commits are reachable from `origin/main` but not local `main`. The three-dot diff compares each side from their merge base and is useful for reviewing branch work. These notations are precise but easy to reverse; state the question before trusting the output.

When a shared base moves while your feature branch is open, fetch first. The repository may prefer merging `origin/main` into the feature or rebasing the feature onto it. Rebasing rewrites commit identities and therefore requires coordination; do not rebase commits that other people may have based work upon unless the team workflow explicitly permits it.

B.15 Worked lesson 3: create and resolve a conflict

A conflict is not Git corruption. It means two histories made incompatible changes and Git refuses to invent the intended result. Practice locally in `git-practice` while its status is clean.

Step 1: create competing histories

Create a branch from `main`:

```
git switch main
git switch -c experiment/use-observed-rate
```

Edit one specific README sentence to say "The reported estimate is the observed success rate." Commit it:

```
git add README.md
git commit -m "Define the estimate as an observed rate"
```

Return to `main`, create another branch, and change the same original sentence to "The reported estimate is a model probability."

```
git switch main
git switch -c experiment/use-model-probability
git add README.md
git commit -m "Define the estimate as a model probability"
```

Step 2: attempt integration

While on `experiment/use-model-probability`, run:

```
git merge experiment/use-observed-rate
git status
```

Git should report a content conflict. VS Code will show a merge editor or the underlying markers:

```
  <<<<<<< HEAD
The reported estimate is a model probability.
  =======
The reported estimate is the observed success rate.
  >>>>>>> experiment/use-observed-rate
```

`HEAD` is the checked-out side; the other label names the merged side. The final answer need not be either side verbatim. Decide the domain meaning first. For this example, replace the entire marked region with a

scientifically precise sentence such as “The script reports an observed success rate; it estimates a probability only under stated sampling assumptions.” Remove all markers.

Step 3: validate and complete

```
git diff --check
git diff
git add README.md
git status
git commit -m "Reconcile the probability interpretation"
git log --oneline --decorate --graph --all
```

Staging the file marks the conflict as resolved because you have selected its final content. The merge commit records both parent histories. Run relevant tests after resolution: choosing text that removes markers does not prove the combined behavior is correct.

If you realize the merge began from the wrong state and have not committed its resolution, `git merge --abort` normally returns to the pre-merge state. Inspect `git status` before and after. Do not use destructive cleanup commands merely to make the conflict display disappear.

Checkpoint

Explain why Git could not safely choose between “observed rate” and “model probability.” Then identify the scientific assumption introduced by the resolved sentence. The conflict was textual, but the correct resolution required domain reasoning.

B.16 Recover conservatively

Recovery begins by classifying the state: untracked, unstaged, staged, committed locally, pushed publicly, or merged. A command appropriate for one state may destroy evidence in another.

Intent	Conservative command	Meaning and caution
Inspect current state	`git status`; `git diff`; `git diff --staged`	Read before changing anything
Remove a path from staging	`git restore --staged PATH`	Keeps the working-tree edit but removes it from the proposed commit
Discard an unstaged tracked edit	`git restore PATH`	Overwrites uncommitted content; inspect and preserve needed work first
Correct the most recent unpushed commit	`git commit --amend`	Replaces that commit with a new identity; avoid after sharing
Counteract a shared commit	`git revert COMMIT`	Creates a new commit whose change reverses the selected commit, preserving public history
Abandon an unfinished merge	`git merge --abort`	Attempts to restore the pre-merge state; check status and preserve unrelated work
Locate recently moved references	`git reflog`	Diagnostic record that can help an experienced user recover otherwise unreachable commits

Commands such as `git reset --hard`, `git clean -fd`, and force push can permanently discard uncommitted work or rewrite shared history. They are not routine fixes. Stop, inspect exact targets, copy irreplaceable files outside the repository, and seek review before using them. Never follow a destructive command copied from an error search without understanding which state it changes.

Failure mode

Git does not record ordinary uncommitted edits. If a file was never committed or stashed, Git may be unable to recover it after a destructive restore, clean, or reset. Version control complements backups and editor recovery; it is not a substitute for either.

B.17 Notebooks, data, and generated artifacts

Jupyter notebooks are JSON documents containing source, metadata, execution counts, and possibly outputs. A tiny logical edit can therefore create a noisy diff, and hidden kernel state can make a recorded output disagree with visible source. Before committing a teaching or analysis notebook:

1. select the intended project kernel;
2. restart and run all cells from top to bottom;
3. inspect warnings, outputs, execution order, and data paths;
4. remove accidental exploration, secrets, and machine-specific metadata;
5. retain outputs only when repository policy says they teach or document something useful;
6. inspect the Git diff and run the notebook regression tests; and
7. keep reusable logic in package modules with focused tests.

Data requires a separate versioning design. Git can identify small immutable fixtures, schemas, metadata, and transformation code. It is often the wrong storage system for sensitive records, frequently changing databases, or large scientific arrays. Record a dataset identifier, checksum, provenance, schema, access procedure, and transformation revision so that Git history can refer to the evidence without embedding it improperly.

Generated artifacts should have an explicit policy. If a PDF, figure, or model is tracked, document why the built output belongs in review and how to reproduce it. Otherwise ignore it and let CI or a release system build it. Avoid commits in which meaningful source changes are hidden beneath hundreds of regenerated lines.

B.18 GitHub Actions turns history into automated evidence

GitHub Actions is an automation platform attached to repository events. A **workflow** is a YAML file under `.github/workflows`. An event such as a push, pull request, manual dispatch, or schedule triggers one or more jobs. Each job runs on a runner and contains ordered steps. A step may run a shell command or invoke a reusable action.

This repository's `course-ci.yml` workflow runs on pull requests, pushes to `main`, and manual dispatch. Restricting ordinary push runs to `main` avoids duplicating the pull-request matrix for a feature branch. It grants read-only repository contents permission, cancels obsolete runs for the same pull request or reference, and evaluates the course on Linux, macOS, and Windows. Each runner installs the pinned tools, reproduces the locked environment, prepares the notebook kernel, checks style, builds the package, and runs all package, repository, and notebook tests. A stable final job named `CI gate` requires every operating-system job to pass.

The core structure is:

```yaml
name: Course CI

on:
  push:
    branches: [main]
  pull_request:
  workflow_dispatch:

permissions:
  contents: read

jobs:
  course-quality:
    strategy:
      matrix:
        os: [ubuntu-latest, macos-latest, windows-latest]
    runs-on: ${{ matrix.os }}
    steps:
      - uses: actions/checkout@3d3c42e5aac5ba805825da76410c181273ba90b1
      - run: uv sync --locked
      - run: uv run ruff check src tests scripts
      - run: uv run pytest -q
```

The excerpt omits setup steps for focus; the checked-in workflow is the executable authority. Third-party actions are code executed with the workflow's permissions. Pinning an action to a reviewed commit identifier reduces the risk that a moving tag silently changes behavior. Keep workflow permissions narrow, avoid exposing secrets to untrusted changes, set timeouts and concurrency deliberately, and review dependency updates.

A green check has a precise meaning: the configured workflow passed for that revision under those runner conditions. It does not prove the tests are sufficient, the statistical design is valid, or deployment is safe. A red check is evidence to inspect, not a button to rerun until it turns green. Open the job, find the first meaningful failure, reproduce it locally when possible, repair the cause, and push a new commit.

The repository also contains path-specific textbook, dependency-review, and labeling workflows, plus two publication paths. Relevant merges to `main` deploy the compiled textbook through a static course site. Matching annotated `course-vX.Y.Z` tags build a checksummed release bundle and pause at a protected approval environment before publication. Appendix C traces those paths as a complete worked example and distinguishes integration, delivery, deployment, and release.

B.19 A command map by intention

Memorize questions before commands.

Question or intention	Command
Where am I and what changed?	`git status`; `git status -short`
Which branch is checked out?	`git branch -show-current`
What is unstaged?	`git diff`

Question or intention	Command
What is staged for the next commit?	`git diff --staged`
Does the diff contain whitespace errors?	`git diff --check`; `git diff --staged --check`
Select a path for the next commit	`git add PATH`
Unstage while keeping the working edit	`git restore --staged PATH`
Record the staged snapshot	`git commit -m "Imperative summary"`
Inspect compact history	`git log --oneline --decorate --graph --all`
Inspect one commit	`git show COMMIT`
Create and switch to a branch	`git switch -c BRANCH`
Switch to an existing branch	`git switch BRANCH`
List local and remote-tracking branches	`git branch -avv`
List configured remotes	`git remote -v`
Download remote history without integrating	`git fetch origin`
Fast-forward the current branch from its upstream	`git pull --ff-only`
Publish a new branch and record its upstream	`git push -u origin BRANCH`
Integrate only if a fast-forward is possible	`git merge --ff-only BRANCH`
Abort an unfinished merge	`git merge --abort`
Create a public counteracting commit	`git revert COMMIT`
Determine why a path is ignored	`git check-ignore -v PATH`
Determine whether a path is tracked	`git ls-files PATH`

Run `git COMMAND --help` for the complete installed manual. Options and defaults matter; read the command you are about to execute rather than assembling fragments from unrelated examples.

B.20 Principles to carry into professional work

1. **Inspect before changing state.** Status and diffs are part of the operation, not optional cleanup.
2. **Commit one coherent intent.** Make history readable enough to review, test, and reverse selectively.
3. **Branch by purpose.** Keep unrelated work and review conversations independent.
4. **Never use the repository as a secret store.** Ignore files for convenience; use credential systems for security.
5. **Keep data identity separate from data bulk.** Version schemas, provenance, code, and identifiers; store sensitive or large evidence in an appropriate controlled system.

6. **Treat pull requests as reasoning records.** Explain intent, evidence, risk, and review decisions.
7. **Protect shared history.** Prefer additive correction with revert; coordinate any history rewrite.
8. **Interpret CI precisely.** A check supports only the contracts it actually exercises.
9. **Make recovery proportional and conservative.** Classify the state, preserve evidence, then choose the narrowest operation.
10. **Name released artifacts by immutable revisions.** Moving branch names are convenient for development, not sufficient provenance for a result.

B.21 Exercises

Foundational

1. Draw the working tree, staging area, local repository, and remote repository. Place `add`, `commit`, `push`, and `fetch` on the correct transitions. Explain what each command does not do.
2. Distinguish a branch, a remote-tracking branch, a fork, and a pull request. Give a situation in which all four appear.
3. A file is listed as both staged and modified. Explain how this state can arise and which two diff commands reveal its two versions.

Applied

Complete Worked Lessons 1 through 3 in a disposable practice repository. Submit the output of `git log --oneline --decorate --graph --all`, one staged diff, and a short explanation of the conflict resolution. Do not submit the hidden `.git` directory.

Inspect this course repository's `.gitignore` and `.github/workflows/course-ci.yml`. For five ignored path groups, explain the failure prevented. For every CI step, name the contract it checks and one important failure it cannot detect.

Design

Design a GitHub workflow for a four-person scientific software team. Specify branch naming, commit expectations, required pull-request evidence, reviewers, CI checks, data and secret policy, merge strategy, release tags, and emergency recovery authority. Include one case where a green CI run should still block merge and one case where rewriting history is justified but requires coordination.

Chapter review

Key ideas. Git records selected project snapshots and their history; GitHub organizes shared review and automation around that history. The staging area constructs the next commit. Branches are movable commit references, not copied folders. Pull requests expose proposed integration, discussion, and CI evidence. Recovery begins by identifying state and choosing the narrowest safe operation.
Vocabulary. repository; working tree; staging area; commit; branch; HEAD; remote; remote-tracking branch; clone; fetch; push; merge; conflict; fork; pull request; workflow; runner; revert.
Explain aloud. Why are "my file is saved," "my change is committed," and "my branch is on GitHub" three different claims?

B.22 Official references

Interfaces and recommendations evolve. Verify account, authentication, and workflow details against the current official documentation:

- Pro Git: Recording Changes to the Repository
- Pro Git: Branches in a Nutshell
- Git command reference
- GitHub flow
- GitHub authentication
- Pull requests and review
- GitHub Actions
- GitHub large-file guidance

Concept check. A teammate says, "Everything is safe because I pushed it to a branch and CI passed." Which claims are supported, which are not, and what additional evidence would you request before merging?

APPENDIX C

From Source to Release: CI/CD Through This Textbook

This appendix follows one change through the automation that builds and publishes this book. The example is small enough to inspect completely, but it contains the same boundaries found in a scientific service or machine-learning product: reviewed source, clean builds, immutable artifacts, named environments, scoped authority, post-deployment verification, and recovery.

No prior knowledge of CI/CD is assumed. The objective is not to memorize a particular GitHub Actions syntax. It is to learn which claim each stage makes, which evidence supports that claim, and which authority allows the system to change public state.

After working through this appendix, you should be able to:

- distinguish continuous integration, continuous delivery, and continuous deployment;
- distinguish source, a build, an artifact, a release, a deployment, and an environment;
- trace a pull request, a merge to `main`, and a version tag through this repository's workflows;
- explain why a later stage should promote the artifact that an earlier stage verified rather than rebuild it;
- read a deployment manifest and verify an artifact with a checksum;
- identify the permissions and human decisions that control publication; and
- design a rollback or roll-forward response that preserves evidence.

C.1 A public system has more state than its source

A source file is not a deployed system. The LaTeX sentence being read now is source. The compiled PDF is an artifact. A named collection containing that PDF, a Python wheel, and a source archive is a release bundle. A copy of the PDF served from the public course site is a deployment. These objects can agree or disagree. A disciplined pipeline makes their relationships explicit.

Object	Meaning	Identity in this repository
Source revision	One immutable state of version-controlled inputs	Complete Git commit identifier
Build	Process that transforms source into outputs	A particular workflow job and its logs
Artifact	Bounded output intended to move between stages	Static-site archive, PDF, wheel, or source distribution
Environment	Named destination with configuration and policy	`github-pages` or `course-release`
Deployment	Placement of an artifact into an environment	One GitHub Pages deployment record
Release	Named statement that artifacts represent a version	GitHub Release attached to `course-vX.Y.Z`

The word *environment* is overloaded. A Python virtual environment isolates an interpreter and installed packages. A deployment environment names a destination such as staging or production and may impose approval, configuration, and secret policies. Context must identify which meaning is intended.

Professional practice

A branch name such as `main` is movable. It is convenient for navigation, but it is not sufficient artifact identity. A defensible record binds public state to an immutable commit identifier and, when relevant, an artifact digest and release tag.

C.2 The three terms in CI/CD

Continuous integration (CI) automatically tests an integrated source revision in a clean environment. A pull request is a candidate integration. CI asks whether the candidate satisfies the repository's encoded contracts before it enters the protected branch.

Continuous delivery automatically produces a verified, releasable artifact but retains an explicit decision before production publication. The software is continuously in a state that *could* be released. A reviewer, scheduled window, regulatory control, or business decision may govern the last promotion.

Continuous deployment automatically publishes every qualifying change. There is no manual approval between the verified candidate and the production deployment. This does not remove control. Review, tests, branch protection, scoped permissions, deployment policy, smoke tests, and monitoring remain controls.

Thus the slash in "CI/CD" is ambiguous. State whether *CD* means delivery or deployment for the system under discussion. This repository uses both:

- the course site uses continuous deployment from reviewed `main`; and
- a versioned course release uses continuous delivery to a protected approval boundary, followed by an approved publication.


Neither choice is intrinsically mature. The appropriate choice follows from consequence, reversibility, regulation, available evidence, and recovery cost. A static site can be replaced quickly and carries no database migration. A clinical model service has a different release boundary.

C.3 The running system

The repository contains four related products:

1. LaTeX source under `textbook/`;
2. a compiled PDF under `output/pdf/`;
3. the `rice_dsm` Python distribution built from `src/`; and
4. a static course site built from reviewed files under `site/`.

The textbook is therefore both an explanation of delivery and a delivered artifact. The workflows are executable course material. Their checked-in YAML is the authority when an excerpt in the prose and the live configuration ever differ.



The upper path is integration. The lower path is deployment. Passing the upper path does not imply that the lower path ran, and a successful upload in the lower path does not imply that users can retrieve the expected artifact. The final smoke test addresses that last boundary.

C.4 Path one: a pull request becomes verified source

The `course-ci.yml` workflow responds to pull requests, pushes to `main`, and manual dispatch. It creates one job for each supported operating system. Every job:

1. checks out the exact revision without retaining write credentials;
2. installs the pinned `uv` tool and Python version;
3. reproduces the dependency graph from `uv.lock`;
4. prepares the installed package and named notebook kernel;
5. checks Python style;
6. builds the wheel and source distribution; and
7. executes package, repository, and notebook tests.

The matrix is not three redundant green lights. It probes distinct path, filesystem, shell, process, and environment behavior. A hard-coded POSIX path may pass on Linux and fail on Windows. A case mismatch may pass on a case-insensitive filesystem and fail elsewhere.

After the matrix completes, a stable job named `CI gate` requires the entire matrix to succeed. Branch protection can require this one name even when the internal matrix changes. The gate makes evidence consequential: a failed candidate cannot enter protected `main` through the ordinary merge path.

Other workflows add narrower evidence. The textbook workflow compiles relevant LaTeX changes, rejects unresolved references and layout warnings, and uploads the PDF for review. Dependency review examines newly introduced dependency risk. The pull-request labeler assigns review areas without checking out or executing untrusted pull-request code.

Checkpoint

A pull request receives a green `CI gate`, but the new statistical test uses the wrong null hypothesis. What has CI established? What has it not established? Identify the missing review evidence without claiming that CI is useless.

C.5 Path two: `main` becomes a public course site

The `course-pages.yml` workflow is the repository's real continuous deployment example. A relevant merge to `main` triggers the path. Manual dispatch is also available, but the build job checks that the selected revision is

`main`; a feature branch cannot use that route to deploy itself.

C.5.1 Build a bounded artifact

The workflow compiles the textbook, checks the LaTeX log, and runs `scripts/build_course_site.py`. The builder creates an empty output tree containing only:

- the generated landing page and fallback page;
- reviewed style and icon assets;
- the compiled textbook at a stable public path; and
- a machine-readable deployment manifest.

The builder refuses to merge files into a nonempty output directory. Without that check, a file left by an earlier run could survive even though the current source no longer produces it. Clean output is a simple defense against stale artifact state.

The site artifact is deliberately smaller than the repository. It excludes tests, source history, local data, caches, notebook outputs, development tools, and secrets. A deployment boundary should state what enters production rather than publish whatever happens to be nearby.

C.5.2 Record identity in a manifest

The generated `manifest.json` binds the deployment to its inputs and primary artifact:

```
{
  "course": "CMOR 438 / INDE 577",
  "package_version": "0.1.0",
  "revision": "8e66ba305f7bb22e5459a4c039999250e29aa35a",
  "generated_at": "2026-08-30T18:00:00Z",
  "artifacts": {
    "textbook": {
      "path": "textbook/data-science-machine-learning-textbook.pdf",
      "bytes": 765614,
      "sha256": "1119dc07f6a9a5cee16444c3272ac67d032c84c4fd1856f77054716595e8691f"
    }
  }
}
```

The concrete values above illustrate one local build and will change. The commit identifier answers which source was built. The byte count catches gross truncation or substitution. SHA-256 supplies a content digest: changing one byte is expected to change the digest. A matching digest proves identity with the recorded bytes under the hash assumption; it does not prove that the book's mathematics or prose is correct.

C.5.3 Promote and then observe

The build job uploads one Pages artifact. A separate deploy job downloads and promotes that artifact to the `github-pages` environment. It does not compile the text again. Only that job receives permission to write Pages and request the short-lived identity token required by the deployment mechanism.

After deployment, `scripts/smoke_test_course_site.py` requests the public page, manifest, and textbook. It checks the page identity, complete source revision, PDF signature, byte count, and SHA-256 digest. Retries

allow a new edge cache to converge, but retries are bounded. A persistent mismatch is a failed deployment, not an invitation to loop forever.

An operated model service needs the same identity in its telemetry. The repository's monitoring laboratory emits a `service_started` structured event and a `rice_dsm_model_info` metric containing model and release versions. Its dashboard annotates service starts and exposes release identity. Without this join between deployment and operating evidence, a team cannot compare symptoms before and after a release or know which artifact produced a prediction.

This verification distinguishes three claims:

Claim	Evidence	Remaining uncertainty
The artifact was accepted	Deploy action completed	Public routing or cache may still be wrong
The public site is reachable	HTTP request succeeded	It may expose an older or incorrect revision
The intended PDF is public	Revision, size, and digest match	Content may still contain an untested error

C.6 Path three: a version becomes an approved release

The course site answers "What is currently published?" A versioned release answers a different question: "Which immutable files constitute version *v*?" The `course-release.yml` workflow starts only from tags matching `course-v*`.

The version declared in `pyproject.toml` is the source of truth. If the package version is `0.1.0`, the release tag must be exactly `course-v0.1.0`. The tag must be annotated rather than lightweight:

```
git tag -a course-v0.1.0 -m "Course release 0.1.0"
git push origin course-v0.1.0
```

An annotated tag is a Git object with a tagger, message, date, and target. The workflow rejects a mismatched or lightweight tag before publication. It then reproduces the locked environment, reruns style and test checks, builds the Python distributions, compiles the textbook, and assembles:

- `data-science-machine-learning-textbook.pdf`;
- the versioned `rice_dsm` wheel;
- the versioned `rice_dsm` source archive;
- `release-manifest.json`; and
- `SHA256SUMS`.

The release builder selects exact distribution names for the declared version. A stale wheel with a similar name in a developer's `dist/` directory is not silently included. The checksum file allows a recipient to recompute the digest of every release file. Build provenance records that GitHub Actions produced the subjects from a particular repository workflow and revision.

Professional practice

Provenance and checksums answer origin and identity questions. They do not make malicious source safe, make a weak test suite sufficient, or establish that a model is scientifically valid. Supply-chain evidence composes with source review, testing, access control, and domain evidence; it does not replace them.

C.6.1 The approval boundary

The verified bundle is uploaded once as a workflow artifact. The publication job names the protected `course-release` environment and waits for its required reviewer. Approval authorizes public release of the already verified bundle. The job then downloads that exact bundle and attaches its files to the tag's GitHub Release.

This is continuous delivery because automation reaches a releasable state and stops at an explicit production decision. The decision should inspect evidence, not merely confirm that somebody clicked a button. A useful approval view includes the source revision, tag and project version, completed checks, artifact names and digests, known limitations, and rollback plan.

If publication is interrupted after creating the GitHub Release but before all attachments arrive, a rerun replaces the attachments with files from the verified workflow artifact. Idempotent or repairable operations matter because distributed systems can fail between two externally visible steps.

C.7 Build once, promote the same artifact

Suppose a build job tests PDF A, then an approval job checks out the same commit and recompiles PDF B for publication. Even with identical source, the outputs may differ because a dependency, compiler, clock, generated input, or configuration changed. Approval evidence about A does not necessarily apply to B.

The safer rule is:

> Build once. Identify the artifact. Verify it. Promote those same bytes.

Configuration may vary by deployment environment, but changing configuration should not silently mutate the artifact. A container image digest, wheel hash, or PDF checksum provides a stable subject for evidence. This separation also makes rollback concrete: retain a known-good artifact and its compatible configuration rather than hoping an old source revision can be rebuilt later.

Reproducible builds strengthen the design further by allowing independent builds to produce the same bytes. They do not eliminate the need to promote the verified artifact; reproducibility itself must be measured and maintained.

C.8 Authority is part of the pipeline

Automation that can only read source cannot publish. Automation that can write every repository resource has unnecessary authority. The workflows declare a read-only default and grant additional permissions to the narrow job that needs them.

Job	Additional authority	Reason
CI and build jobs	None beyond reading source	Untrusted or fallible build steps should not publish
Pages deploy job	Pages write and short-lived identity token	Promote the one uploaded Pages artifact
Release provenance job	Attestation write and identity token	Bind provenance to built subjects
Release publication job	Repository contents write	Create or repair assets on the tagged GitHub Release

The repository does not need a personal access token, AWS key, or other long-lived credential for these paths. GitHub supplies a short-lived repository token to each job, and job-level permissions narrow its use. Third-party actions still execute code with the job's available authority, so actions are pinned to immutable commit identifiers and updated through review.

If a later exercise deploys to a cloud provider, prefer workload identity or an equivalent short-lived exchange. Store unavoidable secrets in the platform's secret facility, scope them to the environment, prevent them from reaching untrusted pull-request code, mask them in logs, and plan rotation before an incident.

C.9 Failure is a state to diagnose

A pipeline is a state machine with evidence at each transition. "CI/CD failed" is too imprecise to diagnose.

Observed state	Likely boundary	First evidence
One matrix job fails	Platform-specific source or environment behavior	First causal traceback on that runner
All tests pass; site build fails	Artifact construction contract	Missing input, unresolved template marker, nonempty output
Deploy action fails	Hosting authority or environment policy	Deployment job, token permission, Pages configuration
Deploy succeeds; smoke fails	Public routing, cache, or artifact mismatch	Requested URL, manifest revision, byte count, digest
Release build rejects tag	Version identity policy	Tag object type and `pyproject.toml` version
Release waits	Protected environment decision	Reviewer and environment policy
Release exists with incomplete files	Interrupted publication	Release assets versus verified workflow artifact

Start with the earliest causal failure, not the last cascade message. Reproduce locally when the failing boundary exists locally. A Pages permission error cannot be reproduced by rerunning a unit test; a malformed manifest can.

Flaky tests deserve diagnosis. Repeatedly rerunning until green changes the sample, hides uncertainty, and

teaches the gate to accept noise. Record the failure, isolate nondeterminism, repair the test or system, and preserve a regression case.

C.10 Rollback and roll-forward

Static-site rollback is unusually simple because the artifact has no mutable database state. The normal repair is a focused revert or corrective pull request, followed by the same CI and deployment path used for forward changes. This preserves review, evidence, and an auditable transition. Directly editing files on a server creates unreviewed state that the next deployment will erase.

A published version tag should not be deleted and moved to different source. Doing so makes two consumers receive different bytes under the same name. Fix a bad `course-v0.1.0` release by incrementing the project to `0.1.1`, merging the correction, and publishing `course-v0.1.1`. This is a roll-forward.

Rollback becomes harder when a deployment mutates durable state. Old and new application versions may overlap during a rolling release. A database migration must often be backward-compatible until both versions no longer run. A model rollback may fail if the feature schema or population has changed. Recovery design must therefore name the state being reversed, compatibility assumptions, owner, trigger, and evidence of rehearsal.

C.11 A complete worked change

Consider a pull request that corrects one equation and changes one reusable Python function used by a notebook.

1. **Propose.** The branch records the source diff. The pull request explains the mathematical correction, interface consequence, and relevant tests.
2. **Integrate.** The CI matrix rebuilds the package and executes every notebook. The textbook workflow compiles the PDF and makes it available for visual review. Neither artifact is public production state.
3. **Review.** A reviewer examines the equation, API behavior, test evidence, and rendered page. The required `CI gate` passes.
4. **Merge.** The protected branch advances to the reviewed commit. This event makes the revision eligible for site deployment.
5. **Build.** The Pages workflow compiles the text and creates one bounded site artifact with a manifest naming the merge commit and PDF digest.
6. **Deploy.** The Pages job promotes the artifact to the public environment with narrowly scoped authority.
7. **Observe.** The smoke job requests the public artifacts and compares their identities with the manifest and expected commit.
8. **Release when intended.** If the change belongs to a named course version, the maintainer increments `pyproject.toml` through a pull request, creates the matching annotated tag after merge, inspects the release evidence, and approves publication.

The example contains two distinct public transitions. The site changes after merge; the immutable version changes only after a tag and approval. A team can choose other policies, but it must not blur these identities.

C.12 Inspect the system locally

Local execution cannot reproduce GitHub's identity tokens, environment approval, or Pages infrastructure. It can reproduce artifact construction and verification logic.

Build the text and site from the repository root:

```
make -C textbook
uv run python scripts/build_course_site.py \
  --revision local-preview \
  --textbook output/pdf/data-science-machine-learning-textbook.pdf
uv run python -m http.server 8000 --directory build/course-site
```

Open `http://localhost:8000` and inspect the page and `manifest.json`. Stop the server with `Ctrl+C`. Before rebuilding, remove only the generated `build/course-site/` directory; the builder's refusal to mix old and new output is intentional.

The following investigation distinguishes mechanisms:

1. Recompute the PDF SHA-256 digest with an operating-system tool or a short Python program and compare it with the manifest.
2. Change a copy of one byte in the PDF and recompute the digest. Do not modify the tracked course PDF for this experiment.
3. Explain why a new digest detects the change but cannot say whether the change improved the book.
4. Identify which workflow-only controls were absent from the local run.

C.13 Design exercises

1. Draw the state machine for the Pages workflow. Label every transition with its triggering event, required evidence, and authority.
2. Suppose the public page identifies the expected commit but the PDF hash differs. Give three non-equivalent hypotheses and the observation that would distinguish each.
3. Design a staging environment for a model API. State which artifact is promoted, which configuration varies, which tests run after deployment, and which evidence permits production release.
4. A release approver sees green tests but no visual PDF review. Should the release proceed? State the claim the missing review protects.
5. Extend the failure table for a database migration that succeeds on one replica and fails on another. Identify why restoring application code alone may be insufficient.
6. Compare a manual production approval with a fully automatic policy. Name one system for which each is reasonable and justify the difference from consequence and recovery evidence.
7. Write a release dossier for `course-v0.1.0`: source revision, artifacts, digests, checks, approver, limitations, and recovery action.

C.14 Operational checklist

Before calling a pipeline complete, ask:

- Is the source revision immutable and recorded?

- Does the build start from a clean, locked environment?
- Is each artifact bounded, named, and content-addressable by a digest?
- Do later stages promote the verified bytes without rebuilding?
- Are tests attached to risks at unit, integration, contract, system, and deployed boundaries as appropriate?
- Can untrusted source obtain a secret or publication permission?
- Does each job have only the authority required for its stage?
- Is the release decision automatic or manual, and is that policy stated?
- Does post-deployment verification observe the public boundary?
- Is recovery possible with a known-good artifact and compatible state?
- Will a future investigator be able to connect public behavior to source, configuration, evidence, and decision?

C.15 Summary

CI tests an integrated source candidate. Continuous delivery produces a verified releasable artifact and retains an explicit production decision. Continuous deployment publishes every qualifying change automatically. This repository uses all three ideas: a cross-platform required gate, automatic course-site deployment from protected `main`, and an approved tagged release of the textbook and Python package.

The central engineering invariant is not a product name or YAML keyword. It is the evidence chain:

> immutable source ⟶ bounded artifact ⟶ verification ⟶ authorized promotion ⟶ operational observation.

Breaking any arrow weakens the claim that a public result is the one that was reviewed and tested.

APPENDIX D

Course glossary

This glossary is a navigation aid, not a substitute for the chapters where each term is motivated and connected to examples. Acronyms are expanded here, but a definition also explains the concept's purpose and distinguishes it from nearby ideas. A term may have a more specialized meaning in another discipline; these are the working meanings used throughout the text.

Term	Working definition
agent	System in which a model may choose some sequence of actions from observations within externally enforced tools, policy, budgets, and stopping rules. The model is a component, not the whole agent.
activation function	Nonlinear transformation applied within a neural network. Without nonlinear activations, a composition of affine layers collapses to one affine map.
alert	Owned notification that a monitored symptom has satisfied a stated condition and duration. It initiates investigation but rarely proves a cause.
API	Application programming interface: a supported contract through which software components interact. It may be an in-process function/package API or a request/response web API.
API key	Secret credential used to identify or authorize an API caller; it may permit spending or data access.
array	Regular multidimensional collection governed by a shape and data type.
artifact	Identifiable output of a process, such as a package distribution, dataset snapshot, model file, container image, report, or compiled application.
authentication	Process of establishing which identity is making a request. It answers "Who are you?" and does not by itself decide what that identity may do.
authorization	Decision about whether an authenticated identity may perform a specific action on a specific resource.
branch	Movable Git reference that points to a commit. A branch provides a name for one line of work; it is not a copied project directory.
axis	One dimension of an array together with its domain meaning, such as observations, features, time points, or simulation runs.
backend	Server-side code implementing interfaces, policy, orchestration, and integrations.
broadcasting	NumPy rules that allow compatible array dimensions, especially dimensions of size one, to participate in an operation without explicitly copying repeated values. Dimensional compatibility does not prove semantic compatibility.
calibration	Agreement between predicted probabilities and observed event frequencies on a named population. Calibration differs from ranking ability and can change when the population changes.

Term	Working definition
CD	Continuous delivery or continuous deployment, depending on the stated workflow. Delivery keeps an explicit production-release decision; deployment automates that decision for qualifying changes.
CI	Continuous integration: automated checks of integrated changes in a clean environment.
CLI	Command-line interface: a contract based on command arguments, standard input/output, messages, and exit status.
client	Browser, device, script, or service that makes a request to an API.
commit	Git object recording a project snapshot, metadata, message, and parent commit or commits. A commit is local until its history is transferred to a remote.
container	Running or stopped process instance created from a container image with configured filesystem, network, resource, and environment boundaries.
container image	Immutable, content-identifiable template containing a filesystem and startup contract from which containers are created.
cross-validation	Resampling design that rotates training and validation roles to estimate a procedure under the population assumptions encoded by its folds. Grouped and temporal variants estimate different use settings.
data provenance	Evidence about the origin, transformations, versions, and ownership of data.
DataFrame	pandas table with named columns, an index, and potentially different data types across columns. It is an in-memory representation, not a database.
database	Organized persisted data plus its logical structure.
DBMS	Database-management system: software that stores, queries, coordinates, and protects database state.
dependency	External package or component whose behavior a project uses.
deployment	Placement of an identified artifact into a named environment under specified configuration and policy; it is not synonymous with build or release.
DNS	Domain Name System: distributed naming infrastructure that resolves names such as a service hostname to routing information such as an IP address.
distribution	Installable Python project with metadata and packaged files.
dtype	NumPy data type governing the representation and operations of array elements, including numerical range, precision, and missing-value strategy.
error budget	Failure permitted by a service-level objective over its window, used to reason about reliability risk and release pace.
endpoint	One web-API operation commonly identified by an HTTP method and path.
ensemble	Predictor formed by combining multiple fitted learners. Bagging, boosting, voting, and stacking use different combination mechanisms and should not be treated as synonyms.
environment	Collection of runtime configuration and installed dependencies available to a process. A virtual environment is one Python-specific mechanism for isolating such state.

Term	Working definition
feature	Measurable or constructed input supplied to a model. A feature's definition includes its population, time of availability, units, and transformation history.
fork	GitHub-hosted repository related to another repository and owned under a different account or organization, commonly used to propose changes without write access to the source repository.
frontend	Code and assets that present state and interaction to a user.
generator	Iterator commonly created by a function that yields values while preserving suspended state.
Git	Distributed version-control system that records project snapshots and their relationships in a repository.
GitHub	Hosted collaboration platform for Git repositories, pull requests, reviews, issues, Actions, releases, and access control. Git and GitHub are distinct systems.
HTTP	Application protocol carrying requests and responses between networked software components.
HTTPS	HTTP carried through Transport Layer Security so that endpoints can authenticate the server and protect data in transit. It does not validate the scientific truth of the payload.
idempotency	Property that repeating the same logical operation does not create additional effects beyond the first successful application.
import package	Python namespace organizing related modules.
inference	Running a trained model to produce scores, predictions, generated content, or other output.
label	Observed target value attached to an example for supervised learning. The term does not guarantee that the value is correct, contemporaneous, or free of measurement and selection processes.
leakage	Use during model construction of information that is unavailable at the intended prediction time or improperly crosses an evaluation boundary.
loss function	Numerical function that assigns cost to a prediction and target and thereby defines a training or comparison objective. It need not be the same as the reported metric or operational decision cost.
integration test	Test that exercises a meaningful boundary between real components, such as application code and an actual database engine.
invariant	Condition that must remain true for every valid state or after every supported operation of an object or system.
iterator	Stateful object that yields the next value in a traversal.
join cardinality	Expected relationship between keys on two sides of a join, such as one-to-one, one-to-many, or many-to-many; it predicts possible row multiplication.
JSON	Text representation for objects, arrays, strings, numbers, Booleans, and null; it is a representation, not an API or domain schema by itself.
kernel	Long-running process that receives notebook code, retains state, and returns results.

Term	Working definition
lockfile	Recorded resolved dependency graph used to reproduce an environment.
LLM	Large language model: a model trained to represent and generate sequences of tokens. A model is one component of an assistant or agent system.
metric	Quantitative summary with a defined population, units, aggregation, and interpretation; operational metrics also support monitoring.
model	Mathematical or computational representation that maps input to scores, distributions, categories, generated objects, or action proposals.
model artifact	Versioned release object binding fitted state to its feature schema, transformations, output semantics, runtime, provenance, and evaluation evidence. Parameters alone are not a complete artifact contract.
model monitoring	Repeated examination of feature validity, populations, scores, decisions, slices, joined outcomes, and model and policy identity.
merge	Git operation that integrates histories and, when necessary, creates a commit with multiple parents. A conflict asks a human to choose final content.
module	Importable Python file.
monitoring	Repeated evaluation of selected evidence and conditions. A dashboard or alert can participate without making a system observable.
NumPy	Python package providing multidimensional arrays and numerical operations. Its array API makes shape, axes, and data type central.
object	Runtime value with a type, identity, and associated behavior.
object storage	Service that stores byte objects under keys with metadata; it is not an ordinary local filesystem or relational database.
orchestrator	System that owns durable workflow state, schedules, dependencies, retries, concurrency, and recovery.
observability	Ability to investigate a system's behavior from evidence such as logs, metrics, traces, and client outcomes. It is a system property, not the name of one monitoring product.
package API	Supported names and behaviors a package intends callers to use.
pandas	Python package for labeled Series and DataFrame operations. Labels make alignment explicit but do not establish data validity.
parameterized query	Database query in which values are bound separately from SQL syntax, protecting representation and reducing injection risk. Dynamic identifiers require a different controlled design.
port mapping	Rule forwarding traffic from a host address and port to a port at a process or container boundary.
prompt injection	Untrusted content attempting to redirect a model-driven system or expand its authority. The durable defense is to keep authority in application policy rather than in untrusted text.
pull request	GitHub review record proposing that changes from one branch be integrated into another. It connects a diff, discussion, reviews, commits, and automated checks.

Term	Working definition
random seed	Initializer used to reproduce a particular pseudorandom stream. A seed supports repeatability but does not prove robustness or model validity.
request	Operation, metadata, and optional input sent by a client to an API.
response	Status, metadata, and optional result or error data returned by a server.
remote	Named Git configuration referring to another repository location. `origin` is a conventionally assigned name, not a special server.
registry	Service that stores, identifies, and distributes artifacts such as container images or model versions under access and retention policy.
release	Named, reviewed statement that a bounded set of identified artifacts represents a version suitable for stated use.
repository	Version-controlled project directory containing source, configuration, tests, and documentation.
runbook	Reviewed operational procedure containing safe checks, authority limits, mitigations, escalation, and verification for a class of symptoms.
schema	Explicit structure and constraints for data or messages.
SDK	Software development kit: client libraries and tools that help developers use a platform or API.
server	Process that receives requests and provides responses or services.
shape	Ordered tuple giving the number of array elements along each axis. Shape describes dimensions; domain knowledge supplies their meaning.
staging area	Git's proposed content for the next commit, also called the index. It permits selected changes to form one coherent snapshot.
supervised learning	Estimation of a prediction rule from observations paired with targets under a stated population, information, loss, and evaluation contract.
target	Outcome a supervised-learning task attempts to estimate. Its definition includes measurement process, time or horizon, units, and eligible population.
service-level objective	Measurable target for a user-relevant aspect of reliability over a defined interval.
service-level indicator	Measured user-relevant quantity, including its population, units, aggregation, exclusions, and time window.
span	Timed operation within a trace, carrying controlled attributes and relationships to parent and child work.
structured log	Machine-readable event record with named fields and controlled content.
telemetry	Evidence emitted about a running system, including selected logs, metrics, traces, and client outcomes, subject to privacy and retention policy.
test oracle	Independent basis for deciding whether observed behavior is acceptable.
TLS	Transport Layer Security: protocol used to authenticate an endpoint and protect network data in transit. It does not authorize application actions.
tool	Narrow application operation that an agent or workflow may request. Application code, not the model's description, enforces the tool's argument, authorization, resource, and side-effect contract.
trace	Causal record linking work across components, commonly as related spans.

Term	Working definition
transaction	Group of database operations treated as an atomic success or rollback boundary.
training	Procedure that uses observations to choose fitted parameters or state. Training-objective improvement does not by itself establish generalization or scientific validity.
type	Family of objects and associated operations and behavior.
unit test	Focused test of one coherent behavior with controlled inputs. A unit is defined by the behavior under test, not necessarily by a single function.
vectorization	Expression of related operations through an array interface so looping is performed by optimized lower-level code. It does not eliminate computational complexity or memory cost.
virtual environment	Project-specific Python installation context used to isolate dependencies.
volume	Container-managed persistent storage whose lifecycle is distinct from one container instance.
web API	Request/response interface exposed across a process or network boundary, often using HTTP.
workflow	Mostly predetermined graph of steps, decisions, inputs, and outputs. Unlike an agent, it does not generally ask a model to choose the action sequence at runtime.

Checkpoint

Select five neighboring concepts that are easy to confuse, such as SDK, API, service, server, and model. Draw them as distinct boxes and label what crosses each boundary.

Where the book goes next

Parts I and II establish the computational systems foundation and a complete supervised-learning arc from prediction contract to monitored release. A later part will develop unsupervised and representation-learning methods, followed by modern applications and scientific discovery. Each part will preserve the same standard: mathematical argument, executable investigation, reusable software, and evidence about operation.

Index

action, 103
application programming interface, 52
array, 38

backend, 59

Calibration, 112
client, 59
conditional probability, 103
Continuous delivery, 234
continuous delivery, 35
Continuous deployment, 234
continuous deployment, 35
Continuous integration, 234
continuous integration, 35

database, 46
database-management system, 46
DataFrame, 40
Discrimination, 112
distribution, 33
dtype, 39

encapsulation, 31
epoch, 97
evaluation setting, 67

fixture, 36
frontend, 59
functional margin, 119

generator, 23
Git, 211
GitHub, 211

heavy-ball method, 97
hypothesis class, 67

import package, 33
inductive bias, 68
iterable, 23
iterator, 23

kernel, 16

Leakage, 79
learning algorithm, 67
learning rule, 75
logit, 103

model class, 75
module, 33

objective, 67
observed outcome, 103
odds, 106

path, 15
postactivation, 104
preactivation, 104
prediction rule, 75

representation, 67

schema, 46
script, 33
Series, 40
spectrum effect, 113
string, 22

time to quality, 100

virtual environment, 16

workflow, 228