

Lab 1 (3 points)

Exploring Data

This Lab uses the College data set, which can be found in the file College.csv. It contains a number of variables for 777 different universities and colleges in the US. The variables are

- Private: Public/private indicator
- Apps: Number of applications received
- Accept: Number of applicants accepted
- Enroll: Number of new students enrolled
- Top10perc: New students from top 10% of high school class
- Top25perc: New students from top 25% of high school class
- F.Undergrad: Number of full-time undergraduates
- P.Undergrad: Number of part-time undergraduates
- Outstate: Out-of-state tuition
- Room.Board: Room and board costs
- Books: Estimated book costs
- Personal: Estimated personal spending
- PhD: Percent of faculty with Ph.D.'s
- Terminal: Percent of faculty with terminal degree
- S.F.Ratio: Student/faculty ratio
- perc.alumni: Percent of alumni who donate
- Expend: Instructional expenditure per student
- Grad.Rate: Graduation rate

Before reading the data into R, it can be viewed in Excel or a text editor.

- (a) Use the `read.csv()` function to read the data into R. Call the loaded data `college`. Make sure that you have the directory set to the correct location for the data.
- (b) Look at the data using the `fix()` function. You should notice that the first column is just the name of each university. We don't really want R to treat this as data. However, it may be handy to have these names for later. Try the following commands:

```
> rownames (college )=college [,1]  
> fix (college )
```

You should see that there is now a `row.names` column with the name of each university recorded. This means that R has given each row a name corresponding to the appropriate university. R will not try to perform calculations on the row names. However, we still need to eliminate the first column in the data where the

names are stored. Try

```
> college = college[, -1]
> fix (college )
```

Now you should see that the first data column is Private. Note that another column labeled row.names now appears before the Private column. However, this is not a data column but rather the name that R is giving to each row.

(c) i. Use the summary() function to produce a numerical summary of the variables in the data set.

ii. Use the pairs() function to produce a scatterplot matrix of the first ten columns or variables of the data. Recall that you can reference the first ten columns of a matrix A using A[,1:10].

iii. Use the plot() function to produce side-by-side boxplots of Outstate versus Private.

iv. Create a new qualitative variable, called Elite, by binning the Top10perc variable. We are going to divide universities into two groups based on whether or not the proportion of students coming from the top 10% of their high school classes exceeds 50%.

```
> Elite = rep ("No", nrow(college ))
> Elite [college$Top10perc > 50] = " Yes"
> Elite = as.factor (Elite)
> college = data.frame(college , Elite)
```

Use the summary() function to see how many elite universities there are. Now use the plot() function to produce side-by-side boxplots of Outstate versus Elite.

v. Use the hist() function to produce some histograms with differing numbers of bins for a few of the quantitative variables. You may find the command par(mfrow=c(2,2)) useful: it will divide the print window into four regions so that four plots can be made simultaneously. Modifying the arguments to this function will divide the screen in other ways.

(d) i. Which of the predictors are quantitative, and which are qualitative?

ii. What is the range of Enroll? What are the mean and standard deviation?

iii. Now remove the 100th through 200th observations. What are the range, mean, and standard deviation of Enroll in the subset of the data that remains?