```
You, last month | 1 author (You)
//! Math Function
/*
    ! include :
        #include <cmath>

    // functins :
        is a part of code (built in - user defined)
        that write once and use it in different places
        ~ note :
            you can use function inside function    You, last month • minishell
            the result of in function will be the input of the outside function

        ! link of the math library:
            https://en.cppreference.com/w/cpp/header/cmath.html

    ! functions
        ! 1) sqrt  (squair root)
            % description :
                ? this function used to get the squair root of the number
            % prototype :
                $ sqrt (number or number variable)
            % return :
                # double number
            % example (negative , positive) :

        ! 2) round (Rounding numbers)
            % description :
                ? this functions used to round number to the closest integer number
                .5 and up --> go to next number
                .4 and lss --> still in current number
            % prototype :
                $ round(number)
            % return :
                # int number
            % example (negative , positive) :

        ! 3) pow (power function)
            % description :
                ? this function used to power the number
            % prototype :
                ? pow ( basis  number , exponent number)
            % return :
                # int number
            % example (negative , positive) :
```

```
! 4) ceil & floor (ceil & floor functions)
    % description :
    $ ceil  :
    ? this function used to trancate number to the bigest number even if .1 and up
    $ floor  :
    ? this function used to  trancate number to the smallest number even if .1 and up
    % prototype :
    $ ceil  :
        ? ceil (number)
    $ floor  :
        ? floor (number)
    % return :
        # int number
    % example (negative , positive) :

! 5) abs (absolute function)
    % description :
        ? this function used to convert number to positive
    % prototype :
        ? abs (number)
    % return :
        # number
    % example (negative , positive) :


*/
```