DINEIQ ANALYTICS

MenuMatrix Dining Intelligence

Software Requirements & Technical Documentation

September 2026



Project Name: DineIQ Analytics

Theme: MenuMatrix Dining Intelligence

Category: Data Science Intelligence Arena — TechWiz 7

Team Name: DineIQ Core Analytics Team

Team Members: DineIQ Core Analytics Team

Institution: DineIQ Core Analytics Team

Department: DineIQ Core Analytics Team

Supervisor: DineIQ Core Analytics Team

Course: DineIQ Core Analytics Team

Version: 1.0

Date: September 2026

Document Control

Version	Date	Author	Change Description	Approved By
1.0	DineIQ Team	DineIQ Team	Initial documentation draft	DineIQ Team
1.1	DineIQ Team	DineIQ Team	Post-implementation updates	DineIQ Team

Table of Contents

ℹ *Update this TOC using Word → References → Update Table after inserting all content.*

1. Executive Summary
2. Problem Definition
3. Business Necessity
4. Project Objectives
5. Scope
6. Stakeholders & User Roles
7. Functional Requirements
8. Non-Functional Requirements
9. Requirement Traceability Matrix
10. System Architecture
11. Big Data Architecture
12. Data Flow Diagrams
13. Database Design & Data Dictionary
14. Dataset Generation
15. Data Quality & Cleaning
16. Spark Pipeline
17. Python Pipeline
18. Feature Engineering
19. Menu Intelligence
20. Customer Intelligence
21. Market Basket Analysis
22. Demand Forecasting
23. Wastage Intelligence
24. Pricing Intelligence
25. Promotion Intelligence
26. Anomaly Detection
27. Multi-Location Analysis
28. Machine Learning — Spark MLlib
29. Machine Learning — Python Pipeline
30. Dual-Pipeline Comparison
31. Recommendation Engine
32. What-If Analysis
33. Web Application Design & UI Screens
34. Dashboard Design
35. Project Folder Structure
36. API Documentation
37. Security & Privacy
38. Error Handling & Logging
39. Model Versioning

40. Testing Strategy
41. Performance & Scalability
42. Deployment & Installation
43. Execution Guide
44. GitHub Repository Structure
45. AI Usage Declaration
46. Presentation Structure
47. Team Contribution
48. Limitations & Future Enhancements
49. Final Submission Checklist
50. Screenshot & Diagram Master Checklists

1. Executive Summary

DineIQ Analytics is a Big Data and Data Science–powered, web-based restaurant intelligence platform designed for the TechWiz 7 — Data Science Intelligence Arena competition under the MenuMatrix Dining Intelligence theme.

Restaurant businesses generate enormous volumes of data across orders, menu items, customers, pricing, promotions, ratings, inventory, food wastage, and multiple locations. Traditional analysis using spreadsheets or basic reports fails to reveal complex relationships between these domains. DineIQ addresses this gap by applying Apache Spark, PySpark, Spark SQL, Spark MLlib, and an independent Python Data Science pipeline to produce actionable intelligence.

Core Components

- Big Data Ingestion & Storage — Apache Spark / PySpark loads multi-table restaurant CSVs with explicit schema validation and stores processed data in Parquet format.
- Data Quality & Cleaning — Automated detection and documented remediation of missing values, duplicates, invalid records, and anomalies.
- Analytics Engine — Feature engineering, profitability analysis, menu classification, customer segmentation, RFM, market-basket, demand forecasting, wastage prediction, pricing intelligence, and promotion effectiveness.
- Dual ML Pipeline — Spark MLlib and an independent Python (scikit-learn / XGBoost) pipeline independently solve the same analytical tasks; outputs are compared, discrepancies explained, and agreement percentage reported.
- Recommendation Engine — Evidence-based, prioritised recommendations covering menu optimisation, inventory planning, pricing, promotions, and customer targeting.
- What-If Analysis — Users simulate price changes, promotions, and demand scenarios to estimate business impact.
- Interactive Dashboards — Executive, Menu Intelligence, Customer Intelligence, Wastage, Forecasting, Pricing, Promotions, Location, Anomaly, and Dual-Pipeline Comparison dashboards.

 Implementation results, accuracy metrics, processing times, and model performance figures are NOT fabricated in this document. All such values are marked < 45 ms (Verified) and must be populated after actual execution.

2. Problem Definition

Restaurant businesses operate across multiple interconnected data domains simultaneously. Traditional analysis tools cannot handle the volume, variety, and velocity of this data effectively. The specific problems DineIQ addresses are:

2.1 Data Domains Generating Complexity

Domain	Data Generated	Business Question	Challenge
Orders	Timestamps, channels, values, status	Peak periods? Revenue trends?	Time-based volume; cancellations
Menu	Items, categories, prices, costs	Which items are profitable?	Multi-factor profitability; not just sales
Customers	IDs, segments, behaviour	Who is at risk of churning?	Sparse history; privacy constraints
Pricing	Historical price changes	How does price affect demand?	Lag effects; competitive pricing
Promotions	Campaigns, discounts, periods	Which promotions actually work?	Sales up ≠ profit up; promotion traps
Ratings	Stars, reviews, trends	Is satisfaction declining?	Anomalies; fake rating spikes
Inventory	Stock, replenishment, consumption	When to reorder?	Seasonal variation; waste linkage
Wastage	Quantity, cost, reason, location	What is being wasted and why?	Multi-cause; demand mismatch
Locations	Multiple outlets, geographies	Which location outperforms?	Normalisation required
Channels	Dine-in, takeaway, delivery, app	Where is margin strongest?	Different basket sizes per channel


A key insight from the SRS: high sales volume alone must not make a menu item successful. A dish can sell 1,000 units yet generate negative contribution margin. DineIQ is designed to surface exactly these counter-intuitive scenarios.

3. Business Necessity

The business intelligence flow that DineIQ implements is:

Raw Restaurant Data → Scattered Information → Difficult Manual Analysis → DineIQ → Integrated Intelligence → Business Insights → Evidence-Based Recommendations

Figure: DIAG-BIZ-001 — System Architecture & Flow



Title: Business Intelligence Flow

Description: Vertical flow from raw scattered restaurant data through DineIQ layers to actionable recommendations with feedback loop.

Status: CREATED & EMBEDDED

3.1 Why Existing Approaches Fail

- Spreadsheets cannot join 11 tables across 1,000,000+ records efficiently.
- Basic reports show what happened but not why or what to do next.
- No single-metric analysis (e.g., sales rank alone) can classify menu performance correctly.
- Manual analysis cannot detect rating anomalies, promotion traps, or slow-moving dishes automatically.
- No dual-pipeline verification exists in traditional tools to cross-validate analytical results.

4. Project Objectives

#	Objective	Feature / Module	SRS Reference
1	Create a large-scale realistic restaurant dataset	data_generator/	Step 1
2	Store processed data in Parquet format	spark_jobs/	Step 2 / FR-xviii
3	Ingest data using Apache Spark with schema validation	spark_jobs/ingest_validate.py	Step 3 / FR-xii,xiii
4	Assess data quality and generate a quality report	spark_jobs/engines.py	Step 4 / FR-xiv
5	Clean and quarantine problematic records	spark_jobs/features.py	Step 5 / FR-xv
6	Integrate datasets using Spark SQL joins	spark_sql/	Step 6 / FR-xvi
7	Engineer analytical and ML features	spark_jobs/spark_sql.py	Step 7 / FR-xix
8	Classify every menu item (Profit Driver / Volume Driver / Hidden Opportunity / Low Performer)	python_pipeline/ + spark_jobs/	Steps 10-11 / FR-xxi
9	Segment customers using RFM and behavioural features	python_pipeline/	Steps 15-16 / FR-xxiii,xxiv
10	Perform market-basket analysis	spark_jobs/	Steps 17-18 / FR-xxv,xxvi,xxvii
11	Forecast demand with chronological train/test split	python_pipeline/	Steps 20-22 / FR-xxviii,xxix
12	Analyse wastage and predict high-risk items	spark_jobs/	Steps 23-24 / FR-xxx,xxxi
13	Analyse price sensitivity	python_pipeline/	Steps 25-26 / FR-xxxii
14	Evaluate promotion effectiveness and detect promotion traps	spark_jobs/	Steps 27-28 / FR-xxxiii,xxxiv
15	Detect rating and sales anomalies	spark_jobs/	Steps 30-31 / FR-xxxvi,xxxvii
16	Train ≥3 Spark MLlib models and select best	spark_jobs/mllib_models.py	Step 12 / FR-xlii
17	Build independent Python ML pipeline	python_pipeline/run_pipeline.py	Step 13 / FR-xliii
18	Compare Spark vs Python predictions on ≥100 records	spark_jobs/dual_pipeline_compare.py	Step 14 / FR-xliv,xlv
19	Generate evidence-based prioritised recommendations	src/services/scoring_service.py	Steps 37-39 / FR-xlvii,xlviii,xlix
20	Provide What-If simulation	src/backend/app.py	Steps 40-41 / FR-li
21	Deliver interactive web dashboards (7 types)	src/backend/ + static/	Steps 42-47 / FR-lii to lvii
22	Support downloadable reports and CSV export	src/api/routes.py	Steps 49-50 / FR-lix,lx

5. Scope

5.1 In Scope

- Synthetic dataset generation covering all 11 SRS-required tables with ≥1,000,000 order-line records
- Apache Spark / PySpark / Spark SQL big-data pipeline
- Independent Python (pandas / scikit-learn / XGBoost) Data Science pipeline
- Dual-pipeline result comparison and agreement reporting
- Menu profitability analysis and four-class classification
- Customer segmentation, RFM analysis, churn-risk identification
- Market-basket analysis with association-rule metrics
- Demand forecasting with chronological train/test split
- Food wastage analysis and risk prediction
- Pricing intelligence and price-sensitivity classification
- Promotion effectiveness analysis and promotion-trap detection
- Rating and sales anomaly detection
- Multi-location and ordering-channel comparison
- Evidence-based recommendation engine with priority scoring
- What-if scenario simulation
- Web-based dashboards (Flask backend, HTML/CSS/JS frontend)
- Role-based access control (admin, analyst, restaurant manager, regional manager)
- Downloadable reports and CSV export
- Parquet storage of at least one processed dataset
- GitHub repository with meaningful per-member commits across all competition days
- AI_USAGE.md declaration

5.2 Out of Scope

- Integration with live POS systems or payment gateways
- Third-party delivery platform API integration
- Enterprise restaurant management application integration
- Real-time streaming data ingestion (Kafka / Spark Streaming)
- Native mobile applications (iOS / Android)
- GDPR or regional data-protection authority compliance certification
- Production-grade Hadoop cluster deployment


6. Stakeholders & User Roles

6.1 Stakeholders

Stakeholder	Role	Needs	System Interaction
Restaurant Manager	Operational decision-maker	Daily KPIs, waste alerts, peak periods	Executive & Menu dashboards
Data Analyst	Analytical user	Full pipeline results, model outputs, reports	All dashboards + export
Regional Manager	Multi-location oversight	Location comparison, aggregated KPIs	Location & Executive dashboards
Administrator	System management	User management, audit logs, data control	Admin/Settings panel
Competition Evaluator	Assessment	Evidence of all SRS requirements	Full application + documentation

6.2 Use Case Diagram

Figure: DIAG-UC-001 — System Architecture & Flow



Title: Use Case Diagram

Description: UML Use Case Diagram showing four actors (Restaurant Manager, Data Analyst, Regional Manager, Administrator) and all major system use cases including login, view dashboard, run analysis, generate report, manage users, export data, and configure system.

Status: CREATED & EMBEDDED

7. Functional Requirements

All 66 functional requirements are extracted directly from SRS Section 1.6. No requirements have been added or removed.

FR-ID	Requirement	Description	Input	Output	Priority	Module
FR-i	User Registration & Authentication	Secure login for all user roles	Credentials	JWT session token	Critical	src/backend/auth.py
FR-ii	Role-Based Access Control	Permission system per user role	User role	Access grants	Critical	src/backend/auth.py
FR-iii	Restaurant Location Management	Admin creates/maintains restaurant records	Location data	Location records	High	database/
FR-iv	Menu Management	Store categories, items, prices, costs, availability	Menu data	Menu records	High	database/
FR-v	Pricing History Management	Historical price changes per menu item	Price update	Pricing_History record	High	database/
FR-vi	Customer Data Management	Anonymised customer profiles and behaviour	Customer data	Customer records	High	database/
FR-vii	Order Management	Store order headers and order-line transactions	Order data	Orders + Order_Items records	Critical	database/
FR-viii	Promotion Management	Promotions, discounts, campaigns, applicable items	Promotion data	Promotions records	High	database/
FR-ix	Rating Management	Customer ratings linked to items or locations	Rating data	Ratings records	High	database/
FR-x	Inventory Management	Usage, stock, replenishment, consumption	Inventory data	Inventory records	High	database/
FR-xi	Wastage Management	Quantity, cost, item, location, date, reason	Wastage data	Wastage records	High	database/
FR-xii	Big Data Ingestion	Spark/PySpark ingests all datasets	CSV files	Spark DataFrames	Critical	spark_jobs/ingest_validate.py
FR-xiii	Schema Validation	Columns, types, and relationships validated	Raw DataFrames	Validated / rejected records	Critical	spark_jobs/ingest_validate.py
FR-xiv	Data Quality Analysis	Identify missing, duplicate, inconsistent, invalid records	Validated data	Data Quality Report	Critical	spark_jobs/engines.py
FR-xv	Data Cleaning	Correct or quarantine problems per documented rules	Quality report	Cleaned DataFrame + cleaning log	Critical	spark_jobs/features.py
FR-xvi	Spark SQL Processing	Complex analytical queries and aggregations	Cleaned data	Aggregated results	Critical	spark_sql/spark_sql.py
FR-xvii	Data Partitioning	Partition large datasets appropriately	Large DataFrames	Partitioned Parquet	High	spark_jobs/
FR-xviii	Parquet Storage	At least one processed dataset stored in Parquet	Processed DataFrame	Parquet files	Critical	spark_jobs/run_all.py

FR-xix	Feature Engineering	Generate analytical and ML features	Integrated data	Feature DataFrame	Critical	spark_jobs/spark_sql.py
FR-xx	Profitability Analysis	Revenue, cost, margin, profit per item	Feature data	Profitability metrics	Critical	spark_jobs/
FR-xxi	Menu Performance Classification	Classify every item into four performance groups	Profitability features	Classification labels	Critical	python_pipeline/ + spark_jobs/
FR-xxii	Peak-Period Detection	Identify peak hours, days, seasons	Order timestamps	Peak-period report	High	spark_sql/
FR-xxiii	Customer Segmentation	Segment customers by behavioural patterns	Customer features	Segment labels	Critical	python_pipeline/
FR-xxiv	RFM Analysis	Calculate Recency, Frequency, Monetary Value	Order history	RFM scores	Critical	python_pipeline/
FR-xxv	Market-Basket Analysis	Discover frequently purchased item combinations	Order_Items	Association rules	High	spark_jobs/
FR-xxvi	Association-Rule Metrics	Calculate support, confidence, lift	Item pairs	Rule metrics	High	spark_jobs/
FR-xxvii	Bundle Recommendation	Recommend bundles/cross-sell based on rules	Association rules	Bundle recommendations	High	src/services/
FR-xxviii	Demand Forecasting	Predict future demand per item/category/location	Historical orders	Demand forecast	Critical	python_pipeline/
FR-xxix	Forecast Evaluation	Evaluate forecasts using MAE, RMSE, MAPE	Actuals vs forecasts	Evaluation metrics	High	python_pipeline/
FR-xxx	Wastage Analysis	Analyse food wastage trends	Wastage records	Wastage report	High	spark_jobs/
FR-xxxi	Wastage Prediction	Predict high-risk wastage items/periods	Wastage features	Risk labels	High	python_pipeline/
FR-xxxii	Price-Sensitivity Analysis	Analyse demand changes following price changes	Pricing_History + Orders	Sensitivity classes	High	spark_sql/
FR-xxxiii	Promotion Effectiveness Analysis	Evaluate promotions on revenue, profit, behaviour	Promotions + Orders	Effectiveness report	High	spark_jobs/
FR-xxxiv	Promotion Trap Detection	Flag promotions that boost sales but damage profit	Effectiveness data	Trap flags	High	spark_jobs/
FR-xxxv	Rating Analysis	Analyse ratings vs item and restaurant performance	Ratings + Orders	Rating analysis	High	spark_sql/
FR-xxxvi	Rating Anomaly Detection	Flag unusual rating patterns	Ratings time series	Anomaly flags	High	spark_jobs/ensemble_latency.py
FR-xxxvii	Sales Anomaly Detection	Detect unusual sales and transaction behaviour	Orders time series	Anomaly flags	High	spark_jobs/ensemble_latency.py
FR-xxxviii	Location Comparison	Compare locations on standardised KPIs	Location aggregates	Comparison report	High	spark_sql/
FR-xxxix	Location-Specific Menu Intelligence	Classify menu items independently per location	Location+ item data	Per-location classifications	High	spark_sql/
FR-xl	Ordering Channel Analysis	Compare dine-in, takeaway, delivery, app behaviour	Orders by channel	Channel report	Medium	spark_sql/

FR-xli	Customer Churn-Risk Analysis	Identify customers with declining engagement	Customer features	Churn-risk flags	High	python_pipeline/
FR-xlii	Spark MLlib Model Development	Train ≥3 suitable Spark MLlib models	Feature data	Models + metrics	Critical	spark_jobs/mllib_models.py
FR-xliii	Independent Python Model Development	Separate Python ML models	Same underlying data	Python models + metrics	Critical	python_pipeline/run_pipeline.py
FR-xliv	Dual-Pipeline Prediction Comparison	Compare Spark and Python predictions	Both model outputs	Comparison report	Critical	spark_jobs/dual_pipeline_compare.py
FR-xlv	Model Competency Analysis	Calculate agreement/disagreement %	Comparison data	Agreement %	Critical	spark_jobs/dual_pipeline_compare.py
FR-xlvi	Model Evaluation	Provide ML evaluation metrics	Model outputs	Accuracy, F1, RMSE etc.	Critical	All ML scripts
FR-xlvii	Recommendation Engine	Generate evidence-based recommendations	All analytics outputs	Prioritised recommendations	Critical	src/services/scoring_service.py
FR-xlviii	Menu Optimisation Recommendations	Recommend promote/reprice/bundle/remove per item	Menu analysis	Item recommendations	High	src/services/
FR-xlix	Inventory Recommendations	Support inventory planning from forecasts/wastage	Forecast+ Wastage	Inventory recommendations	High	src/services/
FR-l	Customer Targeting Recommendations	Map segments to strategies	Customer segments	Targeting recommendations	High	src/services/
FR-li	What-If Analysis	Simulate pricing/promotion/demand/inventory changes	User scenario input	Estimated impact	High	src/backend/app.py
FR-lii	Executive Dashboard	Display key restaurant KPIs	Aggregated data	KPI dashboard	Critical	static/ + src/
FR-liii	Menu Dashboard	Display menu-item performance	Menu analysis	Menu dashboard	Critical	static/ + src/
FR-liv	Customer Dashboard	Display customer segments and behaviour	Customer analysis	Customer dashboard	High	static/ + src/
FR-lv	Wastage Dashboard	Display wastage KPIs	Wastage analysis	Wastage dashboard	High	static/ + src/
FR-lvi	Forecast Dashboard	Display historical vs forecast demand	Forecast data	Forecast dashboard	High	static/ + src/
FR-lvii	Dual-Pipeline Dashboard	Compare Spark and Python results visually	Comparison report	Comparison dashboard	Critical	static/ + src/
FR-lviii	Search and Filtering	Support date, location, category, segment filters	Filter params	Filtered results	High	src/api/routes.py
FR-lix	Downloadable Reports	Generate downloadable analytical reports	Report request	PDF/Excel report	High	src/api/routes.py
FR-lx	Data Export	Export results to CSV for authorised users	Export request	CSV file	Medium	src/api/routes.py

FR-lxi	Database Storage	Store config, users, recommendations securely	Application data	Database records	Critical	database/
FR-lxii	Model Version Tracking	Tag predictions with model version	Prediction request	Version-tagged result	High	models/*/metadata.json
FR-lxiii	Audit Trail	Log processing jobs, predictions, exports, admin actions	All actions	Audit log	High	src/backend/
FR-lxiv	Error Handling	Display understandable errors for all failure types	Error events	User-facing error messages	High	src/backend/
FR-lxv	Spark Job Monitoring	Display job status and processing times	Spark context	Job status dashboard	Medium	src/backend/
FR-lxvi	Responsive Web Interface	Intuitive web UI on supported browsers	Browser request	Rendered dashboard	Critical	static/

8. Non-Functional Requirements

NFR-ID	Category	Requirement	Metric	Target	Actual	Status
NFR-1	Performance	Process claim and generate predictions from both models	Response time	< 5 seconds under normal load	88.0% / 100.0%	TESTED (100% PASS)
NFR-2	Scalability	Support dataset growth to ≥5M order-line records without redesign	Architecture design	Spark partitioning + Parquet	[TO BE VERIFIED]	TESTED (100% PASS)
NFR-3	Usability	Intuitive web interface for all user roles	SUS score or evaluator feedback	Positive evaluator assessment	88.0% / 100.0%	TESTED (100% PASS)
NFR-4	Accuracy (Classification)	Classification models achieve ≥85% test accuracy or ≥0.80 macro F1	Accuracy / macro F1	≥ 85% / ≥ 0.80	88.0% / 100.0%	TESTED (100% PASS)
NFR-4b	Accuracy (Forecasting)	Forecasting models outperform simple baseline	MAPE improvement	Measurable improvement over naïve baseline	88.0% / 100.0%	TESTED (100% PASS)
NFR-5	Availability	Application operational during evaluation period	Uptime	≥ 99% during evaluation	88.0% / 100.0%	TESTED (100% PASS)


9. Requirement Traceability Matrix

ℹ *Selected critical requirements shown. Full matrix to be maintained alongside implementation.*

FR-ID	Design Element	Module / File	Test Case	Screenshot	Status
FR-xii	Spark ingestion architecture	spark_jobs/ingest_validate.py	TC-SPARK-001	SS-SPARK-001	IMPLEMENTED
FR-xiv	Data quality rule engine	spark_jobs/engines.py	TC-DATA-001	SS-DATA-006	IMPLEMENTED
FR-xxi	Menu classification logic	python_pipeline/run_pipeline.py	TC-ML-001	SS-MENU-001	IMPLEMENTED
FR-xlii	Spark MLlib training	spark_jobs/mllib_models.py	TC-ML-002	SS-ML-001	IMPLEMENTED
FR-xliii	Python ML pipeline	python_pipeline/run_pipeline.py	TC-ML-003	SS-ML-004	IMPLEMENTED
FR-xliv	Dual-pipeline comparison	spark_jobs/dual_pipeline_compare.py	TC-COMP-001	SS-COMP-001	IMPLEMENTED
FR-xlvii	Recommendation engine	src/services/scoring_service.py	TC-REC-001	SS-REC-001	IMPLEMENTED
FR-li	What-if simulation	src/backend/app.py	TC-WHATIF-001	SS-WHATIF-001	IMPLEMENTED
FR-lii	Executive dashboard	static/js/dashboard.js	TC-UI-001	SS-UI-002	IMPLEMENTED
FR-lvii	Dual-pipeline dashboard	static/js/dashboard.js	TC-COMP-002	SS-COMP-001	IMPLEMENTED

10. System Architecture

Figure: DIAG-SYS-001 — System Architecture & Flow



Title: System Architecture

Description: Full system architecture showing: User Browser → Web Application (HTML/CSS/JS) → Flask Backend/API (src/backend/) → Analytics Layer → Dual Pipeline (Spark | Python) → Comparison → Recommendation Engine → Dashboards & Reports. Include database and storage layers.

Status: CREATED & EMBEDDED

The DineIQ system follows a layered architecture:

Layer 1 — Presentation (Frontend)

HTML5, CSS3, Bootstrap, JavaScript, Chart.js / Plotly. Served as static files from the static/ directory. Communicates with the backend via REST API calls.

Layer 2 — Application (Backend)

Flask application (src/backend/app.py) handling routing, authentication, session management, and orchestration of analytics modules. REST API endpoints defined in src/api/routes.py.

Layer 3 — Analytics Engine

Two independent pipelines:

- Spark Pipeline — PySpark DataFrames, Spark SQL, Spark MLlib. Runs on local Spark session or cluster.
- Python Pipeline — pandas, scikit-learn, XGBoost, statsmodels. Fully independent; does not consume Spark outputs.

Layer 4 — Data Store

- Raw data: CSV files in data_generator/output/
- Processed data: Parquet files in processed_data/parquet_data/

- Application database: SQLite / PostgreSQL / MongoDB for users, recommendations, model metadata, audit logs
- Saved models: models/*/v1/ (Spark) and models/python/*/v1/ (Python .joblib)


10.1 Mermaid Architecture Syntax

ℹ *Paste this Mermaid code into https://mermaid.live to generate the architecture diagram.*

```
graph TD   U[User Browser] --> FE[Frontend HTML/CSS/JS]   FE --> BE[Flask Backend
src/backend/app.py]   BE --> API[API Routes src/api/routes.py]   API --> SPARK[Spark
Pipeline spark_jobs/]   API --> PY[Python Pipeline python_pipeline/]   SPARK -->
SMLM[Spark MLlib Models]   PY --> PYML[Python ML Models sklearn/XGBoost]   SMLM -->
CMP[Dual-Pipeline Comparison]   PYML --> CMP   CMP --> REC[Recommendation Engine]   REC --
> DASH[Dashboards & Reports]   BE --> DB[(Application Database)]   SPARK --> PQ[(Parquet
Storage)]
```

11. Big Data Architecture

Figure: DIAG-BD-001 — System Architecture & Flow



Title: Big Data Architecture

Description: Layered Big Data architecture: Restaurant Data Sources (11 domains) → Data Ingestion Layer (PySpark read) → Big Data Storage (CSV/JSON/Parquet) → Apache Spark Processing → Data Cleaning & Validation → Spark SQL Processing → Feature Engineering → Dual Analytics (Spark/Python) → MLlib & Python ML → Result Comparison → Restaurant Intelligence → Recommendation Engine → Web Dashboard.


Status: CREATED & EMBEDDED

DineIQ follows the Lambda-lite architecture appropriate for batch analytics competitions:

Layer	Technology	Files	Purpose
Source	CSV/JSON	data_generator/output/	Raw multi-table restaurant data
Ingestion	PySpark	spark_jobs/ingest_validate.py	Schema-validated loading with error quarantine
Storage	Parquet	processed_data/parquet_data/	Efficient columnar storage for analytics
Processing	Spark SQL	spark_sql/spark_sql.py	Joins, aggregations, analytical queries
Feature Engineering	PySpark + Spark SQL	spark_jobs/spark_sql.py	Create ML-ready features
Batch ML	Spark MLlib	spark_jobs/mllib_models.py	Distributed model training
Python ML	pandas + sklearn	python_pipeline/run_pipeline.py	Independent model training
Comparison	Python	spark_jobs/dual_pipeline_compare.py	Cross-validate pipeline outputs
Intelligence	Python	src/services/scoring_service.py	Recommendations, What-If
Serving	Flask	src/backend/app.py	REST API serving dashboard
Presentation	HTML/JS/Plotly	static/	Interactive dashboards

12. Data Flow Diagrams

Figure: DIAG-DFD-0 — System Architecture & Flow




Title: DFD Level 0 — Context Diagram

Description: Single process box "DineIQ Analytics System" with external entities: Restaurant Manager, Data Analyst, Regional Manager, Administrator. Show data flows: order data, menu data, customer data, ratings, inventory, wastage → System; dashboards, reports, recommendations, alerts → users.

Status: CREATED & EMBEDDED

Figure: DIAG-DFD-1 — System Architecture & Flow




Title: DFD Level 1 — Major Processes

Description: Explode the context into: P1 Data Ingestion, P2 Data Quality, P3 Spark Processing, P4 Python Pipeline, P5 Analytics Engine, P6 Recommendation Engine, P7 Dashboard. Show data flows between processes and data stores (D1 Raw CSV, D2 Parquet, D3 App DB, D4 Models).

Status: CREATED & EMBEDDED

Figure: DIAG-DFD-2 — System Architecture & Flow




Title: DFD Level 2 — Analytics Processes

Description: Decompose P5 Analytics Engine into: P5.1 Menu Profitability, P5.2 Customer Segmentation, P5.3 Market Basket, P5.4 Demand Forecasting, P5.5 Wastage Analysis, P5.6 Price Intelligence, P5.7 Promotion Analysis, P5.8 Anomaly Detection. Show feature data flows between sub-processes.

Status: CREATED & EMBEDDED

13. Database Design & Data Dictionary

Figure: DIAG-ER-001 — System Architecture & Flow



Title: Entity Relationship Diagram

Description: Full crow's foot ER diagram showing all 11 entities: Restaurants, Customers, Menu_Categories, Menu_Items, Orders, Order_Items, Ratings, Inventory, Wastage, Promotions, Pricing_History. Show PK, FK, and cardinality (1:N, M:N). Relationships: Restaurant 1→N Menu_Categories, Restaurant 1→N Orders, Customer 1→N Orders, Order 1→N Order_Items, Menu_Item 1→N Order_Items, Menu_Item 1→N Ratings, Menu_Item 1→N Inventory, Menu_Item 1→N Wastage, Menu_Item 1→N Pricing_History, Restaurant 1→N Promotions.

Status: CREATED & EMBEDDED

Screenshot Evidence: SS-DB-001



Title: Database Tables

What to show: All 11 tables visible in the database management tool

Where to capture: Database tool (pgAdmin / DB Browser / MySQL Workbench)

Evidence required: Table names, column counts, and record counts visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DB-002



Title: ER Diagram in Tool

What to show: Auto-generated ER diagram from database tool

Where to capture: Database management tool

Evidence required: All relationships and foreign keys visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DB-003



Title: Sample Customer Records

What to show: First 20 rows of Customers table

Where to capture: Database query tool

Evidence required: customer_id, anonymised name/email, loyalty_tier, registration_date visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DB-004



Title: Sample Order Records

What to show: First 20 rows of Orders table joined with Order_Items

Where to capture: Database query tool

Evidence required: order_id, customer_id, restaurant_id, total_amount, order_type, status visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DB-005



Title: Sample Menu Records

What to show: First 20 rows of Menu_Items with categories

Where to capture: Database query tool

Evidence required: item_id, item_name, category, base_price, cost, is_available visible

Status: CAPTURED & VERIFIED

13.1 Data Dictionary

Table: Restaurants

Field	Type	Key	Nullable	Description	Example
restaurant_id	VARCHAR(10)	PK	NO	Unique restaurant identifier	R001
name	VARCHAR(100)	—	NO	Restaurant name	DineIQ Karachi Central
city	VARCHAR(50)	—	YES	City of operation	Karachi
area	VARCHAR(50)	—	YES	Sub-area / neighbourhood	Clifton
cuisine_type	VARCHAR(50)	—	YES	Primary cuisine type	Pakistani
opening_date	DATE	—	YES	Date restaurant opened	2020-03-15
seating_capacity	INT	—	YES	Total seating capacity	120
is_active	BOOLEAN	—	NO	Whether location is currently active	TRUE

Table: Customers

Field	Type	Key	Nullable	Description	Example
customer_id	VARCHAR(10)	PK	NO	Unique customer identifier	C00001
name	VARCHAR(100)	—	YES	Anonymised customer name	Customer_00001
email	VARCHAR(100)	—	YES	Anonymised email	cust_00001@example.com
phone	VARCHAR(20)	—	YES	Anonymised phone	03XX-XXXXXXX
city	VARCHAR(50)	—	YES	Customer city	Karachi
registration_date	DATE	—	NO	Date of first registration	2023-01-15

loyalty_tier	VARCHAR(20)	—	YES	Bronze / Silver / Gold / Platinum	Gold

Table: Menu_Items

Field	Type	Key	Nullable	Description	Example
item_id	VARCHAR(10)	PK	NO	Unique menu item identifier	M001
restaurant_id	VARCHAR(10)	FK→Restaurants	NO	Restaurant this item belongs to	R001
category_id	VARCHAR(10)	FK→Menu_Categories	NO	Category this item belongs to	CAT003
item_name	VARCHAR(100)	—	NO	Display name of the menu item	Chicken Karahi
description	TEXT	—	YES	Item description	Traditional slow-cooked chicken dish
base_price	DECIMAL(10,2)	—	NO	Current base price in PKR	850.00
cost	DECIMAL(10,2)	—	YES	Preparation/ingredient cost in PKR	340.00
is_available	BOOLEAN	—	NO	Whether item is currently on menu	TRUE
launch_date	DATE	—	YES	Date item was added to menu	2023-06-01

Table: Orders

Field	Type	Key	Nullable	Description	Example
order_id	VARCHAR(15)	PK	NO	Unique order identifier	ORD00000001
restaurant_id	VARCHAR(10)	FK→Restaurants	NO	Restaurant that received the order	R001
customer_id	VARCHAR(10)	FK→Customers	YES	Customer who placed order (may be null for walk-ins)	C00001
order_date	TIMESTAMP	—	NO	Date and time of order placement	2023-08-14 13:45:00
order_type	VARCHAR(20)	—	NO	dine-in / takeaway / delivery / app	dine-in
total_amount	DECIMAL(10,2)	—	NO	Total order value after discounts in PKR	2340.00
discount_amount	DECIMAL(10,2)	—	YES	Discount applied in PKR	200.00
promotion_id	VARCHAR(10)	FK→Promotions	YES	Promotion applied (if any)	PROMO007
status	VARCHAR(20)	—	NO	completed / cancelled / refunded	completed

Table: Order_Items

Field	Type	Key	Nullable	Description	Example
order_item_id	VARCHAR(15)	PK	NO	Unique order-line identifier	OI000000001
order_id	VARCHAR(15)	FK→Orders	NO	Parent order	ORD00000001
item_id	VARCHAR(10)	FK→Menu_Items	NO	Menu item ordered	M001
quantity	INT	—	NO	Quantity ordered	2
unit_price	DECIMAL(10,2)	—	NO	Price at time of order in PKR	850.00
subtotal	DECIMAL(10,2)	—	NO	quantity × unit_price in PKR	1700.00

ℹ *Data dictionary for Ratings, Inventory, Wastage, Promotions, Pricing_History, and Menu_Categories follows the same format. Team to complete these tables in the final document.*

14. Dataset Generation

The DineIQ dataset is fully synthetic, generated by a custom Python script (data_generator/generate_dineiq_data.py). No pre-existing restaurant dataset has been downloaded. The SRS explicitly requires a generation script to be submitted.


14.1 SRS Dataset Requirements

Entity	Minimum Requirement	Complexity Injected
Order_Items	≥ 1,000,000 records	Seasonal patterns, peak hours, weekend uplift, channel mix
Orders	≥ 100,000 unique orders	Cancelled orders, duplicate attempts, high-value outliers
Customers	≥ 50,000 unique customers	Churned, new, high-value, promotion-sensitive segments
Menu_Items	≥ 150 items	High-margin low-sales, high-sales low-margin, high-wastage
Menu_Categories	≥ 10 categories	Mains, Starters, Desserts, Beverages, Specials etc.
Restaurants	≥ 20 locations	Different cities, performance profiles, seasonal patterns
Ratings	≥ 100,000 records	Rating anomalies, sudden spikes, inconsistent patterns
Wastage	≥ 50,000 records	Demand mismatch, over-preparation, seasonal waste
Pricing_History	Multiple records per item	Price increases/decreases with demand impact
Promotions	Multiple campaigns	Profitable promotions and promotion traps

14.2 Generation Methodology

- Seed-based random generation (seed=42) for reproducibility
- Restaurants generated first with realistic city/area distribution across Pakistani cities (Karachi, Lahore, Islamabad, Faisalabad, Multan, Rawalpindi, Peshawar, Quetta, Hyderabad, Sialkot)
- Menu items generated per restaurant with realistic PKR pricing and cost structures producing varied contribution margins
- Customer profiles generated with realistic registration date distribution, loyalty tier assignment, and anonymised PII
- Orders generated with time-series patterns: seasonal multipliers, peak-hour Gaussian distributions, weekend uplift, promotion period uplift
- Deliberate data quality issues injected: missing customer_id (2%), duplicate order records (0.5%), invalid prices (0.5%), negative quantities (0.3%), future dates (0.2%), rating anomalies (1%), cancelled transactions (3%)
- Wastage records generated as a function of preparation quantity, demand, and day-of-week
- Pricing history generated with 2–5 price changes per item across the 12-month period
- Association rules planted between specific item pairs to ensure market-basket analysis produces meaningful results

Screenshot Evidence: SS-DATA-001



Title: Dataset Generator Running


What to show: Terminal showing generate_dineiq_data.py executing

Where to capture: Terminal / Jupyter Notebook

Evidence required: Script running, progress output, no errors

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DATA-002



Title: Generated Dataset Preview

What to show: pandas DataFrame.head() output for each major table

Where to capture: Jupyter Notebook

Evidence required: Column names, data types, sample values visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DATA-003

DineIQ Environment — Dataset Statistics & Benchmark Compliance

```
$ python -c "from data_generator.stats import print_summary; print_summary()"
================== DINEIQ DATASET RECORD COUNTS & SRS AUDIT ==================
Table Name             Actual Count       SRS Requirement     Compliance Status
------------------------------------------------------------------------------
Order_Items             1,089,728          >= 1,000,000        PASS (108.9%)
Orders                    100,000          >= 100,000          PASS (100.0%)
Customers                  50,000          >= 50,000           PASS (100.0%)
Menu_Items                    156          >= 150              PASS (104.0%)
Menu_Categories                12          >= 10               PASS (120.0%)
Restaurants                    25          >= 20               PASS (125.0%)
Ratings                   104,974          >= 100,000          PASS (104.9%)
Wastage                    54,978          >= 50,000           PASS (109.9%)
Pricing_History             1,248          Multiple/item       PASS
Promotions                     16          Multiple campaigns  PASS
Inventory                     850          Current stock       PASS
------------------------------------------------------------------------------
[VERIFIED] All 11 relational tables exceed SRS minimum benchmarks.
```

Title: Dataset Statistics


What to show: DataFrame.describe() and record counts per table

Where to capture: Jupyter Notebook

Evidence required: All ≥ SRS minimums: 1M+ order lines, 100K+ orders, 50K+ customers confirmed

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DATA-004



Title: Data Distribution Charts


What to show: Histograms of order_amount, rating distribution, wastage by category

Where to capture: Jupyter Notebook / matplotlib

Evidence required: Realistic distributions, seasonal patterns visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS_DATA_005



Title: Injected Data Quality Problems

What to show: Data quality report showing counts of each problem type injected


Where to capture: Terminal or Jupyter

Evidence required: Problem types and counts match injection rates

Status: CAPTURED & VERIFIED

15. Data Quality & Cleaning

Figure: DIAG-DQ-001 — System Architecture & Flow



Title: Data Quality Pipeline

Description: Flow: Raw Data → Schema Validation → Missing Value Detection → Duplicate Detection → Invalid Value Detection → Anomaly Detection → Data Quality Report → Cleaning Rules Applied → Quarantine Layer → Clean DataFrame → Cleaning Log.

Status: CREATED & EMBEDDED

15.1 Data Quality Rules

Rule ID	Problem	Table	Detection Method	Action	Severity
DQ-001	Missing customer_id on non-walk-in order	Orders	IS NULL check	Flag as anomaly; assign WALK_IN_UNKNOWN	Medium
DQ-002	Duplicate order records	Orders	Exact duplicate on all non-ID columns	Keep first; quarantine duplicates	High
DQ-003	Duplicate order-line records	Order_Items	Duplicate order_id + item_id	Keep first; quarantine duplicates	High
DQ-004	Invalid menu price (≤ 0 or > 50,000 PKR)	Menu_Items / Order_Items	Range check	Quarantine record; flag for manual review	Critical
DQ-005	Negative quantity	Order_Items	quantity < 0	Quarantine; log	Critical
DQ-006	Invalid dates (future or before 2020)	Orders / Ratings	Date range check	Quarantine; log	High
DQ-007	Invalid rating value	Ratings	rating NOT IN (1,2,3,4,5)	Nullify rating; log	Medium
DQ-008	Missing menu_id reference	Order_Items	FK integrity check	Quarantine order line	Critical
DQ-009	Invalid restaurant_id reference	Orders	FK integrity check	Quarantine order	Critical
DQ-010	Impossible wastage quantity (> 10,000 units)	Wastage	Range check	Quarantine; flag	High
DQ-011	Discount exceeding order total	Orders	discount_amount > total_amount	Cap discount at total; log	Medium

DQ-012	Cancelled transaction with completed status	Orders	status conflict check	Correct status; log	Medium
DQ-013	Inconsistent units across wastage records	Wastage	Unit standardisation check	Standardise to kg; log	Medium
DQ-014	Invalid location reference in wastage	Wastage	FK integrity check	Quarantine; log	High

Screenshot Evidence: SS-DATA-006



Title: Data Quality Report Output


What to show: Complete data quality report generated by spark_jobs/engines.py

Where to capture: Terminal / Spark output

Evidence required: All 14 rule IDs, counts detected per rule, and total affected records visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DATA-007



Title: DataFrame Before Cleaning


What to show: Sample rows showing data quality issues (nulls, invalid values)

Where to capture: Jupyter / terminal

Evidence required: At least 3 different problem types visible in raw data

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DATA-008



Title: DataFrame After Cleaning

What to show: Same dataset after cleaning — problems resolved or quarantined


Where to capture: Jupyter / terminal

Evidence required: No null/invalid values remain; quarantine count logged

Status: CAPTURED & VERIFIED

16. Spark Pipeline

Figure: DIAG-SPARK-001 — System Architecture & Flow



Title: Spark Pipeline Flow

Description: Detailed Spark pipeline: Raw CSV Files → SparkSession Initialisation → Explicit Schema Definition → DataFrame Loading → Schema Validation & Type Coercion → Data Quality Assessment → Cleaning Transformations → Multi-table Joins (Spark SQL) → Feature Engineering Transformations → Parquet Write → Analytics Aggregations → Spark MLlib Training → Model Save.


Status: CREATED & EMBEDDED

16.1 Spark Pipeline Steps

Step	File	Function	Spark Operations Used	Output
1. Initialise	spark_jobs/run_all.py	create_spark_session()	SparkSession.builder	SparkSession object
2. Load & Validate Schema	spark_jobs/ingest_validate.py	load_with_schema()	spark.read.csv() with explicit StructType	Validated DataFrames
3. Data Quality Assessment	spark_jobs/engines.py	assess_quality()	filter(), groupBy(), countDistinct(), isNull()	Data Quality Report JSON
4. Cleaning	spark_jobs/features.py	apply_cleaning_rules()	where(), fillna(), dropDuplicates(), when()	Clean DataFrames + Quarantine
5. Integration (Joins)	spark_sql/spark_sql.py	integrate_tables()	Spark SQL JOIN, LEFT JOIN, broadcast()	Integrated DataFrame
6. Feature Engineering	spark_jobs/spark_sql.py	engineer_features()	withColumn(), UDF, window functions	Feature DataFrame
7. Parquet Write	spark_jobs/run_all.py	write_parquet()	df.write.parquet(partition_by=)	Parquet files in processed_data/
8. Analytics Aggregations	spark_sql/spark_sql.py	run_analytics()	Spark SQL GROUP BY, HAVING, RANK()	Analytics DataFrames

9. MLlib Training	spark_jobs/mllib_models.py	train_models()	Pipeline, VectorAssembler, RF/DT/GBT/LR	Saved Spark models

Screenshot Evidence: SS-SPARK-001



Title: Spark Application Running


What to show: Spark session initialised, SparkContext Web UI URL visible

Where to capture: Terminal

Evidence required: Spark version, app name "DineIQ", executor info visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-002



Title: Spark Schema Output

What to show: df.printSchema() output for the main integrated DataFrame

Where to capture: Terminal / Jupyter

Evidence required: All column names, data types, and nullable flags visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-003



Title: Spark DataFrame Preview

What to show: df.show(20) output showing integrated data

Where to capture: Terminal / Jupyter

Evidence required: Joined columns from multiple tables visible in one DataFrame

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-004



Title: Spark Transformation

What to show: Feature engineering transformation adding derived columns

Where to capture: Terminal / Jupyter

Evidence required: New feature columns (contribution_margin, profit_pct, repeat_rate) visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-005



Title: Spark Join Operation

What to show: Multi-table join showing Orders joined to Order_Items, Menu_Items, Customers

Where to capture: Terminal / Jupyter

Evidence required: Successful join; row count matches expected

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-006



Title: Spark Aggregation


What to show: groupBy().agg() result showing revenue/profit per menu item

Where to capture: Terminal / Jupyter

Evidence required: All 150+ menu items with aggregated metrics

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-007



Title: Spark Execution Plan


What to show: df.explain() output showing physical plan

Where to capture: Terminal

Evidence required: Joins, shuffles, and partition info visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-008



Title: Parquet Output Files


What to show: File listing of processed_data/parquet_data/ directory

Where to capture: Terminal (ls -la)

Evidence required: Parquet part files, partition folders visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-009



Title: Spark SQL Query

What to show: Spark SQL query for menu profitability in spark_sql/spark_sql.py
Where to capture: Code editor or terminal
Evidence required: SQL syntax, multi-table joins, analytical functions visible
Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-SPARK-010




Title: Spark SQL Query Result

What to show: Result of Spark SQL analytical query
Where to capture: Terminal / Jupyter
Evidence required: Profitability ranking, menu classification inputs visible
Status: CAPTURED & VERIFIED

17. Python Data Science Pipeline

 The Python pipeline is COMPLETELY INDEPENDENT of the Spark pipeline. It reads the same underlying CSV data directly. It must NOT consume Spark outputs. This is a hard SRS requirement.

Figure: DIAG-PY-001 — System Architecture & Flow




Title: Python Pipeline Flow

Description: Independent Python pipeline: Raw CSV → pandas.read_csv() → Independent Cleaning (no Spark) → Independent Feature Engineering → Train/Validation/Test Split (chronological for time-based tasks) → sklearn/XGBoost Model Training → Evaluation → Save .joblib Model → Generate Predictions → Export Results for Comparison.

Status: CREATED & EMBEDDED

Step	File	Library	Operations	Output
1. Load Data	python_pipeline/run_pipeline.py	pandas	pd.read_csv() for all 11 tables	Raw DataFrames
2. Clean Data	python_pipeline/run_pipeline.py	pandas	dropna(), fillna(), drop_duplicates(), type coercion	Cleaned DataFrames
3. Feature Engineering	python_pipeline/model_artifacts.py	pandas, numpy	compute RFM, margins, wastage %, repeat rates	Feature DataFrames
4. Train/Test Split	python_pipeline/run_pipeline.py	sklearn	train_test_split() or chronological slice for forecasting	X_train, X_test, y_train, y_test
5. Model Training	python_pipeline/run_pipeline.py	sklearn, XGBoost	RandomForest, GradientBoosting, LogisticRegression	Fitted model objects
6. Evaluation	python_pipeline/run_pipeline.py	sklearn.metrics	accuracy_score, classification_report, confusion_matrix	Metrics dict
7. Save Models	python_pipeline/run_pipeline.py	joblib	joblib.dump()	models/python/*/v1/model.joblib
8. Generate Predictions	python_pipeline/run_pipeline.py	pandas	model.predict() on test set	predictions_py.csv



Title: Python Pipeline Running

What to show: Terminal output showing python_pipeline/run_pipeline.py executing

Where to capture: Terminal

Evidence required: Data loading, training progress, evaluation metrics printed

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-PY-002



Title: Python Feature Engineering


What to show: pandas DataFrame with engineered features

Where to capture: Jupyter / terminal

Evidence required: RFM columns, contribution_margin, wastage_pct, repeat_rate visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-PY-003



Title: Python Model Training

What to show: sklearn model training output with hyperparameters

Where to capture: Terminal

Evidence required: Model class, n_estimators/params, training completion visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-PY-004



Title: Python Model Predictions

What to show: DataFrame showing customer_id, actual, python_prediction, probability


Where to capture: Terminal / Jupyter

Evidence required: Prediction labels and probabilities visible for test set

Status: CAPTURED & VERIFIED

18. Feature Engineering

Figure: DIAG-FE-001 — System Architecture & Flow



Title: Feature Engineering Flow

Description: Show how raw columns from multiple tables are combined to produce analytical features, then ML features. Two tracks: Spark track and Python track producing identical feature definitions from different code.


Status: CREATED & EMBEDDED

Feature	Formula / Definition	Source Tables	Purpose	Pipeline
item_revenue	quantity × unit_price	Order_Items	Total revenue per item per period	Both
item_cost	quantity × cost (from Menu_Items)	Order_Items + Menu_Items	Total cost per item per period	Both
contribution_margin	item_revenue − item_cost	Derived	Gross profit per item	Both
profit_percentage	(contribution_margin / item_revenue) × 100	Derived	Margin percentage	Both
order_frequency	COUNT(DISTINCT order_id) per item per period	Order_Items	How often item is ordered	Both
item_popularity_rank	RANK() OVER (ORDER BY order_frequency DESC)	Derived	Relative popularity	Spark
repeat_purchase_rate	customers ordering item ≥2 times / total customers	Orders + Order_Items	Customer loyalty signal	Both
avg_rating	AVG(food_rating) per item	Ratings	Customer satisfaction	Both
rating_trend	AVG(rating) last 30 days − AVG(rating) prev 30 days	Ratings + date filter	Improving/declining satisfaction	Both
wastage_percentage	total_wasted_qty / total_prepared_qty × 100	Wastage + Order_Items	Operational efficiency	Both
promotion_dependency	orders with promo / total orders per item	Orders + Promotions	Reliance on discounts	Both
discount_percentage	discount_amount / (total_amount + discount_amount) × 100	Orders	Average discount depth	Both

customer_recency	DATEDIFF(max_date, last_order_date) per customer	Orders	Days since last purchase	Both
customer_frequency	COUNT(DISTINCT order_id) per customer	Orders	Purchase frequency	Both
customer_monetary	SUM(total_amount) per customer	Orders	Total spend	Both
rfm_score	Weighted R+F+M scores (quintile-based)	Derived from above	Customer segment input	Both
avg_order_value	SUM(total_amount) / COUNT(order_id) per customer	Orders	Spending level	Both
peak_hour_frequency	COUNT orders between 11AM–2PM and 7PM–9PM / total	Orders	Peak-period order share	Spark SQL
weekend_order_ratio	COUNT weekend orders / total orders per item	Orders	Weekend demand pattern	Spark SQL
basket_size	AVG(COUNT(order_item_id)) per order	Order_Items	Items per order	Both
price_change_percentage	(new_price − old_price) / old_price × 100	Pricing_History	Price change magnitude	Spark SQL
demand_after_price_change	% change in order_frequency after price change	Orders + Pricing_History	Price elasticity proxy	Spark SQL
location_performance_index	location_revenue / AVG(location_revenue) across locations	Orders + Restaurants	Relative location performance	Spark SQL
channel_preference	mode(order_type) per customer	Orders	Preferred ordering channel	Both

19. Menu Intelligence

Figure: DIAG-MENU-001 — System Architecture & Flow



Title: Menu Classification Flow

Description: Decision tree showing how a menu item's 10 indicators (quantity sold, revenue, cost, margin, rating, repeat-purchase rate, wastage %, promotion dependency, sales trend, location spread) feed into a weighted scoring model that outputs one of four classes: Profit Driver, Volume Driver, Hidden Opportunity, Low Performer. Show the tricky edge cases.

Status: CREATED & EMBEDDED

19.1 Multi-Dimensional Performance Analysis

The SRS explicitly states: high sales volume alone must not make a menu item successful. DineIQ evaluates every menu item across 10 dimensions simultaneously:

Dimension	Good Signal	Warning Signal	Bad Signal
Quantity Sold	High vs category avg	Medium	Very low (slow-mover)
Revenue	High absolute revenue	Medium	Low revenue
Contribution Margin	> 60% of category avg	40-60%	< 40% or negative
Profit Percentage	> 50%	30-50%	< 30%
Customer Rating	≥ 4.0	3.0–3.9	< 3.0
Repeat Purchase Rate	> 40%	20-40%	< 20%
Wastage Percentage	< 5%	5-15%	> 15%
Promotion Dependency	< 20% of orders use promo	20-40%	> 40%
Sales Trend (30d)	Upward	Stable	Declining
Location Spread	Present in ≥70% locations	50-70%	< 50% or location-specific

19.2 Classification Rules


Class	Criteria (All must be satisfied)	Business Meaning

Profit Driver	High demand (top 40% by freq) AND contribution_margin > category median AND wastage_pct < 15% AND rating ≥ 3.5	Promote, protect, invest in quality
Volume Driver	High demand (top 40%) BUT contribution_margin ≤ category median OR promotion_dependency > 40%	Review pricing; reduce promo dependency
Hidden Opportunity	contribution_margin > category median AND rating ≥ 4.0 AND repeat_rate > 35% BUT demand in bottom 40%	Promote aggressively; increase visibility
Low Performer	Low demand (bottom 40%) AND (margin < 30% OR wastage_pct > 15% OR rating < 3.0)	Consider removal or redesign

19.3 Tricky Menu Performance Cases (SRS Steps 11)

Case	Classification Result	Explanation
High-selling, loss-making dish	Volume Driver (flagged: negative margin)	Sales rank alone would make this look successful; DineIQ flags negative contribution
Highly profitable but rarely purchased	Hidden Opportunity	Strong margin + rating but low visibility; recommend promotion
Popular dish with excessive wastage	Volume Driver (flagged: high wastage)	Preparation-demand mismatch; recommend reduced batch sizes
Highly rated, poor profitability	Hidden Opportunity (flagged: low margin)	Customer loves it but price/cost structure needs review
Low-rated, high-sales dish	Volume Driver (flagged: declining repeat)	Sales driven by novelty or location proximity; satisfaction concern
Promotion-dependent dish	Volume Driver (flagged: promotion trap)	Remove promo → sales likely collapse; margin during promo may be negative
Location-specific performer	Varies by location	Classified per location; appears in location-specific menu intelligence
Weekend-only performer	Hidden Opportunity	High weekend demand but low weekday; recommend weekend-specific promotion
New item (< 30 days)	Unclassified / Needs History	Insufficient data for reliable classification; flagged separately
Seasonal item (off-season)	Unclassified / Seasonal	Seasonal label applied; evaluated within relevant season window

Screenshot Evidence: SS-MENU-001



Title: Menu Intelligence Dashboard


What to show: Full menu dashboard showing all four classification cards with item counts

Where to capture: Web application — Menu Intelligence page

Evidence required: Profit Driver, Volume Driver, Hidden Opportunity, Low Performer sections all visible with item lists

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-MENU-002



Title: Profit Driver Items


What to show: Filtered view showing only Profit Driver items with their metrics

Where to capture: Web application — Menu Intelligence page

Evidence required: Item name, revenue, margin %, rating, repeat rate, wastage % all visible

Status: CAPTURED & VERIFIED


Screenshot Evidence: SS-MENU-003



Title: Volume Driver Items

What to show: Filtered view of Volume Driver items with warning flags
Where to capture: Web application
Evidence required: Promotion dependency or margin warning flags visible
Status: CAPTURED & VERIFIED


Screenshot Evidence: SS-MENU-004



Title: Hidden Opportunity Items

What to show: Filtered view of Hidden Opportunity items with promotion suggestion
Where to capture: Web application
Evidence required: High margin and rating but low sales count visible; recommendation card shown
Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-MENU-005



Title: Low Performer Items


What to show: Filtered view of Low Performers with removal/redesign flags

Where to capture: Web application

Evidence required: Multiple negative indicators visible per item

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-MENU-006



Title: Tricky Business Case

What to show: One item showing contradictory signals (e.g. high sales, negative margin)


Where to capture: Web application

Evidence required: Sales rank high but margin negative; system correctly classifies as Volume Driver with alert

Status: CAPTURED & VERIFIED

20. Customer Intelligence

Figure: DIAG-CUST-001 — System Architecture & Flow



Title: Customer Segmentation Flow

Description: Flow: Order history → RFM Calculation (Recency/Frequency/Monetary) → Quintile Scoring → RFM Composite Score → K-Means or Rule-Based Segmentation → Segment Labels (High-Value Loyal, Frequent, Promotion-Driven, At-Risk, New, Occasional) → Churn Risk Scoring → Recommendations per Segment.

Status: CREATED & EMBEDDED


20.1 RFM Analysis

RFM Dimension	Definition	Calculation	Scoring
Recency (R)	Days since last order	DATEDIFF(analysis_date, MAX(order_date)) per customer	1=most recent (low days), 5=least recent (high days)
Frequency (F)	Total number of orders	COUNT(DISTINCT order_id) per customer	1=low frequency, 5=high frequency
Monetary (M)	Total amount spent	SUM(total_amount) per customer	1=low spend, 5=high spend

20.2 Customer Segments

Segment	RFM Pattern	Characteristics	Recommended Action
High-Value Loyal	R≥4, F≥4, M≥4	Recent, frequent, high-spend; low churn risk	VIP treatment, exclusive offers, loyalty rewards
Frequent Customers	F≥4, R≥3, M any	Regular visitors but may not be high-spend	Upsell to premium items; basket-size growth campaigns
Promotion-Driven	F≥3, high promo_usage	Order often but only with discounts; margin pressure	Test price sensitivity; gradually reduce discount depth
At-Risk Customers	R=1-2, formerly F≥3	Were frequent; now lapsing	Win-back campaign; personalised offer
New Customers	Registration < 90 days	Limited history; potential high-value	Onboarding offers; loyalty programme enrolment
Occasional Customers	F=1-2, R any	Infrequent visitors; may be location-specific	Event-based promotions; awareness campaigns

Screenshot Evidence: SS-CUST-001



Title: Customer Dashboard


What to show: Full customer intelligence dashboard

Where to capture: Web application — Customer Intelligence page

Evidence required: Segment donut chart, RFM distribution, segment counts, and at-risk count visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CUST-002



Title: RFM Analysis Results


What to show: Table showing sample customers with R, F, M scores and composite

Where to capture: Web application or Jupyter

Evidence required: Individual customer RFM scores and segment labels visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CUST-003



Title: Customer Segments Breakdown


What to show: Segment counts and percentages

Where to capture: Web application

Evidence required: All 6 segment types with customer counts

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CUST-004



Title: Churn Risk Analysis

What to show: At-risk customers list with churn probability


Where to capture: Web application

Evidence required: Customer IDs, last order date, churn probability, recommended action visible

Status: CAPTURED & VERIFIED

21. Market Basket Analysis

Figure: DIAG-MBA-001 — System Architecture & Flow



Title: Market Basket Flow


Description: Flow: Order_Items → Transaction Encoding (order_id as basket) → FP-Growth / Apriori Algorithm → Frequent Itemsets (min_support ≥ 0.01) → Association Rules → Filter by Confidence (≥ 0.3) and Lift (≥ 1.2) → Bundle Recommendations → Cross-Sell / Upsell Suggestions.

Status: CREATED & EMBEDDED

21.1 Association Rule Metrics

Metric	Formula	Interpretation	Threshold Used
Support	freq(A∪B) / N transactions	How often A and B appear together	≥ 0.01 (1% of orders)
Confidence	freq(A∪B) / freq(A)	Of orders with A, % also contain B	≥ 0.30 (30%)
Lift	Confidence(A→B) / Support(B)	How much more likely B given A vs random	≥ 1.20 (20% above baseline)

Screenshot Evidence: SS-BASKET-001



Title: Market Basket Results

What to show: Top 20 association rules sorted by lift

Where to capture: Web application or Jupyter


Evidence required: Item pairs, support, confidence, lift values, and bundle recommendation visible

Status: CAPTURED & VERIFIED

22. Demand Forecasting

 Chronological train/test split is MANDATORY per SRS Step 21. Random splits are not acceptable for time-series forecasting.

Figure: DIAG-FORECAST-001 — System Architecture & Flow




Title: Forecasting Pipeline

Description: Flow: Historical Orders → Daily/Weekly Aggregation per Item → Time Features (day_of_week, month, is_weekend, is_holiday, is_promotion_active) → Chronological Split (80% train / 20% test, respecting time order) → Model Training (SARIMA / Prophet / GBT with lag features) → Forecast for next 30/60/90 days → Evaluation (MAE, RMSE, MAPE) → vs Naïve Baseline → Dashboard display.

Status: CREATED & EMBEDDED


Element	Detail
Forecast Target	Daily order quantity per menu item / per category / per location
Forecast Horizon	30 days (default), configurable to 60 or 90 days
Train Period	First 80% of date range chronologically
Test Period	Last 20% of date range (unseen future relative to training)
Features	day_of_week, month, week_of_year, is_weekend, is_holiday_season, lag_7, lag_14, rolling_7_avg, is_promotion_active, price_at_time
Models Compared	SARIMA (statsmodels), Prophet (if installed), GBT Regressor (sklearn), Linear Regression (sklearn)
Baseline	Naïve forecast: next_value = last_known_value
Evaluation Metrics	MAE, RMSE, MAPE, R^2
Acceptance Criteria	Model MAPE < Naïve Baseline MAPE



Title: Forecast Dashboard

What to show: Demand forecast chart showing historical + forecasted demand
Where to capture: Web application — Forecast Dashboard
Evidence required: Historical line, forecast line, confidence interval, item/location filter visible
Status: CAPTURED & VERIFIED


Screenshot Evidence: SS-FORECAST-002



Title: Actual vs Forecast Comparison

What to show: Side-by-side comparison of actual vs predicted values on test set
Where to capture: Jupyter or web application
Evidence required: Actual values, predicted values, error per period visible
Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-FORECAST-003



Title: Forecast Evaluation Metrics

What to show: MAE, RMSE, MAPE values for selected model vs naïve baseline

Where to capture: Terminal or web application

Evidence required: Model outperforms baseline; all metric values visible

Status: CAPTURED & VERIFIED

23. Wastage Intelligence

Food wastage is analysed by menu item, category, restaurant location, day of week, time period, and demand correlation. The wastage risk prediction model identifies items/periods with a high probability of excess wastage before it occurs.

Figure: DIAG-WASTE-001 — System Architecture & Flow




Title: Wastage Analysis Flow

Description: Raw Wastage records → Aggregation by item/location/day → Wastage % calculation (wasted/prepared) → Trend analysis → Correlation with demand, promotions, preparation quantity → Risk Prediction Model (features: historical_wastage, day_of_week, forecast_demand, promotion_active, inventory_stock) → High/Medium/Low risk labels → Recommendations (reduce preparation, adjust stock).

Status: CREATED & EMBEDDED

Screenshot Evidence: SS-WASTE-001



Title: Wastage Dashboard


What to show: Full wastage dashboard with KPI cards

Where to capture: Web application

Evidence required: Total wastage PKR value, top 5 wasted items, wastage % by category, location heatmap visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-WASTE-002



Title: High-Wastage Items


What to show: Items with wastage_pct > 15% sorted by cost

Where to capture: Web application

Evidence required: Item name, category, location, wastage %, estimated cost, risk level visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-WASTE-003



Title: Wastage Prediction Output

What to show: Model predictions for next 7 days showing high-risk items

Where to capture: Web application

Evidence required: Date, item, location, risk level (High/Medium/Low), recommended action visible


Status: CAPTURED & VERIFIED

24. Pricing Intelligence

DineIQ analyses historical price changes from Pricing_History and their impact on order frequency to classify items by price sensitivity.

Class	Definition	Criteria	Action
Highly Price Sensitive	Demand drops >20% for <10% price increase	Elasticity > 2	Avoid price increases; focus on cost reduction
Moderately Price Sensitive	Demand drops 5-20% for 10% price increase	Elasticity 0.5–2	Small incremental price increases only
Low Price Sensitivity	Demand drops <5% for 10% price increase	Elasticity < 0.5	Price increase opportunity; test premium positioning

Screenshot Evidence: SS-PRICE-001



Title: Pricing Intelligence Dashboard

What to show: Price sensitivity classification of menu items

Where to capture: Web application

Evidence required: Item, current price, price change history, demand change %, sensitivity class visible


Status: CAPTURED & VERIFIED

25. Promotion Intelligence

Promotion effectiveness is evaluated across 8 dimensions. An increase in sales alone does NOT classify a promotion as successful (SRS Step 27).

Dimension	How Measured	Promotion Trap Signal
Order Volume	Orders during promo vs equivalent non-promo period	Volume up but all other signals negative
Revenue	Revenue during promo vs non-promo	Revenue up due to volume but per-unit revenue down
Contribution Margin	Total margin during vs without promo	Margin collapses due to discount depth
Customer Acquisition	New customers during promo	New customers don't return after promo ends
Repeat Purchases	Post-promo repeat rate of promo customers	Customers only buy during promo periods
Average Order Value	Basket size and AOV during promo	AOV decreases; customers cherry-pick discounted items
Wastage Impact	Wastage during vs outside promo	Promo drives over-ordering → higher waste
Post-Promotion Behaviour	Sales 30 days after promo ends	Sales drop below pre-promo baseline (demand borrow)

Screenshot Evidence: SS-PROMO-001



Title: Promotion Dashboard


What to show: Overview of all promotion campaigns with effectiveness scores

Where to capture: Web application

Evidence required: Campaign name, period, revenue impact, margin impact, overall effective/trap classification visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS_PROMO_002



Title: Promotion Trap Detection

What to show: At least one promotion flagged as a trap with evidence

Where to capture: Web application


Evidence required: Promotion name, sales increased, but margin decreased and/or post-promo drop visible

Status: CAPTURED & VERIFIED

26. Anomaly Detection

Anomaly Type	Detection Method	Flag Criteria	SRS Step
Sudden rating spike	Z-score on daily avg rating per item	|z| > 2.5 on a single day	Step 30
Sudden rating drop	Z-score on daily avg rating per item	|z| > 2.5 downward	Step 30
Excessive identical ratings	Count of same rating value in 24h	> 50 identical ratings in < 24h	Step 30
Sales spike	IQR method on daily order count per item	Value > Q3 + 3×IQR	Step 31
Sales drop	IQR method on daily order count per item	Value < Q1 − 3×IQR	Step 31
Abnormally high order value	Z-score on order total_amount	|z| > 3	Step 31
Unusual discount	discount_amount / total_amount > 0.7	Discount > 70% of order value	Step 31
Duplicate transaction	Exact match on customer_id + items + timestamp	Same basket within 5 minutes	Step 31

Screenshot Evidence: SS-ANOM-001



Title: Rating Anomaly Detection


What to show: Flagged rating anomalies with evidence

Where to capture: Web application

Evidence required: Item, date, anomaly type, normal range, anomalous value visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ANOM-002



Title: Sales Anomaly Detection


What to show: Flagged sales anomalies

Where to capture: Web application

Evidence required: Date, item/location, expected range, actual value, anomaly type visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ANOM-003



Title: Anomaly Dashboard

What to show: Combined anomaly overview with alert count

Where to capture: Web application


Evidence required: Total anomalies today, rating anomalies, sales anomalies, alert cards visible

Status: CAPTURED & VERIFIED

27. Multi-Location Analysis

All 20+ restaurant locations are compared on standardised KPIs. The same menu item may be a Profit Driver at one location and a Low Performer at another.

Screenshot Evidence: SS-LOC-001



Title: Location Comparison Dashboard

What to show: Table/heatmap comparing all locations

Where to capture: Web application

Evidence required: All locations ranked by revenue, profit, AOV, customer count, repeat rate, wastage %, rating visible

Status: CAPTURED & VERIFIED

28. Machine Learning — Spark MLlib


At least three Spark MLlib algorithms must be trained, compared, and the best selected. The SRS requires evidence of multi-model comparison.

Model Task	Algorithms Compared	Features	Evaluation Metric	Target Variable
Menu Performance Classification	Logistic Regression, Decision Tree, Random Forest	profit_pct, avg_rating, repeat_rate, wastage_pct, promotion_dependency, order_frequency	Accuracy, Macro F1	menu_class (4 classes)
Customer Churn Risk	Logistic Regression, Gradient-Boosted Trees, Random Forest	recency, frequency, monetary, avg_order_value, promotion_sensitivity, days_since_last_order	Accuracy, Macro F1, AUC-ROC	is_at_risk (binary)
Demand Prediction	Linear Regression, Generalized Linear Regression, GBT Regressor	lag_7, lag_14, rolling_avg, day_of_week, month, is_promotion, price	RMSE, MAE, MAPE	daily_order_count

28.1 Spark MLlib Pipeline Architecture

Each Spark MLlib model uses a Pipeline object containing: VectorAssembler → StringIndexer (for categorical features) → StandardScaler (for regression tasks) → Classifier/Regressor → Model evaluation on held-out test set → Save to models/*/v1/

Screenshot Evidence: SS-ML-001



Title: Spark Model Training Output


What to show: Terminal showing Spark MLlib training all 3 models

Where to capture: Terminal

Evidence required: All 3 algorithms training, evaluation metrics printed for each, best model selected

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ML-002



Title: Spark Model Evaluation


What to show: Comparison table of all 3 models with their metrics

Where to capture: Terminal or Jupyter

Evidence required: Algorithm, accuracy/F1/RMSE for each; winning model clearly identified

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ML-003



Title: Spark Model Predictions

What to show: Sample predictions from best Spark model

Where to capture: Terminal or Jupyter


Evidence required: record_id, actual_label, spark_prediction, probability visible

Status: CAPTURED & VERIFIED

29. Machine Learning — Python Pipeline

The Python ML pipeline independently solves the same three tasks using scikit-learn / XGBoost. Results must be generated independently — Spark outputs must not be imported.

Screenshot Evidence: SS-ML-004



Title: Python Model Training


What to show: sklearn model training on same tasks as Spark

Where to capture: Terminal / Jupyter

Evidence required: All 3 task models training with cross-validation visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ML-005



Title: Python Model Evaluation


What to show: classification_report() and confusion_matrix() output

Where to capture: Terminal / Jupyter

Evidence required: Precision, recall, F1 per class; confusion matrix; overall accuracy visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-ML-006



Title: Python Model Predictions CSV

What to show: predictions_py.csv preview

Where to capture: Terminal / Jupyter


Evidence required: record_id, actual, python_prediction, probability columns visible

Status: CAPTURED & VERIFIED

30. Dual-Pipeline Comparison

 Spark predictions must NOT be copied into the Python pipeline or vice versa. Both pipelines must generate their results independently and be compared afterwards.

Figure: DIAG-COMP-001 — System Architecture & Flow




Title: Dual Pipeline Comparison Architecture

Description: Same underlying CSV data → [Spark Pipeline: clean → feature engineer → train MLlib model → predict] AND [Python Pipeline: clean → feature engineer → train sklearn model → predict] → Both prediction files loaded → Row-by-row comparison → Match/Mismatch flags → Agreement % calculation → Disagreement analysis.

Status: CREATED & EMBEDDED

The comparison report covers at minimum 100 unseen records across all three analytical tasks (menu classification, churn prediction, demand prediction).

Column	Description	Example Value
record_id	Customer ID, Item ID, or Order ID	C00001
actual_class	Ground-truth label from test set	At Risk
spark_prediction	Output from Spark MLlib model	At Risk
python_prediction	Output from Python sklearn model	Safe
match	Whether both models agree	No
numerical_difference	For regression tasks: |spark_value − python_value|	0.0 (classification) or 14.2 (demand)
spark_probability	Model confidence (if available)	0.83
python_probability	Model confidence (if available)	0.61
agreement_status	Final: Match / Mismatch	Mismatch
disagreement_explanation	Why models differ	Spark used tree ensemble; Python used logistic; borderline case at 0.5 threshold



Title: Dual-Pipeline Comparison Table


What to show: First 50 rows of comparison report

Where to capture: Web application — Dual-Pipeline Dashboard

Evidence required: All comparison columns visible; match/mismatch colour coded

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-COMP-002



Title: Agreement Percentage


What to show: Overall agreement % prominently displayed

Where to capture: Web application

Evidence required: Agreement percentage, total compared, match count, mismatch count visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-COMP-003



Title: Disagreement Case Analysis

What to show: Drill-down on a disagreement case with explanation


Where to capture: Web application

Evidence required: Specific record, Spark confidence, Python confidence, feature values, disagreement reason visible

Status: CAPTURED & VERIFIED

31. Recommendation Engine

Figure: DIAG-REC-001 — System Architecture & Flow



Title: Recommendation Engine Flow

Description: Analytics outputs (menu classification + customer segments + forecasts + wastage analysis + pricing + promotion analysis + anomalies) → Rule-based evidence collector → Priority scoring (business impact × urgency) → Recommendation generation with structured evidence → Priority assignment (Low/Medium/High/Critical) → Dashboard display → Export.

Status: CREATED & EMBEDDED


Every recommendation must display its evidence. The SRS states the application must not provide unexplained recommendations.

31.1 Recommendation Types

Type	Trigger Condition	Priority	Example Evidence
Promote Hidden Opportunity	menu_class = Hidden Opportunity AND margin > 50%	High	Item M042: 68% margin, 4.7 rating, only 3.2% of orders; 61% of buyers reorder
Review Pricing	price_sensitivity = Highly Sensitive AND price_change > 5%	High	Item M018: demand fell 31% after last 8% price increase
Reduce Preparation	wastage_pct > 20% AND last_3_days_demand < preparation_qty	Critical	Item M091: 28% wasted; last 3 days avg demand 45 units vs 62 prepared
Bundle Frequently Purchased Items	lift > 1.5 AND support > 0.03	Medium	Items M007+M023 bought together in 8.4% of orders; lift = 2.1
Remove/Redesign Low Performer	menu_class = Low Performer AND metric_count ≥ 4 negative	High	Item M066: 3 negative signals (margin <15%, rating 2.8, wastage 22%), last 90 days
Increase Stock Before Peak	forecast_demand > avg_demand × 1.3 AND current_stock < threshold	Critical	Weekend forecast for Item M012 is 140% of weekday avg; current stock at risk
Target At-Risk Customers	churn_risk = High AND last_order_days > 60	High	Customer C04521: 3.8 avg orders/month; 0 orders last 68 days; was Gold tier
Review Promotion	promotion_trap = True	Critical	Promo P011: orders +24% but margin −18%; new customers 0% retention post-promo

Investigate Anomalous Location	anomaly_count_location > 5 in 7 days	Medium	Location R007: 6 rating anomalies + 2 sales anomalies in last 7 days

Screenshot Evidence: SS-REC-001



Title: Recommendations Dashboard


What to show: Full recommendation list with priorities

Where to capture: Web application

Evidence required: All recommendation types visible; Critical/High/Medium/Low colour-coded; count per priority shown

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-REC-002



Title: Recommendation Evidence Card


What to show: Expanded view of one recommendation with full evidence

Where to capture: Web application

Evidence required: Action, reason bullets with supporting numbers, affected entity, priority, data source visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-REC-003



Title: Critical Priority Recommendations

What to show: Filtered view of Critical recommendations only

Where to capture: Web application

Evidence required: Only critical items shown; immediate action flags visible


Status: CAPTURED & VERIFIED

32. What-If Analysis

All What-If outputs must be clearly labelled as ESTIMATES / SIMULATED RESULTS — not actual business outcomes.

Scenario Type	User Input	Estimated Impact Shown	Calculation Method
Increase Menu Price	Item, new price %	Revenue change, demand change, margin change	Price elasticity class × demand × margin formula
Reduce Item Price	Item, discount %	Revenue at risk, demand uplift estimate	Elasticity-based projection
Change Discount %	Promotion, new discount %	Margin impact, volume change estimate	Promotion effectiveness model output
Increase Promotion Frequency	Promotion, extra days/week	Revenue, margin, wastage impact estimate	Historical promotion per-day impact extrapolated
Remove Menu Item	Item ID	Revenue lost, wastage saving, margin impact	Current item revenue − cross-sell revenue (basket analysis)
Reduce Preparation Quantity	Item, reduced qty	Wastage saving, stockout risk	Forecast demand vs reduced preparation
Increase Predicted Demand	Item/location, uplift %	Stock requirement, revenue potential	Demand × price × margin
Change Wastage Assumption	Item, new wastage %	Cost saving estimate	(current_wastage − new_wastage) × cost_per_unit

Screenshot Evidence: SS-WHATIF-001



Title: What-If Dashboard


What to show: What-If simulation interface with controls

Where to capture: Web application

Evidence required: Dropdown for scenario type, input fields, Simulate button visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-WHATIF-002



Title: What-If Simulation Result

What to show: Output showing estimated impact of a scenario

Where to capture: Web application


Evidence required: "ESTIMATED RESULT" label clearly visible; before/after KPIs shown; confidence note displayed

Status: CAPTURED & VERIFIED

33. Web Application Design & UI Screens

33.1 Screen Inventory

Screen	Purpose	Key Components	API / Data Source	Auth Required
Login	User authentication	Username, password, role selector, login button, error state	POST /auth/login	No
Executive Dashboard	High-level KPIs	Revenue card, orders card, profit card, wastage card, AOV card, repeat rate card, sales trend chart, channel mix donut, top items table, alerts panel	GET /api/executive	Yes
Menu Intelligence	Menu classification	Four-class filter tabs, item performance table, margin chart, wastage bar, rating scatter, tricky-case highlight	GET /api/menu	Yes
Customer Intelligence	Segment analysis	Segment donut, RFM heatmap, at-risk list, segment detail cards, churn probability table	GET /api/customers	Yes
Wastage Dashboard	Wastage analysis	Total wastage KPI, high-wastage items table, wastage trend line, location heatmap, risk predictions	GET /api/wastage	Yes
Forecast Dashboard	Demand forecast	Historical + forecast line chart, horizon selector, accuracy metrics, high-demand alerts	GET /api/forecast	Yes
Pricing Dashboard	Price sensitivity	Sensitivity class table, price-demand scatter, price change history timeline	GET /api/pricing	Yes
Promotions Dashboard	Promotion analysis	Campaign cards, effectiveness scores, promotion trap alerts, post-promo trend	GET /api/promotions	Yes
Location Dashboard	Multi-location compare	Location ranking table, KPI heatmap, location-specific menu performance toggle	GET /api/locations	Yes
Recommendations	Action recommendations	Priority filter, recommendation cards with evidence, mark-as-done toggle	GET /api/recommendations	Yes
What-If Analysis	Scenario simulation	Scenario selector, input controls, Simulate button, result panel (ESTIMATE labelled)	POST /api/whatif	Yes (Analyst+)
Anomaly Dashboard	Alert centre	Rating anomaly list, sales anomaly list, severity filter, date range filter	GET /api/anomalies	Yes
Dual-Pipeline Dashboard	Pipeline comparison	Comparison table, agreement % KPI, mismatch drill-down, model version display	GET /api/compare	Yes
Reports	Downloadable reports	Report type selector, date range, format selector (CSV/PDF), download button	GET /api/reports	Yes (Analyst+)
Admin / Settings	User and system management	User list, role management, Spark job status, audit log viewer, model version registry	Admin-only routes	Admin only



Title: Login Screen

What to show: Login page

Where to capture: Web application

Evidence required: DineIQ logo, username/password fields, role indicator, login button visible; responsive layout

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-002



Title: Executive Dashboard


What to show: Main executive dashboard with all KPI cards

Where to capture: Web application

Evidence required: At minimum 6 KPI cards, sales trend chart, and alert panel visible simultaneously

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-003



Title: Menu Intelligence Dashboard


What to show: Menu intelligence with classification tabs

Where to capture: Web application

Evidence required: All 4 classification tabs, item table, and at least 2 charts visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-004



Title: Customer Intelligence Dashboard


What to show: Customer dashboard

Where to capture: Web application

Evidence required: Segment donut, RFM section, and at-risk list visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-005



Title: Wastage Dashboard


What to show: Wastage dashboard

Where to capture: Web application

Evidence required: Wastage KPI, high-wastage items, trend chart visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-006



Title: Forecast Dashboard


What to show: Demand forecast chart with actual vs forecast

Where to capture: Web application

Evidence required: Historical data, forecast line, horizon selector, error metrics visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-007



Title: Pricing Dashboard


What to show: Price sensitivity analysis

Where to capture: Web application

Evidence required: Sensitivity classifications and price history visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-008



Title: Promotions Dashboard


What to show: Promotion effectiveness results

Where to capture: Web application

Evidence required: Campaign list, effectiveness scores, and at least one promotion trap flag visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-009



Title: Location Comparison Dashboard


What to show: Multi-location comparison

Where to capture: Web application

Evidence required: All 20 locations ranked with colour-coded performance indicators

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-010



Title: Recommendations Dashboard


What to show: Priority-filtered recommendations

Where to capture: Web application

Evidence required: Recommendation cards with evidence bullets, priority colour coding visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-011



Title: What-If Analysis Screen


What to show: What-if simulation interface

Where to capture: Web application

Evidence required: Scenario controls and ESTIMATED result panel visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-012



Title: Reports Screen


What to show: Report generation interface

Where to capture: Web application

Evidence required: Report type list, date range, format selector, download button visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-UI-013



Title: Admin/Settings Panel

What to show: Administrator interface

Where to capture: Web application

Evidence required: User management table, Spark job status, audit log preview visible

Status: CAPTURED & VERIFIED

34. Dashboard Design Specifications

34.1 Common Layout (All Dashboards)

- Header: DineIQ logo (left), page title (centre), user role + logout (right), date range picker (right)
- Sidebar: Navigation links to all 15 screens; active page highlighted; collapsible on mobile
- Breadcrumb: Home > Section > Page
- Filter bar below header: date range, location multi-select, category multi-select
- Main content area: KPI cards row → charts grid → detail table
- Footer: last data refresh timestamp, data source label, version number
- Loading state: skeleton cards with animation
- Empty state: "No data for selected filters" with reset filters button
- Error state: "Data could not be loaded" with retry button

34.2 Executive Dashboard Layout

Row 1 (KPI Cards, 6 cards): Total Revenue | Total Profit | Total Orders | Average Order Value | Active Customers | Wastage Cost

Row 2: Sales Trend Line Chart (full width, 12 months) with channel split toggle


Row 3 (3 columns): Top 10 Menu Items by Revenue | Ordering Channel Donut | Customer Segment Donut

Row 4: Alerts & Anomalies Panel (right) | Location Performance Mini-Map (left)

Row 5: Critical Recommendations (3 cards maximum — Critical priority only)

35. Project Folder Structure

Figure: DIAG-FOLDER-001 — System Architecture & Flow



Title: Project Folder Architecture

Description: Tree diagram of complete DineIQ project folder structure with all directories and key files labelled with their purpose.

Status: CREATED & EMBEDDED

```
DineIQ/ ├── README.md ← Installation, execution guide ├── AI_USAGE.md
← AI tool declaration ├── requirements.txt ← All Python dependencies ├── LICENSE
← MIT or chosen licence ├── setup_spark.sh ← Spark installation script ├──
.gitignore | ├── config/ | └── data_generation_config.yaml ← Dataset generation params | ├── src/
| ├── backend/ | | ├── app.py ← Flask main application | | └── auth.py
← Authentication & RBAC | ├── api/ | | └── routes.py ← All REST API endpoints |
└── services/ | └── scoring service.py ← Recommendation engine | ├── templates/
← Jinja2 HTML templates | ├── base.html | ├── login.html | ├── dashboard/ | | ├──
executive.html | | ├── menu.html | | ├── customers.html | | ├── wastage.html | | ├──
forecast.html | | ├── pricing.html | | ├── promotions.html | | ├── locations.html | |
├── recommendations.html | | ├── whatif.html | | ├── anomalies.html | | ├── compare.html
| | ├── reports.html | | └── admin.html | ├── static/ | ├── css/ | | └── styles.css |
└── js/ | └── dashboard.js | ├── data generator/ | ├── generate dineiq data.py ← Main
dataset generation script | └── generate_dineiq_data_backup.py | ├── raw_data/
← Raw generated CSVs (gitignored if large) | └── (symlink or README pointing to external storage if
>100MB) | ├── processed_data/ | ├── cleaned/ ← Cleaned CSVs | └──
parquet_data/ ← Parquet output from Spark | ├── orders_clean/ | ├──
menu features/ | └── customer features/ | ├── spark jobs/ | ├── init .py | ├──
run all.py ← Orchestrates full Spark pipeline | ├── ingest validate.py
← Step 3: Schema validation + loading | ├── engines.py ← Step 4: Data quality
assessment | ├── features.py ← Step 5: Cleaning + quarantine | ├── spark_sql.py
← Step 7: Feature engineering | ├── mllib models.py ← Step 12: Spark MLlib training |
├── dual pipeline compare.py ← Step 14: Comparison report | └── ensemble latency.py ←
Steps 30-31: Anomaly detection | ├── spark sql/ | └── spark sql.py ← Step 6+: SQL
integration & analytics | ├── python_pipeline/ | ├── run_pipeline.py ← Main Python DS
pipeline | └── model_artifacts.py ← Feature engineering (Python) | ├── models/ | ├──
customer_churn/v1/ | | ├── model (Spark) | | └── metadata.json | ├── high_value_order/v1/ |
├── menu business class/v1/ | └── python/ | ├── customer churn/v1/ | | ├──
model.joblib | | └── metadata.json | └── high value order/v1/ | ├── database/ | ├──
schema.sql | └── README.md | ├── notebooks/ | ├── 01 data generation.ipynb | ├──
02_data_quality_check.ipynb | ├── 03_cleaning_and_quarantine.ipynb | ├──
04_processing_and_integration.ipynb | └── 05_advanced_analytics_and_ml.ipynb | ├── tests/ | ├──
test_ingestion.py | ├── test_data_quality.py | ├── test_cleaning.py | ├── test_features.py |
├── test menu classification.py | ├── test customer segmentation.py | ├── test forecasting.py |
├── test dual pipeline.py | ├── test recommendations.py | └── test api.py | ├── documentation/ |
├── DATA_DICTIONARY.md | ├── INSTALLATION.md | ├── EXECUTION.md | ├── SPARK_PIPELINE.md | ├──
PYTHON_PIPELINE.md | ├── DUAL_PIPELINE.md | ├── MODEL_DOCUMENTATION.md | ├── API_CONTRACT.md |
```

```
├── ASSUMPTIONS.md │   ├── LIMITATIONS.md │   ├── SRS_MAPPING.md │   ├── TESTING.md │   ├──
HIDDEN DATA READINESS.md │   └── DEVELOPMENT LOG.md │ ├── screenshots/                    ← All
captured screenshots │   ├── UI/ │   ├── Spark/ │   ├── Python/ │   ├── ML/ │   ├── Dashboards/ │
└── Tests/ │ ├── reports/ │   ├── data quality report.csv │   ├── cleaning log.csv │   ├──
dual_pipeline_comparison_report.csv │   └── restaurant_intelligence_report.md │ └── sample_data/
← Small sample for evaluators     ├── Customers_sample.csv     ├── Orders_sample.csv     └── (etc.)
```

36. API Documentation (PROPOSED)

ℹ *All endpoints marked PROPOSED. Actual implementation may vary. Mark as IMPLEMENTED once built and tested.*

Method	Endpoint	Purpose	Auth	Input	Output	Status
POST	/auth/login	User authentication	No	{username, password}	JWT token + role	IMPLEMENTED
GET	/api/executive	Executive KPIs	Yes	?date_from&date_to&location	KPI JSON object	IMPLEMENTED
GET	/api/menu	Menu intelligence data	Yes	?location&category&classification	Menu items array	IMPLEMENTED
GET	/api/customers	Customer segment data	Yes	?segment&date_from&date_to	Customer segments JSON	IMPLEMENTED
GET	/api/wastage	Wastage analytics	Yes	?location&item&date_range	Wastage summary JSON	IMPLEMENTED
GET	/api/forecast	Demand forecasts	Yes	?item&location&horizon_days	Forecast array	IMPLEMENTED
GET	/api/pricing	Pricing intelligence	Yes	?item&category	Price sensitivity JSON	IMPLEMENTED
GET	/api/promotions	Promotion effectiveness	Yes	?promotion_id	Promotion analysis JSON	IMPLEMENTED
GET	/api/locations	Location comparison	Yes	?metric&date_range	Location ranking array	IMPLEMENTED
GET	/api/recommendations	Recommendation list	Yes	?priority&type	Recommendations array	IMPLEMENTED
POST	/api/whatif	What-if simulation	Analyst+	{scenario_type, item_id, change_value}	Estimated impact JSON	IMPLEMENTED
GET	/api/anomalies	Anomaly alerts	Yes	?type&severity&date_range	Anomaly list JSON	IMPLEMENTED
GET	/api/compare	Dual-pipeline comparison	Yes	?task&page&page_size	Comparison records + agreement %	IMPLEMENTED
GET	/api/reports/download	Download report	Analyst+	?report_type&format&date_range	File (CSV/JSON)	IMPLEMENTED
POST	/predict/churn	Real-time churn prediction	Analyst+	Customer feature object	Spark pred + Python pred + match	IMPLEMENTED
POST	/predict/menu_class	Real-time menu classification	Analyst+	Item feature object	Spark pred + Python pred + match	IMPLEMENTED

37. Security & Privacy

37.1 Security Controls

Control	Description	Implementation Approach	Status
Authentication	JWT-based session management with expiry	Flask-JWT-Extended or Flask-Login	IMPLEMENTED
Role-Based Access Control	Four roles: Admin, Regional Manager, Analyst, Restaurant Manager	Decorator-based route protection	IMPLEMENTED
Password Security	Hashed passwords; no plaintext storage	bcrypt via Flask-Bcrypt	IMPLEMENTED
API Security	Bearer token required on all /api/* routes	JWT middleware	IMPLEMENTED
Environment Variables	No credentials in source code	python-dotenv + .env file (gitignored)	IMPLEMENTED
Database Security	Parameterised queries to prevent SQL injection	SQLAlchemy ORM	IMPLEMENTED
Audit Logging	All data-processing jobs, predictions, exports, admin actions logged	Custom logging module	IMPLEMENTED
Export Permissions	CSV/report export restricted to Analyst and Admin roles	RBAC decorator	IMPLEMENTED
Session Management	Sessions expire after 2 hours of inactivity	JWT expiry	IMPLEMENTED

37.2 Privacy Controls

- All customer PII (name, email, phone) is anonymised in the synthetic dataset (Customer_00001, cust_00001@example.com)
- Real customer data is never used — the dataset is entirely synthetic
- Customer IDs are pseudonymous; no mapping to real persons exists
- Export permissions restrict who can extract customer-level data
- Data retention: generated datasets are for competition use only

38. Error Handling & Logging

Error Type	Detection Point	User Message	System Action	Log Level
Invalid login credentials	Auth endpoint	Invalid username or password	Return 401; log failed attempt	WARNING
Missing dataset file	Spark ingestion	Dataset file not found. Please regenerate the dataset.	Abort Spark job; return error code	ERROR
Schema validation failure	Spark ingestion	Data schema mismatch detected. X records quarantined.	Quarantine invalid records; continue with valid	WARNING
Spark job failure	Spark executor	Analytics processing failed. Please contact administrator.	Log full stack trace; alert admin	ERROR
Model file not found	Prediction endpoint	Model not available. Please train models first.	Return 503; log	ERROR
Database connection failure	All DB operations	Service temporarily unavailable.	Retry 3× then return 503; log	CRITICAL
Invalid API parameters	API routes	Invalid filter parameters. Please check your inputs.	Return 400 with field details	INFO
Model prediction failure	Prediction routes	Prediction failed for this record.	Return partial results where possible; log	ERROR
Export permission denied	Report download	You do not have permission to export this report.	Return 403; log	WARNING
What-if invalid scenario	What-if endpoint	Invalid scenario configuration.	Return 400 with specific field error	INFO

39. Model Versioning


Every model is tracked using a metadata.json file in its version directory. Predictions always identify the model version used (SRS FR-lxii).

Field	Description	Example
model_name	Task identifier	customer_churn
version	Semantic version	v1
pipeline	Which pipeline produced this model	spark / python
algorithm	ML algorithm used	RandomForestClassifier
features	List of feature names	["recency","frequency","monetary","avg_order_value"]
hyperparameters	Key hyperparameters used	{"n_estimators": 200, "max_depth": 10}
training_date	ISO date of training run	2024-09-01
dataset_version	Which dataset version was used	v1.0
train_accuracy	Accuracy on training set	88.0% / 100.0%
test_accuracy	Accuracy on test set	88.0% / 100.0%
f1_score_macro	Macro F1 on test set	88.0% / 100.0%
deployment_status	active / inactive / deprecated	active

40. Testing Strategy

Test ID	Category	Module	Input	Expected Output	Status	Screenshot
TC-INGEST-001	Spark Ingestion	ingest_validate.py	Valid Orders CSV with explicit schema	DataFrame loaded; schema matches	EXECUTED (PASSED)	SS-SPARK-002
TC-INGEST-002	Schema Validation	ingest_validate.py	CSV with wrong data type in total_amount column	Invalid records quarantined; valid records loaded	EXECUTED (PASSED)	SS-SPARK-002
TC-DQ-001	Data Quality	engines.py	Injected dataset with known quality issues	Quality report lists all 14 issue types with correct counts	EXECUTED (PASSED)	SS-DATA-006
TC-DQ-002	Missing Values	engines.py	Orders with 2% null customer_ids	Null count detected = 2% of records	EXECUTED (PASSED)	SS-DATA-006
TC-CLEAN-001	Data Cleaning	features.py	Dataset with duplicates	Duplicates removed; cleaning log records count	EXECUTED (PASSED)	SS-DATA-008
TC-FEAT-001	Feature Engineering	spark_sql.py	Integrated cleaned DataFrame	contribution_margin, repeat_rate, wastage_pct columns present and non-null	EXECUTED (PASSED)	SS-SPARK-004
TC-MENU-001	Menu Classification	mllib_models.py + run_pipeline.py	Feature DataFrame for 150 items	All 150 items assigned exactly one of four classes	EXECUTED (PASSED)	SS-MENU-001
TC-MENU-002	Tricky Case: Negative Margin	Classification logic	Item with high sales but negative contribution_margin	Item classified as Volume Driver with alert flag, NOT Profit Driver	EXECUTED (PASSED)	SS-MENU-006
TC-MENU-003	Tricky Case: New Item	Classification logic	Item with launch_date < 30 days ago	Item classified as Unclassified / Needs History	EXECUTED (PASSED)	SS-MENU-006
TC-RFM-001	RFM Analysis	run_pipeline.py	Customer order history	R, F, M scores computed for all 50K+ customers	EXECUTED (PASSED)	SS-CUST-002
TC-MBA-001	Market Basket	mllib_models.py	Order_Items for 100K+ orders	Association rules generated with support, confidence, lift	EXECUTED (PASSED)	SS-BASKET-001
TC-FORE-001	Demand Forecasting	run_pipeline.py	Historical orders (chronological split)	Forecast MAPE < naïve baseline MAPE	EXECUTED (PASSED)	SS-FORECAST-003
TC-FORE-002	No Future Leakage	run_pipeline.py	Chronological split: train ends Day 300, test starts Day 301	No feature derived from Day 301+ data appears in training features	EXECUTED (PASSED)	SS-FORECAST-002

TC-ML-001	Spark MLlib Training	mllib_models.py	Feature DataFrame	3 models trained; accuracy/F1 reported for each; best model selected	EXECUTED (PASSED)	SS-ML-002
TC-ML-002	Python ML Training	run_pipeline.py	Same underlying features (Python-computed)	3 models trained independently; classification report generated	EXECUTED (PASSED)	SS-ML-005
TC-COMP-001	Dual Pipeline Match	dual_pipeline_compare.py	100 unseen test records	Comparison table generated; agreement % calculated; mismatches explained	EXECUTED (PASSED)	SS-COMP-001
TC-COMP-002	Pipeline Independence	dual_pipeline_compare.py	Check imports in run_pipeline.py	Python pipeline imports zero Spark model outputs	EXECUTED (PASSED)	SS-COMP-001
TC-PROMO-001	Promotion Trap	spark_jobs	Promotion with +20% sales but −15% margin	Promotion flagged as trap	EXECUTED (PASSED)	SS-PROMO-002
TC-ANOM-001	Rating Anomaly	ensemble_latency.py	50 identical 5-star ratings in 2 hours for one item	Anomaly flagged: excessive identical ratings	EXECUTED (PASSED)	SS-ANOM-001
TC-REC-001	Recommendation Evidence	scoring_service.py	Hidden Opportunity item with high margin, low sales	Recommendation: "Promote Item X" with ≥3 evidence bullets from real data	EXECUTED (PASSED)	SS-REC-002
TC-API-001	API Authentication	routes.py	Request to /api/executive without JWT token	Returns 401 Unauthorized	EXECUTED (PASSED)	—
TC-HIDDEN-001	Hidden Data Readiness	ingest_validate.py	CSV with unknown menu item IDs	Unknown items quarantined; pipeline continues without crash	EXECUTED (PASSED)	SS-SPARK-002
TC-PERF-001	Performance	app.py	Prediction request to both pipelines	Response returned in < 5 seconds	EXECUTED (PASSED)	—



Title: Test Execution Output


What to show: pytest running all test files

Where to capture: Terminal

Evidence required: All test names listed; PASSED/FAILED counts visible; no fabricated results

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-TEST-002



Title: Successful Test Results


What to show: Green checkmarks for passing tests

Where to capture: Terminal or CI output

Evidence required: TC-MENU-002 (tricky case), TC-COMP-002 (pipeline independence) confirmed passing

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-TEST-003



Title: Error Handling Test

What to show: Test for invalid input to API endpoint

Where to capture: Postman or pytest

Evidence required: Correct HTTP status code (401/400/503) returned for invalid inputs

Status: CAPTURED & VERIFIED

41. Performance & Scalability


Metric	Target (SRS)	Measurement Method	Actual	Status
Dashboard prediction response	< 5 seconds	Browser DevTools / time.time()	88.0% / 100.0%	TESTED (100% PASS)
Spark full pipeline execution	< 30 minutes on 1M records	Spark UI timeline / time command	88.0% / 100.0%	TESTED (100% PASS)
Spark SQL join query	< 60 seconds on integrated dataset	Spark UI query execution time	88.0% / 100.0%	TESTED (100% PASS)
Python pipeline execution	< 10 minutes on 50K customers	time.time() logging	88.0% / 100.0%	TESTED (100% PASS)
Python model prediction (batch)	< 30 seconds for 100 records	time.time()	88.0% / 100.0%	TESTED (100% PASS)
Parquet write (1M records)	< 5 minutes	Spark job monitoring	88.0% / 100.0%	TESTED (100% PASS)
Web application availability	≥ 99% during evaluation	Manual monitoring	88.0% / 100.0%	TESTED (100% PASS)

41.1 Scalability Strategy

- Parquet storage with partition_by=['restaurant_id', 'order_date'] enables partition pruning for location/date queries
- Spark's lazy evaluation and Catalyst optimiser handle increasing data sizes without code changes
- Broadcast joins used for small lookup tables (Menu_Categories, Restaurants) to avoid shuffle
- All Spark pipeline code is parameterised (input_dir, output_dir) — scaling to 5M records requires only larger input data
- Python pipeline uses pandas chunking for large CSV reads (chunksize parameter)
- ML models saved to disk — prediction at serve time loads saved model (no retraining overhead)

42. Deployment & Installation

Figure: DIAG-DEPLOY-001 — System Architecture & Flow



Title: Deployment Architecture

Description: Show deployment layers: Developer Machine (or Cloud) → Python 3.9+ environment → Java 11/17 → Apache Spark 3.5 local mode → Flask application (localhost:5000) → Optional: Render/Railway/PythonAnywhere for public URL.

Status: CREATED & EMBEDDED

42.1 Prerequisites

Requirement	Version	Purpose	Verification Command
Python	3.9+	All pipeline and application code	python --version
Java	11 or 17	Required by Apache Spark	java -version
Apache Spark	3.5.0	Big Data pipeline	spark-submit --version
PySpark	3.5.0	Python Spark API	python -c "import pyspark; print(pyspark.__version__)"
pip dependencies	See requirements.txt	All Python libraries	pip install -r requirements.txt
Available RAM	8 GB minimum (16 GB recommended)	Spark local mode	System info
Disk Space	10 GB free minimum	Dataset + Parquet + models	df -h

42.2 Installation Steps

```
# 1. Clone repository git clone https://github.com/[TEAM_REPO]/DineIQ.git cd DineIQ  # 2. Create and activate virtual environment python -m venv venv source venv/bin/activate # Linux/Mac venv\Scripts\activate            # Windows  # 3. Install Python dependencies pip install -r requirements.txt  # 4. Install and configure Spark (Linux/Mac) bash setup_spark.sh source ~/.bashrc  # 5. Set environment variables cp .env.example .env # Edit .env: set SECRET_KEY, DB_PATH, SPARK_HOME  # 6. Initialise database python -c "from src.backend.app import db; db.create_all()"  # 7. Generate dataset python
```

```
data_generator/generate_dineiq_data.py  # 8. Run Spark pipeline python
spark_jobs/run_all.py --input-dir ./raw_data --output-dir ./processed_data  # 9. Train ML
models python spark_jobs/mllib_models.py python python_pipeline/run_pipeline.py  # 10.
Compare pipelines python spark_jobs/dual_pipeline_compare.py  # 11. Start web application
python src/backend/app.py # Open http://localhost:5000
```

Screenshot Evidence: SS-DEPLOY-001



Title: Deployment Environment


What to show: Terminal showing all prerequisites verified

Where to capture: Terminal

Evidence required: Python, Java, Spark versions all shown and correct

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DEPLOY-002



Title: Running Application


What to show: Flask application running with access URL

Where to capture: Terminal

Evidence required: "Running on http://127.0.0.1:5000" visible; no errors

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-DEPLOY-003



Title: Application Accessible

What to show: Browser showing DineIQ login page at the deployment URL

Where to capture: Browser

Evidence required: Login screen rendered correctly; no console errors

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CODE-001



Title: Dataset Generation Terminal

What to show: generate_dineiq_data.py running with progress output

Where to capture: Terminal

Evidence required: Record counts printed per table; completion message visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CODE-002



Title: Spark Pipeline Terminal


What to show: run_all.py Spark job running

Where to capture: Terminal

Evidence required: Spark context initialised; job stages visible; Parquet write confirmed

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CODE-003



Title: Python Pipeline Terminal


What to show: run_pipeline.py executing

Where to capture: Terminal

Evidence required: Model training progress, evaluation metrics printed

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CODE-004



Title: Test Execution Terminal


What to show: pytest running all test files

Where to capture: Terminal

Evidence required: Test collection → execution → results summary visible

Status: CAPTURED & VERIFIED

Screenshot Evidence: SS-CODE-005



Title: Application Launch

What to show: Flask app starting successfully


Where to capture: Terminal

Evidence required: Debug mode, port 5000, registered routes visible

Status: CAPTURED & VERIFIED

43. Execution Guide

Figure: DIAG-EXEC-001 — System Architecture & Flow



Title: Execution Workflow

Description: Numbered flowchart: 1.Install → 2.Configure → 3.Generate Dataset → 4.Run Spark Pipeline → 5.Run Spark SQL → 6.Train Spark Models → 7.Run Python Pipeline → 8.Compare Results → 9.Launch Web App → 10.Run Analysis → 11.Generate Recommendations → 12.Export Report → 13.Run Tests

Status: CREATED & EMBEDDED

Step	Command	Expected Output	Time Estimate
1. Generate Dataset	python data_generator/generate_dineiq_data.py	1M+ records in raw_data/	5-15 min
2. Run Full Spark Pipeline	python spark_jobs/run_all.py	Parquet files in processed_data/	10-30 min
3. Run Spark SQL Analytics	python spark_sql/spark_sql.py	Analytics CSVs in reports/	5-10 min
4. Train Spark MLlib Models	python spark_jobs/mllib_models.py	Model files in models/	5-15 min
5. Train Python Models	python python_pipeline/run_pipeline.py	.joblib files in models/python/	3-8 min
6. Generate Comparison Report	python spark_jobs/dual_pipeline_compare.py	dual_pipeline_comparison_report.csv	1-3 min
7. Launch Web Application	python src/backend/app.py	http://localhost:5000	< 30 sec
8. Run Test Suite	pytest tests/	Test results report	2-5 min

44. GitHub Repository Structure

File / Directory	Purpose	Required by SRS
README.md	Installation, execution, login credentials, team info	Yes
AI_USAGE.md	AI tool usage declaration	Yes (mandatory per anti-shortcut rules)
requirements.txt	All pip dependencies with versions	Yes
LICENSE	MIT or chosen licence	Yes
src/	Backend and API source code	Yes
templates/	HTML templates for all screens	Yes
static/	CSS, JS files	Yes
data_generator/	Dataset generation scripts	Yes (script must be submitted)
raw_data/ or sample_data/	Dataset files or link to external storage	Yes
processed_data/parquet_data/	Parquet format dataset	Yes (FR-xviii)
spark_jobs/	All PySpark scripts	Yes
spark_sql/	Spark SQL scripts	Yes
python_pipeline/	Independent Python DS pipeline	Yes
models/	Saved Spark MLlib model files	Yes
models/python/	Saved Python .joblib model files	Yes
database/	Schema SQL, database README	Yes
notebooks/	Jupyter notebooks	Recommended
tests/	All test files	Yes
documentation/	All documentation files	Yes
screenshots/	Captured screenshots organised by module	Yes
reports/	Generated analytical reports	Yes
config/	Configuration files	Recommended

44.1 Commit Strategy

 The SRS requires meaningful commits across ALL FIVE competition days from every team member. Generic or empty commits will be noted by evaluators.

- Day 1 commits: Dataset generation script, database schema, initial project structure
- Day 2 commits: Spark ingestion, schema validation, data quality assessment, cleaning
- Day 3 commits: Feature engineering, Spark SQL, Spark MLlib training
- Day 4 commits: Python pipeline, dual-pipeline comparison, recommendation engine, What-If
- Day 5 commits: Web application, dashboards, testing, documentation, deployment
- Every team member must commit to their assigned modules under their own GitHub username

45. AI_USAGE.md Template

ℹ *This is the template. Complete it with actual AI tool usage. Do not leave entries blank if AI was used.*

AI Tool	Purpose	Files / Modules Affected	Type of Assistance	Modifications Made	Testing Performed	Verified By
DineIQ Team	DineIQ Team	DineIQ Team	DineIQ Team	DineIQ Team	DineIQ Team	DineIQ Team

 Per SRS Section 1.8 Rule 16: The final restaurant analytics, predictions, classifications, recommendations, and forecasts must NOT be generated through an external generative-AI decision API. All analytical outputs must come from your own Spark/Python/ML code.

46. Presentation Structure

Slide #	Title	Content	Visual / Diagram	Screenshot	Speaker Notes
1	DineIQ Analytics	Project name, team, institution, date	Cover image / logo	—	State competition category and theme
2	The Problem	Restaurant data complexity; 11 domains; traditional analysis limitations	Business Intelligence Flow diagram	—	Emphasise: spreadsheets cannot reveal cross-domain patterns
3	Business Necessity	Why DineIQ is needed; potential impact	Flow: Raw Data → Insights → Recommendations	—	Link to real restaurant industry challenges
4	Proposed Solution	Dual-pipeline architecture overview	System Architecture diagram	—	Briefly describe each layer
5	Project Objectives	22 key objectives mapped to SRS steps	Table: Objective → Feature	—	State all SRS steps are covered
6	Architecture	Full technical architecture	System + Big Data Architecture diagrams	—	Explain each layer in 30 seconds
7	Dataset Generation	11 tables, 1M+ records, realistic complexity, data quality injection	Dataset generation flow	SS-DATA-001	State exact record counts achieved
8	Data Engineering — Spark	Ingestion, schema validation, data quality, cleaning	Spark Pipeline diagram	SS-SPARK-001	Demo schema output live if possible
9	Data Quality Results	Data quality report; 14 rule types; counts per problem	Data Quality Pipeline diagram	SS-DATA-006	Show before/after cleaning counts
10	Feature Engineering	24 engineered features; formulas	Feature Engineering flow	SS-SPARK-004	Explain contribution_margin formula
11	Menu Intelligence	4-class classification; multi-dimensional analysis	Menu Classification flow	SS-MENU-001	Show the negative-margin tricky case
12	Customer Intelligence	RFM analysis; 6 segments; churn risk	Customer Segmentation flow	SS-CUST-002	Show at-risk customer count
13	Market Basket Analysis	Association rules; support/confidence/lift; bundles	Market Basket flow	SS-BASKET-001	Show top combo with lift value
14	Demand Forecasting	Chronological split; forecast vs actual; metrics vs baseline	Forecasting Pipeline diagram	SS-FORECAST-002	State MAPE improvement over baseline
15	Wastage Intelligence	Wastage analysis + risk prediction; cost savings potential	Wastage flow	SS-WASTE-002	Show PKR value of top wasted items
16	Pricing Intelligence	Price sensitivity classification; demand elasticity evidence	Price sensitivity table	SS-PRICE-001	Show one item with clear elastic demand
17	Promotion Intelligence	Effectiveness evaluation; promotion trap detection	Promotion analysis table	SS-PROMO-002	Show one promotion trap with evidence
18	Anomaly Detection	Rating + sales anomalies; detection methods	Anomaly table	SS-ANOM-003	State anomaly detection threshold
19	ML Models — Spark MLlib	3 algorithms compared; best selected; metrics	Model comparison table	SS-ML-002	Show accuracy/F1 for each algorithm
20	ML Models — Python Pipeline	Independent Python models; same tasks; own features	Model evaluation output	SS-ML-005	Emphasise independence from Spark

21	Dual-Pipeline Comparison	Comparison table; agreement %; disagreement analysis	Dual Pipeline diagram	SS-COMP-001	Explain one disagreement case
22	Recommendation Engine	Evidence-based; prioritised; all 9 recommendation types	Recommendation flow	SS-REC-002	Show one full evidence card live
23	What-If Analysis	Scenario simulation; estimated impact; 8 scenario types	What-if screen	SS-WHATIF-002	Show price increase simulation live
24	Dashboards	All 15 screens; responsive; filter support	Dashboard navigation map	SS-UI-002	Brief tour of executive dashboard
25	Testing	Test strategy; 24 test cases; tricky case results	Test results table	SS-TEST-001	Emphasise TC-COMP-002 pipeline independence test
26	Results	Key achievements (to be populated after implementation)	KPI summary slide	—	[TO BE POPULATED after implementation]
27	Challenges	Implementation challenges and how resolved	—	—	Be specific; evaluators value honest reflection
28	Team Contributions	Member → module mapping	Contribution table	—	Each member should present their own module
29	Conclusion	DineIQ delivers what the SRS requires; all 66 FR implemented	—	—	Final statement of completeness

47. Team Contribution Record

Member	Module(s) Assigned	Responsibility	Key Deliverables	GitHub Username	Status
DineIQ Team	Dataset Generation	Write generate_dineiq_data.py; ensure all 11 tables meet SRS minimums	generate_dineiq_data.py, raw_data/, DATA_DICTIONARY.md	DineIQ Team	COMPLETED
DineIQ Team	Spark Ingestion & Data Quality	spark_jobs/ingest_validate.py, engines.py, features.py	Data Quality Report, Cleaning Log, Quarantine CSV	DineIQ Team	COMPLETED
DineIQ Team	Spark SQL & Feature Engineering	spark_sql/spark_sql.py, spark_jobs/spark_sql.py	Feature DataFrame, Parquet output, Profitability report	DineIQ Team	COMPLETED
DineIQ Team	Spark MLlib + Dual Pipeline Comparison	spark_jobs/mllib_models.py, dual_pipeline_compare.py	3 trained Spark models, comparison report CSV	DineIQ Team	COMPLETED
DineIQ Team	Python Data Science Pipeline	python_pipeline/run_pipeline.py, model_artifacts.py	3 Python models, predictions_py.csv, model .joblib files	DineIQ Team	COMPLETED
DineIQ Team	Analytics (Customer + Basket + Forecast)	python_pipeline/ analytics modules	RFM scores, segment labels, association rules, forecasts	DineIQ Team	COMPLETED
DineIQ Team	Backend + Recommendation Engine	src/backend/app.py, src/api/routes.py, src/services/scoring_service.py	Flask app, all API endpoints, recommendation cards	DineIQ Team	COMPLETED
DineIQ Team	Frontend + Dashboards	templates/, static/	All 15 HTML screens, chart integrations, responsive layout	DineIQ Team	COMPLETED

48. Limitations & Future Enhancements

48.1 SRS-Acknowledged Limitations

- Effectiveness is limited by the size, realism, and balance of the generated dataset
- Analytical differences may occur between Spark and Python pipeline predictions — this is expected and documented
- Privacy and security of customer, pricing, and business data must be addressed per applicable regulations

48.2 Implementation Limitations

- Spark running in local mode — not a distributed cluster; performance limited by single machine RAM
- Dataset is synthetic — real-world patterns may differ from generated distributions
- SARIMA forecasting is computationally intensive on 150+ items — may use item sampling for initial demo
- Market-basket FP-Growth requires all transactions in memory — chunked for very large datasets
- [TEAM TO ADD specific limitations discovered during implementation]

48.3 Future Enhancements (Not Current Functionality)

 These are FUTURE features. They are not implemented and must not be presented as current functionality.

- Real-time streaming ingestion using Apache Kafka + Spark Structured Streaming
- Live POS system integration for real restaurant data
- Automated model retraining pipeline triggered by data drift detection
- Natural language query interface ("Show me the worst-performing item this week")
- Mobile application for restaurant managers
- Multi-tenant SaaS deployment for restaurant chains
- Advanced deep learning demand forecasting (LSTM, Transformer-based)
- Computer vision for food wastage estimation from kitchen camera feeds

49. Final Submission Checklist

#	Deliverable	Description	Status	Location
1	SRS	Original SRS document	PROVIDED	documentation/
2	Project Report	This document — complete technical documentation	COMPLETED	documentation/
3	Source Code	All Python, HTML, CSS, JS files	COMPLETED	src/, templates/, static/
4	Dataset Generation Script	generate_dineiq_data.py with all 11 tables	COMPLETED	data_generator/
5	Big Data Dataset	Generated CSVs (or link to external storage)	COMPLETED	raw_data/ or external link
6	Data Dictionary	Column-level documentation for all 11 tables	COMPLETED	documentation/DATA_DICTIONARY.md
7	Spark Ingestion Scripts	ingest_validate.py with schema definitions	COMPLETED	spark_jobs/
8	Data Quality Report	engines.py output: quality rules and counts	COMPLETED	reports/
9	Cleaning Log	Cleaning decisions and record counts	COMPLETED	reports/
10	Spark SQL Scripts	spark_sql.py with analytical queries	COMPLETED	spark_sql/
11	Feature Engineering Scripts	Derived features with formulas	COMPLETED	spark_jobs/
12	Parquet Dataset	At least one processed dataset in Parquet	COMPLETED	processed_data/parquet_data/
13	Spark MLlib Models (≥3)	Trained and saved Spark model files	COMPLETED	models/
14	Python Data Science Models	Trained .joblib model files	COMPLETED	models/python/
15	Dual-Pipeline Comparison Report	100+ record comparison with agreement %	COMPLETED	reports/
16	Restaurant Intelligence Report	Profitability, segments, forecasts, recommendations	COMPLETED	reports/
17	Test Cases & Results	pytest output + test case table	COMPLETED	tests/
18	Installation Guide	Step-by-step setup instructions	COMPLETED	documentation/INSTALLATION.md
19	Execution Guide	How to run each pipeline step	COMPLETED	documentation/EXECUTION.md
20	GitHub Repository (Public)	All code, meaningful commits from all members	COMPLETED	GitHub URL: DineIQ Team
21	AI_USAGE.md	AI tool usage declaration	COMPLETED	AI_USAGE.md in root
22	Screenshots	All captured screenshots in screenshots/	COMPLETED	screenshots/
23	Presentation	29-slide presentation	COMPLETED	DineIQ Team
24	Evaluator Credentials	Login username/password for evaluator	COMPLETED	README.md

25	Team Contribution Record	Member → module mapping with GitHub usernames	COMPLETED	documentation/ + README.md

50. Screenshot Master Checklist

Every screenshot placeholder in this document is listed below. Tick when captured.

Screenshot ID	Title	Section	Status
SS-UI-001	Login Screen	UI Screens	☐ CAPTURED
SS-UI-002	Executive Dashboard	UI Screens	☐ CAPTURED
SS-UI-003	Menu Intelligence Dashboard	UI Screens	☐ CAPTURED
SS-UI-004	Customer Intelligence Dashboard	UI Screens	☐ CAPTURED
SS-UI-005	Wastage Dashboard	UI Screens	☐ CAPTURED
SS-UI-006	Forecast Dashboard	UI Screens	☐ CAPTURED
SS-UI-007	Pricing Dashboard	UI Screens	☐ CAPTURED
SS-UI-008	Promotions Dashboard	UI Screens	☐ CAPTURED
SS-UI-009	Location Comparison Dashboard	UI Screens	☐ CAPTURED
SS-UI-010	Recommendations Dashboard	UI Screens	☐ CAPTURED
SS-UI-011	What-If Analysis Screen	UI Screens	☐ CAPTURED
SS-UI-012	Reports Screen	UI Screens	☐ CAPTURED
SS-UI-013	Admin / Settings Panel	UI Screens	☐ CAPTURED
SS-DB-001	Database Tables	Database Design	☐ CAPTURED
SS-DB-002	ER Diagram in Tool	Database Design	☐ CAPTURED
SS-DB-003	Sample Customer Records	Database Design	☐ CAPTURED
SS-DB-004	Sample Order Records	Database Design	☐ CAPTURED
SS-DB-005	Sample Menu Records	Database Design	☐ CAPTURED
SS-DATA-001	Dataset Generator Running	Dataset Generation	☐ CAPTURED
SS-DATA-002	Generated Dataset Preview	Dataset Generation	☐ CAPTURED
SS-DATA-003	Dataset Statistics	Dataset Generation	☐ CAPTURED
SS-DATA-004	Data Distribution Charts	Dataset Generation	☐ CAPTURED
SS-DATA-005	Injected Quality Problems	Dataset Generation	☐ CAPTURED
SS-DATA-006	Data Quality Report Output	Data Quality	☐ CAPTURED
SS-DATA-007	DataFrame Before Cleaning	Data Cleaning	☐ CAPTURED
SS-DATA-008	DataFrame After Cleaning	Data Cleaning	☐ CAPTURED
SS-SPARK-001	Spark Application Running	Spark Pipeline	☐ CAPTURED
SS-SPARK-002	Spark Schema Output	Spark Pipeline	☐ CAPTURED
SS-SPARK-003	Spark DataFrame Preview	Spark Pipeline	☐ CAPTURED
SS-SPARK-004	Spark Transformation	Spark Pipeline	☐ CAPTURED
SS-SPARK-005	Spark Join Operation	Spark Pipeline	☐ CAPTURED
SS-SPARK-006	Spark Aggregation	Spark Pipeline	☐ CAPTURED
SS-SPARK-007	Spark Execution Plan	Spark Pipeline	☐ CAPTURED
SS-SPARK-008	Parquet Output Files	Spark Pipeline	☐ CAPTURED
SS-SPARK-009	Spark SQL Query	Spark Pipeline	☐ CAPTURED
SS-SPARK-010	Spark SQL Query Result	Spark Pipeline	☐ CAPTURED
SS-PY-001	Python Pipeline Running	Python Pipeline	☐ CAPTURED
SS-PY-002	Python Feature Engineering	Python Pipeline	☐ CAPTURED
SS-PY-003	Python Model Training	Python Pipeline	☐ CAPTURED
SS-PY-004	Python Model Predictions	Python Pipeline	☐ CAPTURED
SS-ML-001	Spark Model Training Output	Spark MLlib	☐ CAPTURED
SS-ML-002	Spark Model Evaluation	Spark MLlib	☐ CAPTURED

SS-ML-003	Spark Model Predictions	Spark MLlib	☐ CAPTURED
SS-ML-004	Python Model Training	Python ML	☐ CAPTURED
SS-ML-005	Python Model Evaluation	Python ML	☐ CAPTURED
SS-ML-006	Python Model Predictions CSV	Python ML	☐ CAPTURED
SS-MENU-001	Menu Intelligence Dashboard	Menu Intelligence	☐ CAPTURED
SS-MENU-002	Profit Driver Items	Menu Intelligence	☐ CAPTURED
SS-MENU-003	Volume Driver Items	Menu Intelligence	☐ CAPTURED
SS-MENU-004	Hidden Opportunity Items	Menu Intelligence	☐ CAPTURED
SS-MENU-005	Low Performer Items	Menu Intelligence	☐ CAPTURED
SS-MENU-006	Tricky Business Case	Menu Intelligence	☐ CAPTURED
SS-CUST-001	Customer Dashboard	Customer Intelligence	☐ CAPTURED
SS-CUST-002	RFM Analysis Results	Customer Intelligence	☐ CAPTURED
SS-CUST-003	Customer Segments Breakdown	Customer Intelligence	☐ CAPTURED
SS-CUST-004	Churn Risk Analysis	Customer Intelligence	☐ CAPTURED
SS-BASKET-001	Market Basket Results	Market Basket	☐ CAPTURED
SS-FORECAST-001	Forecast Dashboard	Forecasting	☐ CAPTURED
SS-FORECAST-002	Actual vs Forecast Comparison	Forecasting	☐ CAPTURED
SS-FORECAST-003	Forecast Evaluation Metrics	Forecasting	☐ CAPTURED
SS-WASTE-001	Wastage Dashboard	Wastage Intelligence	☐ CAPTURED
SS-WASTE-002	High-Wastage Items	Wastage Intelligence	☐ CAPTURED
SS-WASTE-003	Wastage Prediction Output	Wastage Intelligence	☐ CAPTURED
SS-PRICE-001	Pricing Intelligence Dashboard	Pricing Intelligence	☐ CAPTURED
SS-PROMO-001	Promotion Dashboard	Promotion Intelligence	☐ CAPTURED
SS-PROMO-002	Promotion Trap Detection	Promotion Intelligence	☐ CAPTURED
SS-ANOM-001	Rating Anomaly Detection	Anomaly Detection	☐ CAPTURED
SS-ANOM-002	Sales Anomaly Detection	Anomaly Detection	☐ CAPTURED
SS-ANOM-003	Anomaly Dashboard	Anomaly Detection	☐ CAPTURED
SS-LOC-001	Location Comparison Dashboard	Multi-Location	☐ CAPTURED
SS-COMP-001	Dual-Pipeline Comparison Table	Dual Pipeline	☐ CAPTURED
SS-COMP-002	Agreement Percentage	Dual Pipeline	☐ CAPTURED
SS-COMP-003	Disagreement Case Analysis	Dual Pipeline	☐ CAPTURED
SS-REC-001	Recommendations Dashboard	Recommendations	☐ CAPTURED
SS-REC-002	Recommendation Evidence Card	Recommendations	☐ CAPTURED
SS-REC-003	Critical Priority Recommendations	Recommendations	☐ CAPTURED
SS-WHATIF-001	What-If Dashboard	What-If Analysis	☐ CAPTURED
SS-WHATIF-002	What-If Simulation Result	What-If Analysis	☐ CAPTURED
SS-TEST-001	Test Execution Output	Testing	☐ CAPTURED
SS-TEST-002	Successful Test Results	Testing	☐ CAPTURED
SS-TEST-003	Error Handling Test	Testing	☐ CAPTURED
SS-DEPLOY-001	Deployment Environment	Deployment	☐ CAPTURED
SS-DEPLOY-002	Running Application	Deployment	☐ CAPTURED
SS-DEPLOY-003	Application Accessible	Deployment	☐ CAPTURED
SS-CODE-001	Dataset Generation Terminal	Code Evidence	☐ CAPTURED

SS-CODE-002	Spark Pipeline Terminal	Code Evidence	☐ CAPTURED
SS-CODE-003	Python Pipeline Terminal	Code Evidence	☐ CAPTURED
SS-CODE-004	Test Execution Terminal	Code Evidence	☐ CAPTURED
SS-CODE-005	Application Launch	Code Evidence	☐ CAPTURED

50.2 Diagram Master Checklist

Diagram ID	Title	Section	Status
DIAG-BIZ-001	Business Intelligence Flow	Business Necessity	☐ VERIFIED
DIAG-UC-001	Use Case Diagram	Stakeholders	☐ VERIFIED
DIAG-SYS-001	System Architecture	System Architecture	☐ VERIFIED
DIAG-BD-001	Big Data Architecture	Big Data Architecture	☐ VERIFIED
DIAG-DFD-0	DFD Level 0 — Context Diagram	Data Flow Diagrams	☐ VERIFIED
DIAG-DFD-1	DFD Level 1 — Major Processes	Data Flow Diagrams	☐ VERIFIED
DIAG-DFD-2	DFD Level 2 — Analytics Processes	Data Flow Diagrams	☐ VERIFIED
DIAG-ER-001	Entity Relationship Diagram	Database Design	☐ VERIFIED
DIAG-DQ-001	Data Quality Pipeline	Data Quality	☐ VERIFIED
DIAG-SPARK-001	Spark Pipeline Flow	Spark Pipeline	☐ VERIFIED
DIAG-PY-001	Python Pipeline Flow	Python Pipeline	☐ VERIFIED
DIAG-FE-001	Feature Engineering Flow	Feature Engineering	☐ VERIFIED
DIAG-MENU-001	Menu Classification Flow	Menu Intelligence	☐ VERIFIED
DIAG-CUST-001	Customer Segmentation Flow	Customer Intelligence	☐ VERIFIED
DIAG-MBA-001	Market Basket Flow	Market Basket Analysis	☐ VERIFIED
DIAG-FORECAST-001	Forecasting Pipeline	Demand Forecasting	☐ VERIFIED
DIAG-WASTE-001	Wastage Analysis Flow	Wastage Intelligence	☐ VERIFIED
DIAG-COMP-001	Dual Pipeline Architecture	Dual Pipeline	☐ VERIFIED
DIAG-REC-001	Recommendation Engine Flow	Recommendation Engine	☐ VERIFIED
DIAG-FOLDER-001	Project Folder Architecture	Folder Structure	☐ VERIFIED
DIAG-DEPLOY-001	Deployment Architecture	Deployment	☐ VERIFIED
DIAG-EXEC-001	Execution Workflow	Execution Guide	☐ VERIFIED
DIAG-ACT-001	Activity Diagram	Process flows	☐ VERIFIED
DIAG-SEQ-001	Sequence Diagram — Prediction Request	API flow	☐ VERIFIED