

C:\WINDOWS\system32\cmd.exe

Pinging 20.0.0.1 with 32 bytes of data:

Reply from 20.0.0.1: bytes=32 time<1ms TTL=255

Reply from 20.0.0.1: bytes=32 time<1ms TTL=255

Reply from 20.0.0.1: bytes=32 time<1ms TTL=255

Reply from 20.0.0.1: bytes=32 time=1ms TTL=255

Ping statistics for 20.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Documents and Settings\user>ping 20.0.0.2

Pinging 20.0.0.2 with 32 bytes of data:

Request timed out.

Request timed out.

Request timed out.

Request timed out.

Ping statistics for 20.0.0.2:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ping 30.0.0.1

Pinging 30.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: Destination host unreachable.

Reply from 10.0.0.1: Destination host unreachable.

Reply from 10.0.0.1: Destination host unreachable.

Reply from 10.0.0.1: Destination host unreachable.

Ping statistics for 30.0.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Documents and Settings\user>

C:\Documents and Settings\user>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 40.0.0.10: bytes=32 time=3ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 40.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 3ms, Average = 1ms

C:\Documents and Settings\user>

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    Autoconfiguration IP Address. . . : 169.254.211.141
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 

C:\Documents and Settings\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 40.0.0.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 40.0.0.1

C:\Documents and Settings\user>ping 10.0.0.8

Pinging 10.0.0.8 with 32 bytes of data:

Reply from 40.0.0.1: Destination host unreachable.
Reply from 40.0.0.1: Destination host unreachable.
Reply from 40.0.0.1: Destination host unreachable.
Reply from 40.0.0.1: Destination host unreachable.

Ping statistics for 10.0.0.8:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```

R1 x R2 x R3 x Win-1 x Win-2 x

```
R3(config)#exit
R3#sho
*Aug 23 08:02:37.303: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip interface brief
Interface                IP-Address      OK? Method Status        Protocol
Ethernet0/0              40.0.0.1        YES manual up            up
Ethernet0/1              30.0.0.2        YES manual up            up
Ethernet0/2              unassigned      YES TFTP  down          down
Ethernet0/3              unassigned      YES TFTP  down          down
R3#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        a - application route
        + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
     30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     30.0.0.0/8 is directly connected, Ethernet0/1
L     30.0.0.2/32 is directly connected, Ethernet0/1
     40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     40.0.0.0/8 is directly connected, Ethernet0/0
L     40.0.0.1/32 is directly connected, Ethernet0/0
R3#-
```