#### **NAME**

rgbds — object file format documentation

### DESCRIPTION

This is the description of the object files used by rgbasm(1) and rgblink(1). Please, note that the specifications may change. This toolchain is in development and new features may require adding more information to the current format, or modifying some fields, which would break compatibility with older versions.

### FILE STRUCTURE

The following types are used:

LONG is a 32âbit integer stored in littleâendian format (Intel). BYTE is an 8âbit integer. STRING is a Oâterminated string of BYTE.

```
; Header
BYTE
                         ; "RGB6"
LONG
        NumberOfSymbols ; The number of symbols used in this file
        NumberOfSections; The number of sections used in this file
LONG
; Symbols
        NumberOfSymbols
                        ; Number of symbols defined in this object file.
REPT
                          ; The name of this symbol. Local symbols are stored
    STRING
           Name
                          ; as "Scope.Symbol".
    BYTE
                          ; 0 = LOCAL symbol only used in this file.
            Type
                          ; 1 = IMPORT this symbol from elsewhere (unused).
                          ; 2 = EXPORT this symbol to other objects.
                          ; If symbol is defined in this object file.
    IF
            Type != 1
                         ; File where the symbol is defined.
        STRING FileName
        LONG
                          ; Line number in the file where the symbol is defined.
                LineNum
```

SectionID ; The section number (of this object file) in which

; this symbol is defined.

; The symbols value. It's the offset into that LONG Value

; symbol's section.

ENDC

LONG

ENDR

```
; Sections
```

```
REPT NumberOfSections
    STRING Name ; Name of the section
    LONG
            Size ; Size in bytes of this section
    BYTE
            Type ; 0 = WRAM0
                  i 1 = VRAM
                  ; 2 = ROMX
```

```
; 3 = ROM0
             ; 4 = HRAM
             ; 5 = WRAMX
             ; 6 = SRAM
             ; 7 = OAM
LONG
             ; Address to fix this section at. -1 if the linker should
       Ora
             ; decide (floating address).
       Bank ; Bank to load this section into. -1 if the linker should
LONG
             ; decide (floating bank). This field is only valid for ROMX,
             ; VRAM, WRAMX and SRAM sections.
LONG
       Align ; Alignment of this section (expressed as number of low bits
             ; to leave as 0). -1 if not defined.
IF
       BYTE
           Data[Size]
                           ; Raw data of the section.
   LONG
           NumberOfPatches; Number of patches to apply.
    ; These types of sections may have patches
   REPT
           NumberOfPatches
       STRING SourceFile
                           ; Name of the source file (for printing error
                           ; messages).
       LONG
               Line
                           ; The line of the source file.
                           ; Offset into the section where patch should
       LONG
               Offset
                            ; be applied (in bytes).
       BYTE
               Type
                           ; 0 = BYTE patch.
                            ; 1 = little endian WORD patch.
                            ; 2 = little endian LONG patch.
                            ; 3 = JR offset value BYTE patch.
                            ; Size of the buffer with the RPN.
       LONG
               RPNSize
                            ; expression.
       BYTE
               RPN[RPNSize] ; RPN expression. Definition below.
   ENDR
```

**ENDC** 

**ENDR** 

# RPN DATA

Expressions in the object file are stored as RPN. This is an expression of the form "2 5 +". This will first push the value "2" to the stack. Then "5". The "+" operator pops two arguments from the stack, adds them, and then pushes the result on the stack, effectively replacing the two top arguments with their sum. In the RGB format, RPN expressions are stored as BYTEs with some bytes being special prefixes for integers and symbols.

```
Value Meaning
$00
      + operator
$01
      - operator
$02
     * operator
$03
      / operator
$04
     % operator
$05
    unary -
$10
      operator
$11
      & operator
      ^ operator
$12
$13
      unary ~
$21
      && comparison
      || comparison
$22
$23
      unary!
$30 == comparison
$31 != comparison
      > comparison
$32
$33
      < comparison
$34
      >= comparison
$35
     <= comparison
$40
     << comparison
$41
    >> comparison
$50
      BANK (symbol), a LONG Symbol ID follows.
      BANK (section_name), a null-terminated string follows.
$51
$52
      Current BANK().
      HRAMCheck. Check if the value is in HRAM, AND it with 0xFF.
$60
$80
      LONG integer follows.
      LONG Symbol ID follows.
$81
```

### **SEE ALSO**

rgbasm(1), rgblink(1), rgbds(7), gbz80(7)

## **HISTORY**

**rgbds** was originally written by Carsten Sørensen as part of the ASMotor package, and was later packaged in RGBDS by Justin Lloyd. It is now maintained by a number of contributors at https://github.com/rednex/rgbds.