

join() method

This method is used to join collection of strings into one string using separator

Syntax:

Variable-name=separator.join(iterable)

separator : it is string which is added between two string

Iterable: it is collection which consist of more than one string

Example:

```
>>> A=["naresh","ramesh","kishore"]
>>> s1=" ".join(A)
>>> print(A)
['naresh', 'ramesh', 'kishore']
>>> print(s1)
naresh ramesh kishore
>>> B=["a","b","c","d","e"]
>>> s2=",".join(B)
>>> print(B)
['a', 'b', 'c', 'd', 'e']
>>> print(s2)
a,b,c,d,e
>>> C=["10","20","30"]
>>> s3=":".join(C)
>>> print(s3)
10:20:30
```

Example:

```
# Reverse Words in a Given String in Python
# input : python is simple language
# output: language simple is python
```

```
s1="python is simple language"
A=s1.split()
print(A)
A=A[::-1]
print(A)
```

```
s2=" ".join(A)
print(s2)
```

Output

```
['python', 'is', 'simple', 'language']
['language', 'simple', 'is', 'python']
language simple is python
```

Example:

Python program to print even length words in a string

```
str1="python is simple language than CPP"
A=str1.split()
for s in A:
    if len(s)%2==0:
        print(s)
```

Output

```
python
is
simple
language
than
```

Example:

Python – Uppercase Half String

```
str1="python"
half1=str1[:len(str1)//2]
half2=str1[len(str1)//2:]
str2=half1.upper()+half2.lower()
str3=half1.lower()+half2.upper()
print(str1)
print(str2)
print(str3)
```

Output

```
python
PYThon
```

python

Example:

Python program to capitalize the first and last character of
each word in a string

```
str1="python programming"
```

```
A=str1.split()
```

```
C=[]
```

```
for word in A:
```

```
    B=list(word)
```

```
    B[0]=B[0].upper()
```

```
    B[-1]=B[-1].upper()
```

```
    s="".join(B)
```

```
    C.append(s)
```

```
str2=" ".join(C)
```

```
print(str2)
```

Output

```
['python', 'programming']
```

```
['PythoN', 'ProgramminG']
```

```
PythoN ProgramminG
```

String strip methods

These methods are used to removing leading or trailing characters from string.

1. lstrip()
- 2.rstrip()
3. strip()

lstrip() : This removing leading characters from string (the characters found at left side)

Syntax:

Variable-name=stringname.lstrip(chars=' ')

Default character removed from left side of string is space

```
>>> str1=" nit"
>>> str2=str1.lstrip()
>>> print(len(str1))
5
>>> print(len(str2))
3
>>> print(str1)
nit
>>> print(str2)
nit
>>> str3=" abc xyz pqr"
>>> str4=str3.lstrip()
>>> print(str3)
abc xyz pqr
>>> print(str4)
abc xyz pqr
>>> str5="***nit"
>>> str6=str5.lstrip("***")
>>> print(str5)
***nit
>>> print(str6)
nit
>>> str7="$%***nit"
>>> str8=str7.lstrip("*$%")
>>> print(str7)
$%***nit
>>> print(str8)
nit
```

rstrip() : This method is used to remove trailing characters (The characters found at right side)

Syntax:

variable-name=string-name.rstrip(chars=' ')

by default rstrip remove space characters found at right side.

```

>>> s1="nit  "
>>> s2="nit"
>>> s1==s2
False
>>> s1==s2.rstrip()
False
>>> s1.rstrip()==s2
True
>>> s3=s1.rstrip()
>>> print(len(s1),len(s2))
7 3
>>> print(len(s3))
3
>>> print(s1,s2,s3,sep="\n")
nit
nit
nit
>>> s4="nit*****"
>>> s5=s4.rstrip("*")
>>> print(s4)
nit*****
>>> print(s5)
nit
>>> s6="nit***$$##@@***"
>>> s7=s6.rstrip("*#@$")
>>> print(s6)
nit***$$##@@***
>>> print(s7)
Nit

```

strip() : This method is used to remove leading and trailing characters from string. Default characters removed is space characters

Syntax:

variable-name=string-name.strip(chars=' ')

```

>>> str1=" nit  "
>>> str2="nit"
>>> str1==str2
False

```

```

>>> str1.strip()==str2
True
>>> str3=str1.strip()
>>> print(str1)
  nit
>>> print(str3)
nit
>>> s1="***nit***"
>>> s2=s1.strip("**")
>>> print(s1)
***nit***
>>> print(s2)
nit
>>> s3="***$$nit&&&**%%%"
>>> s4=s3.strip("*$&%")
>>> print(s3)
***$$nit&&&**%%%
>>> print(s4)
nit
>>> s5="www.nareshit.com"
>>> s6=s5.strip("w.com")
>>> print(s5)
www.nareshit.com
>>> print(s6)
nareshit

```

Example:

Login Application

```
uname=input("UserName :")
```

```
pwd=input("Password :")
```

```
if uname.strip()=="nit" and pwd.strip()=="n123":
```

```
    print("Welcome")
```

```
else:
```

```
    print("Invalid username or password")
```

Output

```
UserName :nit
```

```
Password :n123
```

```
Welcome
```

UserName : nit
Password :n123
Invalid username or password

UserName :nit
Password :n123
Welcome

UserName : nit
Password : n123
Welcome

String Searching methods

1. startswith
2. endswith

These methods returns boolean values(True/False)

startswith(prefix): This method find prefix at the beginning of the string if found it returns True else False

```
>>> s1="naresh"  
>>> s1.startswith("n")  
True  
>>> s1.startswith("x")  
False
```

Example:

```
names=["naresh","ramesh","kishore","raman","rajesh","kishore"]  
for name in names:  
    b=name.startswith("r")  
    if b:  
        print(name)
```

```
for name in names:  
    b=name.startswith(("r","k"))  
    if b:  
        print(name)
```

Output

```
ramesh
raman
rajesh
ramesh
kishore
raman
rajesh
kishore
```

endswith(suffix): This method find given suffix at the end of the string, if found return True else False

Syntax: variable-name=stringname.endswith(suffix)

```
>>> s1="python"
>>> s1.endswith("n")
True
>>> email="naresh@nareshit.in"
>>> email.endswith("in")
True
>>> email.endswith("com")
False
```

Example:

```
names=["naresh","ramesh","kishore","raman","rajesh","kiran"]
```

```
for name in names:
```

```
    b=name.endswith("h")
```

```
    if b:
```

```
        print(name)
```

```
print("=====")
```

```
for name in names:
```

```
    b=name.endswith(("h","n"))
```

```
    if b:
```

```
        print(name)
```

Output

```
naresh
```


ramesh
rajesh
=====
naresh
ramesh
raman
rajesh
kiran

Partition methods

String data type provides 2 partition methods

1. partition
2. rpartition

partition methods returns tuple contains 3 values

1. value before separator
2. separator
3. value after separator

```
>>> s1="a,b,c,d,e"  
>>> t1=s1.partition(",")  
>>> print(t1)  
( 'a', ',', 'b,c,d,e' )  
>>> t2=s1.rpartition(",")  
>>> print(t2)  
( 'a,b,c,d', ',', 'e' )
```

Alignment methods

1. ljust()
2. rjust()
3. center()