


DECISION TREE AND RANDOM FOREST

1

Decision Tree Algorithm

2

- Similar to how humans make many different decisions
- **Decision trees** look at one feature/variable at a time




2

Decision Tree Algorithm

3

- Root node
- Parent, child/sub nodes
- Branch, splitting
- Leaf nodes



3

Decision Tree Algorithm

4

- Training dataset

Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

4

Decision Tree Algorithm

5

- How can we build a decision tree given a data set?

5

Decision Tree Algorithm

6

- We will make the **best choice at each step**
- Identify the best feature/attribute for the **each node**

6

Decision Tree Algorithm

7


- Identify the best feature/attribute for **root node**
 - Best split: results of each branch should be as **homogeneous** (or **pure**) as possible
 - a feature that reduces **impurity** as much as possible
 - How do we **measure the impurity** in a set of examples
 - **Entropy** from information theory
 - Alternatively, use **Gini Index**

7

Decision Tree Algorithm

8

- Entropy for a distribution over two outcomes



8

Decision Tree Algorithm

9

- Quantifying the information content of a feature
 - ▣ entropy of the examples **before testing** the feature **minus** the entropy of the examples **after testing** the feature – **Information Gain**

9

Decision Tree Algorithm

10

- Quantifying the information content of a feature
 - ▣ Information gain or entropy reduction


$$\text{InfoGain} = I_{\text{before}} - I_{\text{after}}$$

10

Decision Tree Algorithm

11

- Information Gain (entropy reduction)



11

Decision Tree Algorithm

12

- Entropy of the examples before we select a feature for the root node

$$H_{\text{before}} = - \left(\frac{9}{14} \log_2 \left(\frac{9}{14} \right) + \frac{5}{14} \log_2 \left(\frac{5}{14} \right) \right) \approx 0.94$$

Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

12


Decision Tree Algorithm

13

- Information gain if we select **Outlook** for the **root** node

$$\text{Outlook} = \begin{cases} \text{Sunny} & 2+ & 3- & 5 \text{ total} \\ \text{Overcast} & 4+ & 0- & 4 \text{ total} \\ \text{Rain} & 3+ & 2- & 5 \text{ total} \end{cases}$$

$$\text{Gain}(\text{Outlook}) = 0.94 - \left(\frac{5}{14} \cdot I\left(\frac{2}{5}, \frac{3}{5}\right) + \frac{4}{14} \cdot I\left(\frac{4}{4}, \frac{0}{4}\right) + \frac{5}{14} \cdot I\left(\frac{3}{5}, \frac{2}{5}\right) \right) = 0.247$$



Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

13

Decision Tree Algorithm

14

- Information gain if we select **Humidity** for the **root** node

$$\text{Humidity} = \begin{cases} \text{Normal} & 6+ & 1- & 7 \text{ total} \\ \text{High} & 3+ & 4- & 7 \text{ total} \end{cases}$$

$$\text{Gain}(\text{Humidity}) = 0.94 - \left(\frac{7}{14} \cdot I\left(\frac{6}{7}, \frac{1}{7}\right) + \frac{7}{14} \cdot I\left(\frac{3}{7}, \frac{4}{7}\right) \right) = 0.151$$

Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

14

Decision Tree Algorithm

15

- Outlook has the greatest information gain

Gain(Outlook) = 0.247 Gain(Humidity) = 0.151
Gain(Temp) = 0.029 Gain(Wind) = 0.048


Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

15

Decision Tree Algorithm

16

- Outlook has the greatest information gain



16

Gini Impurity to Build Decision Trees

age income student credit_rate default


```

0 youth high no fair no
1 youth high no excellent no
2 middle_age high no fair yes
3 senior medium no fair yes
4 senior low yes fair yes
5 senior low yes excellent no
6 middle_age low yes excellent yes
7 youth medium no fair no
8 youth low yes fair yes
9 senior medium yes fair yes
10 youth medium yes excellent yes
11 middle_age medium no excellent yes
12 middle_age high yes fair yes
13 senior medium no excellent no
  
```

$$Gini(D) = 1 - \sum_{i=1}^k p_i^2$$

$$Gini_A(D) = \frac{n_1}{n} Gini(D_1) + \frac{n_2}{n} Gini(D_2)$$

$$\Delta Gini(A) = Gini(D) - Gini_A(D)$$




Credit Rating	
Excellent	Fair
Yes 3	Yes 2
No 3	No 6
Gini 0.5	Gini 0.37

Gini Impurity for Credit Rating is 0.429

17

Decision Tree for Regression




18

Feature Space

19

- Two features for classification



Can we improve the performance further? If yes, how?


Image source: Pattern Classification by Duda, Hart and Stork

19

Feature Space

20

- Two features for classification



Perfect Classification! Is there a catch?

Image source: Pattern Classification by Duda, Hart and Stork

20

Generalization

21

- Classification Goal: Make **accurate predictions** for **new/unseen data** - **Good Generalization**
- The model should NOT be tuned to the specific characteristics of the training data – **Overfitting**
- In practice, training data is likely to contain some noise


We are better off with a slightly poorer performance on the training examples if this means that our classifier will have better performance on unseen patterns.

21

Generalization

22

- Classification Goal: Make **accurate predictions** for **new/unseen data** - **Good Generalization**




- A decision boundary that provides an **optimal tradeoff** between **accuracy on the training set** and **unseen data**

22

Avoid Overfitting and Achieve Optimal Tradeoff

23




23

Feature Space

24

Decision Boundaries in Decision Tree




24

Avoid Overfitting and Achieve Optimal Tradeoff

25

Decision Tree versus Random Forest




25

Avoid Overfitting and Achieve Optimal Tradeoff

26

Decision Tree versus Random Forest




26

Random Forest

27

- **Ensemble learning** is a machine learning technique that aggregates two or more learners to produce better predictions
 - committee-based learning



27

Random Forest

28

- Base learner, base model, base estimator - refers to the individual models in ensemble algorithms
- consolidating base learner predictions
 - Majority Voting, Averaging

28

Random Forest

29


- Random forest uses **bagging** to construct ensembles of **randomized decision trees**
 - Bagging - **bootstrap sampling** and **aggregation**
 - Bootstrap sampling to derive multiple new datasets from one initial training dataset to train multiple base learners

29

Bootstrap Sampling

30

- **Random sampling with replacement**




- Each bootstrap sample only contains **approximately 63.2%** of the unique samples from the original dataset

30

Random Forest

31

- Random forest uses **bagging** to construct ensembles of **randomized decision trees**



31

Random Forest

32

- Random forest uses **bagging** to construct ensembles of **randomized decision trees**
 - considers **random subsets** of features when splitting a node
 - `max_features` parameter
- The **greater diversity** among combined models, the **more accurate** the resulting ensemble model


32

Estimating generalization Performance:

Out-of-bag (OOB) error/score

33

- **Out-of-bag** samples as test sets for evaluation
 - Out-of-bag samples are the unique sets of datapoints that are not used for model fitting



- Each bootstrap sample only contains **approximately 63.2%** of the unique samples from the original dataset

33

Thank You!

34