

Estabillo, Ranulf Jay

```
TS mock-heroes.ts x <> heroes.component.html ● TS
src ▸ app ▸ TS mock-heroes.ts ▸ HEROES
1  import{Hero} from './hero';
2
3  export const HEROES: Hero[] = [
4      {id:12 , name:'Jay'},
5      {id:13 , name:'Loop'},
6      {id:14 , name:'ken'},
7      {id:15 , name:'sea'},
8      {id:16 , name:'bob'},
9      {id:17 , name:'chi'},
10     {id:18 , name:'kim'},
11     {id:19 , name:'jaz'},
12     {id:20 , name:'kai'},
13
14 ]
```

```
TS mock-heroes.ts <> heroes.component.html ● TS heroes.component.ts ● #
src ▸ app ▸ heroes ▸ <> heroes.component.html ▸ ...
10
11 <div *ngIf = "selectedHero"></div>
12     <h2>{{selectedHero.name | uppercase}} Details</h2>
13     <div>id: {{selectedHero.id}}</div>
14 </div>
15     <label for="hero-name">Hero Name:</label>
16     <input type="text" id="hero-name"
17         [(ngModel)] = "selectedHero.name" placeholder="name">
18 </div>
19 </div>
```

TS mock-heroes.ts

&lt;&gt; heroes.component.html ●

TS heroes.component.ts ●

src ▸ app ▸ heroes ▸ TS heroes.component.ts ▸ ...

```
1  import { Component } from '@angular/core';
2  import { Hero } from '../hero';
3  import { HEROES } from '../mock-heroes';
4  import { FormsModule } from '@angular/forms';
5
6  import {
7
8      /** ... */
9      NgFor, NgIf, UpperCasePipe
10     /** ... */
11 } from '@angular/common';
12
13
14 @Component({
15     selector: 'app-heroes',
16     standalone: true,
17     templateUrl: './heroes.component.html',
18     styleUrls: ['./heroes.component.css'],
19     imports: [
20         NgFor, NgIf, FormsModule, UpperCasePipe
21     ]
22 })
23 export class HeroesComponent {
24     heroes = HEROES;
25     selectedHero?: Hero;
26     onSelect(hero: Hero): void {
27         this.selectedHero = hero;
28     }
29 }
30
```

```
TS mock-heroes.ts    <> heroes.component.html    TS heroes.component.ts    # heroes.compo

src > app > TS app.module.ts > AppModule
1  import { NgModule } from '@angular/core';
2  import { BrowserModule } from '@angular/platform-browser';
3  import { FormsModule } from '@angular/forms';
4  import { AppRoutingModule } from './app-routing.module';
5  import { AppComponent } from './app.component';
6  import { HeroesComponent } from './heroes/heroes.component';
7
8  @NgModule({
9    declarations: [
10
11    ],
12    imports: [
13      BrowserModule,
14
15    ],
16    providers: [],
17    bootstrap: [AppComponent]
18  })
19  export class AppModule { }
20
21
```

```
TS mock-heroes.ts    <> heroes.component.html

src > app > <> app.component.html > h1
1  <h1>{{title}}</h1>
2  <app-heroes></app-heroes>
3
4
```

ck-heroes.ts

<> heroes.component.html ●

TS heroes.component.ts ●

# heroes.co

src ▸ app ▸ TS app.component.ts ▸ ...

```
1  import { Component } from '@angular/core';
2  import { HeroesComponent } from '../heroes/heroes.component'
3  import { CommonModule } from '@angular/common'
4  @Component({
5    selector: 'app-root',
6    templateUrl: './app.component.html',
7    standalone: true,
8    styleUrls: ['./app.component.css'],
9    imports: [CommonModule, HeroesComponent]
10 })
11 export class AppComponent {
12   title = 'my-angular-app';
13
14 }
15 |
```