

DMClinical

Alleviate Patient Status API

via Azure API Management (APIM)

Audience: Alleviate integration team **Version:** 1.0 (APIM) **Last updated:** 2026-06-12

A read-only endpoint, exposed through the DMClinical Azure API Management (APIM) gateway, that returns a patient's Comtrak status-change history so Alleviate can sync post-call / post-visit outcomes.

1. Environments

Environment	Gateway base URL
QA	https://apim-data-ingestion-qa.azure-api.net
Sandbox	https://api-sandbox.dmcclinical.com

All paths below are relative to the gateway base URL.

2. Authentication

Two headers are required on every request:

Header	Purpose
Ocp-Apim-Subscription-Key	APIM gateway subscription key (identifies your APIM subscription).
apiKey	Backend application key for the Alleviate integration.

Ocp-Apim-Subscription-Key: <your-subscription-key>
apiKey: <your-api-key>

Both keys are environment-specific and provided to you separately by DMClinical.

- A missing/invalid Ocp-Apim-Subscription-Key is rejected by the gateway with 401.
- A missing/invalid apiKey is rejected by the backend with 401.

3. Endpoint

```
GET /recruitment/v1/getalleviatestatuschanges
```

Returns the patient's status changes within a UTC date window.

Query parameters

Parameter	Type	Required	Description
patientId	integer	Yes	Comtrak patient identifier.
startDateTime	datetime (UTC)	Yes	Start of the window. ISO 8601 UTC, e.g. 2026-06-11T00:00:00Z (date-only like 2026-06-11 is accepted as midnight UTC).
endDateTime	datetime (UTC)	Yes	End of the window. Must be later than startDateTime.

Parameter	Type	Required	Description
recruiterId	integer	Yes	The Alleviate recruiter identifier. Must be a recruiter that belongs to Alleviate.
studyId	integer	No	If supplied, limits results to a single study.

Notes on dates: send UTC values; appending “Z” is recommended. Results begin no earlier than the date the patient was first assigned to Alleviate, even if startDateTime is earlier.

Example — QA (raw HTTP)

```
GET https://apim-data-ingestion-qa.azure-api.net/recruitment/v1/getalleviatestatuschanges?patientId=23456&startDateTime=2026-06-11&endDateTime=2026-06-21&recruiterId=1965 HTTP/1.1
Host: apim-data-ingestion-qa.azure-api.net
Ocp-Apim-Subscription-Key: <your-subscription-key>
apiKey: <your-api-key>
Accept: application/json
```

Example — Sandbox (raw HTTP)

```
GET https://api-sandbox.dmclinical.com/recruitment/v1/getalleviatestatuschanges?patientId=23456&startDateTime=2026-06-11&endDateTime=2026-06-21&recruiterId=1965 HTTP/1.1
Host: api-sandbox.dmclinical.com
Ocp-Apim-Subscription-Key: <your-subscription-key>
apiKey: <your-api-key>
Accept: application/json
```

Example — curl (QA)

```
curl --location \
  "https://apim-data-ingestion-qa.azure-api.net/recruitment/v1/getalleviatestatuschanges?patientId=23456&startDateTime=2026-06-11&endDateTime=2026-06-21&recruiterId=1965" \
  --header "Ocp-Apim-Subscription-Key: <your-subscription-key>" \
  --header "apiKey: <your-api-key>" \
  --header "Accept: application/json"
```

4. Response

All responses use a common envelope:

```
{
  "success": true,
  "code": 200,
  "message": "Success",
  "data": { ... }
}
```

4.1 Success (data found)

```
{
  "success": true,
  "code": 200,
  "message": "Success",
  "data": { ... }
}
```

```

"data": {
  "patientId": 23456,
  "items": [
    {
      "event_datetime": "2026-06-12T21:52:16Z",
      "studyId": 64,
      "siteId": 5,
      "new_statusId": 56,
      "new_status_label": "Enrolled - Screen Pass",
      "new_status_notes": null
    },
    {
      "event_datetime": "2026-06-12T21:52:16Z",
      "studyId": 64,
      "siteId": 5,
      "new_statusId": 49,
      "new_status_label": "Enrolled - Dropped",
      "new_status_notes": "Patient withdrew consent"
    }
  ]
}

```

4.2 No data

Returned when the patient has no qualifying status changes in the window (or was never assigned to Alleviate). data is null.

```

{
  "success": true,
  "code": 200,
  "message": "No Patient or Interactions Found",
  "data": null
}

```

4.3 recruiterId not recognized as an Alleviate recruiter

```

{
  "success": true,
  "code": 200,
  "message": "RecruiterID is not a valid.",
  "data": null
}

```

Item fields

Field	Type	Description
event_datetime	datetime (UTC)	When the status change was recorded.
studyId	integer	Study associated with the interaction.
siteId	integer / null	Site associated with the interaction.
new_statusId	integer	Comtrak status identifier (see section 5).
new_status_label	string	Human-readable Alleviate status label (see section 5).

Field	Type	Description
new_status_notes	string / null	Populated only for specific statuses (see section 6); otherwise null.

5. Status reference

The label your integration should key on is new_status_label.

new_statusId	new_status_label
1	DNQ - Not Interested
2	DNQ - No Response
17	DNQ - Criteria Not Met
18	Scheduled for Screen
20	Scheduled for Pre-Screen
30	Missed Call - Rescheduling
42	Enrolled - No Show
44	Enrolled - Screening
45	Enrolled - Screen Fail
49	Enrolled - Dropped
50	Enrolled - Completed
56	Enrolled - Randomized
56	Enrolled - Screen Pass
56	Enrolled - No Show

Important: new_statusId 56 can carry three different labels (Enrolled - Randomized, Enrolled - Screen Pass, Enrolled - No Show) depending on the patient's progression. Always read new_status_label, not new_statusId, to determine the outcome for status 56.

6. The new_status_notes field

Notes are returned only for the statuses below; for all other statuses new_status_notes is null.

new_statusId	Label	Note content
17	DNQ - Criteria Not Met	Reason the patient did not meet criteria (free text).
45	Enrolled - Screen Fail	Screen-fail reason (free text).
49	Enrolled - Dropped	Drop / early-termination reason (free text).
18	Scheduled for Screen	Derived value: "Site: <siteId> Visit: <visit time UTC>".
20	Scheduled for Pre-Screen	Derived value: "Site: <siteId> Visit: <visit time UTC>".

If a free-text note is empty, new_status_notes is returned as null.

7. Behavior rules

1. Recruiter validation — recruiterId must be an Alleviate recruiter. If not, the response is 200 with message “RecruiterID is not a valid.” and data: null.
2. Assignment requirement — only patients who have been assigned to Alleviate are returned. A patient never assigned to Alleviate returns “No Patient or Interactions Found”.
3. Start-date floor — results never include status changes recorded before the patient’s first Alleviate assignment, regardless of startDateTime.
4. Empty windows — if nothing matches, the response is 200 with “No Patient or Interactions Found”.

8. Status / error codes

HTTP	Source	message	Meaning
200	backend	Success	Data returned in data.
200	backend	No Patient or Interactions Found	Valid request, no qualifying data.
200	backend	RecruiterID is not a valid.	recruiterId is not an Alleviate recruiter.
400	backend	patientId is required.	patientId missing or ≤ 0 .
400	backend	startDateTime and endDateTime are required.	One or both dates missing.
400	backend	endDateTime must be after startDateTime.	Invalid date range.
401	gateway	(subscription key error)	Missing or invalid Ocp-Apim-Subscription-Key.
401	backend	(unauthorized)	Missing or invalid apiKey.
500	backend	Internal error. correlationId=<id>	Unexpected server error. Share the correlationId with DMClinical.

9. Contact

For subscription keys, API keys, environment access, or issues (include the correlationId for 500s), below is a one time link. With password “abc@123”

[ApiLink](#)