#editor { font-family: 'Times New Roman'; font-size: 12px; color: black !important; overflow: visible !important; height: auto !important; max-height: none !important; } #editor * { page-break-inside: avoid; break-inside: avoid; color: black !important; font-family: 'Times New Roman', serif !important; font-size: 12px !important; } .table strong { color: black !important; font-family: 'Times New Roman', sans-serif !important; font-size: 12px !important; } .table > :not(caption) > * > * { color: black !important; } .table tbody tr td { border-color: #b8b3a9; color: black !important; font-family: 'Times New Roman', sans-serif !important; font-size: 12px !important; white-space: normal; word-wrap: break-word; letter-spacing: 0.75px; } .workflow-html { font-family: "Times New Roman", Times, serif !important; font-size: 12px !important; color: black !important; } /* Make document more compact so table is more likely to fit */ .workflow-html, .quill-content, #description-content { font-family: "Times New Roman", serif; font-size: 11.0pt; /* slightly smaller on print */ line-height: 1.15; /* tighter line-height */ word-break: break-word; } /* ---------- Table keep-together rules ---------- */ /* Wrap table in a protective wrapper */ #approver-table-wrapper { /* Prefer to avoid breaking inside wrapper */ page-break-inside: avoid !important; break-inside: avoid !important; -webkit-column-break-inside: avoid; -moz-column-break-inside: avoid; } /* Ensure table's header repeats when table must continue on next page */ #approver-table thead { display: table-header-group; /* header repeats on next pages */ } #approver-table tfoot { display: table-footer-group; /* optional */ } /* Prevent rows from being split across pages. Many engines respect this. */ #approver-table tbody, #approver-table tr, #approver-table td, #approver-table th { page-break-inside: avoid !important; break-inside: avoid !important; -webkit-column-break-inside: avoid; -moz-column-break-inside: avoid; } /* If a single TD has huge content, allow it to wrap but prefer not to split */ #approver-table td { white-space: normal; word-break: break-word; vertical-align: top; } /* Compact table spacing for print */ #approver-table th, #approver-table td { padding: 4px 6px !important; font-size: 10.5pt !important; } /* Prevent rowspans from causing weird breaks (makes row height predictable) */ #approver-table td[rowspan], #approver-table th[rowspan] { /* avoid using large rowspan if you can — this is a best-effort */ page-break-inside: avoid; } /* If the table still must move to new page entirely, use wrapper class .start-new-page (you would add this class server-side if needed; CSS alone cannot toggle it conditionally) */ #approver-table-wrapper.start-new-page { page-break-before: always; break-before: page; } /* Widows/orphans: help keep small paragraphs with neighbors */ p, div { orphans: 3; widows: 3; page-break-inside: auto; } /* Images in the signature area: limit heights so they don't make rows huge */ #approver-table img { max-height: 80px; height: auto; width: auto; } .table tbody tr td:last-child { text-align: left; } .table-bordered { border-collapse: collapse; /* Ensures borders don't double up */ width: 100%; /* Optional: Adjust table width as needed */ } .table-bordered th, .table-bordered td { border: 1px solid #ddd; /* Normal inner borders */ } .table-bordered { border: 2px solid #000; /* Thick outer border */ } .ql-container.ql-snow { border: none; height: auto !important; max-height: none !important; overflow: visible !important; } .td-logo { display: flex; justify-content: center; align-items: center; height: 150px; } .td-logo img { max-width: 200px; max-height: 100%; object-fit: contain; } .feedback-cell { white-space: normal !important; vertical-align: top !important; } .feedback-item { margin-bottom: 6px !important; padding-bottom: 4px !important; border-bottom: 1px dotted #aaa !important; } .feedback-item:last-child { border-bottom: none !important; } .feedback-text { font-size: 16px !important; font-family: 'Times New Roman', serif !important; } .feedback-datetime { font-size: 13px !important; font-style: italic !important; color: #555 !important; } Inter Office Memo Dated: 15-Jan-2026 Department:Information Technology Reference No.:HL-IT-2026-56 To: Deputy Director Hamdard Laboratories (WAQF) Pakistan Karachi Subject: SIr Bashir issue testing 15-01-2026 Dear Sir/Madam, SIr Bashir issue testing 15-01-2026SIr Bashir issue testing 15-01-2026SIr Bashir issue testing 15-01-2026

2026SIr Bashir issue testing 15-01-2026 Your approval is requested. Name Signature Feedback Prepared by: Muhammad Moiz Ahmed Officer Information Technology Digitally Created By: m.moiz@hamdard.com.pk On: 15-Jan-2026 05:57 PM IP Address: 45.249.8.106 Verified by: Muhammad Moiz AhmedOfficer Information Technology Digitally Verified By: m.moiz@hamdard.com.pk On: 15-Jan-2026 IP Address: 45.249.8.106 Reviewed by: Muhammad Huzaifa Senior Officer Information Technology Digitally Reviewed By: m.huzaifa@hamdard.com.pk On: 15-Jan-2026 11:25 PM IP Address: 101.53.228.86 reviewed 15-Jan-2026 11:25 PM Ehtasham HussainAssistant Manager Information Technology Digitally Reviewed By: ehtasham.hussain@hamdard.com.pk On: 15-Jan-2026 11:31 PM IP Address: 101.53.228.86 reviewed 15-Jan-2026 11:31 PM Muhammad BashirSenior Manager Sales Operation Digitally Reviewed By: m.bashir@hamdard.com.pk On: 15-Jan-2026 11:33 PM IP Address: 101.53.228.86 Reviewed 15-Jan-2026 11:33 PM Approved by: Ahsan Shaikh System Administrator Information Technology Digitally Approved By: ahsan.shaikh@hamdard.com.pk On: 15-Jan-2026 11:34 PM IP Address: 101.53.228.86 Approved 15-Jan-2026 11:34 PM Syed Muzamil AliDeputy Director Information Technology Digitally Approved By: muzamil.ali@hamdard.com.pk On: 15-Jan-2026 11:35 PM IP Address: 101.53.228.86 Approved 15-Jan-2026 11:35 PM Approved 15-Jan-2026 11:35 PM Scan to validate

```
$(document).ready(function () { var content = $('#Content').val(); editor = new Quill('#editor', { modules: { toolbar: false }, theme: 'snow' }); try { // Parse the data if it's a JSON string const delta = typeof content === 'string' ? JSON.parse(content) : content; editor.setContents(delta); editor.enable(false); // disable user input } catch (error) { console.error('Error setting editor contents:', error); } });
```