

Classification models

Puteaux, Fall/Winter 2020-2021

```
#####  
##                               ##  
##  Deep Learning in Python  ##  
##                               ##  
#####
```

§1 Introduction to Deep Learning in Python

§1.3 Building deep learning models with keras

§1.3.3 Classification models

1. How to compile the classification model with Keras?

- Use 'categorical_crossentropy' loss function, which is similar to log loss, but lower is better.
- Add metrics = ['accuracy'] to compile step for easy-to-understand diagnostics.
- The output layer has a separate node for each possible outcome and uses 'softmax' activation.

2. How to transform the target value into categorical?

shot_clock	dribbles	touch_time	shot_dis	close_def_dis	shot_result	shot_result	Outcome 0	Outcome 1
10.8	2	1.9	7.7	1.3	1	1	0	1
3.4	0	0.8	28.2	6.1	0	0	1	0
0	3	2.7	10.1	0.9	0	0	1	0
10.3	2	1.9	17.2	3.4	0	0	1	0

3. Code of classification:

```
[1]: import pandas as pd  
from keras.layers import Dense  
from keras.models import Sequential  
  
def data_preparation(df):
```

```

df = df.reindex(columns=[
    'SHOT_CLOCK', 'DRIBBLES', 'TOUCH_TIME', 'SHOT_DIST', 'CLOSE_DEF_DIST',
    'SHOT_RESULT'
])
df['SHOT_CLOCK'] = df['SHOT_CLOCK'].fillna(0)
df['SHOT_RESULT'].replace('missed', 0, inplace=True)
df['SHOT_RESULT'].replace('made', 1, inplace=True)
df.columns = df.columns.str.lower()
return df

```

```

[2]: from keras.utils.np_utils import to_categorical

data = pd.read_csv('ref5. Basketball shot log.csv')

data = data_preparation(data)

predictors = data.drop(['shot_result'], axis=1).to_numpy()
n_cols = predictors.shape[1]
target = to_categorical(data.shot_result)

model = Sequential()
model.add(Dense(100, activation='relu', input_shape=(n_cols, )))
model.add(Dense(100, activation='relu'))
model.add(Dense(100, activation='relu'))
model.add(Dense(2, activation='softmax'))
model.compile(optimizer='adam',
              loss='categorical_crossentropy',
              metrics=['accuracy'])

model.fit(predictors, target)

```

```

4003/4003 [=====] - 7s 2ms/step - loss: 0.6682 -
accuracy: 0.6051

```

```

[2]: <tensorflow.python.keras.callbacks.History at 0x7fdc8ab75d90>

```

4. Practice question for understanding the classification data:

- To start modeling with a new dataset for a classification problem. This data includes information about passengers on the Titanic. The predictors such as **age**, **fare**, and where each passenger embarked to could be used to predict who will survive. This data is from [a tutorial on data science competitions](#). There are descriptions of the features.
- It's smart to review the maximum and minimum values of each variable to ensure the data isn't misformatted or corrupted. What was the maximum age of passengers on the Titanic? Use the `.describe()` method in the IPython Shell to answer this question.

☐ 29.699.

☒ 80.

☐ 891.

☐ It is not listed.

► Package pre-loading:

```
[3]: import pandas as pd
```

► Data pre-loading:

```
[4]: df = pd.read_csv('ref6. Titanic.csv')
```

► Question-solving method:

```
[5]: df.head()
```

```
[5]:   survived  pclass   age  sibsp  parch   fare  male  age_was_missing \
0         0      3  22.0      1      0   7.2500      1             False
1         1      1  38.0      1      0  71.2833      0             False
2         1      3  26.0      0      0   7.9250      0             False
3         1      1  35.0      1      0  53.1000      0             False
4         0      3  35.0      0      0   8.0500      1             False
```

```
   embarked_from_cherbourg  embarked_from_queenstown \
0                        0                        0
1                        1                        0
2                        0                        0
3                        0                        0
4                        0                        0
```

```
   embarked_from_southampton
0                          1
1                          0
2                          1
3                          1
4                          1
```

```
[6]: df['age'].describe()
```

```
[6]: count      891.000000
mean       29.699118
std        13.002015
min         0.420000
25%        22.000000
50%        29.699118
75%        35.000000
max        80.000000
Name: age, dtype: float64
```

```
[7]: max_age = int(df['age'].max())  
print('The maximum age of passengers on the Titanic is {}'.format(max_age))
```

The maximum age of passengers on the Titanic is 80.

5. Practice exercises for classification models:

► Package pre-loading:

```
[8]: import pandas as pd
```

► Data pre-loading:

```
[9]: df = pd.read_csv('ref6. Titanic.csv')  
  
df['age_was_missing'].replace(False, 0, inplace=True)  
df['age_was_missing'].replace(True, 1, inplace=True)  
  
predictors = df.drop(['survived'], axis=1).to_numpy()  
n_cols = predictors.shape[1]
```

► Classification models practice:

```
[10]: # Import necessary modules  
import keras  
from keras.layers import Dense  
from keras.models import Sequential  
from keras.utils import to_categorical  
  
# Convert the target to categorical: target  
target = to_categorical(df.survived)  
  
# Set up the model  
model = Sequential()  
  
# Add the first layer  
model.add(Dense(32, activation='relu', input_shape=(n_cols, )))  
  
# Add the output layer  
model.add(Dense(2, activation='softmax'))  
  
# Compile the model  
model.compile(optimizer='sgd',  
              loss='categorical_crossentropy',  
              metrics=['accuracy'])  
  
# Fit the model  
model.fit(predictors, target)
```

```
28/28 [=====] - 0s 18ms/step - loss: 1.6349 - accuracy:  
0.5943
```

```
[10]: <tensorflow.python.keras.callbacks.History at 0x7fdc8c230e50>
```