
Forward propagation

Puteaux, Fall/Winter 2020-2021

- §1 Introduction to Deep Learning in Python
- §1.1 Basics of deep learning and neural networks

1 Forward propagation

- 1.1 How does the forward propagation function?
 - Multiply add process.
 - Dot product.
 - Forward propagation is for one data point at a time.
 - The output is the prediction for that data point.



1.2 Code of the forward propagation:

```
[1]: import numpy as np

input_data = np.array([2, 3])
weights = {
    'node_0': np.array([1, 1]),
    'node_1': np.array([-1, 1]),
    'output': np.array([2, -1])
```

```
}
node_0_value = (input_data * weights['node_0']).sum()
node_1_value = (input_data * weights['node_1']).sum()

hidden_layer_values = np.array([node_0_value, node_1_value])
print(hidden_layer_values)
```


[5 1]

```
[2]: output = (hidden_layer_values * weights['output']).sum()
print(output)
```

9

1.3 Practice exercises for the forward propagation:

▶ Diagram of the forward propagation:



► Package pre-loading:

```
[3]: import numpy as np
```

▶ Data pre-loading:

```
[4]: input_data = np.array([3, 5])

weights = {
    'node_0': np.array([2, 4]),
        'node_1': np.array([4, -5]),
        'output': np.array([2, 7])
}
```

▶ The forward propagation algorithm practice:

```
[5]: # Calculate node 0 value: node_0_value
node_0_value = (input_data * weights['node_0']).sum()

# Calculate node 1 value: node_1_value
node_1_value = (input_data * weights['node_1']).sum()

# Put node values into array: hidden_layer_outputs
hidden_layer_outputs = np.array([node_0_value, node_1_value])
```

```
# Calculate output: output
output = (hidden_layer_outputs * weights['output']).sum()
# Print output
print(output)
```

-39

