



# GMT Corporation Pvt. Ltd.

## Pre-Dispatch Inspection Report

Format No.: GMT/C/QA/F/04  
Rev. No.: 00  
Rev. Date: 01/04/2025  
Page No.: 01 of 01

Part Name: FLANGED HEAD

Customer Name: DESSIMATE LLC

Date: 16-08-2026

Part No.: 007157-001

Challan / Invoice No.: GMT/CX/2627/0628

Sample Size: 03

Rev. No: N

Control Plan No.: GMT/C/DSS/CP/007157-001

Dispatch Qty.: 640

| Sr. No. | Parameter                | Specification              | Instrument / Gauge                        | Special Characteristics | Sample No. (All Dimensions are in Inch) |           |           | Remark   |
|---------|--------------------------|----------------------------|-------------------------------------------|-------------------------|-----------------------------------------|-----------|-----------|----------|
|         |                          |                            |                                           |                         | 1                                       | 2         | 3         |          |
| 1       | Outer Diameter           | 3.3750 + 0.0000 / - 0.0017 | Air Ring Gauge                            | (X)                     | 3.3744                                  | 3.3743    | 3.3740    | Accepted |
| 2       | Distance                 | 0.655 ± 0.005              | Ht. Gauge                                 | (X)                     | 0.655                                   | 0.653     | 0.654     | Accepted |
| 3       | Pocket Diameter          | 0.800 ± 0.005              | CMM                                       | (X)                     | 0.8002                                  | 0.8005    | 0.7999    | Accepted |
| 4       | Bore Size                | 1.540 ± 0.005              | Plain Plug Gauge                          | (X)                     | OK                                      | OK        | OK        | Accepted |
| 5       | Bore Size                | 1.255 + 0.000 / - 0.003    | Inside Vernier Caliper / Plain Plug Gauge | (X)                     | 1.253                                   | 1.254     | 1.253     | Accepted |
| 6       | Bore Deep                | 0.042 + 0.002 / - 0.000    | Ht. Gauge                                 | (X)                     | 0.0429                                  | 0.0429    | 0.0433    | Accepted |
| 7       | Distance                 | 0.200 ± 0.005              | CMM                                       | (X)                     | 0.2021                                  | 0.2012    | 0.2016    | Accepted |
| 8       | Hole Size                | 0.125 + 0.005 / - 0.001    | Plain Plug Gauge                          | (X)                     | OK                                      | OK        | OK        | Accepted |
| 9       | Distance                 | R0.718 ± 0.005             | CMM                                       | (X)                     | 0.7186                                  | 0.7192    | 0.7194    | Accepted |
| 10      | Pocket Width             | 0.400 ± 0.005              | Width Gauge                               | (X)                     | OK                                      | OK        | OK        | Accepted |
| 11      | Chamfer Length           | 0.050 ± 0.005              | Contracter                                | (X)                     | 0.0500                                  | 0.0497    | 0.0500    | Accepted |
| 12      | Chamfer Angle            | 30° ± 1°                   | Contracter                                | (X)                     | 30°14'29"                               | 30°10'44" | 29°58'26" | Accepted |
| 13      | 3 x Drill Depth To Point | 0.500 Max.                 | Special Point Pin with Dial               | (X)                     | 0.470                                   | 0.462     | 0.464     | Accepted |
|         |                          |                            |                                           |                         | 0.469                                   | 0.464     | 0.470     | Accepted |
|         |                          |                            |                                           |                         | 0.470                                   | 0.466     | 0.466     | Accepted |
| 14      | 2 x Drill Depth To Point | 0.320 Max.                 | Special Point Pin with Dial               | (X)                     | 0.310                                   | 0.309     | 0.308     | Accepted |
|         |                          |                            |                                           |                         | 0.308                                   | 0.309     | 0.310     | Accepted |
| 15      | Bore Size                | 2.430 ± 0.005              | Plain Plug Gauge                          |                         | OK                                      | OK        | OK        | Accepted |
| 16      | Groove Width             | 0.081 ± 0.005              | Plain Plug Gauge                          |                         | OK                                      | OK        | OK        | Accepted |
| 17      | 4 x Hole Size            | 0.250 ± 0.005              | Plain Plug Gauge                          |                         | OK                                      | OK        | OK        | Accepted |
| 18      | 2 x Tap                  | 10-32 UNF-2B               | Thread Plug Gauge                         |                         | OK                                      | OK        | OK        | Accepted |
| 19      | 5 x Tap                  | 4-40 UNC-2B                | Thread Plug Gauge                         |                         | OK                                      | OK        | OK        | Accepted |
| 20      | Hole                     | 0.625 ± 0.005              | Plain Plug Gauge                          |                         | OK                                      | OK        | OK        | Accepted |
| 21      | Hole                     | 0.500 ± 0.005              | Plain Plug Gauge                          |                         | OK                                      | OK        | OK        | Accepted |
| 22      | Groove Width             | 0.140 ± 0.005              | Width Gauge                               |                         | OK                                      | OK        | OK        | Accepted |

Legends: Critical- (X) Safety Critical- (S)

Major - (M)

Minor - (No Symbol)

Key Instructions

Pass Through Characteristic- (P)

Lot: ☒ Accepted ☐ Rejected

Checked By: Karan Parit

Approved By: Dhruj Patil

