



GMT Corporation Pvt. Ltd.

Pre-Dispatch Inspection Report

Format No.: GMT/QM/F04
Rev. No.: 00
Rev. Date: 01/04/2025
Page No.: 01 of 01

Part Name: FLANGED HEAD

Customer Name: DESSIMATELLC

Part No.: 007157-001

Challan / Invoice No.: GMT/CX/2627/0477

Date: 21-07-2026

Sample Size: 03

Rev. No: N

Control Plan No.: GMT/C/DSS/CP/007157-001

Dispatch Qty.: 320

Sr. No.	Parameter	Specification	Instrument / Gauge	Special Characteristics	Sample No. (All Dimensions are in Inch)			Remark
					1	2	3	
1	Outer Diameter	3.3750 + 0.0000 / - 0.0017	Air Ring Gauge	(X)	3.3742	3.3743	3.3741	Accepted
2	Distance	0.655 ± 0.005	Ht. Gauge	(X)	0.656	0.654	0.655	Accepted
3	Pocket Diameter	0.800 ± 0.005	CMM	(X)	0.802	0.801	0.802	Accepted
4	Bore Size	1.540 ± 0.005	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
5	Bore Size	1.255 + 0.000 / - 0.003	Inside Vernier Caliper / Plain Plug Gauge	(X)	1.253	1.254	1.253	Accepted
6	Bore Deep	0.042 + 0.002 / - 0.000	Ht. Gauge	(X)	0.0432	0.0430	0.0431	Accepted
7	Distance	0.200 ± 0.005	CMM	(X)	0.201	0.202	0.201	Accepted
8	Hole Size	0.125 + 0.005 / - 0.001	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
9	Distance	R 0.718 ± 0.005	CMM	(X)	0.7187	0.7192	0.7185	Accepted
10	Pocket Width	0.400 ± 0.005	Width Gauge	(X)	OK	OK	OK	Accepted
11	Chamfer Length	0.050 ± 0.005	Contracer	(X)	0.0504	0.0505	0.0503	Accepted
12	Chamfer Angle	30° ± 1°	Contracer	(X)	30°11'34"	30°17'45"	30°13'55"	Accepted
13	3 x Drill Depth To Point	0.500 Max.	Special Point Pin with Dial	(X)	0.465	0.467	0.464	Accepted
					0.466	0.463	0.469	Accepted
					0.473	0.468	0.465	Accepted
14	2 x Drill Depth To Point	0.320 Max.	Special Point Pin with Dial	(X)	0.307	0.308	0.306	Accepted
15	Bore Size	2.430 ± 0.005	Plain Plug Gauge		0.308	0.309	0.308	Accepted
16	Groove Width	0.081 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
17	4 x Hole Size	0.250 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
18	2 x Tap	10-32 UNF-2B	Thread Plug Gauge		OK	OK	OK	Accepted
19	5 x Tap	4-40 UNC-2B	Thread Plug Gauge		OK	OK	OK	Accepted
20	Hole	0.625 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
21	Hole	0.500 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
22	Groove Width	0.140 ± 0.005	Width Gauge		OK	OK	OK	Accepted

Legends: Critical- (X)

Safety Critical- (S)

Major - (M)

Minor - (No Symbol)

Key Instructions

Pass Through Characteristic- (P)

Lot: ☒ Accepted

☐ Rejected

Checked By: Karan Parit

Approved By: Dhiraaj Patil

