

**GORECHA METAL TECH PVT. LTD.**

Address : Survey No. 55 / P7, Plot No. 1, Shreeji Industrial Area 2,
Rajkot Gondal NH-27, Pipaliya Sadak, Dist. Rajkot - 360 311 (Gujarat, India)
Telefax : +91 85111 55652
Email : inquiry@gorechametals.com, Web : www.gorechametal.com
GSTIN : 24AAICG4703F1ZY, State Code : 24 - Gujarat

TEST CERTIFICATE

AS PER EN - 10204 TYPE 3.1

M/s. GMT CORPORATION PRIVATE LIMITED

TC No. : 78 - 09/04/2026
DC No. : 80/28-27 - 09/04/2026
Invoice No. : 26/27-81 - 09/04/2026
PO No. : 00-01-26, 00-02-26

Specification : ASTM A351/351M Gr:CF8M

SPECTRO CHEMICAL ANALYSIS

Heat No.	C %	Si %	Mn %	P %	S %	Cr %	Mo %	Ni %								Heat Code
Min.						18.000	2.000	9.000								
Max.	0.080	1.500	1.500	0.040	0.040	21.000	3.000	12.000								
EN-255	0.038	1.198	1.130	0.037	0.001	18.290	2.170	9.610								
EN-256	0.045	1.230	1.110	0.039	0.003	18.530	2.130	9.500								
EO-015	0.032	1.320	1.150	0.032	0.002	18.290	2.110	9.680								
EO-016	0.022	1.210	1.070	0.036	0.002	18.520	2.140	9.590								

MECHANICAL PROPERTIES

Heat No.	TS MPa	YS MPa By 0.2% Offset	Elgn. %	R.A. %	Hardness	Impact Test at Test Temp. °C				Die No.	Description	Qty.
Min.	485	205	30.00	--	--							
Max.	--	--	--	--	--	1	2	3	Avg			
EN-255	569	328	50.08	--	158	--	--	--	--	G-250103	007156-001 Cust. Part ID : 00716-001	13
EN-256	566	321	54.08	--	152	--	--	--	--	G-250103	007156-001 Cust. Part ID : 00716-001	38
EO-015	538	343	50.76	--	155	--	--	--	--	G-250103	007156-001 Cust. Part ID : 00716-001	64
EO-015	538	343	50.76	--	150	--	--	--	--	G-250103	007156-001 Cust. Part ID : 00716-001	40
EO-016	524	335	51.56	--	152	--	--	--	--	G-250103	007156-001 Cust. Part ID : 00716-001	61

Casting Process : Lost Wax Investment Casting
Supply Condition : Solution Annealing at 1060° C ± 20° C for 1hr/inch, then Water Quenched.
Dimensional Inspection : Accepted
Material Identification : Casting are identified with Heat No. / Grade / Foundry Logo etc.

We hereby certify that the items mentioned above confirms to PO
Specification : ASTM A351/351M Gr:CF8M

QUALITY ASSURANCE SYSTEM IN ACCORDANCE WITH THE
PRESSURE EQUIPMENT DIRECTIVE 2014/68/EU, ANNEX I,
SECTION 4.3, AD 2000-MERKBLATT W-0 AS WELL AS EN
784-5, PARA. 4.2.

Tested By

For, Gorecha Metal Tech Pvt. Ltd.

Quality Control Dept.



GORECHA METAL TECH PVT. LTD.

Address : Survey No. 55 / P7, Plot No. 1, Shreeji Industrial Area 2,
Rajkot Gondal NH-27, Pipaliya Sadak, Dist. Rajkot - 360 311 (Gujarat, India)
Telefax : +91 85111 55652
Email : inquiry@gorechametal.com, Web : www.gorechametal.com
GSTIN : 24AACG4703F1ZY, State Code : 24 - Gujarat

TEST CERTIFICATE

AS PER EN - 10204 TYPE 3.1

M/s. GMT CORPORATION PRIVATE LIMITED

TC No. : 147 - 18/04/2026
DC No. : 146/26-27 - 18/04/2026
Invoice No. : 26/27-151 - 18/04/2026
PO No. : 00-02-26

Specification : ASTM A351/351M Gr:CF8M

SPECTRO CHEMICAL ANALYSIS

Heat No.	C %	SI %	Mn %	P %	S %	Cr %	Mo %	Ni %										
Min.						18.000	2.000	9.000										
Max.	0.080	1.500	1.500	0.040	0.040	21.000	3.000	12.000										Heat Code
EO-016	0.022	1.210	1.070	0.036	0.002	18.520	2.140	9.590										
EO-037	0.039	1.400	1.080	0.040	0.002	18.650	2.160	9.590										
EO-077	0.049	1.320	1.050	0.038	0.005	18.600	2.230	9.440										

MECHANICAL PROPERTIES

Heat No.	TS MPa	YS MPa 8y 0.2% Offset	Elgn. %	R.A. %	Hardness	Impact Test at Test Temp. °C				Die No.	Description	Qty.
Min.	485	205	30.00	--	--							
Max.	--	--	--	--	--	1	2	3	Avg			
EO-016	524	335	51.56	--	159	--	--	--	--	G-250103	007156-001 Cust Part ID : 00716-001	119
EO-037	555	334	50.32	--	151	--	--	--	--	G-250103	007156-001 Cust Part ID : 00716-001	85
EO-077	530	349	50.08	--	155	--	--	--	--	G-250103	007156-001 Cust Part ID : 00716-001	84

Casting Process : Lost Wax Investment Casting
Supply Condition : Solution Annealing at 1060° C ± 20° C for 1hr/inch, then Water Quenched.
Dimensional Inspection : Accepted
Material Identification : Casting are identified with Heat No. / Grade / Foundry Logo etc.

We hereby certify that the items mentioned above confirms to PO
Specification : ASTM A351/351M Gr:CF8M

QUALITY ASSURANCE SYSTEM IN ACCORDANCE WITH THE
PRESSURE EQUIPMENT DIRECTIVE 2014/68/EU, ANNEX I,
SECTION 4.3, AD 2000-MERKBLATT W-0 AS WELL AS EN
764-5, PARA 4.2

Tested By

For, Gorecha Metal Tech Pvt. Ltd.

Quality Control Dept.



GMT Corporation Pvt. Ltd.

Pre-Dispatch Inspection Report

Format No.: GMTC/QA/F/04
Rev. No.: 00
Rev. Date: 01/04/2025
Page No.: 01 of 01

Part Name: FLANGED HEAD

Customer Name: DESSIMATE LLC

Date: 15-05-2026

Part No.: 007157-001

Challan / Invoice No.: GMTCX/2627/0192

Sample Size: 03

Rev. No: N

Control Plan No.: GMTC/DSS/CP/007157-001

Dispatch Qty.: 300

Sr. No.	Parameter	Specification	Instrument / Gauge	Special Characteristics	Sample No. (All Dimensions are in Inch)			Remark
					1	2	3	
1	Outer Diameter	3.3750 + 0.0000 / - 0.0017	Air Ring Gauge	(X)	3.3741	3.374	3.3744	Accepted
2	Distance	0.655 ± 0.005	Ht. Gauge	(X)	0.653	0.655	0.654	Accepted
3	Pocket Diameter	0.800 ± 0.005	CMM	(X)	0.8016	0.8013	0.8017	Accepted
4	Bore Size	1.540 ± 0.005	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
5	Bore Size	1.255 + 0.000 / - 0.003	Inside Vernier Caliper / Plain Plug Gauge	(X)	1.253	1.253	1.254	Accepted
6	Bore Deep	0.042 + 0.002 / - 0.000	Ht. Gauge	(X)	0.0429	0.0433	0.0433	Accepted
7	Distance	0.200 ± 0.005	CMM	(X)	0.2021	0.202	0.2018	Accepted
8	Hole Size	0.125 + 0.005 / - 0.001	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
9	Distance	R 0.718 ± 0.005	CMM	(X)	0.7162	0.7181	0.7192	Accepted
10	Pocket Width	0.400 ± 0.005	Width Gauge	(X)	OK	OK	OK	Accepted
11	Chamfer Length	0.050 ± 0.005	Contracer	(X)	0.0502	0.0493	0.0505	Accepted
12	Chamfer Angle	30° ± 1°	Contracer	(X)	29°57'47"	30°17'01"	30°02'51"	Accepted
13	3 x Drill Depth To Point	0.500 Max.	Special Point Pin with Dial	(X)	0.472	0.470	0.470	Accepted
					0.472	0.470	0.469	Accepted
					0.470	0.472	0.470	Accepted
14	2 x Drill Depth To Point	0.320 Max.	Special Point Pin with Dial	(X)	0.308	0.307	0.309	Accepted
15	Bore Size	2.430 ± 0.005	Plain Plug Gauge		0.309	0.308	0.308	Accepted
16	Groove Width	0.081 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
17	4 x Hole Size	0.250 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
18	2 x Tap	10-32 UNF -2B	Thread Plug Gauge		OK	OK	OK	Accepted
19	5 x Tap	4-40 UNC-2B	Thread Plug Gauge		OK	OK	OK	Accepted
20	Hole	0.625 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
21	Hole	0.500 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
22	Groove Width	0.140 ± 0.005	Width Gauge		OK	OK	OK	Accepted

Legends: Critical- (X)

Safety Critical- (S)

Major- (M)

Minor- (No Symbol)

Key Instructions- (K)

Pass Through Characteristic- (P)

Lot: ☒ Accepted ☐ Rejected


Checked By: Shreejyot Vharate

Approved By: Dhiraj Patil





INDACO METAL COATS PVT LTD
Sr. No. 430/2, Bhutaramanahatti, Honaga, Belgaum, Karnataka, India -
591156



CERTIFICATE OF CONFORMANCE

Report No.:IMC/COC/E+P/2026/037		Customer:	GMT CORPORATION PVT. LTD.	Date:	23/04/2026
Part Name:	FLANGED HEAD	Part No.:	007157-001	Rev No.:	-
Drawing No.:	NA	FAI No.:	-		
Material	CF8M SS	WO/DC No.:	58	PO No.:	-
Job Card No.:	IMC/P/E+P/JC/2026/037	Traveler No.:	IMC/P/E+P/PT/2026/037		
Quantity:	60 No's	Part Serial No.:	-		
Inspected Quantity (No's):	60 No's	Accepted Quantity (No's):	60 No's	Rejected Quantity (No's):	0

Customer Specification: Electropolish as per (ASTM B912)

Process Specification:Electropolish as per (ASTM B912)

Sl. No.	Parameter	Control Limits	Observation	Result	Quantity Accpeted	Quantity Rejected
1	Visual Inspection	After completion of processing, there shall be no evidence of etching, pitting, smutting, frosting, dimensional changes, or other chemical attack on the parts when visually examined without aid of magnification. However, loss of temper color	After completion of processing, there is no evidence of etching, pitting, smutting, frosting, dimensional changes, and other chemical attack on the parts when visually examined without aid of magnification. No loss of temper color	Satisfactory	60 No's	Nil



Customer Deviation If Any: Nil

This is to caertify that all the above mentioned parts are processed, Inspected and unless otherwise satisfactory to the above mentiones Type / Class / Method / Drawing / Specification and / Contract.

Prepared By: Pooja K

Pooja K
23/04/26

Approved By: Poonam Kutre


Poonam Kutre
23/4/26

Format No.: QC-IMC-003

Rev No.: K & Date: 13-03-2025



INDACO METAL COATS PVT LTD
Sr. No. 430/2, Bhutaramanahatti, Honaga, Belgaum, Karnataka, India - 591156



CERTIFICATE OF CONFORMANCE

Report No.:IMC/COC/E+P/2026/041		Customer:	GMT CORPORATION PVT. LTD.	Date:	05/05/2026
Part Name:	FLANGED HEAD	Part No.:	007157-001	Rev No.:	-
Drawing No.:	NA	FAI No.:	-		
Material	CF8M SS	WO/DC No.:	2627/000139	PO No.:	-
Job Card No.:	IMC/P/E+P/JC/2026/041	Traveler No.:	IMC/P/E+P/PT/2026/041		
Quantity:	120 No's	Part Serial No.:	-		
Inspected Quantity (No's):	120 No's	Accepted Quantity (No's):	120 No's	Rejected Quantity (No's):	0

Customer Specification: Electropolish as per (ASTM B912)

Process Specification:Electropolish as per (ASTM B912)

Sl. No.	Parameter	Control Limits	Observation	Result	Quantity Accpeted	Quantity Rejected
1	Visual Inspection	After completion of processing, there shall be no evidence of etching, pitting, smutting, frosting, dimensional changes, or other chemical attack on the parts when visually examined without aid of magnification. However, loss of temper color	After completion of processing, there is no evidence of etching, pitting, smutting, frosting, dimensional changes, and other chemical attack on the parts when visually examined without aid of magnification. No loss of temper color	Satisfactory	120 No's	Nil



Customer Deviation If Any: Nil

This is to caertify that all the above mentioned parts are processed, Inspected and unless otherwise satisfactory to the above mentiones Type / Class / Method / Drawing / Specification and / Contract.

Prepared By: Pooja K.

PJK 5/05/26

Approved By: Nagesh Metri


Nagesh 5/5/26

Format No.: QC-IMC-003

Rev No.: K & Date: 13-03-2025



INDACO METAL COATS PVT LTD
Sr. No. 430/2, Bhutaramanahatti, Honaga, Belgaum, Karnataka, India -
591156



CERTIFICATE OF CONFORMANCE

Report No.:IMC/COC/E+P/2026/042		Customer:	GMT CORPORATION PVT. LTD.	Date:	07/05/2026
Part Name:	FLANGED HEAD	Part No.:	007157-001	Rev No.:	-
Drawing No.:	NA	FAI No.:	-		
Material	CF8M SS	WO/DC No.:	2627/000166	PO No.:	-
Job Card No.:	IMC/P/E+P/JC/2026/042	Traveler No.:	IMC/P/E+P/PT/2026/042		
Quantity:	101 No's	Part Serial No.:	-		
Inspected Quantity (No's):	101 No's	Accepted Quantity (No's):	101 No's	Rejected Quantity (No's):	0

Customer Specification: Electropolish as per (ASTM B912)

Process Specification:Electropolish as per (ASTM B912)

Sl. No.	Parameter	Control Limits	Observation	Result	Quantity Accepted	Quantity Rejected
1	Visual Inspection	After completion of processing, there shall be no evidence of etching, pitting, smutting, frosting, dimensional changes, or other chemical attack on the parts when visually examined without aid of magnification. However, loss of temper color	After completion of processing, there is no evidence of etching, pitting, smutting, frosting, dimensional changes, and other chemical attack on the parts when visually examined without aid of magnification. No loss of temper color	Satisfactory	101 No's	Nil



Customer Deviation If Any: Nil

This is to certify that all the above mentioned parts are processed, Inspected and unless otherwise satisfactory to the above mentioned Type / Class / Method / Drawing / Specification and / Contract.

Prepared By: Pooja K.


Approved By: Nagesh Metri

Format No.: QC-IMC-003

Rev No.: K & Date: 13-03-2025



INDACO METAL COATS PVT LTD
Sr. No. 430/2, Bhutaramanahatti, Honaga, Belgaum, Karnataka, India - 591156



CERTIFICATE OF CONFORMANCE

Report No.:IMC/COC/E+P/2026/043		Customer:	GMT CORPORATION PVT. LTD.	Date:	13/05/2026
Part Name:	FLANGED HEAD	Part No.:	007157-001	Rev No.:	-
Drawing No.:	NA	FAI No.:			
Material	CF8M SS	WO/DC No.:	2627/000199	PO No.:	-
Job Card No.:	IMC/P/E+P/JC/2026/043	Traveler No.:	IMC/P/E+P/PT/2026/043		
Quantity:	24 No's	Part Serial No.:	-		
Inspected Quantity (No's):	24 No's	Accepted Quantity (No's):	24 No's	Rejected Quantity (No's):	0

Customer Specification: Electropolish as per (ASTM B912)

Process Specification: Electropolish as per (ASTM B912)

Sl. No.	Parameter	Control Limits	Observation	Result	Quantity Accepted	Quantity Rejected
1	Visual Inspection	After completion of processing, there shall be no evidence of etching, pitting, smutting, frosting, dimensional changes, or other chemical attack on the parts when visually examined without aid of magnification. However, loss of temper color	After completion of processing, there is no evidence of etching, pitting, smutting, frosting, dimensional changes, and other chemical attack on the parts when visually examined without aid of magnification. No loss of temper color	Satisfactory	24 No's	Nil



Customer Deviation If Any: Nil

This is to certify that all the above mentioned parts are processed, Inspected and unless otherwise satisfactory to the above mentioned Type / Class / Method / Drawing / Specification and / Contract.

Prepared By: Pooja K.

Approved By: Poonam Kutre

Format No.: QC-IMC-003

Rev No.: K & Date: 13-03-2025