



GMT Corporation Pvt. Ltd.

Pre-Dispatch Inspection Report

Format No.: GMT/C/QA/F/04
Rev. No.: 00
Rev. Date: 01/04/2025
Page No.: 01 of 01

Part Name: FLANGED HEAD

Customer Name: DESSIMATE LLC

Date :10-04-2026

Part No.: 007157-001

Challan / Invoice No.: GMT/CX/2627/0045

Sample Size: 03

Rev. No: N

Control Plan No.: GMT/C/DSS/CP/007157-001

Dispatch Qty.: 300

Sr. No.	Parameter	Specification	Instrument / Gauge	Special Characteristics	Sample No. (All Dimensions are in Inch)			Remark
					1	2	3	
1	Outer Diameter	3.3750 + 0.0000 / - 0.0017	Air Ring Gauge	(X)	3.374	3.3744	3.3741	Accepted
2	Distance	0.655 ± 0.005	Ht. Gauge	(X)	0.654	0.656	0.655	Accepted
3	Pocket Diameter	0.800 ± 0.005	CMM	(X)	0.8005	0.7999	0.8000	Accepted
4	Bore Size	1.540 ± 0.005	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
5	Bore Size	1.255 + 0.000 / - 0.003	Inside Vernier Caliper / Plain Plug Gauge	(X)	1.253	1.253	1.254	Accepted
6	Bore Deep	0.042 + 0.002 / - 0.000	Ht. Gauge	(X)	0.0429	0.0433	0.0429	Accepted
7	Distance	0.200 ± 0.005	CMM	(X)	0.2012	0.202	0.2015	Accepted
8	Hole Size	0.125 + 0.005 / - 0.001	Plain Plug Gauge	(X)	OK	OK	OK	Accepted
9	Distance	R 0.718 ± 0.005	CMM	(X)	0.7192	0.7181	0.7193	Accepted
10	Pocket Width	0.400 ± 0.005	Width Gauge	(X)	OK	OK	OK	Accepted
11	Chamfer Length	0.050 ± 0.005	Contracer	(X)	0.0507	0.0511	0.0499	Accepted
12	Chamfer Angle	30° ± 1°	Contracer	(X)	29°50'54"	30°10'23"	30°06'11"	Accepted
13	3 x Drill Depth To Point	0.500 Max.	Special Point Pin with Dial	(X)	0.464	0.4690	0.4680	Accepted
					0.468	0.4640	0.4660	Accepted
					0.464	0.466	0.466	Accepted
14	2 x Drill Depth To Point	0.320 Max.	Special Point Pin with Dial	(X)	0.311	0.307	0.307	Accepted
					0.307	0.309	0.309	Accepted
15	Bore Size	2.430 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
16	Groove Width	0.081 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
17	4 x Hole Size	0.250 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
18	2 x Tap	10-32 UNF-2B	Thread Plug Gauge		OK	OK	OK	Accepted
19	5 x Tap	4-40 UNC-2B	Thread Plug Gauge		OK	OK	OK	Accepted
20	Hole	0.625 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
21	Hole	0.500 ± 0.005	Plain Plug Gauge		OK	OK	OK	Accepted
22	Groove Width	0.140 ± 0.005	Width Gauge		OK	OK	OK	Accepted

Legends: Critical- (X) Safety Critical- (S)

Major - (M)

Minor- (No Symbol)

Key Instructions- (K)

Pass Through Characteristic- (P)

Lot: ☒ Accepted ☐ Rejected

Checked By: Shreejyot Vharate

Approved By: Dhiraj Patil