

Exploring the AKS cluster – Kubernetes side

- **azure-ip-masq-agent**

- Implemented as a DaemonSet
- Masquerading, in the context of networking, refers to a technique used to hide the true identity of a device on a network
- acts as an IP masquerade agent and helps in configuring IP masquerade rules in the nodes

```
$kubectl logs azure-ip-masq-agent-5tqkr -n kube-system | tail -n 2
I0216 07:53:55.167331      1 ip-masq-agent.go:211] syncing config file "ip-masq-agent-reconciled" at "/etc/config/"
I0216 07:53:55.167489      1 ip-masq-agent.go:199] using config: {"nonMasqueradeCIDRs":["10.244.0.0/16"],"masqLinkLocal":true,"masqLinkLocalIPv6":false}
```

- iptables is a command line tool for configuring the Linux kernel's built-in firewall

```
root@aks-nodepool1-33156667-vmss000000:/# iptables -t nat -nL IP-MASQ-AGENT
Chain IP-MASQ-AGENT (1 references)
target      prot opt source                destination          /* ip-masq-agent: local traffic is not subject to MASQUERADE */
RETURN      all  --  0.0.0.0/0             10.244.0.0/16
MASQUERADE  all  --  0.0.0.0/0             0.0.0.0/0            /* ip-masq-agent: outbound traffic is subject to MASQUERADE (must be last in chain) */
```