Visoka škola strukovnih studija za informacione i komunikacione tehnologije



Dokumentacija

http://shopedia-belgrade.000webhostapp.com

Nikola Nedeljković 2/17

Sadržaj

Do	kumer	ntacija	1
Sa	držaj		2
1.	UVC	dC	4
	1.1	Korišćeni programski / markap jezici	4
	1.2	Opis funkcionalnosti	4
	1.3	Izgled stranica	7
2.	ORG	SANIZACIJA	8
	2.1	Organizacija sajta	8
	1.		9
	2.2	Organizacija baze	9
	2.3	Sitemap.xml	. 10
	2.4	Slike stranica sa funkcionalnostima	. 11
3.	KOD	OVI	. 17
	3.1	index.php	. 17
	3.2.	api.php → komunikacija između index i kontrolera	. 18
	3.3.	data.php $ ightarrow$ dohvatanje podataka za prikaz	. 19
	3.4	autoload.php	. 20
	3.5.	DATABASE.php → SQL upiti i kreiranje baze	. 20
	3.6	ItemController.php	. 21
	3.7	LoginController.php	. 22
	3.8.	MeasureController.php	. 23
	3.9	RegisterController.php	. 24
	3.10	RoleController.php	. 24
	3.11.	ShopController.php	. 25
	3.12	UserController.php	. 26
	3.13.	Item.php	. 26
	3.14.	Measure.php	. 27

3.15.	Role.php	28
3.16.	Shop.php	28
3.17.	User.php	28
3.18.	footer.php	29
3.19.	header.php	30
3.20.	404.php	31
3.21.	admin.php	31
3.22.	login.php	32
3.23.	main.php	33
3.24.	register.php	35
3.25.	teacher.php	35
3.26.	style.css	36
3.27.	main.js	44
HIIFR	VBHIISKI BBEGLED	12

1. UVOD

1.1 Korišćeni programski / markap jezici

- Za izradu ovog sajta korišćene su sledeće tehnologije:
 - Mark-up jezici: HTML 5, XML
 - CSS3
 - Skripting-programski jezici: JavaScript, PHP
- Sajt je napisan u Atom-u

1.2 Opis funkcionalnosti

- index.php
 - ✓ Dinamičko učitavanje stranica po stanju korisnika i odabranom linku
- o api.php
 - ✓ Komunikacija između indexa i kontrolora
- o data.php
 - ✓ Stranica za dohvatanje podataka koji treba da se prikažu na stranici
- o app/Config/autoload.php
 - ✓ Autoload skripta
- o app/Config/config.php
 - ✓ Promenljive za povezivanje na bazu
- $\circ \quad app/Config/DATABASE.php$
 - ✓ Klasa baze podataka
 - ✓ Inicijalizacija i izvršavanje upita
- $\circ \ app/Controllers/ItemController.php\\$
 - ✓ Klasa ItemController
 - ✓ Inicijalizacija i rad sa podacima za tabelu item
- $\circ \quad app/Controllers/LoginController.php \\$
 - ✓ Klasa LoginController

✓ Inicijalizacija i rad sa podacima za logovanje korisnika

$\circ \quad app/Controllers/MeasureController.php$

- ✓ Klasa MeasureController
- ✓ Inicijalizacija i rad sa podacima za tabelu measure

$\circ \quad app/Controllers/RegisterController.php$

- ✓ Klasa RegisterController
- ✓ Inicijalizacija i rad sa podacima za registraciju korisnika

o app/Controllers/RoleController.php

- ✓ Klasa RoleController
- ✓ Inicijalizacija i rad sa podacima za tabelu role

app/Controllers/ShopController.php

- ✓ Klasa ShopController
- ✓ Inicijalizacija i rad sa podacima za tabelu shop

app/Controllers/UserController.php

- ✓ Klasa UserController
- ✓ Inicijalizacija i rad sa podacima za tabelu user

o app/Models/Item.php

- ✓ Klasa Item
- ✓ Inicijalizacija i rad sa tabelom item

o app/Models/Measure.php

- ✓ Klasa Measure
- ✓ Inicijalizacija i rad sa tabelom measure

o app/Models/Role.php

- ✓ Klasa Role
- ✓ Inicijalizacija i rad sa tabelom role

o app/Models/Shop.php

- ✓ Klasa Shop
- ✓ Inicijalizacija i rad sa tabelom shop

o app/Models/User.php

- ✓ Klasa User
- ✓ Inicijalizacija i rad sa tabelom user

o app/Views/fixed/footer.php

✓ Dinamički prikaz linkova i copyright

o app/Views/fixed/header.php

- ✓ Head tag
- ✓ Logo
- ✓ Dinamički prikaz log in/log out dugmića

o app/Views/pages/404.php

✓ Error stranica

o app/Views/pages/admin.php

- ✓ Prikaz admin stranice
- ✓ Funkcionalnosti vezane samo za admin naloge

o app/Views/pages/login.php

- ✓ Prikaz login stranice
- ✓ Logovanje korisnika

o app/Views/pages/main.php

- ✓ Glavna stranica korisnika
- ✓ Prikaz, dodavanje i izmena podataka iz šoping liste
- ✓ Prikaz, dodavanje i izmena radnji u kojima korisnik kupuje

o app/Views/pages/register.php

- ✓ Prikaz register stranice
- ✓ Registracija korisnika

o app/Views/pages/teacher.php


✓ Prikaz stranice o autoru

1.3 Izgled stranica




2. ORGANIZACIJA

2.1 Organizacija sajta




2.2 Organizacija baze




2.3 Sitemap.xml

2.4 Slike stranica sa funkcionalnostima




login.php

- Ispisivanje login forme, korisnička provera unetih podataka, prosleđivanje na kontroler i dalja obrada toga. Redirekcija na osnovu dobijenih parametara. Sajtu se ne može pristupiti bez prvog logovanja.




main.php

- Dinamičko ispisivanje podataka i korisnička obrada novih i starih fajlova pred slanje na kontroler




admin.php

- Dinamičko ispisivanje podataka i korisnička obrada novih i starih fajlova pred slanje na kontroler. Kontrole kojima samo admin može pristupiti.




register.php

Ispisivanje forme za registraciju, korisnička provera unetih podataka, prosleđivanje na kontroler i dalja obrada toga. Redirekcija na osnovu dobijenih parametara.



teacher.php

- Stranica o autoru.



404.php

- 404 stranica za greške.

3. KODOVI

3.1 index.php

```
<?php
    session start();
include("app/Views/fixed/header.php");
    if (isset($ GET["page"])) {
        switch($ GET["page"]) {
            case "login":
                if(isset($ SESSION['user'])) {
                    include "app/Views/pages/main.php";
                } else {
                    include "app/Views/pages/login.php";
                break;
            case "register":
                if(isset($ SESSION['user'])) {
                    include "app/Views/pages/main.php";
                    include "app/Views/pages/register.php";
                break;
            case "main":
                include "app/Views/pages/main.php";
                break;
            case "admin":
                if(isset($ SESSION['user'])) {
                    if (($ SESSION['user']->role id != 1) &&
($ SESSION['user']->role id != 3)) {
                        include "app/Views/pages/main.php";
                    } else {
                        include "app/Views/pages/admin.php";
                } else {
                    include "app/Views/pages/login.php";
                break;
            case "teacher":
                if(isset($ SESSION['user'])) {
                    if ($ SESSION['user']->role id != 3) {
                        include "app/Views/pages/main.php";
                    } else {
                        include "app/Views/pages/teacher.php";
                } else {
                    include "app/Views/pages/login.php";
                break;
            default:
                include "app/Views/pages/404.php";
                break;
    } else {
      if(!isset($ SESSION['user'])) {
```

```
include "app/Views/pages/login.php";
} else {
    include "app/Views/pages/main.php";
}
include("app/Views/fixed/footer.php");
?>
```

3.2. api.php → komunikacija između index i kontrolera

```
<?php
    require once "app/Config/autoload.php";
    require "app/Config/config.php";
    use App\Controllers\LoginController;
   use App\Controllers\RegisterController;
   use App\Controllers\ShopController;
   use App\Controllers\UserController;
   use App\Controllers\MeasureController;
   use App\Controllers\ItemController;
   $login = new LoginController();
   $register = new RegisterController();
   $shopcont = new ShopController();
   $usercont = new UserController();
   $measurecont = new MeasureController();
   $itemcont = new ItemController();
   session_start();
   function logFunction ($content) {
        $log path = $ SERVER["DOCUMENT ROOT"] . "/data/log.txt";
        $open = fopen($log path, "a");
        if ($open && isset($ SESSION["user"])) {
            $date = date('d-m-Y H:i:s');
            fwrite($open, "{$content}\t{$date}\t{$ SESSION['user']-
>username}\t\n");
          fclose ($open);
}
logFunction($ GET['page']);
   switch ($_GET['page']) {
        case 'login':
           $login->login($ POST);
           break;
        case 'logout':
            if(isset($ SESSION['user'])) {
               unset($\subsets SESSION['user']);
              session destroy();
           header("Location: index.php?page=login");
           die();
           break;
        case 'register':
            $register->register($ POST);
           break;
        case 'shop edit':
        if ($ POST["shop add edit id"] != "") {
```

```
$shopcont->updateShop($ POST);
            } else {
               $shopcont->addShop($ POST, $ SESSION['user']->ID);
            break;
        case 'shop delete':
            $shopcont->deleteShop($ GET['id']);
           break;
        case 'item edit':
            if ($ POST["item add edit id"] != "") {
                $itemcont->updateItem($ POST, $ SESSION['user']->ID);
            } else {
              $itemcont->addItem($ POST, $ SESSION['user']->ID);
            break;
        case 'item delete':
            $itemcont->deleteItem($ GET['id']);
        case 'add measure':
            $measurecont->addMeasure($ POST);
            break;
        case 'edit measure':
            $measurecont->updateMeasure($ POST);
            break;
        case 'delete measure':
            $measurecont->deleteMeasure($ POST);
        case 'edit user':
            $usercont->editUserRight($_POST);
            break;
        case 'delete user':
            $usercont->deleteUser($ POST);
            break;
        default:
            header("Location: index.php?page=main");
            die();
            break;
?>
```

3.3. data.php → dohvatanje podataka za prikaz

```
require_once "app/Config/autoload.php";
    require "app/Config/config.php";
    use App\Controllers\ShopController;
    use App\Controllers\RoleController;
    use App\Controllers\UserController;
    use App\Controllers\MeasureController;
    use App\Controllers\ItemController;
    use App\Controllers\ItemController;
    shopcont = new ShopController();
    $rolecont = new RoleController();
    $usercont = new UserController();
    $measurecont = new MeasureController();
    $itemcont = new ItemController();
    $itemcont = new ItemController();
```

```
$measure_data = $measurecont->getMeasures();
$shop_data = $shopcont->getShops($_SESSION['user']->ID);
$user_data = $usercont->getUsers($_SESSION['user']->ID);
$role_data = $rolecont->getRoles();
```

3.4 autoload.php

```
<?php
// AUTOLOAD
spl_autoload_register(function ($path) {
          $path = str_replace("\\", DIRECTORY_SEPARATOR, $path);
          $path[0] = strtolower($path[0]);
          $path .= ".php";
          require_once $path;
});</pre>
```

3.5. DATABASE.php → SQL upiti i kreiranje baze

```
namespace App\Config;
class DATABASE {
 private $connection;
private static $database;
   private function construct() {
   $this->connect();
public static function instance() {
       if(self::$database === null) {
          self::$database = new DATABASE();
      return self::$database;
   private function connect() {
           $this->connection = new
\PDO("mysql:host=".SERVER.";dbname=".DBNAME.";charset=utf8", USERNAME,
PASSWORD);
           $this->connection->setAttribute(\PDO::ATTR DEFAULT FETCH MODE,
\PDO::FETCH OBJ);
           $this->connection->setAttribute(\PDO::ATTR ERRMODE,
\PDO::ERRMODE EXCEPTION);
       catch (PDOException $ex) {
          echo $ex->getMessage();
 public function executeQuery(string $query) {
    return $this->connection->query($query)->fetchAll();
}
```

```
public function executeQueryAll(string $query, Array $params) {
       $prepare = $this->connection->prepare($query);
       $prepare->execute($params);
     return $prepare->fetchAll();
public function executeQueryOneRow(string $query, Array $params) {
       $prepare = $this->connection->prepare($query);
       $prepare->execute($params);
     return $prepare->fetch();
public function executeInsert(string $query, Array $params) {
       $prepare = $this->connection->prepare($query);
     $prepare->execute($params);
public function executeUpdate(string $query, Array $params) {
      $prepare = $this->connection->prepare($query);
     $prepare->execute($params);
public function executeDelete(string $query, Array $params) {
$prepare = $this->connection->prepare($query);
     $prepare->execute($params);
```

3.6 ItemController.php

```
namespace App\Controllers;
   use App\Models\Item;
use App\Config\DATABASE;
class ItemController {
private $model;
       public function __construct() {
        $this->model = new Item(DATABASE::instance());
       public function getItems($user id) {
       return $this->model->getItems($user id);
       public function addItem($request, $user id) {
           if(isset($request['item add edit submit'])) {
               $name = $request['item add edit name'];
               $quantity = $request['item add edit quantity'];
               $measure = $request['item add edit measure'];
               $shop = $request['item add edit shop'];
 if ($name != "" && $quantity != "" && $measure != "" && $shop
!= "") {
         $this->model->addItem($name, $quantity, $measure,
$user id, $shop);
```

```
header("Location: index.php?page=main");
       public function updateItem($request) {
           if(isset($request['item add edit submit'])) {
               $name = $request['item add edit name'];
               $id = $request['item add edit id'];
               $quantity = $request['item add edit quantity'];
               $measure = $request['item add edit measure'];
            $shop = $request['item add edit shop'];
 if ($name != "" && $quantity != "" && $measure != "" && $shop
!= "") {
              $this->model->updateItem($name, $quantity, $measure,
$shop, $id);
           header("Location: index.php?page=main");
 public function deleteItem($id) {
           $this->model->deleteItem($id);
           header("Location: index.php?page=main");
```

3.7 LoginController.php

```
namespace App\Controllers;
   use App\Models\User;
use App\Config\DATABASE;
   class LoginController {
  private $model;
       public function construct() {
          $this->model = new User(DATABASE::instance());
       public function login($request) {
           if(isset($request['signin'])) {
               $username = $request['username'];
               $password = $request['password'];
               $user = $this->model->getUser($username, $password);
               if($user) {
                   $ SESSION['user'] = $user;
                   $ SESSION['l error'] ="User not registered or wrong
credentials!";
               header("Location: index.php?page=login");
     } else {
```

```
http_response_code(404);

}
```

3.8. MeasureController.php

```
<?php
   namespace App\Controllers;
   use App\Models\Measure;
   use App\Config\DATABASE;
   class MeasureController {
private $model;
       public function construct() {
       $this->model = new Measure(DATABASE::instance());
       public function getMeasures() {
           return $this->model->getMeasures();
       public function addMeasure($request) {
           if(isset($request['submit_add_measure'])) {
             $name = $request['add measure'];
         if ($name != "") {
     $this->model->addMeasure($name);
          header("Location: index.php?page=admin");
       public function updateMeasure($request) {
           if(isset($request['submit edit measure'])) {
               $name = $request['edit measure'];
               $id = $request['edit measure id'];
               if ($name != "") {
                  $this->model->updateMeasure($name, $id);
           header("Location: index.php?page=admin");
       public function deleteMeasure($request) {
           if(isset($request['submit delete measure'])) {
               $id = $request['measure delete select'];
               if ($id != "") {
                   $this->model->deleteMeasure($id);
           header("Location: index.php?page=admin");
```

3.9 RegisterController.php

```
namespace App\Controllers;
use App\Models\User;
 use App\Config\DATABASE;
class RegisterController {
private $model;
       public function construct() {
          $this->model = new User(DATABASE::instance());
       public function register($request) {
           if(isset($request['register'])) {
               $username = $request['username'];
               $password = $request['password'];
               $email = $request['email'];
               if(!filter var($email, FILTER VALIDATE EMAIL)) {
                   $ SESSION['r error'] = "Email not valid!";
               else {
                   $user = $this->model->existsUser($username, $email);
                   if($user) {
                       $ SESSION['r error'] ="Email or username already in
use!";
                   } else {
                   $this->model->createUser($username, $email,
$password);
                  $ SESSION['r error'] ="User created successfully, you
can now login with your credentials!";
               header("Location: index.php?page=register");
               \http response code (404);
```

3.10 RoleController.php

```
public function getRoles() {
    return $this->model->getRoles();
}
```

3.11. ShopController.php

```
namespace App\Controllers;
   use App\Models\Shop;
use App\Config\DATABASE;
class ShopController {
private $model;
       public function construct() {
       $this->model = new Shop(DATABASE::instance());
       public function getShops($user id) {
           return $this->model->getShops($user id);
       public function addShop($request, $user_id) {
           if(isset($request['shop add edit submit'])) {
           $name = $request['shop add edit name'];
        if ($name != "") {
                $this->model->addShop($name, $user id);
           header("Location: index.php?page=main");
       public function updateShop($request) {
           if(isset($request['shop add edit submit'])) {
               $name = $request['shop add edit name'];
               $id = $request['shop add edit id'];
             if ($name != "") {
                $this->model->updateShop($name, $id);
           header("Location: index.php?page=main");
       public function deleteShop($id) {
           $this->model->deleteShop($id);
         header("Location: index.php?page=main");
```

3.12 UserController.php

```
<?php
   namespace App\Controllers;
   use App\Models\User;
use App\Config\DATABASE;
 class UserController {
  private $model;
       public function construct() {
       $this->model = new User(DATABASE::instance());
       public function getUsers($id) {
           return $this->model->getUsers($id);
       public function editUserRight($request) {
           if(isset($request['submit edit user id'])) {
               $user = $request['edit user right id'];
           $role = $request['user right select'];
               if ($user != "" && $role != "") {
                $this->model->editUserRight($role, $user);
           header("Location: index.php?page=admin");
       public function deleteUser($request) {
           if(isset($request['submit delete user'])) {
               $id = $request['user delete select'];
               if ($id != "") {
                 $this->model->deleteUser($id);
           header("Location: index.php?page=admin");
}
```

3.13. Item.php

```
<?php
   namespace App\Models;
   use App\Config\DATABASE;

class Item {
    private $database;

   public function __construct(DATABASE $database) {
        $this->database = $database;
   }

   public function getItems($user id) {
```

ID = ?", [\$name, \$id]);

public function deleteMeasure(\$id) {

}

?", [\$id]); }

```
return $this->database->executeQueryAll("SELECT i.ID as item id,
i.name AS name, i.quantity AS quantity, m.name AS measure, s.name AS shop,
m.ID AS measure id, s.ID AS shop id FROM item i INNER JOIN measure m ON
i.measure id = m.ID INNER JOIN shop s ON i.shop id = s.ID WHERE i.user id =
?", [$user id]);
}
public function addItem($name, $quantity, $measure, $user_id, $shop)
$this->database->executeInsert("INSERT INTO item (name, quantity,
measure id, user id, shop id) VALUES (?, ?, ?, ?) ", [$name, $quantity,
$measure, $user id, $shop]);
}
public function updateItem($name, $quantity, $measure, $shop, $id) {
          $this->database->executeUpdate("UPDATE item SET name = ?,
quantity = ?, measure id = ?, shop id = ? WHERE ID = ?", [$name, $quantity,
$measure, $shop, $id]);
}
public function deleteItem($id) {
      $this->database->executeDelete("DELETE FROM item WHERE ID = ?",
[$id]);
}
          Measure.php
  3.14.
<?php
   namespace App\Models;
use App\Config\DATABASE;
class Measure {
private $database;
     public function __construct(DATABASE $database) {
       $this->database = $database;
public function getMeasures() {
       return $this->database->executeQuery("SELECT * FROM measure");
public function addMeasure($name) {
          $this->database->executeInsert("INSERT INTO measure (name) VALUES
(?)", [$name]);
}
       public function updateMeasure($name, $id) {
          $this->database->executeUpdate("UPDATE measure SET name = ? WHERE
```

\$this->database->executeDelete("DELETE FROM measure WHERE ID =

}

3.15. Role.php

3.16. Shop.php

```
<?php
   namespace App\Models;
use App\Config\DATABASE;
class Shop {
    private $database;
public function construct(DATABASE $database) {
      public function getShops($user id) {
          return $this->database->executeQueryAll("SELECT ID, name FROM
shop WHERE user id = ?", [$user id]);
public function addShop($name, $user id) {
      $this->database->executeInsert("INSERT INTO shop (name, user id)
VALUES (?, ?)", [$name, $user id]);
}
public function updateShop($name, $id) {
   $this->database->executeUpdate("UPDATE shop SET name = ? WHERE ID
= ?", [$name, $id]);
}
public function deleteShop($id) {
      $this->database->executeDelete("DELETE FROM shop WHERE ID = ?",
[$id]);
}
```

3.17. User.php

<?php

```
namespace App\Models;
use App\Config\DATABASE;
class User {
private $database;
$this->database = $database;
public function getUsers($id) {
          return $this->database->executeQueryAll("SELECT ID, username,
role id FROM user WHERE ID != ?", [$id]);
public function getUser($username, $password) {
          return $this->database->executeQueryOneRow("SELECT ID, username,
email, role id FROM user WHERE username = ? AND password=MD5(?)", [$username,
$password]);
 }
public function existsUser($username, $email) {
          return $this->database->executeQueryOneRow("SELECT username,
email, role id FROM user WHERE username = ? OR email = ?", [$username,
$email]);
}
public function createUser($username, $email, $password) {
          $this->database->executeInsert("INSERT INTO user(username, email,
password, role id) VALUES (?, ?, MD5(?), 2)", [$username, $email,
$password]);
}
public function editUserRight($role, $user) {
         $this->database->executeUpdate("UPDATE user SET role id = ? WHERE
ID = ?", [$role, $user]);
}
public function deleteUser($id) {
     $this->database->executeDelete("DELETE FROM user WHERE ID = ?",
[$id]);
   }
}
  3.18. footer.php
       <div class="footer panel">
          <a href="https://www.linkedin.com/in/nikola-nedeljkovic-
8110b5150">© Nikola Nedeljkovic 2020    @ ICT</a>
          <div class="site links">
              <h3>Site links:</h3>
              <u1>
                 <?php
                     if(isset($ SESSION['user'])) {
                        echo "<a
href=\"index.php?page=main\">Shopping list</a>";
```

if ((\$ SESSION['user']->role id == 1) ||

```
($ SESSION['user']->role id == 3)) {
                               echo "<a
href=\"index.php?page=admin\">Admin</a>";
                            if ($ SESSION['user']->role id == 3) {
                               echo "<a
href=\"index.php?page=teacher\">Author</a>";
                               echo "<a
href=\"sitemap.xml\">Sitemap</a>";
                        } else {
                           echo "<a
href=\"index.php?page=login\">Login</a>";
                           echo "<a
href=\"index.php?page=register\">Register</a>";
                </div>
       </div>
    </body>
        <script type="text/javascript" src="assets/js/main.js"></script>
</html>
  3.19. header.php
<!DOCTYPE html>
<html>
    <head>
        <title>Shopedia</title>
        <meta name="viewport" content="width=device-width, initial-</pre>
scale=1.0"/>
        <meta name="author" content="Nikola Nedeljkovic"/>
        <meta name="copyright" content="RarOks 1008 Entertainment @ 2020"/>
       <meta name="robots" content="index,follow"/>
       <meta name="keywords" content="shopping, list, grocery"/>
       <meta name="description" content="Here you can add your own shopping</pre>
list and use it from all devices."/>
        <meta name="abstract" content="Shop with Shopedia."/>
        <link rel="shortcut icon" href="favicon.ico"/>
        <link rel="stylesheet"</pre>
href="https://use.fontawesome.com/releases/v5.8.1/css/all.css"
integrity="sha384-
50oBUHEmvpQ+11W4y57PTFmhCaXp0ML5d60M1M7uH2+nqUivzIebhndOJK28anvf"
crossorigin="anonymous"/>
        <link rel="stylesheet" href="assets/css/style.css"/>
    </head>
    <body>
        <div class="header holder">
            <a href="index.php?page=main">
               <h1>Shopedia</h1>
           </a>
            <?php if(isset($ SESSION["user"])) : ?>
                <a href="api.php?page=logout"
class="login logout button">Sign Out</a>
           <?php else : ?>
```

```
<a href="index.php?page=login"
class="login logout button">Sign In</a>
            <?php endif; ?>
        </div>
           404.php
   3.20.
<div class="fourofour">
    <div class="lost text">
        <h2>You seem to be lost</h2>
        <a href="index.php?page=main">Click here to return to home page</a>
    </div>
    <imq src="assets/img/travolta.gif" alt="Lost"/>
            admin.php
   3.21.
<?php include once "data.php"; ?>
Welcome back <?php echo $ SESSION['user']->username;
?>!
<div class="admin panel">
    <h2>Admin Page</h2>
    <div class="admin item">
        <h3>Add Measure</h3>
        <form onsubmit="return add measure check()" method="POST"</pre>
action="api.php?page=add measure">
            <input type="text" name="add measure" id="add measure"</pre>
Placeholder="Measure"/>
            <button type="submit" name="submit add measure">Add</button>
        </form>
    </div>
    <div class="admin item with more">
        <div class="more admin options">
            <h3>Edit Measure</h3>
            <select id="measure edit select"</pre>
onchange="admin_measure_change()">
                <?php foreach($measure data as $measure): ?>
                    <option value="<?=$measure->ID; ?>"><?=$measure-</pre>
>name;?></option>
                <?php endforeach; ?>
            </select>
        </div>
        <form class="more admin options" onsubmit="return</pre>
edit measure check()" method="POST" action="api.php?page=edit measure">
            <input type="hidden" name="edit measure id"</pre>
id="edit_measure_id"/>
            <input type="text" name="edit measure" id="edit measure"</pre>
Placeholder="Measure"/>
            <button type="submit" name="submit edit measure">Edit</button>
        </form>
    </div>
    <div class="admin item">
        <h3>Delete Measure</h3>
        <form onsubmit="return delete measure check()" method="POST"</pre>
action="api.php?page=delete measure">
            <select id="measure delete select" name="measure delete select">
                <?php foreach($measure data as $measure): ?>
```

```
<option value="<?=$measure->ID; ?>"><?=$measure-</pre>
>name;?></option>
                <?php endforeach; ?>
            </select>
            <button type="submit"</pre>
name="submit delete measure">Delete</button>
        </form>
    </div>
    <div class="admin item">
        <h3>Delete User</h3>
        <form method="POST" action="api.php?page=delete user">
            <select id="user delete select" name="user delete select">
                <?php foreach($user data as $user): ?>
                    <option value="<?=$user->ID; ?>"><?=$user-</pre>
>username;?></option>
                <?php endforeach; ?>
            </select>
            <button type="submit" name="submit delete user">Delete/button>
        </form>
    <div class="admin item with more">
        <div class="more admin options">
            <h3>Extend or demote user right</h3>
            <select id="user change select" onchange="admin user change()">
                <?php foreach($user data as $user): ?>
                    <option value="<?=$user->ID; ?>" data-id="<?=$user-</pre>
>role id;?>"><?=$user->username;?></option>
                <?php endforeach; ?>
            </select>
        </div>
        <form class="more admin options" onsubmit="return edit user check()"</pre>
method="POST" action="api.php?page=edit user">
            <input type="hidden" name="edit user right id"</pre>
id="edit user right id"/>
            <select id="user right select" name="user right select">
                <?php foreach($role data as $role): ?>
                    <option value="<?=$role->ID; ?>"><?=$role-</pre>
>role; ?></option>
                <?php endforeach; ?>
            </select>
            <button type="submit" name="submit edit user id">Edit/button>
        </div>
    </div>
</div>
   3.22.
            login.php
<?php</pre>
    if(isset($ SESSION['l error'])) {
        echo $ SESSION['l error'];
    } else {
        echo "Please enter your username and password.";
    } ?>
<div class="login panel">
    <form onsubmit="return login check()" method="POST"</pre>
action="api.php?page=login">
```

```
<input type="text" name="username" id="username"</pre>
placeholder="Username"/>
      <input type="password" name="password" id="password"</pre>
placeholder="Password"/>
      <button type="submit" name="signin" id="signin">SIGN IN/button>
   <a href="index.php?page=register">Don't have an account? Click here to
register...</a>
</div>
         main.php
  3.23.
<?php include once "data.php"; ?>
Welcome back <?php echo $ SESSION['user']->username;
?>!
<div class="main panel">
   <h2>Your personal shopping list</h2>
   \langle t.r \rangle
         Number
         Name
         Quantity
         Measure
         Shop
         Edit
         Delete
      <?php $item num = 1; foreach($item data as $item): ?>
      "><?=$item num;?>
         "><?=$item->name;?>
         "><?=$item->quantity;?>
         " data-id="<?=$item-
>measure id; ?>"><?=$item->measure; ?>
         " data-id="<?=$item-
>shop id; ?>"><?=$item->shop; ?>
         <button onclick="item edit click(<?=$item num;?>, <?=$item-
>item id;?>)"><span class="far fa-edit"></span></button>
         <a href="api.php?page=item delete&id=<?=$item-
>item id;?>"><span class="far fa-trash-alt"></span></a>
      <?php $item num++; endforeach; ?>
   </div>
<div class="main panel not first">
   <h2>Add or edit list item</h2>
   Number
         Name
         Quantity
         Measure
         Shop
         Save
         Discard
```

```
<form onsubmit="return add edit item check()" method="POST"</pre>
action="api.php?page=item edit">
              <input type="hidden" name="item add edit id"</pre>
id="item add edit id" value=""/>
              <td id="item add edit number" data-
id="<?=$item num; ?>"><?=$item num; ?>
              <input type="text" name="item add edit name"
id="item add edit name" placeholder="Name"/>
              <-d><-input type="number" name="item add edit quantity"</pre>
<select name="item add edit measure"</pre>
id="item add edit measure">
                 <?php foreach($measure data as $measure): ?>
                     <option value="<?=$measure->ID; ?>"><?=$measure-</pre>
>name; ?></option>
                 <?php endforeach; ?>
              </select>
              <select name="item add edit shop"
id="item add edit shop">
                 <?php foreach($shop data as $shops): ?>
                     <option value="<?=$shops->ID;?>"><?=$shops-</pre>
>name;?></option>
                 <?php endforeach; ?>
              </select>
              <button type="submit" name="item add edit submit"><span
class="fas fa-save"></span></button>
          <button onclick="item edit discard()"><span class="fas fa-
times-circle"></span></button>
       </div>
<div class="main panel not first your shops">
   <h2>Your personal shops</h2>
   Number
          Name
          Edit
          Delete
       <?php $shop num = 1; foreach($shop data as $shop): ?>
       "><?=$shop num; ?>
          "><?=$shop->name;?>
          <button onclick="shop edit click(<?=$shop num;?>, <?=$shop-
>ID; ?>) "><span class="far fa-edit"></span></button>
          <a href="api.php?page=shop delete&id=<?=$shop->ID;?>"><span
class="far fa-trash-alt"></span></a>
       <?php $shop num++; endforeach; ?>
   </div>
<div class="main panel not first your shops">
   <h2>Add or edit a shop</h2>
   \langle t.r \rangle
```

```
Number
           Name
           Save
           Discard
       <form onsubmit="return add edit shop check()" method="POST"</pre>
action="api.php?page=shop edit">
               <input type="hidden" name="shop add edit id"</pre>
id="shop add edit id" value=""/>
               <td id="shop add edit number" data-
id="<?=$shop num; ?>"><?=$shop num; ?>
               <input type="text" name="shop add edit name"
id="shop add edit name" placeholder="Name"/>
               <button type="submit" name="shop add edit submit"><span</pre>
class="fas fa-save"></span></button>
           </form>
           <button onclick="shop edit discard()"><span class="fas fa-
times-circle"></span></button>
    </div>
  3.24. register.php
<?php</pre>
    if(isset($ SESSION['r error'])) {
       echo $ SESSION['r error'];
    } else {
       echo "Please provide the information to create an account.";
<div class="register panel">
    <form onsubmit="return register check()" method="POST"</pre>
action="api.php?page=register">
       <input type="text" name="username" id="username"</pre>
placeholder="Username"/>
       <input type="password" name="password" id="password"</pre>
placeholder="Password"/>
       <input type="email" name="email" id="email" placeholder="Email"/>
       <button type="submit" name="register" id="register">REGISTER</button>
    <a href="index.php?page=login">Already have an account? Click here to
sign in...</a>
</div>
           teacher.php
   3.25.
<div class="teacher panel">
    <div class="teacher text">
       <h2>Author</h2>
       <a href="https://www.linkedin.com/in/nikola-nedeljkovic-</pre>
8110b5150">Nikola Nedeljkovic 2/17</a>
       <div><a href="assets/documentation/documentation.pdf"><span</pre>
class="far fa-file-pdf"></span></a></div>
    <imq src="assets/img/author.jpg" alt="Author"/>
</div>
```

3.26. style.css

```
@font-face {
  font-family: HelveticaNeue;
  src: url(../fonts/HelveticaNeue.ttf);
}
* {
   margin: 0px;
   padding: 0px;
   box-sizing: border-box;
   font-family: HelveticaNeue;
}
html {
   background: url('../img/food background.jpg') no-repeat center center
fixed;
}
h1 {
   width: 100px;
   height: 50px;
   background: url('../img/logo.png') top left no-repeat;
   text-indent: -9999px;
   background-size: cover;
   color: #fff;
   background-color: #263238;
}
.red border {
   border: 1px solid #f31413 !important;
   border-radius: 3px;
/*Header Stranica*/
.header holder {
    width: 100%;
   background-color: #263238;
   display: flex;
    justify-content: space-between;
   align-items: center
}
.header holder a {
   color: #fff;
   text-decoration: none;
.header holder .login logout button {
   font-size: 18px;
   padding: 5px 15px;
.header holder .login logout button:hover {
   background-color: rgba(0,0,0,0.1);
    color: #23527c;
@media screen and (max-width: 200px) {
    .header holder {
       flex-direction: column;
    .header holder .login logout button {
       margin-top: 5px;
       margin-bottom: 5px;
```

```
}
}
/*404 i Teacher Stranice*/
.fourofour, .teacher panel {
   border-radius: 5px;
   width: 90%;
   margin-left: 5%;
   background-color: rgba(255, 255, 255, 0.4);
   display: flex;
    justify-content: space-around;
   align-items: center;
.fourofour .lost_text, .teacher_panel .teacher_text {
   text-align: center;
.fourofour .lost text h2, .teacher panel .teacher text h2 {
   font-size: 30px;
}
.fourofour .lost text a, .teacher panel .teacher text a {
   color: #000;
   text-decoration: none;
}
.fourofour .lost text a:hover, .teacher panel .teacher text a:hover {
   text-decoration: underline;
.fourofour img, .teacher panel img {
   margin-top: 30px;
   width: 100%;
   max-width: 260px;
}
.teacher panel img {
   max-width: 300px;
   margin-bottom: 10px;
   border-radius: 3px;
}
.teacher panel .teacher text div {
   margin-top: 15px;
}
.teacher panel .teacher text div a span {
   font-size: 40px;
.teacher panel .teacher text div a span:hover {
   color: #999;
}
@media screen and (max-width: 700px) {
    .fourofour, .teacher panel {
        flex-direction: column;
    .fourofour .lost text, .teacher panel .teacher text {
       margin-top: 30px;
    .teacher panel img {
       margin-bottom: 0;
    }
}
```

```
/* Login i Register Stranice */
#login error, #register_error {
    width: 90%;
   margin-left: 5%;
   color: #a94442;
   background-color: #f2dede;
   padding: 15px;
   margin-bottom: 20px;
   border: 1px solid transparent;
   border-color: #ebccd1;
   border-radius: 4px;
   margin-bottom: 10px;
.login panel, .register panel {
   border-radius: 5px;
   width: 90%;
   margin-left: 5%;
   background-color: rgba(255, 255, 255, 0.4);
   display: flex;
    justify-content: space-around;
    align-items: center;
   flex-direction: column;
}
.login panel form, .register_panel form {
    width: 100%;
   display: flex;
   justify-content: space-around;
   align-items: center;
   flex-direction: column;
   margin-top: 50px;
   margin-bottom: 50px;
}
.login panel input, .register panel input {
   margin-top: 20px;
   width: 80%;
   padding: 10px;
   border: none;
   border-bottom: 1px solid #9e9e9e;
   background-color: transparent;
   font-size: 18px;
.login panel input:focus, .register panel input:focus {
    outline: none;
   border-bottom: 2px solid #9e9e9e;
.login panel button, .register panel button {
   margin-top: 20px;
   padding: 10px 25px;
   cursor: pointer;
    color: #fff;
   background-color: #26a69a;
    font-size: 18px;
   margin-bottom: 10px;
   box-shadow: 0 2px 2px 0 rgba(0,0,0,0.14), 0 1px 5px 0 rgba(0,0,0,0.12), 0
3px 1px -2px rgba(0,0,0,0.2);
   border: none;
   border-radius: 3px;
```

```
.login panel button: focus, .register panel button: focus {
   background-color: #1d7d74;
   border-color: #122b40;
}
.login_panel button:hover, .register panel button:hover {
   box-shadow: 0 3px 3px 0 rgba(0,0,0,0.14), 0 1px 7px 0 rgba(0,0,0,0.12), 0
3px 1px -1px rgba(0,0,0,0.2);
   background-color: #2bbbad;
.login panel a, .register panel a {
    font-size: 17px;
   text-decoration: none;
   color: #000;
   margin-bottom: 20px;
   text-align: center;
}
.login panel a:hover, .register panel a:hover {
    text-decoration: underline;
/* Main Stranica */
#welcome sign {
   width: 90%;
   margin-left: 5%;
   color: #31708f;
   background-color: #d9edf7;
   padding: 15px;
   margin-bottom: 20px;
   border: 1px solid transparent;
   border-color: #bce8f1;
   border-radius: 4px;
   margin-bottom: 10px;
}
.main panel {
  border-radius: 5px;
   width: 90%;
   margin-left: 5%;
   background-color: rgba(255, 255, 255, 0.4);
   display: flex;
   justify-content: space-around;
   align-items: center;
   flex-direction: column;
}
.main panel h2 {
   margin-top: 10px;
   margin-bottom: 10px;
.main panel table {
   width: 100%;
   table-layout: fixed;
}
.main_panel table button {
  border: none;
   background-color: transparent;
   color: #fff;
   cursor: pointer;
```

```
}
.main panel table input, .main panel table select {
   width: 100%;
   border: none;
   background-color: transparent;
   font-size: 16px;
   color: #fff;
}
.main panel table a {
  color: #fff;
}
.main panel table select option {
  color: #000;
}
.main panel table input:focus, .main panel table select:focus {
   outline: none;
}
.main panel table input::placeholder {
   color: #fff;
   opacity: 0.7;
}
.main panel.not first {
  margin-top: 50px;
.main panel table tr:nth-child(even) {
  background-color: rgba(0, 0, 0, 0.3);
   color: #fff;
.main panel table tr:nth-child(odd) {
   background-color: rgba(0, 0, 0, 0.2);
   color: #fff;
}
.main panel table tr:first-child {
  background-color: transparent;
   color: #000;
}
.main panel table tr:hover {
  background-color: rgba(0, 0, 0, 0.5);
}
.main panel table tr:first-child:hover {
  background-color: transparent;
.main panel table tr th {
   border-bottom: 1px solid #000;
   border-right: 1px solid #000;
   box-shadow: 2px 2px 3px #888;
}
.main panel table tr td {
  text-align: center;
.main panel table tr th, .main panel table tr td {
  padding: 5px;
   text-overflow: ellipsis;
   overflow: hidden;
.main panel table tr th:nth-child(1), .main panel table tr th:nth-child(3),
.main panel table tr th:nth-child(4),
```

```
.main panel table tr th:nth-child(6), .main panel table tr th:nth-child(7),
.main panel table tr td:nth-child(1),
.main panel table tr td:nth-child(3), .main panel table tr td:nth-child(4),
.main panel table tr td:nth-child(6),
.main panel table tr td:nth-child(7) {
   width: 10%;
.main panel table tr th:nth-child(2), .main panel table tr td:nth-child(2) {
   width: 30%;
}
.main panel table tr th:nth-child(5), .main panel table tr td:nth-child(5) {
  width: 20%;
}
.your shops table tr th:nth-child(1), .your shops table tr th:nth-child(3),
.your shops table tr th:nth-child(4),
.your_shops table tr td:nth-child(1), .your_shops table tr td:nth-child(3),
.your shops table tr td:nth-child(4) {
   width: 10%;
}
.your shops table tr th:nth-child(2), .your shops table tr td:nth-child(2) {
@media screen and (max-width: 500px) {
    .main panel table tr {
       display: table;
       table-layout: fixed;
       width: 100%;
       overflow: hidden;
    .main panel table tr td {
       display: table-row;
    }
    .main panel table tr th {
       display: none;
    }
}
/*Admin Stranica*/
.admin panel {
   border-radius: 5px;
   width: 90%;
   margin-left: 5%;
   background-color: rgba(255, 255, 255, 0.4);
   display: flex;
    justify-content: space-around;
   align-items: center;
   flex-direction: column;
.admin panel .admin item {
   margin-top: 70px;
   padding: 5px;
   width: 100%;
   display: flex;
    justify-content: space-between;
   align-items: center;
   text-align: center;
   box-shadow: 0px 2px 3px #888;
```

```
padding-bottom: 15px;
.admin panel .admin item form {
   display: flex;
   justify-content: space-between;
   align-items: center;
   width: 80%;
}
.admin panel .admin item input, .admin panel .admin item select {
   width: 80%;
   padding: 10px;
   border: none;
   border-bottom: 1px solid #9e9e9e;
   background-color: transparent;
   font-size: 18px;
.admin panel .admin item form select {
   margin-bottom: 5px;
}
.admin panel .admin item input:focus, .admin panel .admin item select:focus {
   outline: none;
   border-bottom: 2px solid #9e9e9e;
}
.admin panel .admin item button {
   padding: 10px 25px;
   cursor: pointer;
   color: #fff;
   background-color: #26a69a;
   font-size: 18px;
   box-shadow: 0 2px 2px 0 rgba(0,0,0,0.14), 0 1px 5px 0 rgba(0,0,0,0.12), 0
3px 1px -2px rgba(0,0,0,0.2);
   border: none;
   border-radius: 3px;
}
.admin panel .admin item button:focus {
   background-color: #1d7d74;
   border-color: #122b40;
}
.admin panel .admin item button:hover {
  box-shadow: 0 3px 3px 0 rgba(0,0,0,0.14), 0 1px 7px 0 rgba(0,0,0,0.12), 0
3px 1px -1px rgba(0,0,0,0.2);
   background-color: #2bbbad;
}
.admin panel .admin item.with more {
   flex-direction: column;
.admin panel .admin item .more admin options {
   margin-top: 10px;
   width: 100%;
   display: flex;
   justify-content: space-between;
   align-items: center;
   text-align: center;
@media screen and (max-width: 300px) {
    .admin panel, .admin item, .admin panel .admin item .more admin options,
.admin panel .admin item form {
```

```
flex-direction: column;
    .admin panel, .admin item input {
       width: 90%;
       margin-top: 5px;
       margin-bottom: 5px;
}
/*Footer Stranica*/
.footer panel {
   width: 100%;
.footer panel p {
   width: 100%;
   text-align: center;
   background-color: rgba(255, 255, 255, 0.6);
   font-size: 18px;
   text-align: center;
   padding: 5px;
   margin-top: 40px;
}
.footer panel p a {
   text-decoration: none;
   color: #000;
   font-weight: bold;
.footer panel p a:hover {
   text-decoration: underline;
}
.footer panel .site links {
   margin-top: 30px;
   width: 100%;
   background-color: rgba(255, 255, 255, 0.4);
   display: flex;
   flex-direction: column;
   align-items: center;
.footer panel .site links h3 {
  margin-top: 10px;
   margin-bottom: 20px;
.footer panel .site links ul {
   list-style-type: none;
}
.footer panel .site links ul li {
  margin-bottom: 7px;
.footer panel .site links ul li a {
   text-decoration: none;
   color: #000;
   font-weight: bold;
.footer panel .site links ul li a:hover {
   text-decoration: underline;
}
```

3.27. main.js

```
function login check() {
    var username = document.getElementById("username").value,
        password = document.getElementById("password").value;
    if (username == "" || password == "") {
       document.getElementById("login error").innerHTML = "Username and
password can not be empty";
       return false;
    document.getElementById("login error").innerHTML = "";
    return true;
}
function register check() {
    var username = document.getElementById("username").value,
       password = document.getElementById("password").value,
       email = document.getElementById("email").value,
        email pattern = /^[a-zA-Z0-9.!#$%&'*+/=?^ `{|}~-]+@[a-zA-Z0-9-
]+(?:\.[a-zA-Z0-9-]+)*$/;
    if (username == "" || password == "" || email == "") {
       document.getElementById("register error").innerHTML = "You must not
leave empty fields";
       return false;
    }
    if (!email pattern.test(email)) {
       document.getElementById("register error").innerHTML = "Email not
valid";
       return;
   document.getElementById("register error").innerHTML = "";
    return true;
}
function item edit click(number, item id) {
    var num field = document.getElementById("itemnum" + number),
        name field = document.getElementById("itemname" + number),
        quantity field = document.getElementById("itemquantity" + number),
       measure field = document.getElementById("itemmeasure" + number),
        shop field = document.getElementById("itemshop" + number),
        item add edit number field =
document.getElementById("item add edit number"),
        item add edit name field =
document.getElementById("item add edit name"),
        item add edit quantity field =
document.getElementById("item add edit quantity"),
        item add edit measure field =
document.getElementById("item add edit measure"),
        item add edit shop field =
document.getElementById("item add edit shop"),
        item add edit id field = document.getElementById("item add edit id");
        item add edit number field.innerHTML = num field.innerHTML;
        item add edit name field.value = name field.innerHTML;
        item add edit quantity field.value = quantity field.innerHTML;
        item add edit measure field.value = measure field.getAttribute('data-
id');
```

```
item add edit shop field.value = shop field.getAttribute('data-id');
        item add edit id field.value = item id;
}
function item edit discard() {
    var item add edit id field = document.getElementById("item add edit id"),
        item add edit number field =
document.getElementById("item add edit number"),
        item add edit name field =
document.getElementById("item add edit name"),
        item add edit quantity field =
document.getElementById("item add edit quantity"),
        item add edit measure field =
document.getElementById("item add edit measure"),
        item add edit shop field =
document.getElementById("item add edit shop");
    item add edit id field.value = "";
    item add edit number field.innerHTML =
item add edit number field.getAttribute('data-id');
    item add edit name field.value = "";
    item add edit quantity field.value = "";
    item add edit measure field.selectedIndex = 0;
    item add edit shop field.selectedIndex = 0;
function shop edit click(number, shop id) {
    var num field = document.getElementById("shopnum" + number),
        name field = document.getElementById("shopname" + number),
        shop add edit number field =
document.getElementById("shop add edit number"),
        shop add edit name field =
document.getElementById("shop add edit name"),
        shop add edit id field = document.getElementById("shop add edit id");
        shop add edit number field.innerHTML = num field.innerHTML;
        shop add edit name field.value = name field.innerHTML;
        shop add edit id field.value = shop id;
}
function shop edit discard() {
    var shop add edit number field =
document.getElementById("shop add edit number"),
    shop add edit name field = document.getElementById("shop add edit name"),
    shop add edit id field = document.getElementById("shop add edit id");
    shop add edit id field.value = "";
    shop add edit number field.innerHTML =
shop add edit number field.getAttribute("data-id");
    shop add edit name field.value = "";
function add edit shop check() {
    var name = document.getElementById("shop add edit name");
    if (name.value == "") {
       name.classList.add("red border");
        return false;
```

```
}
    name.classList.remove("red border");
    return true;
}
function add edit item check() {
    var name = document.getElementById("item add edit name"),
        quantity = document.getElementById("item add edit quantity");
    if (name.value == "") {
        name.classList.add("red border");
        return false;
    }
    name.classList.remove("red border");
    if (quantity.value == "") {
        quantity.classList.add("red border");
        return false;
    quantity.classList.remove("red border");
    return true;
}
function add measure check() {
    var name = document.getElementById("add measure");
    if (name.value == "") {
       name.classList.add("red border");
       return false;
    name.classList.remove("red border");
    return true;
}
function admin measure change() {
    var measures = document.getElementById("measure edit select"),
        id field = document.getElementById("edit measure id"),
        name field = document.getElementById("edit measure");
    id field.value = measures.value;
    name field.value = measures.options[measures.selectedIndex].text;
}
function edit measure check() {
    var measures = document.getElementById("measure edit select"),
        id_field = document.getElementById("edit measure id"),
        name field = document.getElementById("edit measure");
    if (id field.value == "") {
        measures.classList.add("red border");
        return false;
    }
    measures.classList.remove("red border");
    if (name field.value == "") {
        name field.classList.add("red border");
        return false;
    name field.classList.remove("red border");
    return true;
}
function admin user change() {
```

```
var user = document.getElementById("user change select"),
        id field = document.getElementById("edit user right id"),
        right = document.getElementById("user right select");
    id field.value = user.value;
    right.value = user.options[user.selectedIndex].getAttribute('data-id');
}
function edit user check() {
    var right id = document.getElementById("edit user right id"),
        right = document.getElementById("user right select"),
       user = document.getElementById("user change select");
    if (right id.value == "") {
       user.classList.add("red border");
        return false;
    user.classList.remove("red border");
    if (right.value == "") {
        right.classList.add("red border");
        return false;
    right.classList.remove("red border");
   return true;
}
```

4. HIJERARHIJSKI PREGLED

