


MySQL Setup

```
create database jlcompdb;  
use jlcompdb;
```

```
create table employees(  
  empld char(6),  
  ename char(15),  
  email char(15),  
  phone char(10),  
  role char(15),  
  username char(15),  
  password char(15),  
  status char(15)  
);
```

```
create table requests(  
  reqld int,  
  empld char(6),  
  description char(35),  
  priority char(10),  
  status char(15)  
);
```

```
insert into employees values('E-99','Sri','sri@jlc','9999','Manager','srinivas','srinivas','Working');
```

Struts1 Tag Library Reference

Bean Tag Library Tags		
1	<bean:parameter>	id,name,value,multiple
2	<bean:header>	id,name,value,multiple
3	<bean:cookie>	id,name,value,multiple
4	<bean:include>	forward,href,page
5	<bean:page>	id,property
6	<bean:size>	id,name,property,scope
7	<bean:define>	id,name,property,scope,toScope,type,value
8	<bean:write>	name,property,scope
9	<bean:message>	key,arg0,arg1,arg2,arg3,arg4

Logic Tag Library Tags		
1	<logic:empty>	name,property,scope
2	<logic:notEmpty>	name,property,scope
3	<logic:present>	parameter,cookie,header, name,property,scope,role,user
4	<logic:notPresent>	parameter,cookie,header, name,property,scope,role,user
5	<logic:equal>	parameter,cookie,header, name,property,scope,value
6	<logic:notEqual>	parameter,cookie,header, name,property,scope,value
7	<logic:lessThan>	parameter,cookie,header, name,property,scope,value
8	<logic:lessEqual>	parameter,cookie,header, name,property,scope,value
9	<logic:greaterThan>	parameter,cookie,header, name,property,scope,value
10	<logic:greaterEqual>	parameter,cookie,header, name,property,scope,value
11	<logic:match>	parameter,cookie,header, name,property,scope,value,location
12	<logic:notMatch>	parameter,cookie,header, name,property,scope,value,location
13	<logic:messagesPresent>	name,property,message
14	<logic: messagesNotPresent >	name,property,message
15	<logic:forward>	name
16	<logic:redirect>	forward,page,href
17	<logic:iterate>	id,name,property,scope,type,offset,length

HTML Tag Library Tags		Common Attributes of HTML Tags
1	<html:button>	property
2	<html:cancel>	value
3	<html:checkbox>	onblur
4	<html:errors>	onclick
5	<html:file>	onfocus
6	<html:form>	onkeypress
7	<html:hidden>	onmousedown
8	<html:image>	onmouseout
9	<html:img>	onmouseup
10	<html:javascript>	onsubmit
11	<html:link>	onchange
12	<html:messages>	ondblclick
13	<html:option>	onkeydown
14	<html:options>	onkeyup
15	<html:password>	onmousemove
16	<html:radio>	onmouseover
17	<html:reset>	onreset
18	<html:select>	tabindex
19	<html:submit>	styleClass
20	<html:text>	style
21	<html:textarea>	

Struts Tag Library

1) Bean Tag Library :

To use the tags in Bean Tag Library, you need to do the following.


A)Copy struts-bean.tld into WEB-INF folder.

B)Use the following <taglib> in any jsp where you want to use tags of Bean Tag Library

```
<%@ taglib uri="/WEB-INF/struts-bean.tld" prefix="bean"%>
```

List of tags in Bean Tag Library

- 1)<bean:parameter>
3)<bean:header>
5)<bean:page>
7)<bean:include>
9)<bean:message>
- 2)<bean:cookie>
4)<bean:size>
6)<bean:define>
8)<bean:write>



1)<bean:parameter> : parameter tag gets the value of Specified request parameter and stores that in the jsp scripting variable.

attributes : id , name , value, multiple

usage:

- 1)<bean:parameter id="em" name="email"/>
- 2)<bean:parameter id="em" name="email" value="sri@jlc"/>
- 3)<bean:parameter id="em" name="email" multiple="true"/>

2)<bean:cookie> : cookie tag gets the value of Specified request cookie and stores that in the jsp scripting variable.

attributes : id , name , value, multiple

usage:

- 1)<bean:cookie id="em" name="email"/>
- 2)<bean:cookie id="em" name="email" value="sri@jlc"/>
- 3)<bean:cookie id="em" name="email" multiple="true"/>

3)<bean:header> : header tag gets the value of Specified request header and stores that in the jsp scripting variable.

attributes : id , name , value, multiple

usage:

- 1)<bean:header id="ho" name="host"/>
- 2)<bean:header id="re" name="referer" value="sri@jlc"/>
- 3)<bean:header id="al" name="accept-language" multiple="true"/>

4)<bean:size> : size tag gets the size of Specified collection or map or array and stores that in the jsp scripting variable.

attributes : id , name , property, scope, collection


usage:

in Action

```
req.setAttribute("AL",al);
ses.setAttribute("STO",sto);
StudentTO-> sid,sname,list of emails
```

In jsp

- 1)<bean:size id="x" name="AL" scope="request"/>



```
2)<bean:size id="y" name="STO" property="emails" scope="session" />
<%
```

```
ArrayList al=(ArrayList) request.getAttribute("AL");
```

```
%>
```

```
3)<bean:size collection="<%= al %>" />
```

5)<bean:page> : page tag gets the reference to JSP implicit objects and stores that in the jsp scripting variable.

attributes : id , property

usage:

```
1)<bean:page id="req" proeprty="request"/>
```

```
2)<bean:page id="S" property="session" />
```

```
3)<bean:size id="x" name="AL" scope="S"/>
```

6)<bean:define> : define tag gets the reference to Attribute from specified scope and stores that in the jsp scripting variable.

attributes : id , name,property,scope,toScope,type,value

usage:

In Action

```
req.setAttribute("MSG",msg);
```

```
ses.setAttribute("STO",sto);
```

```
req.setAttribute("AL",al);
```

StudentTO-> sid,sname,list of emails

In JSP

```
1)<bean:define id="msg" name="MSG" scope="request" toScope="session" />
```


```
2)<bean:define id="msg" name="MSG" scope="request" toScope="request" type="java.lang.String"
value="Hello guys"/>
```

```
3)<bean:define      id="sto"      name="STO"      scope="session"      toScope="session"
type="com.jlc.StudentTO"/>
```

```
4)<bean:define      id="al"      name="AL"      scope="request"      toScope="session"
type="java.util.ArrayList"/>
```

```
5)<bean:define id="msg" name="MSG"/>
```

```
6)<bean:define id="sn" name="STO" property="sname" scope="session" toScope="session" />
```

7) **<bean:include>** : include tag includes the specified jsp or html .

attributes : page,forward,href

usage :

1) **<jsp:include page="header.jsp"/>**

2) **<bean:include page="header.jsp"/>**

3) **<bean:include forward="header"/>**

<forward name="header" path="/header.jsp"/>

4) **<bean:include href="http://www.techunt.com/header.jsp"/>**

5) **<bean:include forward="header"/>**

<forward name="header" path="http://www.techunt.com/header.jsp"/>

8) **<bean:write>** : write tag is used to write data to JSP output stream.

Attributes : name,property,scope

usage :

In Action

req.setAttribute("MSG",msg);

ses.setAttribute("STO",sto);

In JSP

1) **<bean:write name="MSG" scope="request"/>**

2) **<bean:write name="STO" scope="session"/>**

3) **<bean:write name="STO" property="sid" scope="session"/>**

4) **<bean:write name="STO" property="sname"/>**

9) **<bean:message>** : message tag is used to get value of Specified key from message bundle and to write value to JSP output stream.

attributes : key,arg0,arg1,arg2,arg3,arg4

usage:

in properties file

x.y=Hello guys

a.b={0} is ok.


a.c={0} and {1} are OK.

in jsp

<bean:message key="x.y"/>

<bean:message key="a.b" arg0="Hello"/>

<bean:message key="a.c" arg0="Hello" arg1="Hai"/>



2) Logic Tag Library :

To use the tags in Logic Tag Library, you need to do the following.

A) copy struts-logic.tld into WEB-INF folder.

B) use the following <taglib> in any jsp where you want to use tags of Bean Tag Library

<%@ taglib uri="/WEB-INF/struts-logic.tld" prefix="logic"%>

List of tags in Logic Tag Library

- | | |
|-----------------------------|--------------------------------|
| 1) <logic:empty> | 2) <logic:notEmpty> |
| 3) <logic:present> | 4) <logic:notPresent> |
| 5) <logic:equal> | 6) <logic:notEqual> |
| 7) <logic:greaterThan> | 8) <logic:greaterEqual> |
| 9) <logic:lessThan> | 10) <logic:lessEqual> |
| 11) <logic:match> | 12) <logic:notMatch> |
| 13) <logic:messagesPresent> | 14) <logic:messagesNotPresent> |
| 15) <logic:iterate> | 16) <logic:redirect> |
| 17) <logic:forward> | |

<logic:empty> and <logic:notEmpty> :

- empty tag is used to check whether given object is empty.
- notEmpty tag is used to check whether given object is not empty.

attributes : name, property, scope.

usage:

```
1) <logic:empty name="MSG">
<h1> MSG attribute is empty</h1>
</logic:empty>
<logic:notEmpty name="MSG">
<h1> MSG attribute is not empty</h1>
</logic:notEmpty>
```

```
2) <logic:empty name="STO" scope="session">
```

Student Not Found.


```
</logic:empty>
```

```
<logic:notEmpty name="STO" scope="session">
```

```
<bean:write name="STO" property="sid" scope="session"/>
```

```
<bean:write name="STO" property="sname" scope="session"/>
```

```
</logic:notEmpty>
```



```
3)<logic:empty name="STO" property="email" scope="session">
```

Your Email id not found.

```
</logic:empty>
```

```
<logic:notEmpty name="STO" property="email" scope="session">
```

Your email id : <bean:write name="STO" property="email" scope="session"/>

```
</logic:notEmpty>
```

<logic:present> and <logic:notPresent> :

- present tag is used to check whether given object present in the given scope.
- notPresent tag is used to check whether given object not present in the given scope.

attributes: cookie,header,parameter,name,property,scope,role,user.

usage:

```
1)<logic:present name="MSG" scope="request">
```

..

```
</logic:present>
```

```
<logic:notPresent name="MSG" scope="request">
```

...

```
</logic:notPresent>
```

```
2)<logic:present name="STO" proeprty="email" scope="request">
```

..

```
</logic:present>
```

```
<logic:notPresent name="STO" proeprty="email" >
```

...

```
</logic:notPresent>
```

```
3)<logic:present cookie="email">
```

..

```
</logic:present>
```

```
<logic:notPresent cookie="email">
```

...

```
</logic:notPresent>
```

```
4)<logic:present parameter="email">
```


..

```
</logic:present>
```

```
<logic:notPresent parameter="email">
```

...

```
</logic:notPresent>
```

```
6)<logic:present header="host">
```

```
..
```

```
</logic:present>
```

```
<logic:notPresent header="host">
```

```
...
```

```
</logic:notPresent>
```

7) View Student INFO

Update Student INFO

Link2

```
<logic:present role="manager">
```

Add Student

```
</logic:present>
```

```
<logic:present role="admin" >
```

delete Student

```
</logic:present>
```

```
<logic:present role="admin" user="abc">
```

Add Student

```
</logic:present>
```

<logic:equal> and <logic:notEqual> :

- equal tag is used to check whether given object is equals to given value.
- notEqual tag is used to check whether given object is not equals to given value.

attributes: cookie,header,parameter,name,property,scope,value

1)<logic:equal cookie="email" value="sri@jlc.com">

```
...
```

```
</logic:equal/>
```

```
<logic:notEqual cookie="email" value="sri@jlc.com">
```

```
...
```

```
</logic:notEqual/>
```

2)<logic:equal parameter="email" value="sri@jlc.com">


```
...
```

```
</logic:equal/>
```

```
<logic:notEqual parameter="email" value="sri@jlc.com">
```

```
...
```

```
</logic:notEqual/>
```



```
3)<logic:equal header="host" value="http://www.techunt.com/hello.jsp">
```

```
...
```

```
</logic:equal/>
```

```
<logic:notEqual header="host" value="http://www.techunt.com/hello.jsp">
```

```
...
```

```
</logic:notEqual/>
```

```
4)<logic:equal name="PH" scope="request" value="99999">
```

```
</logic:equal/>
```

```
<logic:notEqual name="PH" scope="request" value="99999">
```

```
</logic:notEqual/>
```

```
5)<logic:equal name="STO" property="phone" scope="session" value="99999">
```

```
</logic:equal/>
```

```
<logic:notEqual name="STO" property="phone" scope="session">
```

```
</logic:notEqual/>
```

<logic:greaterThan>, <logic:lessThan> <logic:greaterEqual> and <logic:lessEqual>

same as <logic:equal>

attributes: cookie,header,parameter,name,property,scope,value

usage:

same as <logic:equal>

<logic:match> and <logic:notMatch>

- match tag is used to check where given object is starts with or ends with or contains the given value.

attributes: cookie,header,parameter,name,property,scope,value,location

usage:

```
1)<logic:match cookie="email" value="sri" >
```

```
...
```

```
</logic:match/>
```

```
<logic:notMatch cookie="email" value="sri">
```

```
...
```

```
</logic:notMatch/>
```

```
2)<logic:match name="SN" scope="request" value="sri">
```


```
</logic:match/>
```

```
3)<logic:match name="SN" scope="request" value="sri" location="starts">
```

```
</logic:match/>
```

```
4)<logic:match name="SN" scope="request" value="vas" location="ends">
```

```
</logic:match/>
```

```
5)<logic:match      name="STO"      property="email"      scope="session"      value="jlcindia.com"
location="ends">
</logic:match/>
```

<logic:messagesPresent> and <logic:messagesNotPresent>

- messagesPresent tag is used to check whether ActionErrors object contains any ActionError objects and also to check whether ActionMessages object contains any ActionMessage objects.

attributes: property,message.

Usage:

In Action class

```
ActionErrors errors=new ActionErrors();
errors.add("sid",new ActionError("errors..sid.notfound"));
ActionMessages msgs=new ActionMessages();
msgs.add("sid",new ActionMessage("errors..sid.notfound"));
```

in JSP

```
<logic:messagesPresent>
```

Yes Some Errors Found.

```
</logic:messagesPresent>
```

```
<logic:messagesPresent message="true">
```

Yes Some Messages Found.

```
</logic:messagesPresent>
```

```
<logic:messagesPresent property="sid">
```

Yes Error Found. for sid property

```
</logic:messagesPresent>
```

```
<logic:messagesPresent message="true">
```

Yes Message Found. for sid property

```
</logic:messagesPresent>
```

17)<logic:forward> : forward tag is used to forward the request from one jsp to another jsp.

attributes: name

usage:

```
<logic:forward name="hello"/>
```

```
<forward name="hello" path="/hello.jsp"/>
```




16)<logic:redirect> :redirect tag is used to redirect the request from one application to another application.

attributes : page,forward,href

usage :

- 1)<logic:redirect page="hello.jsp"/>
- 2)<logic:redirect forward="hello"/>
<forward name="hello" path="/hello.jsp" redirect="true"/>
- 3)<logic:redirect href="http://www.techunt.com/hello.jsp"/>
- 4)<logic:redirect forward="hello"/>
<forward name="hello" path="http://www.techunt.com/hello.jsp" redirect="true"/>

15)<logic:iterate> : iterate tag is used access the elements of collection

attributes : id,name,property,scope,type,length,offset

usage:

Using iterate tag ,You can access the following type of data.

- 1)Collection of Strings,Wrappers and Date.
- 2)Collection of Collections
- 3)Collection of User defined class object
- 1)Collection of Strings,Wrappers and Date.

In Action


```
ArrayList al=new ArrayList();  
al.add(new Integer(123));
```

...

```
String str[]={"dd","ss",...};  
req.setAttribute("AL",al);  
ses.setAttribute("STR",str);
```

In jsp

```
<logic:iterate id="x" name="AL" scope="request" >  
<bean:write name="x"/> <br/>  
</logic:iterate>  
<logic:iterate id="x" name="STR" scope="session" >  
<bean:write name="x"/> <br/>  
</logic:iterate>
```

2)Collection of Collections

In Action

```
ArrayList al=new ArrayList();
ArrayList al1=new ArrayList();
al1.add(new Integer(123));
ArrayList al2=new ArrayList();
al2.add(new Integer(123));
al.add(al1);
al.add(al2);
ses.setAttribute("AL",al);
```

In jsp

```
<logic:iterate id="al" name="AL" scope="session" >
<logic:iterate id="x" name="al">
<bean:write name="x"/> <br/>
</logic:iterate>
</logic:iterate>
```

3)Collection of User defined class object

In Action

```
ArrayList al=new ArrayList();
...
al.add(cust1);
al.add(cust2);
ses.setAttribute("AL",al);
```

in JSP

```
<logic:iterate id="cust" name="AL" scope="session">
Cid :<bean:write name="cust" property="cid"/> <br/>
Cname :<bean:write name="cust" property="cname"/> <br/>
...
</logic:iterate >
```



Pagination :

In Action

```
ArrayList al=new ArrayList();
al.add(new Integer(123));
...
req.setAttribute("AL",al);
int offset=0;
int length=100;
ses.setAttribute("OFFSET",offset);
ses.setAttribute("LENGTH",length);
```

```
-----
Inetegr i1=(Integer)ses.getAttribute("OFFSET");
int offset=i1.intValue()+100;
ses.setAttribute("OFFSET",offset);
```

```
<logic:iterate id="x" name="AL" scope="request" offset="{OFFSET}" length="{LENGTH}">
<bean:write name="x"/> <br/>
</logic:iterate>
```

3) Tiles Tag Library :

To use the tags in Tiles Tag Library, you need to do the following.

A) copy struts-tiles.tld into WEB-INF folder.

B) use the following <taglib> in any jsp where you want to use tags of Tiles Tag Library

```
<%@ taglib uri="/WEB-INF/struts-tiles.tld" prefix="tiles"%>
```

List of tags in Tiles Tag Library

1) <tiles:insert>

Usage :

```
<tiles:insert definition="RegDef"/>
<tiles:insert attribute="JLCHeader"/>
```