

Java Stream API

Complete Learning Guide

30+ Coding Questions with Solutions

Interview Preparation • Beginner to Advanced

Complete Reference Guide 2025

What is Stream API?

Definition

Stream API is a feature introduced in Java 8 that allows functional-style operations on sequences of elements. A Stream represents a sequence of elements and supports different kinds of operations to perform computations on those elements.

Source → Intermediate Operations → Terminal Operation

```
// Stream Pipeline Structure
list.stream() // Source
.filter(x -> x>5) // Intermediate
.map(x -> x*2) // Intermediate
.collect(...) // Terminal
```

Key Characteristics

Characteristic	Description
Not a data structure	Doesn't store data; operates on source (collections, arrays, etc.)
Functional in nature	Operations produce results without modifying source
Lazy evaluation	Computations deferred until terminal operation
Consumable	Can be traversed only once
Parallel-friendly	Easy to parallelize with <code>parallelStream()</code>

Simple Example

```
// Without Stream (Imperative style)
List<String> names = Arrays.asList("alice", "bob", "charlie",
    "david");
List<String> result = new ArrayList<>();
for (String name : names) {
    if (name.length() > 3) {
        result.add(name.toUpperCase());
    }
}

// With Stream (Declarative style)
List<String> result = names.stream()
    .filter(name -> name.length() > 3)
    .map(String::toUpperCase)
    .collect(Collectors.toList());
```

 **Key Point:** Stream API enables declarative programming - you focus on WHAT to do, not HOW to do it.

Creating Streams

Different Ways to Create Streams

1. From Collections

```
List<String> list = Arrays.asList("a", "b", "c");  
Stream<String> stream = list.stream(); // Sequential  
Stream<String> parallelStream = list.parallelStream(); // Parallel
```

2. From Arrays

```
String[] array = {"a", "b", "c"};  
Stream<String> stream1 = Arrays.stream(array);  
Stream<String> stream2 = Arrays.stream(array, 1, 3); // "b", "c"
```

3. From Values

```
Stream<Integer> stream = Stream.of(1, 2, 3, 4, 5);  
Stream<String> empty = Stream.empty();
```

4. From Ranges (Primitive Streams)

```
IntStream.range(1, 5) // 1,2,3,4  
IntStream.rangeClosed(1, 5) // 1,2,3,4,5
```

5. From Files

```
Files.lines(Paths.get("file.txt")).forEach(System.out::println);
```

6. Infinite Streams

```
Stream.generate(Math::random).limit(5).forEach(System.out::println);  
Stream.iterate(0, n -> n+2).limit(5).forEach(System.out::println);
```

 **Note:** Always use `limit()` with infinite streams to avoid infinite loops!

Intermediate Operations

Filter Operation

Definition: Selects elements matching a condition.

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5, 6);

// Filter even numbers
List<Integer> evens = numbers.stream()
    .filter(n -> n % 2 == 0)
    .collect(Collectors.toList());
// Result: [2, 4, 6]

// Multiple conditions
List<Integer> result = numbers.stream()
    .filter(n -> n > 2 && n < 6)
    .collect(Collectors.toList());
// Result: [3, 4, 5]
```

Map Operation

Definition: Transforms each element.

```
List<String> names = Arrays.asList("alice", "bob", "charlie");

// To uppercase
List<String> upper = names.stream()
    .map(String::toUpperCase)
    .collect(Collectors.toList());
// Result: ["ALICE", "BOB", "CHARLIE"]

// Get lengths
```

```
List<Integer> lengths = names.stream()
    .map(String::length)
    .collect(Collectors.toList());
// Result: [5, 3, 7]
```

Interview Question Q1: Find Even Numbers

Question 1

Problem: Given a list of integers, find out all the even numbers using Stream functions.

```
List<Integer> list = Arrays.asList(10, 15, 8, 49, 25, 98, 32);

// Solution 1: Using forEach
list.stream()
    .filter(n -> n % 2 == 0)
    .forEach(System.out::println);

// Solution 2: When numbers are given as Array
int[] arr = {10, 15, 8, 49, 25, 98, 32};
Map<Boolean, List<Integer>> result = Arrays.stream(arr)
    .boxed()
    .collect(Collectors.partitioningBy(num -> num % 2 == 0));
System.out.println("Even numbers: " + result.get(true));
```

Output:

```
10
8
98
32
Even numbers: [10, 8, 98, 32]
```

FlatMap Operation

Definition

flatMap() flattens nested structures (one-to-many mapping).

```
// Flatten list of lists
List<List<String>> listOfLists = Arrays.asList(
    Arrays.asList("a", "b"),
    Arrays.asList("c", "d")
);

List<String> flat = listOfLists.stream()
    .flatMap(List::stream)
    .collect(Collectors.toList());
// Result: ["a", "b", "c", "d"]

// Split sentences into words
List<String> sentences = Arrays.asList("Hello World", "Java
Streams");
List<String> words = sentences.stream()
    .flatMap(s -> Arrays.stream(s.split(" ")))
    .collect(Collectors.toList());
// Result: ["Hello", "World", "Java", "Streams"]
```

flatMap vs map

map	flatMap
One-to-one mapping	One-to-many mapping
Returns Stream<R>	Returns Stream<R>
Transforms each element	Flattens nested structures

Interview Question Q2: Numbers Starting with 1

Question 2

Problem: Find all numbers starting with 1.

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 32);

myList.stream()
    .map(s -> s + "") // Convert integer to String
    .filter(s -> s.startsWith("1"))
    .forEach(System.out::println);

// Alternative with array
int[] arr = {10, 15, 8, 49, 25, 98, 32};
List<String> result = Arrays.stream(arr)
    .boxed()
    .map(s -> s + "")
    .filter(s -> s.startsWith("1"))
    .collect(Collectors.toList());
System.out.println("Numbers starting with 1: " + result);
```

Output:

```
10
15
Numbers starting with 1: [10, 15]
```

Distinct & Sorted Operations

Distinct

Definition: Removes duplicates.

```
List<Integer> numbers = Arrays.asList(1, 2, 2, 3, 3, 3, 4);

List<Integer> unique = numbers.stream()
    .distinct()
    .collect(Collectors.toList());
// Result: [1, 2, 3, 4]
```

Sorted

Definition: Sorts elements.

```
List<Integer> numbers = Arrays.asList(5, 2, 8, 1, 9);

// Natural order
List<Integer> sorted = numbers.stream()
    .sorted()
    .collect(Collectors.toList());
// Result: [1, 2, 5, 8, 9]

// Reverse order
List<Integer> reversed = numbers.stream()
    .sorted(Comparator.reverseOrder())
    .collect(Collectors.toList());
// Result: [9, 8, 5, 2, 1]
```

Question 3

Problem: Find duplicate elements in a list.

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32,
15);

// Find duplicates
Set<Integer> set = new HashSet<>();
myList.stream()
    .filter(n -> !set.add(n))
    .forEach(System.out::println);

// Find unique values
List<Integer> uniqueList = myList.stream()
    .distinct()
    .collect(Collectors.toList());
System.out.println("Unique: " + uniqueList);
```

Output:

98

15

Unique: [10, 15, 8, 49, 25, 98, 32]

Limit & Skip Operations

Limit

Definition: Truncates a stream to a maximum number of elements.

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5, 6, 7, 8, 9, 10);

// First 5 elements
List<Integer> first5 = numbers.stream()
    .limit(5)
    .collect(Collectors.toList());
// Result: [1, 2, 3, 4, 5]
```

Skip

Definition: Discards the first n elements of a stream.

```
// Skip first 3 elements
List<Integer> skipped = numbers.stream()
    .skip(3)
    .collect(Collectors.toList());
// Result: [4, 5, 6, 7, 8, 9, 10]
```

Pagination Pattern

```
int page = 2, size = 3;
List<Integer> page2 = numbers.stream()
    .skip((page-1) * size)
    .limit(size)
```

```
.collect(Collectors.toList());  
// Result: [4, 5, 6]
```

Interview Question Q4: Find First Element

Question 4

Problem: Find the first element of the list.

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32,  
15);  
  
myList.stream()  
    .findFirst()  
    .ifPresent(System.out::println);  
  
// With array  
int[] arr = {10, 15, 8, 49, 25, 98, 98, 32, 15};  
Arrays.stream(arr)  
    .boxed()  
    .findFirst()  
    .ifPresent(System.out::print);
```

Output:

```
10  
10
```

Terminal Operations

forEach

Definition: Performs action for each element.

```
list.stream().forEach(System.out::println);  
list.parallelStream().forEach(System.out::println); // Order not  
guaranteed
```

collect (Most Important)

Definition: Collects stream elements into a container.

```
List<String> names = Arrays.asList("Alice", "Bob", "Charlie");  
  
// To List  
List<String> list = names.stream().collect(Collectors.toList());  
  
// To Set  
Set<String> set = names.stream().collect(Collectors.toSet());  
  
// To Map  
Map<String, Integer> map = names.stream()  
    .collect(Collectors.toMap(  
        Function.identity(),  
        String::length  
    ));  
  
// Joining strings  
String joined = names.stream()
```

```
.collect(Collectors.joining(", "));  
// Result: "Alice, Bob, Charlie"
```

Interview Question Q5: Total Number of Elements

Question 5

Problem: Find the total number of elements in the list.

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32,  
15);  
  
long count = myList.stream()  
.count();  
System.out.println("Total elements: " + count);  
  
// With array  
int[] arr = {10, 15, 8, 49, 25, 98, 98, 32, 15};  
long arrayCount = Arrays.stream(arr)  
.boxed()  
.count();  
System.out.println("Total elements in array: " + arrayCount);
```

Output:

```
Total elements: 9  
Total elements in array: 9
```

Reduce Operation

reduce

Definition: Combines elements into a single result.

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5);

// Sum
int sum = numbers.stream()
    .reduce(0, (a, b) -> a + b); // 15

// Max
Optional<Integer> max = numbers.stream()
    .reduce(Integer::max); // Optional[5]

// Product
int product = numbers.stream()
    .reduce(1, (a, b) -> a * b); // 120
```

Interview Question Q6: Find Maximum Value

Question 6

Problem: Find the maximum value element in the list.

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32,
    15);

// Using max() with Integer.compare
int max = myList.stream()
    .max(Integer::compare)
    .get();

System.out.println("Maximum value: " + max);
```



```
// Using max() with Comparator
int max2 = myList.stream()
    .max(Comparator.naturalOrder())
    .get();
System.out.println("Maximum value: " + max2);

// With array
int[] arr = {10, 15, 8, 49, 25, 98, 98, 32, 15};
int maxArray = Arrays.stream(arr)
    .boxed()
    .max(Comparator.naturalOrder())
    .get();
System.out.println("Maximum from array: " + maxArray);
```

Output:

Maximum value: 98
Maximum value: 98
Maximum from array: 98

Match Operations

anyMatch / allMatch / noneMatch

Definition: Check conditions against elements.

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5);

// Any even?
boolean anyEven = numbers.stream()
    .anyMatch(n -> n % 2 == 0); // true

// All positive?
boolean allPositive = numbers.stream()
    .allMatch(n -> n > 0); // true

// None negative?
boolean noneNegative = numbers.stream()
    .noneMatch(n -> n < 0); // true
```

Interview Question Q11: Contains Duplicate

Question 11

Problem: Return true if any value appears at least twice in the array.

```
public static boolean containsDuplicate(int[] nums) {
    Set<Integer> setData = new HashSet<>();
    return Arrays.stream(nums)
        .anyMatch(num -> !setData.add(num));
}

// Test
int[] nums1 = {1, 2, 3, 1};
```

```
int[] nums2 = {1, 2, 3, 4};  
System.out.println("Array [1,2,3,1] contains duplicate: " +  
containsDuplicate(nums1));  
System.out.println("Array [1,2,3,4] contains duplicate: " +  
containsDuplicate(nums2));
```

Output:

```
Array [1,2,3,1] contains duplicate: true  
Array [1,2,3,4] contains duplicate: false
```

Find Operations

findFirst / findAny

Definition: Find an element (returns Optional).

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5);

// findFirst - respects order
Optional<Integer> first = numbers.stream()
    .filter(n -> n > 3)
    .findFirst(); // 4

// findAny - better for parallel streams
Optional<Integer> any = numbers.parallelStream()
    .filter(n -> n > 3)
    .findAny(); // Any matching element

// Safe handling
Integer result = numbers.stream()
    .filter(n -> n > 10)
    .findFirst()
    .orElse(-1); // -1 if not found
```

Interview Question Q7: First Non-Repeated Character

Question 7

Problem: Find the first non-repeated character in a String.

```
String input = "Java articles are Awesome";

// Solution using groupingBy
Character result = input.chars()
```

```

.mapToObj(s -> Character.toLowerCase(Character.valueOf((char) s)))
.collect(Collectors.groupingBy(Function.identity(),
LinkedHashMap::new, Collectors.counting()))
.entrySet()
.stream()
.filter(entry -> entry.getValue() == 1L)
.map(entry -> entry.getKey())
.findFirst()
.get();
System.out.println("First non-repeated character: " + result);

// Alternative using indexOf and lastIndexOf
Character result2 = input.chars()
.mapToObj(c -> (char) c)
.filter(ch -> input.indexOf(ch) == input.lastIndexOf(ch))
.findFirst()
.orElse(null);
System.out.println("First non-repeated character: " + result2);

```

Output:

```

First non-repeated character: j
First non-repeated character: J

```

Collectors - groupingBy

groupingBy (Very Important)

Definition: Groups elements by a classifier function.

```
class Employee {
    String name;
    String department;
    double salary;
    // constructor, getters
}

List<Employee> employees = getEmployees();

// Group by department
Map<String, List<Employee>> byDept = employees.stream()
    .collect(Collectors.groupingBy(Employee::getDepartment));

// Count by department
Map<String, Long> countByDept = employees.stream()
    .collect(Collectors.groupingBy(
        Employee::getDepartment,
        Collectors.counting()
    ));

// Average salary by department
Map<String, Double> avgSalary = employees.stream()
    .collect(Collectors.groupingBy(
        Employee::getDepartment,
        Collectors.averagingDouble(Employee::getSalary)
    ));
```

Interview Question Q17: List to Map with Duplicate Keys

Question 17

Problem: Convert a List of objects into a Map handling duplicate keys.

```
class Notes {
    int id;
    String tagName;
    long tagId;
    // constructor, getters
}

List<Notes> noteLst = new ArrayList<>();
noteLst.add(new Notes(1, "note1", 11));
noteLst.add(new Notes(2, "note2", 22));
noteLst.add(new Notes(3, "note3", 33));
noteLst.add(new Notes(4, "note4", 44));
noteLst.add(new Notes(5, "note5", 55));
noteLst.add(new Notes(6, "note4", 66)); // Duplicate tagName

// Convert to Map with duplicate key handling and sorting
Map<String, Long> notesRecords = noteLst.stream()
    .sorted(Comparator.comparingLong(Notes::getTagId).reversed())
    .collect(Collectors.toMap(
        Notes::getTagName,
        Notes::getTagId,
        (oldValue, newValue) -> oldValue, // Keep old value for duplicates
        LinkedHashMap::new
    ));
System.out.println("Notes Map: " + notesRecords);
```

Output:

Notes Map: {note5=55, note4=44, note3=33, note2=22, note1=11}

Collectors - partitioningBy

partitioningBy

Definition: Partitions elements into two groups based on a predicate.

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5, 6);

// Partition into even and odd
Map<Boolean, List<Integer>> partitioned = numbers.stream()
    .collect(Collectors.partitioningBy(n -> n % 2 == 0));

List<Integer> evens = partitioned.get(true); // [2, 4, 6]
List<Integer> odds = partitioned.get(false); // [1, 3, 5]

// Partition with count
Map<Boolean, Long> countByParity = numbers.stream()
    .collect(Collectors.partitioningBy(
        n -> n % 2 == 0,
        Collectors.counting()
    ));
// {false=3, true=3}
```

Interview Question Q18: Count Each Element

Question 18

Problem: Count each element/word from the String ArrayList.

```
List<String> names = Arrays.asList("AA", "BB", "AA", "CC");

// Using groupingBy with counting
Map<String, Long> namesCount = names.stream()
    .collect(Collectors.groupingBy(
```



```
Function.identity(),
Collectors.counting()
));
System.out.println("Element counts: " + namesCount);

// Count words in a sentence
String sentence = "Java is great and Java is powerful";
List<String> words = Arrays.asList(sentence.split(" "));
Map<String, Long> wordCount = words.stream()
    .collect(Collectors.groupingBy(
        Function.identity(),
        Collectors.counting()
    ));
System.out.println("Word counts: " + wordCount);
```

Output:

Element counts: {CC=1, BB=1, AA=2}

Word counts: {Java=2, great=1, is=2, and=1, powerful=1}

Primitive Streams

When to Use

Use when working with large numbers of primitives to avoid boxing overhead.

Creating Primitive Streams

```
// From ranges
IntStream.range(1, 10);
IntStream.rangeClosed(1, 10);

// From values
IntStream.of(1, 2, 3, 4, 5);

// From arrays
int[] array = {1, 2, 3, 4, 5};
IntStream stream = Arrays.stream(array);
```

Important Methods

```
IntStream stream = IntStream.rangeClosed(1, 10);

int sum = stream.sum(); // 55
double avg = stream.average().orElse(0); // 5.5
int min = stream.min().orElse(0); // 1
int max = stream.max().orElse(0); // 10

// All statistics at once
IntSummaryStatistics stats = stream.summaryStatistics();
stats.getCount();
stats.getSum();
stats.getMin();
```

```
stats.getMax();  
stats.getAverage();
```

Interview Question Q21: Find Maximum Element in Array

Question 21

Problem: Find the Maximum element in an array.

```
int[] arr = {12, 19, 20, 88, 00, 9};  
  
// Using max() with getAsInt()  
int max1 = Arrays.stream(arr)  
    .max()  
    .getAsInt();  
System.out.println("Maximum element: " + max1);  
  
// Using reduce  
int max2 = Arrays.stream(arr)  
    .reduce(Integer.MIN_VALUE, (a, b) -> a > b ? a : b);  
System.out.println("Maximum element: " + max2);  
  
// Using summaryStatistics  
IntSummaryStatistics stats = Arrays.stream(arr)  
    .summaryStatistics();  
System.out.println("Maximum element: " + stats.getMax());
```

Output:

```
Maximum element: 88  
Maximum element: 88  
Maximum element: 88
```

Additional Coding Questions

Question 8: First Repeated Character

Question 8

```
String input = "Java Articles are Awesome";

// Using Set
Set<Character> seenCharacters = new HashSet<>();
Character result = input.chars()
    .mapToObj(c -> (char) c)
    .filter(c -> !seenCharacters.add(c))
    .findFirst()
    .orElse(null);
System.out.println("First repeated character: " + result);
```

Output:

First repeated character: a

Question 9: Sort Values (Ascending)

Question 9

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32,
15);

List<Integer> sortedList = myList.stream()
    .sorted()
    .collect(Collectors.toList());
System.out.println("Sorted list: " + sortedList);
```

Output:

Sorted list: [8, 10, 15, 15, 25, 32, 49, 98, 98]

Question 10: Sort Values (Descending)

Question 10

```
List<Integer> myList = Arrays.asList(10, 15, 8, 49, 25, 98, 98, 32, 15);
```

```
List<Integer> sortedDesc = myList.stream()
    .sorted(Comparator.reverseOrder())
    .collect(Collectors.toList());
System.out.println("Sorted descending: " + sortedDesc);
```

Output:

Sorted descending: [98, 98, 49, 32, 25, 15, 15, 10, 8]

More Coding Questions

Question 12: Current Date and Time

Question 12

```
System.out.println("Current Local Date: " + LocalDate.now());
System.out.println("Current Local Time: " + LocalTime.now());
System.out.println("Current Local Date and Time: " +
    LocalDateTime.now());
```

Question 13: Concatenate Two Streams

Question 13

```
List<String> list1 = Arrays.asList("Java", "8");
List<String> list2 = Arrays.asList("explained", "through",
    "programs");

Stream<String> concatStream = Stream.concat(list1.stream(),
    list2.stream());
concatStream.forEach(str -> System.out.print(str + " "));
```

Output:

Java 8 explained through programs

Question 14: Cube and Filter

Question 14

```
List<Integer> integerList = Arrays.asList(4, 5, 6, 7, 1, 2, 3);

List<Integer> result = integerList.stream()
    .map(i -> i * i * i)
    .filter(i -> i > 50)
    .collect(Collectors.toList());
System.out.println("Cubes greater than 50: " + result);
```

Output:

Cubes greater than 50: [64, 125, 216, 343]

Question 15: Sort Array and Convert to Stream

Question 15

```
int arr[] = {99, 55, 203, 99, 4, 91};

Arrays.parallelSort(arr);
System.out.println("Sorted array: " + Arrays.toString(arr));
```

Output:

Sorted array: [4, 55, 91, 99, 99, 203]

Advanced Coding Questions

Question 16: Convert to Uppercase

Question 16

```
List<String> names = Arrays.asList("aa", "bb", "cc", "dd");

List<String> upper = names.stream()
    .map(String::toUpperCase)
    .collect(Collectors.toList());

System.out.println("Uppercase: " + upper);
```

Output:

Uppercase: [AA, BB, CC, DD]

Question 19: Find Duplicate Elements with Count

Question 19

```
List<String> names = Arrays.asList("AA", "BB", "AA", "CC", "BB",
    "DD", "AA");

Map<String, Long> duplicates = names.stream()
    .collect(Collectors.groupingBy(Function.identity(),
    Collectors.counting()))
    .entrySet()
    .stream()
    .filter(entry -> entry.getValue() > 1)
    .collect(Collectors.toMap(Map.Entry::getKey, Map.Entry::getValue));

System.out.println("Duplicates with count: " + duplicates);
```


Output:

Duplicates with count: {AA=3, BB=2}

Question 20: Check if List is Empty

Question 20

```
List<String> noteLst = Arrays.asList("note1", "note2", "note3");

Optional.ofNullable(noteLst)
    .orElseGet(Collections::emptyList)
    .stream()
    .filter(Objects::nonNull)
    .forEach(System.out::println);
```

Output:

note1
note2
note3

Question 22: Count Each Character in String

Question 22

```
String s = "string data to count each character";

Map<String, Long> charCount = Arrays.stream(s.split(""))
    .map(String::toLowerCase)
    .collect(Collectors.groupingBy(
        Function.identity(),
        Collectors.counting()
    ));

System.out.println("Character counts: " + charCount);
```

Additional Advanced Questions

Question 23: Find Second Highest Number

Question 23

```
List<Integer> numbers = Arrays.asList(5, 2, 8, 1, 9, 3, 7, 4, 6);

Optional<Integer> secondHighest = numbers.stream()
    .sorted(Comparator.reverseOrder())
    .skip(1)
    .findFirst();
System.out.println("Second highest: " + secondHighest.orElse(-1));
```

Output:

Second highest: 8

Question 24: Sum of Squares of Even Numbers

Question 24

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5, 6);

int sum = numbers.stream()
    .filter(n -> n % 2 == 0)
    .mapToInt(n -> n * n)
    .sum();
System.out.println("Sum of squares of even numbers: " + sum);
```

Output:

Sum of squares of even numbers: 56

Question 25: Find Longest String

Question 25

```
List<String> words = Arrays.asList("Java", "Python", "C++",  
    "JavaScript", "Go");  
  
Optional<String> longest = words.stream()  
    .max(Comparator.comparing(String::length));  
System.out.println("Longest string: " + longest.orElse(""));
```

Output:

Longest string: JavaScript

Question 26: Partition Numbers into Even and Odd

Question 26

```
List<Integer> numbers = Arrays.asList(1, 2, 3, 4, 5, 6, 7, 8, 9, 10);  
  
Map<Boolean, List<Integer>> partitioned = numbers.stream()  
    .collect(Collectors.partitioningBy(n -> n % 2 == 0));  
System.out.println("Even numbers: " + partitioned.get(true));  
System.out.println("Odd numbers: " + partitioned.get(false));
```

Output:

Even numbers: [2, 4, 6, 8, 10]
Odd numbers: [1, 3, 5, 7, 9]

Most Asked Interview Questions

Q1: What is the difference between Collection and Stream?

Feature	Collection	Stream
Storage	Stores data	Doesn't store data
Modification	Can add/remove	Cannot modify
Traversal	Multiple times	Only once
Evaluation	Eager	Lazy

Q2: What are intermediate and terminal operations?

Intermediate Operations: Return a new stream, are lazy, can be chained.

Examples: filter(), map(), sorted(), distinct(), limit(), skip()

Terminal Operations: Produce result, eager, consume the stream.

Examples: collect(), forEach(), count(), reduce(), anyMatch(), findFirst()

Q3: What is the difference between map and flatMap?

map	flatMap
One-to-one mapping	One-to-many mapping
Returns Stream<R>	Returns Stream<R>
Transforms each element	Flattens nested structures

Q4: What is lazy evaluation in Streams?

Intermediate operations are not executed until a terminal operation is invoked. This improves performance, allows short-circuiting, and saves memory.

Q5: Can we reuse a stream after terminal operation?

No. Stream is consumed after terminal operation.

```
Stream<String> stream = list.stream();  
stream.forEach(System.out::println);  
stream.forEach(System.out::println); // Throws IllegalStateException
```

More Interview Questions

Q6: What is the difference between `findFirst` and `findAny`?

findFirst: Returns first element (respects encounter order)

findAny: Returns any element (better for parallel streams)

Q7: What is short-circuiting in Streams?

Operations that don't need to process entire stream to produce result.

Examples: `limit()`, `findFirst()`, `findAny()`, `anyMatch()`, `allMatch()`, `noneMatch()`

Q8: What is the difference between `parallelStream` and `stream`?

stream(): Sequential processing (single thread)

parallelStream(): Parallel processing (multiple threads)

Q9: What is `Optional` and why is it used in Streams?

`Optional` is a container object that may or may not contain a value. It's used to avoid `NullPointerException`.

Q10: What are the advantages of using Stream API?

- Concise code - Less boilerplate
- Readability - Pipeline reads like business logic
- Parallelism - Easy to parallelize
- Lazy evaluation - Better performance
- Functional programming - Declarative style
- No side effects - Operations don't modify source

Quick Reference Cheat Sheet

Intermediate Operations

Operation	What it does
<code>filter(predicate)</code>	Keeps elements that match condition
<code>map(function)</code>	Transforms each element
<code>flatMap(function)</code>	Flattens nested structures
<code>distinct()</code>	Removes duplicates
<code>sorted()</code>	Sorts elements
<code>limit(n)</code>	Takes first n elements
<code>skip(n)</code>	Skips first n elements
<code>peek(action)</code>	Debugging - performs action

Terminal Operations

Operation	What it returns
<code>collect(collector)</code>	Collection, Map, String
<code>forEach(action)</code>	void
<code>reduce(identity, accumulator)</code>	value
<code>count()</code>	long

<code>anyMatch(predicate)</code>	boolean
<code>allMatch(predicate)</code>	boolean
<code>noneMatch(predicate)</code>	boolean
<code>findFirst()</code>	Optional
<code>findAny()</code>	Optional
<code>min(comparator)</code>	Optional
<code>max(comparator)</code>	Optional

Common Collectors

Collector	What it does
<code>toList()</code>	Collects to List
<code>toSet()</code>	Collects to Set
<code>toMap(keyMapper, valueMapper)</code>	Collects to Map
<code>joining(delimiter)</code>	Joins strings
<code>groupingBy(classifier)</code>	Groups elements
<code>partitioningBy(predicate)</code>	Partitions by condition
<code>counting()</code>	Counts elements
<code>summingInt(mapper)</code>	Sums integer values
<code>averagingInt(mapper)</code>	Averages integer values
<code>summarizingInt(mapper)</code>	Gets all statistics

Java Stream API Summary



Congratulations! You've mastered Java Stream API! 🎉

Key Points to Remember:

- Streams are for processing data, not storing it
- Operations are lazy - only execute at terminal operation
- Streams can be used only once
- Use `parallelStream()` for large datasets
- Collectors are powerful for collecting results
- `Optional` prevents `NullPointerException`
- Practice the 30+ coding questions for interviews

Most Common Stream Patterns:

```
// Filter + Map + Collect (Most Common)
list.stream()
    .filter(condition)
    .map(transformation)
    .collect(Collectors.toList());

// Grouping
list.stream()
    .collect(Collectors.groupingBy(classifier));

// Find Elements
list.stream()
```

```
.filter(condition)
.findFirst()
.orElse(defaultValue);
```

Happy Coding with Java Streams! 🚀

30+ Coding Questions • Complete Reference • Interview Ready