



Java Learning Center

No.1 In Java Training & placement

Java Learning Center

Java Mail

Reference Guide

Put Into Knowledge & Practice

Doc Version - 1.0

Author


Srinivas Dande



Java Mail

Steps to develop an application to send mails using Java Mail API

- 1) Add the following jar files to project build path.
 - a. activation.jar
 - b. dsn.jar
 - c. imap.jar
 - d. mailapi.jar
 - e. pop3.jar
 - f. smtp.jar
- 2) Create the Properties Object and store mail server information in the Properties object.
Note: Mail Server info will be changed from one server to another
For Gmail Server
 - a. mail.smtp.host = smtp.gmail.com
 - b. mail.smtp.auth = true
 - c. mail.smtp.socketFactory.port = 465
 - d. mail.smtp.socketFactory.class = javax.net.ssl.SSLSocketFactory
 - e. mail.smtp.socketFactory.fallback = false
- 3) Define MyPasswordAuthenticator class by extending the javax.mail.Authenticator class.
- 4) Override the following method and return the javax.mail.PasswordAuthentication object
 - a. protected PasswordAuthentication getPasswordAuthentication()
- 5) Access the javax.mail.Session object using the following method of javax.mail.Session.
 - a. public static Session getInstance(Properties props, Authenticator au)
 - b. public static Session getDefaultInstance(Properties props, Authenticator au)
- 6) Create the MimeMessage object using the session object.
- 7) Store the required information in the MimeMessage object
 - a. void setRecipients(RecipientType type, Address[] addresses)
 - b. void setRecipient(RecipientType type, Address add)
 - c. void setRecipients(RecipientType type, String addresses)
 - d. void setSubject(String subject)
 - e. void setSentDate(Date d)
 - f. void setFrom(Address address)
 - g. void setReplyTo(Address[] addresses)





if want to attach
some file
then use
8,9,10

- 8) To specify the Body Content or attachment
 - a. Create the object of MimeMultipart (Subclass of Multipart)
 - b. Create the object of MimeBodyPart (Subclass of BodyPart)
 - c. Store the content in the body part using the method
 - i. void setContent(Object arg0, String mimeType)
 - d. Add the body part in the MultiPart object using the method
 - i. void addBodyPart(BodyPart part)
- 9) When you want to send Attachments along with the mail then do the following:
 - a. Create the FileDataSource (Subclass of javax.activation.DataSource) using the java.io.File Object
 - b. Create the DataHandler object using the DataSource object.
 - c. Set the DataHandler & Filename in the BodyPart object.
 - i. void setFileName(String arg0)
 - ii. void setDataHandler(DataHandler arg0)
 - d. Add the body part in the MultiPart object using the method
 - i. void addBodyPart(BodyPart part)
- 10) Specify the content for MimeMessage using the following method
 - a. void setContent(Multipart body)
- 11) Use the javax.mail.Transport class following method to send mail
 - a. public static void send(Message msg)

Search as → Gmail SMTP Host → get port No etc



Java Learning Center

No. 1 In Java Training & placement

MailService.java

```
package com.jlcindia.service;
import java.io.*;
import java.util.*;
import javax.activation.*;
import javax.mail.*;
import javax.mail.internet.*;
/*
 * @Author : Srinivas Dande
 * @company : Java Learning Center
 * @see      : www.jlcindia.com
 */
public class MailService {
    private static String UNAME = "<URemail>@gmail.com";
    private static String PASSWORD = "<yourpassword>";
    public static void sendMail(String to, String
    sub, String data) {
        try {
            Message msg = getMessageForMail();
            msg.setSubject(sub);
            msg.setFrom(new InternetAddress(UNAME, "Java
            Learning Center"));
            msg.setRecipient(Message.RecipientType.TO, new
            InternetAddress(to));
            msg.setRecipient(Message.RecipientType.BCC, new
            InternetAddress("manish.r@jlcindia.com"));
            msg.setSentDate(new Date());
            msg.setContent(data, "text/html");
            Transport.send(msg);
        } catch (Exception e) { e.printStackTrace(); }
    }
    private static Message getMessageForMail() {
        Authenticator auth = new MyPasswordAuthenticator();
        Properties p = new Properties();
        p.put("mail.smtp.host", "smtp.gmail.com");
        p.put("mail.smtp.socketFactory.port", "465");
        p.put("mail.smtp.socketFactory.class",
        "javax.net.ssl.SSLSocketFactory");
        p.put("mail.smtp.auth", "true");
        p.put("mail.smtp.port", "465");
        Session sess = Session.getInstance(p, auth);
        Message msg = new MimeMessage(sess);
        return msg; }
}
```

```
public static void
sendMailWithAttachment(String to, String sub,
String data, List<File> files) {
    try {
        Message msg = getMessageForMail();
        msg.setSubject(sub);
        msg.setFrom(new InternetAddress(UNAME, "Java
        Learning Center"));
        msg.setRecipient(Message.RecipientType.TO, new
        InternetAddress(to));
        msg.setRecipient(Message.RecipientType.BCC, new
        InternetAddress("manish.r@jlcindia.com"));
        msg.setSentDate(new Date());
        Multipart body = new MimeMultipart();
        BodyPart part1=new MimeBodyPart();
        part1.setContent(data, "text/html");
        body.addBodyPart(part1);
        if (files != null) {
            for (File f : files) {
                BodyPart part = new MimeBodyPart();
                part.setFileName(f.getName());
                DataSource source=new FileDataSource(f);
                DataHandler handler=new DataHandler(source);
                part.setDataHandler(handler);
                body.addBodyPart(part);
            }
        }
        msg.setContent(body);
        Transport.send(msg);
    } catch (Exception e) { e.printStackTrace(); }
}

static class MyPasswordAuthenticator extends
Authenticator {
    protected PasswordAuthentication
    getPasswordAuthentication() {
        System.out.println("\n-- getPasswordAuthentication
        called --");
        return new PasswordAuthentication(UNAME,
        PASSWORD);
    }
}
```




Java Learning Center

No. 1 In Java Training & placement

Lab1.java

```
import com.jlcindia.service.*;
/*
 * @Author : Srinivas Dande
 * @company : Java Learning Center
 * @see      : www.jlcindia.com
 */
public class Lab1 {
    public static void main(String[] args) {
        String to = "manishranjan.jlc@gmail.com";
        String sub = "Test Mail from JLCINDIA";
        String data = "<font color='red' size='6'> THIS IS MESSAGE  
FROM JAVA APP</font> ";
        MailService.sendMail(to, sub, data);
        System.out.println("** Mail Sent **");
    }
}
```

Lab2.java

```
import java.io.*;
import java.util.*;
import com.jlcindia.service.*;
/*
 * @Author : Srinivas Dande
 * @company : Java Learning Center
 * @see      : www.jlcindia.com
 */
public class SendMailWithAttachmentTest {
    public static void main(String[] args) {
        String to = "manishranjan.jlc@gmail.com";
        String sub = "Test Mail from JLCINDIA With Attachment";
        String data = "<font color='red' size='6'> THIS IS MESSAGE  
FROM JAVA APP</font> ";
        List<File> files = new ArrayList<File>();
        files.add(new File("D:\\hello.jpg"));
        files.add(new File("D:\\qhlicense.pdf"));
        files.add(new File("D:\\info.csv"));
        files.add(new File("D:\\Key1.zip"));
        MailService.sendMailWithAttachment(to, sub, data,
            files);
        System.out.println("** Mail Sent **");
    }
}
```