

SKILL 15 OUTPUTS

15A)

```
rasagnya_07@LAPTOP-7LMHP1NN:~/OSLab/Skill$ touch existing.txt
rasagnya_07@LAPTOP-7LMHP1NN:~/OSLab/Skill$ gcc skill15A.c -o skill15A
rasagnya_07@LAPTOP-7LMHP1NN:~/OSLab/Skill$ ./skill15A
Enter command with combined redirection:
Example: ls existing.txt missing.txt > combined.txt 2>&1

Input: ls existing.txt missing.txt > combined.txt 2>&1

Command      : ls
Argument 1   : existing.txt
Argument 2   : missing.txt
Output file  : combined.txt
Output file opened successfully.

Standard output restored successfully.
Standard error restored successfully.
Child process exited with status: 2
Combined output saved in: combined.txt
```

15B)

```
rasagnya_07@LAPTOP-7LMHP1NN:~/OSLab/Skill$ gcc skill15B.c -o skill15B
rasagnya_07@LAPTOP-7LMHP1NN:~/OSLab/Skill$ ./skill15B
=====
      COMPLEX COMMAND INTERPRETER
=====

Supported operators:
|      Pipe
<      Input redirection
>      Output redirection
>>    Append output
2>     Error redirection
2>&1    Merge stderr with stdout

Enter command:
> ls -l | wc -l

===== EXECUTION PLAN =====

Command 1: ls -l
|
v
PIPE
Command 2: wc -l

=====

Executing commands...

64

Execution completed.
```