

Time Picker Documentation

Feature Name

Event Time Picker (From & To)

Overview

This documentation explains the **Time Picker implementation** used in the `CreateEventScreen`. The time picker allows users to select **From Time** and **To Time** for an event and stores the selected values in variables so they can be displayed and submitted later.

Why Variables Are Required

The time picker only **returns a value**; it does not save it automatically.

Variables are required to: - Store the selected time - Update the UI using `setState()` - Use the time when publishing the event

Variables Used

```
String fromTime = "10:30 AM";  
String toTime = "10:30 AM";
```

- `fromTime` → Stores event start time
 - `toTime` → Stores event end time
-

Time Picker Function

Function Signature

```
Future<void> pickTime(  
  BuildContext context,  
  Function(String) onTimePicked,  
) async
```

Parameters

- **context** → Required to show the dialog
 - **onTimePicked** → Callback that returns the formatted time as `String`
-

Full Time Picker Implementation

```
Future<void> pickTime(
    BuildContext context, Function(String) onTimePicked) async {
  TimeOfDay? pickedTime = await showTimePicker(
    context: context,
    initialTime: TimeOfDay.now(),
    builder: (context, child) {
      return Theme(
        data: Theme.of(context).copyWith(
          textButtonTheme: TextButtonThemeData(
            style: TextButton.styleFrom(
              foregroundColor: AppColors.primaryColor,
              backgroundColor: AppColors.buttonColor,
            ),
          ),
        timePickerTheme: TimePickerThemeData(
          dayPeriodColor: AppColors.buttonColor.withAlpha(80),
          dayPeriodTextColor: AppColors.textColor,
        ),
        colorScheme: ColorScheme.light(
          primary: AppColors.buttonColor,
          onPrimary: AppColors.primaryColor,
          onSurface: AppColors.textColor,
        ),
        dialogTheme: DialogThemeData(
          backgroundColor: AppColors.buttonColor,
        ),
      ),
      child: child!,
    );
},
);

if (pickedTime != null) {
  final now = DateTime.now();
  final dateTime = DateTime(
    now.year,
    now.month,
    now.day,
```

```

        pickedTime.hour,
        pickedTime.minute,
    );

    final formattedTime = DateFormat.jm().format(dateTime);
    onTimePicked(formattedTime);
  }
}

```

How the Time Is Selected

From Time

```

TimeFrom(
  time: fromTime,
  onPressed: () {
    pickTime(context, (selected) {
      setState(() {
        fromTime = selected;
      });
    });
  },
)

```

To Time

```

TimeFrom(
  time: toTime,
  onPressed: () {
    pickTime(context, (selected) {
      setState(() {
        toTime = selected;
      });
    });
  },
)

```

Output Format

- Time is stored as `String`
- Uses **12-hour format with AM/PM**

Example Output

```
10:30 AM  
06:45 PM
```

Important Notes

- Uses Flutter's built-in `showTimePicker`
 - Uses `intl` package for formatting
 - Reusable for multiple time fields
 - `setState()` is required to update UI
-

Common Mistake

✗ Not using a variable → selected time is lost

✓ Always store the time in a variable

Editable Notes Section

(Add future improvements or changes here)

-

.