

Status Checkbox Widget Documentation

Overview

This documentation explains the `_buildStatusCheckbox` widget and its usage within a `Wrap` layout in a Flutter application. The purpose of this widget is to display a custom-styled checkbox with a label, commonly used for filtering or status selection (e.g., Asset Status).

Widget: `_buildStatusCheckbox`

Purpose

Creates a reusable checkbox widget with: - Custom border color based on checked state - Transparent background - Custom check (tick) color - A text label next to the checkbox

Each checkbox maintains its own local state using `StatefulBuilder`.

Source Code

```
Widget _buildStatusCheckbox(String label) {  
  bool isChecked = false;  
  
  return Row(  
    mainAxisAlignment: MainAxisAlignment.min,  
    children: [  
      StatefulBuilder(  
        builder: (context, setState) => Checkbox(  
          value: isChecked,  
          onChanged: (val) {  
            setState(() => isChecked = val!);  
          },  
          activeColor: Colors.transparent, // keeps fill transparent  
          checkColor: AppColors.primary, // tick color  
          fillColor: MaterialStateProperty.all(Colors.transparent),  
          side: BorderSide(  
            color: isChecked ? AppColors.primary : AppColors.cBEBEBE,  
            width: 1,  
          ),  
        ),  
      ),  
      MyText(  
        text: label,
```

```

        fontSize: 10.sp,
        color: AppColors.textColor,
    ),
],
);
}

```

Parameters

Parameter	Type	Description
<code>label</code>	String	The text displayed next to the checkbox

Behavior

- The checkbox starts as **unchecked**.
- Tapping the checkbox toggles its state.
- Border color changes dynamically:
 - **Primary color** when checked
 - **Light grey** (`CBE9E9E9`) when unchecked
- The checkbox background remains transparent at all times.

Styling Details

- `activeColor` : Transparent (prevents default fill)
- `fillColor` : Transparent (ensures no background)
- `checkColor` : `AppColors.primary`
- `side` : Custom `BorderSide` for consistent UI
- Label text uses `MyText` widget with `10.sp` font size

Usage in Wrap Layout

Purpose

Displays multiple status checkboxes that automatically wrap to the next line when space is insufficient.

Example

```

Wrap(
  spacing: 0.w,

```

```
runSpacing: 0.h,  
children: [  
  _buildStatusCheckbox("Active"),  
  _buildStatusCheckbox("Written-off"),  
  _buildStatusCheckbox("De-registered"),  
  _buildStatusCheckbox("Sold"),  
  _buildStatusCheckbox("Out of Service"),  
],  
)
```

Status Options

- Active
- Written-off
- De-registered
- Sold
- Out of Service

Each checkbox operates independently.

Notes & Limitations

- Checkbox state is **local** and not accessible outside the widget.
 - Not suitable if parent widget needs to track selected values.
-

Suggested Improvements (Optional)

- Lift state up using a `List<bool>` or `Map<String, bool>`
 - Use a `ValueNotifier` or state management solution (Provider, Bloc, Riverpod)
 - Add `onChanged` callback to return selected status
-

Use Case Examples

- Asset status filters
 - Multi-select options
 - Lightweight UI filters
-

Author Notes

This widget is ideal for quick UI filters where independent local state is acceptable.