

DropeUrlWidget

`DropeUrlWidget` is a reusable **Flutter StatefulWidget** designed to collect a user profile URL with a simple, clean UX. It dynamically updates button text based on input state and exposes callbacks for both button tap and URL changes.

✨ Features

- Center-aligned multi-line URL input
- Real-time URL change callback
- Dynamic button label (`Skip` / `Next`)
- Uses shared design system components
- Responsive sizing with `flutter_screenutil`

🐘 Dependencies

This widget relies on the following packages and internal components:

- `flutter_screenutil`
- `CustomTextfield`
- `CustomElevatedButton`
- `UIHelper`
- `AppColors`

Make sure these are available in your project before using this widget.

🍂 Constructor

```
const DropeUrlWidget({  
  Key? key,  
  required this.ontap,  
  this.url,  
});
```

Parameters

Name	Type	Required	Description
<code>ontap</code>	<code>VoidCallback</code>	✓ Yes	Triggered when the button is tapped (Skip or Next)

Name	Type	Required	Description
url	Function(String)?	 No	Called whenever the URL text changes

Internal Logic

- Uses a `TextEditingController` to track URL input
- Listens to text changes via `addListener`
- Trims and sends URL text through the `url` callback
- Calls `setState()` to update the button label dynamically

```
final bool isEmpty = urlController.text.trim().isEmpty;
```

- If empty → Button text: **Skip**
- If not empty → Button text: **Next**



UI Structure

```
Column
├ CustomTextfield (URL Input)
├ Vertical Space (24.h)
└ CustomElevatedButton (Skip / Next)
```

Text Field Configuration

- Border radius: `12.r`
- Text alignment: Center
- Hint: "drop your profile url"
- Min lines: 1
- Max lines: 4



Example Usage

```
DropeUrlWidget(
  onTap: () {
    // Navigate to next step
  },
  url: (value) {
    print('User URL: $value');
```

```
    },  
  )  
}
```

Notes & Best Practices

- Dispose is handled correctly to avoid memory leaks
- Suitable for onboarding, profile setup, or optional URL collection flows
- Button action does **not** validate URL format — validation should be handled externally if required

Full Source Code

```
import 'package:flutter/material.dart';  
import 'package:flutter_screenutil/flutter_screenutil.dart';  
import 'package:isaacmwesigw352/assets_helper/app_colors.dart';  
import 'package:isaacmwesigw352/common_widgets/custom_button_widget.dart';  
import 'package:isaacmwesigw352/common_widgets/custom_textfeild.dart';  
import 'package:isaacmwesigw352/helpers/ui_helpers.dart';  
  
class DropeUrlWidget extends StatefulWidget {  
  final VoidCallback onTap;  
  final Function(String)? url;  
  
  const DropeUrlWidget({  
    super.key,  
    required this.onTap,  
    this.url,  
  });  
  
  @override  
  State<DropeUrlWidget> createState() => _DropeUrlWidgetState();  
}  
  
class _DropeUrlWidgetState extends State<DropeUrlWidget> {  
  final TextEditingController urlController = TextEditingController();  
  
  @override  
  void initState() {  
    super.initState();  
  
    urlController.addListener(() {  
      widget.url?.call(urlController.text.trim());  
      setState(() {});  
    });  
  }  
}
```

```

}

@override
void dispose() {
  urlController.dispose();
  super.dispose();
}

@override
Widget build(BuildContext context) {
  final bool isEmpty = urlController.text.trim().isEmpty;

  return Column(
    children: [
      CustomTextfield(
        controller: urlController,
        borderRadius: 12.r,
        fillColor: AppColors.white,
        textAlign: TextAlign.center,
        hintText: "drop your profile url",
        minline: 1,
        maxline: 4,
      ),
      UIHelper.verticalSpace(24.h),
      CustomElevatedButton(
        height: 56.h,
        text: isEmpty ? 'Skip' : 'Next',
        onTap: widget.onTap,
      ),
    ],
  );
}

```

Summary

`DropeUrlWidget` is a clean and flexible widget for collecting optional profile URLs. It provides real-time callbacks, responsive layout support, and dynamic UX behavior, making it ideal for onboarding and multi-step forms.

If you want extensions like: - URL validation - Button disable logic - Animation or error states

I can add them following the same documentation standard ♀