

# A delay-based dynamic scheduling algorithm for bag-of-task workflows with stochastic task execution times in clouds

Zhicheng Cai<sup>a,d,\*</sup>, Xiaoping Li<sup>b</sup>, Rubén Ruiz<sup>c</sup>, Qianmu Li<sup>a</sup>

<sup>a</sup>*School of Computer Science and Engineering, Nanjing University of Science and Technology, Nanjing, 210094, China*

<sup>b</sup>*School of Computer Science and Engineering, Southeast University, Nanjing, China*

<sup>c</sup>*Instituto Tecnológico de Informática, Acc. B. Universitat Politècnica de València, València, Spain.*

<sup>d</sup>*Key Laboratory of Image and Video Understanding for Social Safety, Nanjing, China*

---

## Abstract

Results of DDS and URH algorithms under the uniform distribution type.

---

---

\*Corresponding author.

Email addresses: caizhicheng@njust.edu.cn (Zhicheng Cai),  
xppli@seu.edu.cn (Xiaoping Li), rruiz@eio.upv.es (Rubén Ruiz),  
qianmu@njust.edu.cn (Qianmu Li)




Figure 1: The means plot for PIC and PDV with 95.0% Tukey Honest Significant Difference (HSD) confidence intervals of URH and DDS algorithms with different deadline factors




Figure 2: The means plot for PIC and PDV with 95.0% Tukey Honest Significant Difference (HSD) confidence intervals of URH and DDS with different length of pricing intervals




Figure 3: The means plot for PIC and PDV with 95.0% Tukey Honest Significant Difference (HSD) confidence intervals of URH and DDS with different maximum prediction deviation of task execution times