


Practical Malware Analysis

Ch 12: Covert Malware Launching



Last revised: 4-10-17

Hiding Malware

- Malware used to be visible in Windows Task Manager
 - But users often know how to look there
- So malware authors now try to blend their malware into the normal Windows landscape
- Covert launching techniques

Launchers

Purpose of a Launcher

- Sets itself or another piece of malware
 - For immediate or future covert execution
- Conceals malicious behavior from the user
- Usually contain the malware they're loading
 - An executable or DLL in its own resource section
- Normal items in the resource section
 - Icons, images, menus, strings
 - Not considered part of the executable

Encryption or Compression

- The resource section may be encrypted or compressed
- Resource extraction will use APIs like
 - **FindResource**
 - **LoadResource**
 - **SizeofResource**
- Malware also often contains privilege escalation code

Process Injection

Process Injection

- The most popular covert launching technique
 - Two types: DLL Injection and Direct Injection
- Injects code into a running process
- Conceals malicious behavior
- May bypass firewalls and other process-specific security mechanisms
- Common API calls:
 - **VirtualAllocEx** to allocate space in another process's memory
 - **WriteProcessMemory** to write to it

DLL Injection

- The most commonly used covert launching technique
- Inject code into a remote process that calls **LoadLibrary**
- Forces the DLL to load in the context of that process
- On load, the OS automatically calls **DLLMain** which contains the malicious code

Example

- Launcher wants Internet access
 - To download more code
- But a process-specific firewall won't let the launcher's process access the Internet
- Solution: inject malicious code into Internet Explorer process
 - Which already has Internet access

Gaining Privileges

- Malware code has the same privileges as the code it is injected into




Figure 13-1. DLL injection—the launcher malware cannot access the Internet until it injects into iexplore.exe.

Example 13-1. C Pseudocode for DLL injection

```
hVictimProcess = OpenProcess(PROCESS_ALL_ACCESS, 0, victimProcessID 0);  
  
pNameInVictimProcess = VirtualAllocEx(hVictimProcess,...,sizeof(maliciousLibraryName),...,...);  
WriteProcessMemory(hVictimProcess,...,maliciousLibraryName, sizeof(maliciousLibraryName),...);  
GetModuleHandle("Kernel32.dll");  
GetProcAddress(...,"LoadLibraryA");  
CreateRemoteThread(hVictimProcess,...,...,LoadLibraryAddress,pNameInVictimProcess,...,...);
```

- **CreateRemoteThread** uses 3 parameters
 - Process handle **hProcess**
 - Starting point **lpStartAddress** (LoadLibrary)
 - Argument **lpParameter** Malicious DLL name

004076B8	CALL DWORD PTR DS:[<4KKERNEL32.OpenProcess>]	OpenProcess ①
004076C1	MOV DWORD PTR SS:[EBP-1008],EAX	
004076C7	CMP DWORD PTR SS:[EBP-1008],-1	
004076CE	JNZ SHORT DllInjec.004076D8	
004076D0	OR EAX,FFFFFFFF	
004076D3	JMP DllInjec.0040779D	
004076D8	MOV DWORD PTR SS:[EBP-100C],7D0	
004076E2	JMP DllInjec.00407646	
004076E7	PUSH 4	
004076E9	PUSH 3000	
004076EK	PUSH 104	
004076F3	PUSH 0	
004076F5	MOV EAX,DWORD PTR SS:[EBP-1008]	
004076F8	PUSH EAX	
004076FC	CALL DWORD PTR DS:[<4KKERNEL32.VirtualAllocEx>]	kernel32.VirtualAllocEx ②
00407702	MOV DWORD PTR SS:[EBP-1010],EAX	
00407708	CMP DWORD PTR SS:[EBP-1010],0	
0040770F	JNZ SHORT DllInjec.00407719	
00407711	OR EAX,FFFFFFFF	
00407714	JMP DllInjec.0040779D	
00407719	PUSH 0	bytesWritten = NULL
0040771B	PUSH 104	BytesToWrite = 104 (260.)
00407720	LEA ECX,DWORD PTR SS:[EBP-1180]	Buffer
00407726	PUSH ECX	Address
00407727	MOV EDX,DWORD PTR SS:[EBP-1010]	
0040772D	PUSH EDX	
0040772E	MOV EAX,DWORD PTR SS:[EBP-1008]	
00407734	PUSH EAX	hProcess
00407735	CALL DWORD PTR DS:[<4KKERNEL32.WriteProcessMemory>]	WriteProcessMemory ③
0040773B	PUSH DllInjec.0040ACCC	pModule = "kernel32.dll"
00407740	CALL DWORD PTR DS:[<4KKERNEL32.GetModuleHandleW>]	GetModuleHandleW ④
00407746	MOV DWORD PTR SS:[EBP-1188],EAX	
0040774C	PUSH DllInjec.0040ACB8	ProcNameOrOrdinal = "LoadLibraryA"
00407751	MOV ECX,DWORD PTR SS:[EBP-1188]	
00407757	PUSH ECX	hModule
00407758	CALL DWORD PTR DS:[<4KKERNEL32.GetProcAddress>]	GetProcAddress ⑤
0040775E	MOV DWORD PTR SS:[EBP-1190],EAX	
00407764	PUSH 0	
00407766	PUSH 0	
00407768	MOV EDX,DWORD PTR SS:[EBP-1010]	
0040776E	PUSH EDX	
0040776F	MOV EAX,DWORD PTR SS:[EBP-1190]	
00407775	PUSH EAX	
00407776	PUSH 0	
00407778	PUSH 0	
0040777A	MOV ECX,DWORD PTR SS:[EBP-1008]	
00407780	PUSH ECX	
0040778B	CALL DWORD PTR DS:[<4KKERNEL32.CreateRemoteThread>]	kernel32.CreateRemoteThread ⑥

Figure 13-2. DLL injection debugger view

Analyzing DLL Injection

- Once you find DLL injection activity in disassembly
 - Look for strings containing the name of the malicious DLL and the victim process
 - Or put a breakpoint in the injection code and examine the stack to find them

Direct Injection

- Injects code directly into the remote process
- Without using a DLL
- More flexible than DLL injection
- Requires a lot of customized code
 - To run without negatively impacting the host process
- Difficult to write

Process Replacement

Process Replacement

- Overwrites the memory space of a running object with malicious code
- Disguises malware as a legitimate process
- Avoids risk of crashing a process with process injection
- Malware gains the privileges of the process it replaces
- Commonly replaces *svchost.exe*


Suspended State

- In a *suspended state*, the process is loaded into memory but the primary thread is suspended
 - So malware can overwrite its code before it runs
- This uses the **CREATE_SUSPENDED** value
- in the **dwCreationFlags** parameter
- In a call to the **CreateProcess** function

Example 13-2. Assembly code showing process replacement

```
00401535      push     edi                ; lpProcessInformation
00401536      push     ecx                ; lpStartupInfo
00401537      push     ebx                ; lpCurrentDirectory
00401538      push     ebx                ; lpEnvironment
00401539      push     CREATE_SUSPENDED ; dwCreationFlags
0040153B      push     ebx                ; bInheritHandles
0040153C      push     ebx                ; lpThreadAttributes
0040153D      lea      edx, [esp+94h+CommandLine]
00401541      push     ebx                ; lpProcessAttributes
00401542      push     edx                ; lpCommandLine
00401543      push     ebx                ; lpApplicationName
00401544      mov      [esp+0A0h+StartupInfo.dwFlags], 101h
0040154F      mov      [esp+0A0h+StartupInfo.wShowWindow], bx
00401557      call     ds:CreateProcessA
```

Example 13-3. C pseudocode for process replacement

```
CreateProcess(...,"svchost.exe",...,CREATE_SUSPEND,...);
ZwUnmapViewOfSection(...);
VirtualAllocEx(...,ImageBase,SizeOfImage,...);
WriteProcessMemory(...,headers,...);
for (i=0; i < NumberOfSections; i++) {
     WriteProcessMemory(...,section,...);
}
SetThreadContext();
...
ResumeThread();
```

- **ZwUnmapViewOfSection** releases all memory pointed to by a section
- **VirtualAllocEx** allocates new memory
- **WriteProcessMemory** puts malware in it

Example 13-3. C pseudocode for process replacement

```
CreateProcess(..., "svchost.exe", ..., CREATE_SUSPEND, ...);  
ZwUnmapViewOfSection(...);  
VirtualAllocEx(..., ImageBase, SizeOfImage, ...);  
WriteProcessMemory(..., headers, ...);  
for (i=0; i < NumberOfSections; i++) {  
    1 WriteProcessMemory(..., section, ...);  
}  
SetThreadContext();  
...  
ResumeThread();
```

- **SetThreadContext** restores the victim process's environment and sets the entry point
- **ResumeThread** runs the malicious code

Hook Injection

Hooks

- Windows hooks intercept messages destined for applications
- Malicious hooks
 - Ensure that malicious code will run whenever a particular message is intercepted
 - Ensure that a DLL will be loaded in a victim process's memory space




Figure 13-3. Event and message flow in Windows with and without hook injection

Local and Remote Hooks

- *Local hooks* observe or manipulate messages destined for an internal process
- *Remote hooks* observe or manipulate messages destined for a remote process (another process on the computer)

High-Level and Low-Level Remote Hooks

- *High-level remote hooks*
 - Require that the hook procedure is an exported function contained in a DLL
 - Mapped by the OS into the process space of a hooked thread or all threads
- *Low-level remote hooks*
 - Require that the hook procedure be contained in the process that installed the hook

Keyloggers Using Hooks

- Keystrokes can be captured by high-level or low-level hooks using these procedure types
 - **WH_KEYBOARD**
 - or
 - **WH_KEYBOARD_LL**

Using **SetWindowsHookEx** for Remote Windows Hooking

- Parameters
 - **idHook** - type of hook to install
 - **lpfn** - points to hook procedure
 - **hMod** - handle to DLL, or local module, in which the **lpfn** procedure is defined
 - **dwThreadId**- thread to associate the hook with.
Zero = all threads
- The hook procedure must call **CallNextHookEx** to pass execution to the next hook procedure so the system continues to run properly

Thread Targeting

- Loading into all threads can degrade system performance
- May also trigger an IPS
- Keyloggers load into all threads, to get all the keystrokes
- Other malware targets a single thread
- Often targets a Windows message that is rarely used, such as **WH_CBT** (a computer-based training message)

Explanation of Next Slide

- Malicious DLL *hook.dll* is loaded
- Malicious hook procedure address **MalwareProc** obtained
- The hook procedure calls only **CallNextHookEx**
- A **WH_CBT** message is sent to a Notepad thread
- Forces *hook.dll* to be loaded by Notepad
- It runs in the Notepad process space

Example 13-4. Hook injection, assembly code

```
00401100      push     esi
00401101      push     edi
00401102      push     offset LibFileName ; "hook.dll"
00401107      call     LoadLibraryA
0040110D      mov      esi, eax
0040110F      push     offset ProcName ; "MalwareProc"
00401114      push     esi                ; hModule
00401115      call     GetProcAddress
0040111B      mov      edi, eax
0040111D      call     GetNotepadThreadId
00401122      push     eax                ; dwThreadId
00401123      push     esi                ; hmod
00401124      push     edi                ; lpfn
00401125      push     WH_CBT         ; idHook
00401127      call     SetWindowsHookExA
```

Detours

A Microsoft Product

- Detours makes it easy for application developers to modify applications and the OS
- Used in malware to add new DLLs to existing binaries on disk
- Modifies the PE structure to create a **.detour** section
- Containing original PE header with a new import address table




Figure 13-4. A PView of Detours and the evil.dll

- **setdll** is the Microsoft tool used to point the PE to the new import table
- There are other ways to add a **.detour** section

APC Injection

Asynchronous Procedure Call (APC)

- Directs a thread to execute other code prior to executing its regular path
- Every thread has a queue of APCs attached to it
- These are processed when the thread is in an alterable state, such as when these functions are called
 - **WaitForSingleObjectEx**
 - **WaitForMultipleObjectsEx**
 - **Sleep**

Two Forms of APCs

- Kernel-Mode APC
 - Generated for the system or a driver
- User-Mode APC
 - Generated for an application
- APC Injection is used in both cases

APC Injection from User Space

- Uses API function **QueueUserAPC**
- Thread must be in an alterable state
- **WaitForSingleObjectEx** is the most common call in the Windows API
- Many threads are usually in the alterable state

QueueUserAPC Parameters

- **hThread** handle to thread
- **pfnAPC** defines the function to run
- **dwData** parameter for function

Example 13-5. APC injection from a user-mode application

```
00401DA9      push    [esp+4+dwThreadId]      ; dwThreadId
00401DAD      push    0                        ; bInheritHandle
00401DAF      push    10h                     ; dwDesiredAccess
00401DB1      call    ds:OpenThread 1
00401DB7      mov     esi, eax
00401DB9      test    esi, esi
00401DBB      jz      short loc_401DCE
00401DBD      push    [esp+4+dwData]           ; dwData = dbnet.dll
00401DC1      push    esi                      ; hThread
00401DC2      push    ds:LoadLibraryA 2        ; pfnAPC
00401DC8      call    ds:QueueUserAPC
```

- 1: Opens a handle to the thread
- 2: **QueueUserAPC** is called with **pfnAPC** set to **LoadLibraryA** (loads a DLL)
- **dwData** contains the DLL name (*dbnet.dll*)
- *Svchost.exe* is often targeted for APC injection

APC Injection from Kernel Space

- Malware drivers and rootkits often want to execute code in user space
- This is difficult to do
- One method is APC injection to get to user space
- Most often to *svchost.exe*
- Functions used:
 - **KeInitializeApc**
 - **KeInsertQueueApc**

Example 13-6. User-mode APC injection from kernel space

```
000119BD      push     ebx
000119BE      push     1 ❶
000119C0      push     [ebp+arg_4] ❷
000119C3      push     ebx
000119C4      push     offset sub_11964
000119C9      push     2
000119CB      push     [ebp+arg_0] ❸
000119CE      push     esi
000119CF      call     ds:KeInitializeApc
000119D5      cmp      edi, ebx
000119D7      jz       short loc_119EA
000119D9      push     ebx
000119DA      push     [ebp+arg_C]
000119DD      push     [ebp+arg_8]
000119E0      push     esi
000119E1      call     edi          ;KeInsertQueueApc
```