Technical report — Abstimmungsbüchlein Check: NLI over Swiss federal voting booklets with Apertus

Every number in this report comes from a recorded run (listed at the end), on our development split (dev), a validation set (val) or a probe set of two unseen voting dates; **the sealed test dates were run once, after the freeze (section 1)**.

- **Track:** Track 2A — OST: Multilingual Natural Language Inference over Swiss Official Voting Booklets
- **Event:** Online
- **Project:** Abstimmungsbüchlein Check — multilingual claim verification against Swiss voting booklets
- **Team:** Bissegger & Bayraktar — Rashad Bissegger, Kaan Bayraktar
- **Repository:** https://github.com/Rashad18236/hackapertus-voting-nli
- **Image:** ghcr.io/rashad18236/hackapertus-voting-nli:latest (the sealed run: digest `sha256:0c1a10cd92261cdfede7eb8c191a16eab3f94770f0a7386b45a06ebc06f088be`, commit 71a6d6a)
- **Demo:** none

1. Summary

Before every federal vote, each Swiss voter receives a booklet explaining the proposal and the arguments for and against it. Given a claim in German, French or Italian, our system decides whether the booklet **supports** it (entailment), **does not settle** it (neutral) or **contradicts** it (contradiction). In task B the source is a short passage; in task A it is the whole booklet PDF, and the system must find the passage itself and quote it with its page number.

Apertus v1.5 (8B) makes every decision. Everything else runs locally on a CPU: reading the PDF, choosing what Apertus reads, and turning the paragraphs it cites into evidence.

The challenge's central question is whether Apertus should read the whole booklet or a selected part. On 100 dev cases, the whole booklet scored a Macro-F1 of 0.858 at 37,586 input tokens per case; only the part the claim refers to scored 0.989 at 1,248 tokens; no booklet text at all scored 0.435. Our design follows from this: find the part a claim is about and send only that.

Final system	dev	val	probe
Task A Macro-F1	**0.977**	**0.981**	**0.990**
Task A evidence score	**0.990**	**0.988**	**1.000**
Task A tokens per case (input + output)	1,259 + 14.9	1,233 + 14.9	1,177 + 16.6
Task A local time per case, model at 1.0 / 0.3 s per request	0.020 / 0.027 s	0.010 / 0.010 s	0.039 / 0.035 s
Task B Macro-F1	**0.987**	**0.968**	**0.977**
Task B tokens per case (input + output)	815 + 9.0	820 + 9.3	789 + 8.3
Task B local time per case, 1.0 / 0.3 s per request	0.012 / 0.021 s	0.009 / 0.010 s	0.020 / 0.019 s
Labels not set by Apertus (unreadable answer → neutral)	0 of 600	1 of 1,160	0 of 188
Our estimate of the official score at 1.0 / 0.3 s per request (section 6)	**0.904 / 0.893**	**0.908 / 0.907**	**0.901 / 0.902**

All numbers come from the published Docker image (`sha-7ae78ad87cfd`).

Sealed test dates (2020-02-09, 2022-02-13, 2022-05-15; 173 rows, one task A and one task B case each). Run once through the submission image after every default was frozen; nothing was changed afterwards. No call failed, no label was set by our code, no answer came from the endpoint's cache.

Sealed, run once	all	2020-02-09	2022-02-13	2022-05-15
Rows	173	42	90	41
Task A Macro-F1 / evidence	**0.989 / 0.975**	0.973 / 1.000	1.000 / 0.984	0.975 / 0.935
Task A tokens, in + out	1,276 + 19.2	1,239 + 14.6	1,283 + 23.2	1,299 + 15.2
Task A local time, 1.0 / 0.3 s	0.025 / 0.035 s	0.057 / 0.051 s	0.050 / 0.048 s	0.160 / 0.152 s
Task B Macro-F1	**0.960**	0.926	0.965	0.978
Task B tokens, in + out	845 + 9.8	786 + 8.2	836 + 10.6	928 + 9.7
Task B local time, 1.0 / 0.3 s	0.011 / 0.013 s	0.035 / 0.081 s	0.017 / 0.019 s	0.034 / 0.121 s

Sealed, run once	all	2020-02-09	2022-02-13	2022-05-15
Official score (our estimate), 1.0 / 0.3 s	**0.898 / 0.893**	0.863 / 0.866	0.894 / 0.892	0.808 / 0.803

Per date, start-up falls on fewer cases (task A: 1.8–6.3 s to the first request).

2. Architecture




Figure 1. Blue: local work, no language model. Orange: a call to Apertus. Dashed arrows: taken only when the step before fails.

Each case has two stages: **preparation** (local: read the booklet, find the part, build the prompt) and the **model call** (Apertus answers). Two worker processes prepare cases while the main process sends them to Apertus, so most local work happens while we wait for the model, which is not counted as local time.

Every case gets an answer: if a step fails, the case takes a simpler fallback, and if Apertus's answer cannot be read, the label is neutral. Apertus runs at temperature 0, so the same request gives the same answer.

3. How the booklet is prepared for the model

Reading the PDF. We extract each page's text with its page number, reading a page only when it is needed.

Finding the right part (task A). A booklet covers several votes, each with the same parts: summary, Federal Council's arguments, committee's arguments, detailed explanation and legal text. Claims almost always name their part ("Laut der Zusammenfassung …", "Le Conseil fédéral estime …"). We use this in five steps:

1. **Which part?** Patterns in German, French and Italian map the claim's opening to a part. If none matches, Apertus names the part.
2. **Where is it?** The table of contents gives where each vote and part starts; each start page is checked against its printed heading. If the contents cannot be read, Apertus reads them instead.
3. **Which vote?** The case's vote name is matched to the contents titles, or, failing that, to the title closest in meaning (local embedding model).
4. **What to send.** The part is split into numbered paragraphs, each with its page. Parts over 8,000 characters are cut to the 8 paragraphs most similar to the claim (a fast static embedding model).
5. **Fallback.** If no part or vote is found, we send the 8 chunks of the booklet that share the most words with the claim. If claim and booklet differ in language, Apertus first translates the claim for this search.

Task B. The passage is given. Passages over 3,000 characters are cut to their first line (which names the ballot) and the 4 paragraphs most similar to the claim.

What Apertus sees. The prompt starts with a decision rule based on the challenge's label definitions:

> *Decide in this order: 1. Does the reference text deal with the subject of the claim at all? If not, the label is 1 (neutral). 2. If it does: 0 if it supports the claim; 2 only if it states something that cannot be true together with the claim; otherwise 1. Missing information is never a contradiction. […]*

Then follow the part's name (e.g. "the committee's arguments"), the numbered paragraphs, the vote and the claim. Apertus answers in a fixed JSON format: a label and, in task A, up to three paragraph numbers it relied on.

A second look. When Apertus answers "neutral" but still cites paragraphs, it has often found the right place but is unsure. We then show it only those paragraphs and their neighbours and ask whether they say the **same**, something **different**, or **nothing** about the claim (entailment, contradiction, neutral).

Evidence. We return the paragraphs Apertus cited, word for word, with their page. An item counts if it lies inside the gold passage or contains it, so we fill the five allowed items with the cited paragraphs' halves, the paragraph before (when the cited one starts a page) and the whole cited page. Neutral answers and task B get no evidence.

4. How Apertus is used

Apertus makes every judgement; our code only decides what it reads and never sets a label (except neutral for an unreadable answer: once in 1,948 final answers). We use the 8B model zero-shot, without fine-tuning or examples. Apertus has five roles; only the first is needed in every case:

What Apertus does	When	Calls per 100 cases (A / B)	Tokens per call, in + out
Decides the label and names the paragraphs it rests on	every case	100 / 100	1,251 + 14.6 (A); 815 + 9.0 (B)
Names the booklet part a claim refers to	our patterns do not recognise the claim's opening	0 / –	≈ 236 + 49
Reads the booklet's table of contents	our parser cannot read it	0 / –	≈ 1,825 + 192 per booklet
Translates the claim into the booklet's language	the word-search fallback, across languages	0.33 / –	141 + 55
Takes a second look at the cited paragraphs	the answer is neutral but cites paragraphs	1.7 / –	454 + 8

What Apertus reads matters most. We compared the final system with four other ways of giving Apertus the booklet, everything else unchanged. "Apertus does all the parsing" means it names the part and reads the contents in every case, not only as a backup.

What Apertus reads (task A, dev)	Macro-F1	Evidence	Input tokens per case
nothing: claim and vote only	0.435	—	≈ 200
8 chunks found by embedding search	0.834	0.662	1,868
the whole booklet (100 cases)	0.858	—	37,586
Apertus does all the parsing	0.960	0.891	1,655
the part the claim names (final)	**0.977**	**0.990**	**1,259**




Figure 2. What Apertus reads in task A (dev): Macro-F1 (left) and input tokens per case (right, log scale). Blue: the final system. Dashed: the minimum Macro-F1 for a valid submission (0.60).

The whole booklet is the most expensive and not the most accurate: Apertus loses the passage among tens of thousands of tokens. Apertus doing all the parsing is nearly as good but costs a third more tokens and eight times the local time, so it is only a backup. We could not compare with the 70B model: the endpoint refused all our calls.

Remaining errors (val, an earlier version). Of 23 task A errors, 10 are **search errors** (the right passage was not sent, mostly because a long part was cut) and 13 **reading errors** (negation or direction 6, scope 5, number or date 2). All 18 task B errors are reading errors, most often a claim about another ballot (6) or a wrong number or date (6).

What we tried and did not keep. We evaluated many variants against the system of the time, each changing one thing, with the rule for keeping it fixed before the run:

Variant	Result against the system of that time (Macro-F1, dev unless marked)	Why not kept
shorter prompts (A; B); three examples in the prompt (B)	0.670; 0.667; 0.933 vs 0.947	lower
only the 4 most similar paragraphs	dev 0.990 with 35 % fewer tokens; val 0.944 vs 0.959	did not hold on val
claim split / several languages / separate negation check	A 0.963 / 0.980 / 0.987 vs 0.983; B 0.937 / 0.970 / 0.960 vs 0.967	no clear gain for 1.7–3 calls per case
second look with the 3 most similar paragraphs	dev +0.010, val +0.003	below the +0.015 we required
second look: “related but not settled” = “nothing”	the same answer in all 19 second looks	no change
five rewordings of the task A prompt	dev 0.902–0.983 vs 0.983; on-topic neutrals kept 13–28 of 46 vs 32	lower, or broke correct neutrals
task B as numbered paragraphs; task B cut to 4 paragraphs by embedding	0.963 vs 0.967; 55 % fewer tokens but slower	lower, or slower
other ways to shorten long task B passages	0.973 / 0.993 (+13 % tokens) / 0.967 vs 0.987	lower, or too many tokens
task B: ballots named first / title added / claim first	0.892 (19 unreadable answers) / 0.980 / 0.980 vs 0.987	lower or unreadable
task B: “is the claim about this ballot?” after a contradiction	0.970 vs 0.987; 1 fixed, 6 broken; +7 % tokens	wrongly dismissed claims that misstate their ballot
code rule “neutral with a citation → contradiction”	val +0.014 offline; 3 of 3 on-topic neutrals wrong	the code may not set a label

Who did what. Rashad Bissegger: finding the part (patterns, parser), evidence, speed and memory, the static embedding model, the second look, and the method (a rule fixed before every comparison). Kaan Bayraktar: the word search and translated claim of the fallback; the finding that a claim’s and its negation’s answers disagree on almost every error (all 10 task B and 4 of 5 task A dev errors, about 7 % of cases); the claim-splitting and several-languages experiments; this report’s rewrite, diagram and charts.

5. Data

- **Dataset:** `OSTswiss/MNLIoverSwissVotingBooklets` v1.1 (MIT): 1,488 rows, of which 335 are exact duplicates. Each row gives one task A case and one task B case.
- **Splits** by voting date, duplicates removed: test 5 dates (267 rows), dev 300 rows, val 580 further rows of the dev dates (only for confirming). Two test dates (94 rows) were opened as an unseen **probe**; the other three (173 rows) stayed **sealed** until one run after the freeze (section 1).
- **Booklets:** the Federal Chancellery’s PDFs, not stored in the repository; for parser tests, all 93 federal booklets 2016–2026. Official reports are exempt from Swiss copyright (Art. 5 URG); no personal data.

6. Evaluation

How we measured. We use the organisers’ evaluation script. The official score combines Macro-F1, evidence (task A), tokens per case and **local time** per case (running time minus time waiting for the model), the last two relative to the best team. Our estimate uses fixed reference values instead (600 / 800 tokens, 0.05 / 0.005 s for task A / B). Because the endpoint’s answers drifted between days, we only compared versions within one run, sending each case to every version back to back.




Figure 3. Macro-F1 of the final system on dev, val and the probe (two unseen voting dates). Bars on dev: 95 % bootstrap intervals. The axis starts at 0.95.

Stability. Three runs of all 600 dev cases, 30 minutes apart, gave **identical labels**. The larger uncertainty is the small sample: 95 % bootstrap intervals are [0.958, 0.991] (task A) and [0.973, 0.997] (task B), which covers the differences between dev, val and probe.

Other booklets. On all 93 booklets from 2016–2026, 244 of 249 votes pass every parser check (178 before our fixes).

Fallbacks. Since fallbacks are rare, we forced every case into one (Macro-F1 / evidence):

Situation	dev	val	Tokens per case (dev)
normal: the part is found	0.977 / 0.980	—	1,238 + 14.5
no part found → word search, Apertus translates the claim	0.956 / 0.736	0.957 / 0.755	2,591 + 44.3
table of contents unreadable → Apertus reads it	0.946 / 0.925	0.939 / 0.917	1,564 + 42.8




Figure 4. Every dev case forced into a fallback: the earlier embedding search (grey) against the fallback we kept (blue).

Task B. Cutting long passages raised Macro-F1 (dev 0.967 → 0.987, val 0.954 → 0.968) and cut input tokens per case from 1,994 to 815.

Local time (2 CPUs, 4 GB, a fake model answering after a fixed delay). The faster the model, the less local work hides behind it. Our first ranking model (multilingual-e5-small) took about 3 s per long part; the static model takes milliseconds:

Local time per case, dev	model at 1.0 s per request	0.3 s	0.1 s
Task A, final (static embedding model)	0.020 s	0.027 s	0.062 s
Task A, earlier version (e5)	0.017 s	0.160 s	0.364 s
Task B, final	0.012 s	0.021 s	0.172 s




Figure 5. Local time per case (dev) as the model gets faster. With e5, the ranking no longer hides behind the model; with the static model it does.

Memory. Task A needs 0.2–0.4 GB, task B 1.2–1.7 GB; every case is answered down to 512 MB.

Unseen booklets. On the probe, task A scores 0.990 (evidence 1.000) and task B 0.977. 90 of 94 task A cases are routed; the other 4 concern a committee that the vote does not have and go to the fallback.

Sealed test dates. Their 9 booklets parse completely (27 of 27 votes, 9 per language). Our patterns named the part of 171 of 173 task A claims, Apertus the other 2; the parser found the vote for 150 cases, Apertus reading the contents for 23 (one ballot whose title the parser misread in all three languages). No fallback; all 25 cases Apertus helped were right; the second look fixed 3 of 3. Errors: task A 2, both reading errors; task B 7, of which 2 are passages about another ballot called a contradiction. The sealed run was made with MODEL set to Public AI's id; the fallback added afterwards (session 17) does not change any request the endpoint accepts.

Qualitative examples. TODO: a few typical cases (one correct entailment, one contradiction, one neutral, one error) and one full worked example from claim to prompt to answer and evidence.

7. Limitations

- **Tuned on dev.** Prompts and rules were written looking at dev; val and the unseen probe confirm the scores.
- **Booklet layout.** Part-finding relies on the booklet structure used since 2016; anything else goes to the less accurate fallback.
- **Only the 8B model.** Everything was built on the 8B; we do not know which model the organisers will use.
- **Speed.** With a much faster model, PDF reading would no longer hide behind the model calls.
- **The second look** can turn an on-topic passage that does not settle the claim into a contradiction (2–3 of 46 such cases). We kept it because on val and probe it fixed 18 answers and broke 2.
- **Task B, other ballots.** 8 of 19 final val errors are passages about another ballot called a contradiction; three attempts to fix this cost more than they gained.
- **Evidence pages.** Gold passages often start on the page before the one we cite; if the official check uses the first page, about 40 % of our hits would not count.
- **Not political advice.** The system only checks claims against the booklet's text. Its answers are not voting recommendations; every task A "supports" or "contradicts" is traceable to the booklet: it comes with the page and exact text it rests on.

8. Reproducibility

- **Image:** `ghcr.io/rashad18236/hackapertus-voting-nli:latest`, built from `main`, run with the organisers' command (README); final numbers from `sha-7ae78ad87cfd`; the sealed run used digest `sha256:0c1a10cd92261cdfede7eb8c191a16eab3f94770f0a7386b45a06ebc06f088be` (commit 71a6d6a, the same code). **From source:** `make run`.
- **Model name:** the image asks for `swiss-ai/Apertus-v1.5-8B` and, if the endpoint refuses that name, resolves the Apertus v1.5 8B id from `BASE_URL/models`; `MODEL` can override it.
- **Submission tag:** `submission` (set on main after this PR).
- **Hardware:** CPU only; measured with 2 CPUs and 4 GB. **Determinism:** temperature 0; replaying saved answers reproduces every label and evidence item.
- **License:** code Apache-2.0; report text CC-BY-4.0.

References

- Dataset: OSTswiss/MNLIoverSwissVotingBooklets v1.1, Hugging Face (MIT). Starter: `gitlab.com/ifsoftware/hackapertus-starter`. Apertus v1.5, Swiss AI Initiative.
- Wang, L. et al. (2024). *Multilingual E5 Text Embeddings.* arXiv:2402.05672 (MIT). Static embedding model: `sentence-transformers/static-similarity-mrl-multilingual-v1` (Apache-2.0). Robertson, S., Zaragoza, H. (2009). *The Probabilistic Relevance Framework: BM25 and Beyond* (the word search of the fallback).
- Runs behind the numbers (folders in `docs/runs/`, 8 to 15 October 2026): final system `final-s15_*`; stability `stability-s15-run{1,2,3}_dev600`; memory `memory-grid-final-s15_grid24`, `memory-guard_grid48`; task B shortening `taskb-selectors_*`; parser coverage `parser-coverage_booklets93`; fallbacks `fallbacks_*`, `S-and-fallbacks_devA300`, `bm25ap-fallback_valA300`, `ap-structure-ask_*`; whole booklet `context-curve_devA100`; no booklet text `closed-book_devA300`; embedding chunks `section-route-vs-embed_devA300`; Apertus does all parsing `ap-all_devA300`; variants not kept `prompts-A_*`, `prompts-B_*`, `A6b_*`, `B1f_devB300`, `B6_devB300`; 70B `70B-smoke_devA3-devB3`; Kaan's retrievers and experiments `kaan_strategies_dev600`, `kaan_retrievers_*`; sealed test dates `sealed-once`.