

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```

%LINK-5-CHANGED: Interface FastEthernet2/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet2/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet3/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to up

Switch>enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/1
Switch(config-if)#switchport access vlan 10
% Access VLAN does not exist. Creating vlan 10
Switch(config-if)#int fa2/1
Switch(config-if)#switchport access vlan 20
% Access VLAN does not exist. Creating vlan 20
Switch(config-if)#int fa2/1
Switch(config-if)#switchport access vlan 30
% Access VLAN does not exist. Creating vlan 30
Switch(config-if)#int fa1/1
Switch(config-if)#switchport access vlan 20
Switch(config-if)#int fa3/1
Switch(config-if)#switchport mode trunk
Switch(config-if)#switchport mode trunk

% Invalid input detected at '^' marker.

Switch(config-if)#switchport mode trunk

Switch(config-if)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to down
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to up
Switch(config-if)#exit
  
```

Switch1

Physical
Config
CLI
Attributes

IOS Command Line Interface

```

%LINK-5-CHANGED: Interface FastEthernet3/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet3/1, changed state to up
%SPANTREE-2-RECV_PVID_ERR: Received 802.1Q BPDU on non trunk FastEthernet0/1 VLAN1.

%SPANTREE-2-BLOCK_PVID_LOCAL: Blocking FastEthernet0/1 on VLAN0001. Inconsistent port
type.

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up





Switch>enable
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa1/1
Switch(config-if)#switchport access vlan 10
% Access VLAN does not exist. Creating vlan 10
Switch(config-if)#int fa2/1
Switch(config-if)#switchport access vlan 20
% Access VLAN does not exist. Creating vlan 20
Switch(config-if)#int fa3/1
Switch(config-if)#switchport access vlan 30
% Access VLAN does not exist. Creating vlan 30
Switch(config-if)#int fa2/1
Switch(config-if)#switchport mode trunk

Switch(config-if)#
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet2/1, changed state to down

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet2/1, changed state to up

Switch(config-if)#exit

```

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Edit
	Successful	PC0	PC3	ICMP		0.000	N	0	(edit)
	Failed	PC1	PC3	ICMP		0.000	N	1	(edit)