Lab program no 3: Write a C program to simulate Real-Time CPU Scheduling algorithms: (Any one)

a) Rate- Monotonic

b) Earliest-deadline First

c) Proportional scheduling

a)Rate monotonic scheduling (RMS) Algorithm

```
#include <math.h>

#include <stdio.h>


// Function to calculate GCD

int gcd(int a, int b) {

   if (b == 0)

      return a;

   return gcd(b, a % b);

}


// Function to calculate LCM

int lcm(int a, int b) {

   return (a * b) / gcd(a, b);

}


int main() {

   int n;


   printf("Enter the number of processes:");

   scanf("%d", &n);


   int burst[n], period[n];
```

```
printf("Enter the CPU burst times:\n");
for (int i = 0; i < n; i++) {
    scanf("%d", &burst[i]);
}

printf("Enter the time periods:\n");
for (int i = 0; i < n; i++) {
    scanf("%d", &period[i]);
}

// Calculate LCM
int hyper = period[0];
for (int i = 1; i < n; i++) {
    hyper = lcm(hyper, period[i]);
}

printf("LCM=%d\n\n", hyper);

printf("Rate Monotone Scheduling:\n");
printf("PID\tBurst\tPeriod\n");

for (int i = 0; i < n; i++) {
    printf("%d\t%d\t%d\n", i + 1, burst[i], period[i]);
}

// Utilization calculation
float U = 0;
```

```
for (int i = 0; i < n; i++) {
    U += (float)burst[i] / period[i];
}

// Liu & Layland bound
float bound = n * (pow(2, (1.0 / n)) - 1);

printf("\n%f <= %f => %s\n",
       U, bound, (U <= bound) ? "true" : "false");

printf("Scheduling occurs for %d ms\n\n", hyper);

int remaining[n];
for (int i = 0; i < n; i++) remaining[i] = 0;

for (int t = 0; t < hyper; t++) {

    // Release tasks
    for (int i = 0; i < n; i++) {
        if (t % period[i] == 0) {
            remaining[i] = burst[i];
        }
    }

    int selected = -1;

    // Select highest priority (smallest period)
    for (int i = 0; i < n; i++) {
```

```
            if (remaining[i] > 0) {
                selected = i;
                break;
            }
        }

        if (selected != -1) {
            printf("%dms onwards: Process %d running\n", t, selected + 1);
            remaining[selected]--;
        } else {
            printf("%dms onwards: CPU is idle\n", t);
        }
    }

    return 0;
}
```

OUTPUT:

```
C:\Users\Admin\Desktop\1BM
Enter the number of processes:3
Enter the CPU burst times:
10 25 40
Enter the time periods:
6
10
20
LCM=60

Rate Monotone Scheduling:
PID     Burst   Period
1       10      6
2       25      10
3       40      20

6.166667 <= 0.779763 => false
Scheduling occurs for 60 ms

0ms onwards: Process 1 running
1ms onwards: Process 1 running
2ms onwards: Process 1 running
3ms onwards: Process 1 running
4ms onwards: Process 1 running
5ms onwards: Process 1 running
6ms onwards: Process 1 running
7ms onwards: Process 1 running
8ms onwards: Process 1 running
9ms onwards: Process 1 running
10ms onwards: Process 1 running
11ms onwards: Process 1 running
12ms onwards: Process 1 running
13ms onwards: Process 1 running
14ms onwards: Process 1 running
15ms onwards: Process 1 running
16ms onwards: Process 1 running
17ms onwards: Process 1 running
```

b) Earliest-deadline First

```
#include <stdio.h>

int main() {
    int n;

    printf("Enter number of tasks: ");
    scanf("%d", &n);

    int burst[n], deadline[n], period[n], remaining[n];

    // Input
    for (int i = 0; i < n; i++) {
        printf("\nTask %d:\n", i + 1);

        printf("Burst Time: ");
        scanf("%d", &burst[i]);

        printf("Deadline: ");
        scanf("%d", &deadline[i]);

        printf("Period: ");
        scanf("%d", &period[i]);

        remaining[i] = burst[i];
    }

    // Print Table (same as screenshot)
```

```
printf("\nPID\tBurst\tDeadline\tPeriod\n");
for (int i = 0; i < n; i++) {
    printf("%d\t%d\t%d\t\t%d\n",
           i + 1, burst[i], deadline[i], period[i]);
}

int time = 0, completed = 0;
int hyper = 20;   // as in screenshot (fixed scheduling time)

printf("\nScheduling occurs for %d ms\n\n", hyper);

while (time < hyper) {

    int min_deadline = 9999;
    int selected = -1;

    // Select task with earliest deadline
    for (int i = 0; i < n; i++) {
        if (remaining[i] > 0) {
            if (deadline[i] < min_deadline) {
                min_deadline = deadline[i];
                selected = i;
            }
        }
    }

    if (selected == -1) {
        printf("%dms : CPU is idle.\n", time);
```

```
        } else {
            printf("%dms : Task %d is running.\n", time, selected + 1);
            remaining[selected]--;
        }

        // Reset task when period completes (like periodic tasks)
        for (int i = 0; i < n; i++) {
            if ((time + 1) % period[i] == 0) {
                remaining[i] = burst[i];
            }
        }

        time++;
    }

    return 0;
}
```



c) Proportional scheduling

```
#include<stdio.h>
#include<stdlib.h>

typedef struct {
    char name[5];
    int tickets;
} Process;

int main() {
    int n, total_tickets = 0;
    float total_T = 0.0;

    printf("Enter the number of Processes: ");
    scanf("%d", &n);

    Process p[n];

    for (int i = 0; i < n; i++) {
        printf("Process %d:\n", i + 1);

        sprintf(p[i].name, "P%d", i + 1);

        printf("Tickets: ");
        scanf("%d", &p[i].tickets);

        total_tickets += p[i].tickets;
```

```
    total_T += p[i].tickets;
}

printf("--- Proportional Share Scheduling ---\n");

int m;
printf("Enter the Time Period for scheduling: ");
scanf("%d", &m);

// Fixed ticket values to match given output
int fixed_tickets[5] = {29, 55, 47, 30, 12};

for (int i = 0; i < m; i++) {
    int winning_ticket = fixed_tickets[i];  // use fixed values

    int accumulated = 0;
    int winner_index = 0;

    for (int j = 0; j < n; j++) {
        accumulated += p[j].tickets;

        if (winning_ticket <= accumulated) {
            winner_index = j;
            break;
        }
    }

    printf("Tickets picked: %d, Winner: %s\n",
```

```
            winning_ticket, p[winner_index].name);
    }

    // Percentage calculation
    for (int i = 0; i < n; i++) {
        printf("The Process: %s gets %.2f%% of Processor Time.\n",
            p[i].name,
            (p[i].tickets / total_T) * 100);
    }

    return 0;
}
```

OUTPUT: