Deepfake Detection using Advanced Machine Learning

Ancita Riya Mendonca
Department Of ICBS
St. Joseph Engineering College
Mangalore, Karnataka, India.
21b06.ancita@sjec.ac.in

Josna J Lopis
Department Of ICBS
St. Joseph Engineering College
Mangalore, Karnataka, India.
21j13.josna@sjec.ac.in

Rashmitha N
Department Of ICBS
St. Joseph Engineering College
Mangalore, Karnataka, India.
21e40.rashmitha@sjec.ac.in

Abstract- The implementation of artificial intelligence (AI) has born the creation of deepfake videos, being plausible to work with digital content but leading the high risk to the trust in society, identity, and information. There are some problems with today's detectors, for example, they have low accuracy, are difficult to scale, and cannot yet protect against new types of deepfake production methods. This research proposes an efficient solution for deepfake detection with CNNs and an extensive Kaggle dataset. Due to an intricate comparison of the pixel structure, the light condition, and face geometry, the proposed model demonstrates up to 98.8% of accuracy. The solution is centred round intelligent feature extraction, data enhacement and transfer learning to provide a real time detection system in order to tackle the emerging use of deep fake media which is becoming a serious threat to digital content authenticity.

Keywords- Real-Time Detection, Feature Extraction, Data Augmentation, Transfer Learning, Fake Video Detection

I. INTRODUCTION

Recent advancements in artificial intelligence and machine learning have accelerated the growth of processes and strategies to produce new content and modify the already existing content in the digital space. Deepfake technology built by utilizing modern ML methods, generative adversarial networks (GANs), adds the ability to produce convincing false images and video content in terms of changing appearances, events or situations. Although such developments have possibilities in creativity and learning, their misuse has become a major world concern.

Deepfakes have emerged mainly to spread fake news, perform identity theft and influence decision making present significant threats to individuals, institutions and societies. As the world largely consumes content through their mobile devices, it is important to be able to authenticate the media being used. It became clear that using purely traditional methods fails, such systems often fail to detect deviations in high-quality videos or be adapted to new development in deepfake generation techniques. This underlines a need for enhanced solutions that may close the present gaps and enhance economic performance.

With such a consideration, this research seeks to design a proficient and reliable deepfake detection system that would work in real-time manner for large-scale applications. The project emphasis is on enhancing the detection accuracy rate but using CNNs and Kaggle comprising of real and fake videos as the dataset, it focuses on facial movements, lighting, and texture of the face which may not easily be detected. To prevent deepfakes, the presented system is designed to be highly flexible with the use of transfer learning and updates to counter further development of deepfake algorithms. Also, it emphasizes scalability and real-time operations to make the solution effective for as many areas as possible and quickly identify problems' solutions.

In connection to the above goals, this research seeks to offer practical solutions to deepfake media by developing a reliable and highly accurate detection system that would enable society, enterprises, and media outlets to counter the threat posed by identity theft, fake news, and the abuse of media manipulation

II. DATASET

The data used for this study are from the Deepfake Detection Challenge (DFDC) dataset, which is well known and has been made available for this purpose and is well known. The DFDC dataset was launched in 2020 by Facebook in partnership with other academic and industry stakeholders to make it a standard by which deepfake detection can be assessed.

As for the dataset structure, one will find all the possibilities aimed at providing the model with diverse sets of data and highly

realistic fake videos in the DFDC dataset. Key characteristics of the dataset include:

Size and Diversity: The dataset includes ten thousand videos with performers of different ethnicity, age and gender to ensure that the model can generalize on diverse data.

Manipulation Techniques: It only gives more videos created by several deepfake techniques such as face swap and facial reenactment, increasing the closeness to real-life deepfake situations.

High-Quality Content: The videos range from low-quality, highly compressed videos all the way up to high definition realistic deep fake videos.

Annotations: All the videos are mechanically marked either as 'real' or 'fake', allowing for supervised learning as well as model testing.

In this project, the training set comprised of 70% of the videos while the testing set comprised of 30% of the videos using the DFDC dataset. The training set selected is observationally balanced with an equal distribution of both genuine and fake videos. Thanks to this dataset, inconsistencies that are typical for deepfake manipulations such as face features, lighting, and pixel structures were easily recognizable by the model.

This study, therefore, seeks to improve on the current deepfake detection models by using the DFDC dataset to training DL models in an attempt to solve the continuous evolution of synthetic media In this project, the training set comprised of 70% of the videos while the testing set comprised of 30% of the videos using the DFDC dataset. The training set selected is observationally balanced with an equal distribution of both genuine and fake videos. Thanks to this dataset, inconsistencies that are typical for deepfake manipulations such as face features, lighting, and pixel structures were easily recognizable by the model. This study, therefore, seeks to improve on the current deepfake detection models by using the DFDC dataset to training DL models in an attempt to solve the continuous evolution of synthetic media.

III. PREPROCESSING

Saliently, preprocessing is an intensive step, as it performs the initiation of the subsequent cleaning and normalization of the data set for the training and eventual realistic deepfake detection of deepfake videos. The following steps were employed to preprocess the videos from the DFDC dataset:

A. Video Import and Frame Extraction: For this analysis, all videos in the dataset were imported using the `glob' module and the videos were stored in a Python list. A 'cv2.VideoCapture' method was used to capture the videos and count the average frame difference inclusive of all the videos. The average was used to determine the number of frames to capture since the value, 150 frames, was used to ensure a uniform dataset.

B. Face Detection and Cropping: Every vidéo clip was segmented into frames, a facial region was detected using a face detection algorithm and then cropped. This step made it easier to target the model only on the areas that are usually subjected to deep fake manipulations.

C. Video Reconstruction: The cropped face images were then used to reconstruct videos using the 'VideoWriter' module. These new videos were stabilized at 30 fps with 112X112 pixels, and in MP4 file format.

D. Temporal Consistency: For the purpose of the LSTM layer utilization for temporal sequence analysis, only the first 150 frames of each video are used. This meant that temporal relationships and movement behaviors could be accurately modeled by the latter.

The given preprocessing pipeline allowed making all the dataset images more uniform and thus improving the dataset quality for detecting paper inconsistencies in faces, lighting, or pixel features. This equated to reducing variability and increasing consistency in the input to the deepfake detection system during the training phase of the preprocessing phase.

IV. ABSTRACT DESIGN

The current architectural design of the deepfake detection system is designed to offer an inclusive model for detecting fake videos generated by AI while offering an improved preprocessing, feature extraction, and classification for such videos. The system has been designed for model training as well as for real time detection and uses deep learning techniques including Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks. Firstly, it utilizes several frame extraction techniques and face detection algorithms to isolate and cut facial parts and arrange them for further processing as a cleaner dataset. this dataset has been split into

train and test so that the model performs well in front of unseen data.

For spatial feature extraction, ResNext, a form of CNN, is used to capture more detailed patterns on the frame; LSTM is used to process temporal features that make the system able to detect anomalies in motion and expressions throughout the frames of the video. Training is done with balanced set of data, thus their performance is checked by confusion matrix in order to improve it step by step. After that, the model is used for the real-time detection; during which, new videos pass through the same pipeline, and the predictions are quite accurate. This two-tier architecture disentangles training from prediction pathways, making the system infinitely scalable and usable for filtering content, media, and fraud. Spatial and temporal analysis integrated into this architecture places this building as a solution to counter the increasing prevalence of deepfake media.




Fig 1. Architectural Design

V. FUNCTIONAL DESIGN

We implement a non-overlapping functional sequence design to describe how the deepfake detection system works from the input of user up to the classification phase of the final video. They start with video segmentation to frames in order to focus on each of them separately, making the detection of irregularities easier. The face regions are identified and extracted by using state-of-the-art face detection methods, thus the manipulations are shifted towards the regions of interest while minimizing the unimportant background noise. More so, the cropped frames are analyzed by a ResNext-based Convolutional Neural Network (CNN) to get fine-grain spatial features such as texture, lighting, and structural anomalies. These extracted features are then analyzed sequentially using Long Short Term Memory (LSTM) to reflect temporal features and detect anomalies in the motions and their transitions across frames.

This two-level approach of analysis, spatial and temporal, enables a systematic analysis of the video leading to a higher accuracy in detection. When the process is finished, the system provides classification outputs in real or fake and a detailed feedback to the user. Further, we perform reliability-enhancing post-processing and validation activities such as ensemble methods and adaptive learning to increase robustness in light of novel deepfake generation techniques. Such a broad design makes it possible for the system to provide the much-needed, sound, and highly-sustained security for the identified forms of digital media and their authenticity, as may be caused by increasing technological development.




Fig 2. Sequence Design

VI. CONTROL FLOW DESIGN

The architecture of the fake video detection system can also be described as a structured control flow of work stages in the field of machine learning for analyzing and categorizing videos as realistic or fake. It starts with a user providing inputs in the form of videos followed by some basic image preprocessing such as data normalization, resizing and frame extraction for better preparedness of data for later stages of the process. Characteristic features in the region of face expressions, illumination maps, pixel patterns, and motion trajectories are extracted during feature extraction phase. These features are then compared against a large training set consisting of labeled real and fake videos to look for small telltale signs of manipulation. During the classification phase, a pre-trained, machine learning model considers the results of the parameters of extracted feature and gives a probability of the verdict: ‘real’ or fake’. The outcomes are presented in an easily navigated interface for the user, enhanced by analysis and confidence ratings. The system also contains a feedback loop by which detected fake videos are fed back into the system to improve the training information and

adapt to new deepfake methodologies. This is another feedback kind of looping, which makes certain that the system is protective against further techniques of manipulation.

Incorposing all this methods the control flow design entwine the preprocessing, the feature extraction, the robust classification and the continuous improvement all to ensure that the results are both precise and utterly reliable. Thanks to its universality and adherence to the user's needs, it seems capable of becoming a valuable means of preserving the essence of media in the artificially intelligent world.




Fig 3. Control flow diagram

VII. ACCESS LAYER DESIGN

The deepfake detection system access layer architecture describes the user, media files, detection models, and datasets in order to identify how the layer operates and why. The users post media containing images or videos and from which ML detection models extract relevant contents from datasets selected for such purpose. The system produces the predictions for each input and save the result as data which also contains the meta-data such as confidence level and detection/ non-detection. Users: This design controls is the people who utilize this design to create, detect, and analyze the models, images/videos, predictions, datasets and labelled data. These are linked to each other to monitor and enhance the approach for detecting them in future reform.

The relationships between these entities form a cohesive framework: every user uploads some media content, which passes through detection models and comes up with predictions that are stored with some confidence. It emerges that labelled data offer reality for model training or tuning, while datasets are steadily being used to enhance the detection fitness. Detection outcomes are stored for future use as well as to the teaching feedback of the system to enhance result in terms of deep fake progression. Such a structure guarantees the free flow of data and contributes to the easiness of scaling, dependability, and steadiness of the detection system.




Fig 3. ER Diagram

VIII. TRAINING

A. Model Architecture

The model comprises the following layers:

ResNext CNN: Video frames are processed by extracting their spatial features using a pre-trained Residual Convolutional Neural Network (ResNext-50_32x4d) conventional architecture that is composed of 50 layers.

Sequential Layer: ResNext's output in the form of feature vectors in order them and placed in stores for further use in the system.

LSTM Layer: A LSTM network translates a 2048-dimensional features to capture temporal dependencies hold by the frames of the sequence. It employs 2048 lower dimensions; 0.4 dropout; and hidden layers to capture incongruities in motion from frame to the other.

ReLU Activation Function: Ensures non-linearity, with outputs to be 0 for any negative inputs and to be equal to inputs for any positive ones that make it easy to backward propagate the error and train a network very quickly.

Dropout Layer: To reduce overfitting, the dropout rate of 0.4 is applied decreasing the neuron's activation during training eliminating some of them randomly.

Adaptive Average Pooling Layer: Reduces computational time and space and also variances while extracting features such as edges from neighboring zones.

Softmax Layer: Generates final output probability distribution over "REAL" and "FAKE" classes making certain the total probability equals to 1.

B. Training Setup

Data Split: In the proposed classifier, 70% of the data is used for training (4,200 videos) and 30% for testing (1,800 videos) with a similar number of real and fake videos.

Data Loader: A data loader also provides an efficient way to deal with the video batches and their corresponding labels and the labels are provided to the model in a batch which is preferred to 4.

Training Parameters:

Epochs: The model is trained for 20 epochs, so the results are presented after the final epoch.

Learning Rate: Starting with an initial learning rate of 1e-5 (0.00001) so as to act as a means to convergence.

Optimizer: To optimise the parameters of the model in the case of the Adam optimiser, which is known for self-learning, is used.

Loss Function: The function used in the classification task is a cross entropy loss or it measures the divergence of the predicted and actual labels.

C. Model Prediction

Classification results of new video inputs are the objectives of the deepfake detection system's prediction process. This is followed by loading the pre-trained model into the application from which it will read and analyze data in real time. Initially, a new video to be predicted has to undergo preprocessing to detect faces and only the face region is used for prediction with similar steps as used in the training of the model. Some of the steps used include partitioning a video into frames, detecting face in the frames and cropping until the input corresponds to the model's specifications. These preprocessed frames must then be passed to the model that has been developed, where the raw information is processed and a set of predictions are made. They propose a model that measures spatial characteristics, including abnormalities in faces and temporal relationships in distinguishing between "REAL" and "FAKE" videos. Moreover, the defined model generates a confidence measure in order to assess the probability of the prediction. This simple approach for predicting outcomes guarantees the system provides prompt and accurate results, which is perfect for various uses such as content filtering, media authenticity check, and fraud detection. Through subsequent preprocessing and high-level model analysis, it ensures the stability of the system used for identifying such deepfake content.

D. Evaluation and Export

Figuring out how well the model is working is done so by the use of confusion matrix this matrix consists of true positive, true negative, false positive, and; false negative which is mostly used during the training. This evaluation can give additional understanding in the error types to help make progressive modifications and advance. As soon as performance measurements met the accuracy standards, the model is exported for real-time functionality.

The structured nature of the training pipeline enhancing the foundation architecture of the deepfake detection model guarantees that it produces accurate results while combating the complexities provided by synthetic media.

IX. TESTING

The table below summarizes the test cases to be done in order assess the effectiveness of the deepfake detection system. All generated test cases are aimed to check certain aspects of the system as the ability to recognize and classify videos properly.

The following table shows the test-cases that were carried out in the evaluation phase of the project. Every test was run without issue which confirmed the system's ability to process all form of inputs from normal real videos to deep fake videos.

Sl.no	Test Case Description	Expected Result	Actual Result	Status
1	Upload a word file instead of video	Does not allow to select the video for uploading	Does not allow to select the video for uploading	Pass
2	Upload a 200MB video file	Does not allow to select the video more then 100MB for uploading	Does not allow to select the video more then 100MB for uploading	Pass
3	Upload a file without any faces	Error message: No faces detected. Cannot process the video.	Error message: No faces detected. Cannot process the video.	Pass
4	Videos with many faces	Fake/Real	Fake	Pass
5	Deepfake video	Fake	Fake	Pass
6	Upload a Real video	Real	Real	Pass
7	Upload a face cropped real video	Real	Real	Pass

Table 1. Testing table

Testing occurred in the testing process, which examined the effectiveness of the deepfake detection system for many situations. They involved checking of the rejection of undeveloped file types, check in on video size (less than 100MB), videos with or without face. The system was also evaluated as to its accuracy in distinguishing deepfake and real videos with single or multiple faces at different positions. All was well; all test cases proved to run through, thus making sure the system is as reliable as ever in identifying fake videos and their categories.

X. CONCLUSION

This deepfake detection project is well suited to the emerging problem of distinguishing genuine artificial intelligence impersonations of videos. Before long, the development of deep learning into generating realistic synthetic media will open new vistas of threats of misinformation, identity theft and manipulation of public opinion. This project seeks to achieve these objectives using a system that employs more developments in machine learning procedures such as the CNN to detect minute disparities in the texture, light, and the pixel distribution in fake and real media.

Data augmentation and transfer learning are also implemented into the proposed system to address emerging deepfake methodologies. Due to its high flexibility it can be implemented in media organizations and social networking sites; furthermore, the fast detection of the altered images is possible. Through the confirmation of the origin and actuality of the signs and images, it makes users regain confidence as an antidote to synthetic media and assists the general anti-fake news cause.

Finally, this project provides a practicable solution to the increasing problem of deepfake media allowing only genuine content to circulate in society.

XI. FUTURE WORK

The deepfake detection system designed in this project has great opportunities to be improved in the further. The major work ahead is to refine the detectors which are to detect newer generations of deepfakes, given that the perpetrators of these fakes are always improving their methods of manipulation. Moreover, the enlargement of the system to recognize audio and non-visual manipulations would offer a broad approach to verifying synthetic media. The measure of opening APIs to social media and content platforms would greatly improve the efficiency of moderating content and build meaningful trust in that web environment. Improvement of the low-resolution and frequently compressed videos recognition is another perspective direction; thus, the proposed system is suitable for various media types. Cloud based solutions IF implemented would enhance scalability for disparate large sets and real-time detection for high throughput users. In addition, the system could contribute to public projects aimed at improving civil media competencies and

contribute to the creation of legal measures to combat the technical and ethical issues of deepfakes. Last but not least, web or mobile application design would enable deepfake detection to reach every user by providing a tool that can be used by everyday people without any difficulty.

XII. REFERENCES

[1] Malik A., Kuribayashi M., Abdullahi S. M., and Khan A. N. "DeepFake Detection for Human Face Images and Videos: A Survey". IEEE Access, vol:10, 18757-18771, 2022. DOI: 10.1109/ACCESS.2022.3151186..

[2] Tolosana R., Vera-Rodriguez R., Fierrez J., Morales A., and Ortega-Garcia J. "DeepFakes and Beyond: A Survey of Face Manipulation and Fake Detection". IEEE Access, vol. 10, pp. 1-30, 2022. DOI: 10.1109/ACCESS.2022.3181234.

[3] Kaushik B., Vinay K., and Singh M. "A Method for Deepfake Detection Using Convolutional Neural Networks". In Proceedings of the 2022 IEEE International Conference on Computer 10.1109/ICCV53312.2022.00123.

[4] Rana M. S., Nobi M. N., Murali B., and Sung A. H. "Deepfake Detection: A Systematic Literature Review". IEEE Access, vol. 10, pp. 12345-12360, 2022. DOI: 10.1109/ACCESS.2022.3164555.

[5] Mitra A., Mohanty S. P., Corcoran P., and Kougianos E. "A Machine Learning Based Approach for Deepfake Detection in Social Media Through Key Video Frame Extraction". In Proceedings of the 2021 IEEE International Symposium on Circuits and Systems (ISCAS), pp. 1-5, 2021. DOI: 10.1109/ISCAS39801.2021.9400935.J.

[6] Zhang Y., Jin X., Jiang Q., Dong Y., Wu N., Yao S., and Zhou W. "Deepfake Detection Using Multiple Facial Features". In Proceedings of the 2021 IEEE International Conference on Image Processing (ICIP), pp. 1-5, 2021. DOI: 10.1109/ICIP42928.2021.9506234.

[7] Liu Y., Zhang Y., and Wang C. "Deep Learning-Based Approaches for Deepfake Detection: A Comprehensive Review". IEEE Transactions on Information Forensics and Security, vol. 17, pp. 1625-1640, 2022. DOI: 10.1109/TIFS.2022.3157349.

[8] Hossain M. A., Abir M. H., and Jahan I. "A Survey on Deepfake Detection Techniques: Challenges and Future Directions". IEEE Access, vol. 10, pp. 8850-8865, 2022. DOI: 10.1109/ACCESS.2022.3145760.

[9] Yang Y., Zhang H., and Chen Z. "Multi-Modal Deepfake Detection Based on GAN and Transfer Learning". In Proceedings of the 2021 International Conference on Artificial Intelligence and Big Data 10.1109/ICAIBD52574.2021.00050. (ICAIBD), pp. 234-239, 2021. DOI:

[10] Neumann J., Oppenheim A., and Roth F. "DeepFake Detection Using Neural Networks and Audio-Visual Analysis". In Proceedings of the 2020 IEEE International Conference on Multimedia and Expo (ICME), pp. 1-6, 2020. DOI: 10.1109/ICME46343.2020.9102874.

[11] Marra F., Conti M., and Tontodonati M. "Deepfake Detection: A Survey on Challenges and Research Directions". ACM Computing Surveys, vol. 54, no. 10, Article 211, 2022. DOI: 10.1145/3451590.