

Simple Text Editor

In this challenge, you must implement a simple text editor. Initially, your editor contains an empty string, S . You must perform Q operations of the following 4 types:

1. **append(W)** - Append string W to the end of S .
2. **delete(k)** - Delete the last k characters of S .
3. **print(k)** - Print the k^{th} character of S .
4. **undo()** - Undo the last (not previously undone) operation of type 1 or 2, reverting to the state it was in prior to that operation.

Input Format

The first line contains an integer, Q , denoting the number of operations.

Each line i of the Q subsequent lines (where $0 \leq i \leq Q$) defines an operation to be performed. Each operation starts with a single integer, t (where $t \in \{1, 2, 3, 4\}$), denoting a type of operation as defined in the Problem Statement above. If the operation requires an argument, t is followed by its space-separated argument. For example, if $t = 1$ and $W = \text{"abcd"}$, line i will be **1 abcd**.

Constraints

- $1 \leq Q \leq 10^6$
- $1 \leq k \leq \text{length}(S)$
- The sum of the lengths of all W in the input $\leq 10^6$.
- The sum of k over all delete operations $\leq 2 \times 10^6$.
- All input characters are lowercase English letters.
- It is guaranteed that the sequence of operations given as input is possible to perform.

Output Format

Each operation of type 3 must print the k^{th} character on a new line.

Sample Input

Sample input	Sample output
8	c
1 abc	y

3 3	a
2 3	
1 xy	
3 2	
4	
4	
3 1	

Explanation

Initially, S is empty. The following sequence of 8 operations are described below:

1. $S = ""$. We append **abc** to S , so $S = "abc"$.
2. Print the **3rd** character on a new line. Currently, the **3rd** character is **c**.
3. Delete the last **3** characters in $S(abc)$, so $S = ""$.
4. Append **xy** to S , so $S = "xy"$.
5. Print the **2nd** character on a new line. Currently, the **2nd** character is **y**.
6. Undo the last update to S , making S empty again (i.e., $S = ""$).
7. Undo the next to last update to S (the deletion of the last characters), making $S = "abc"$.
8. Print the **1st** character on a new line. Currently, the **1st** character is **a**.