INSA

Analysis of MAC Protocols in Wireless Sensor Networks

A Comparative Study of WSN MAC Protocols

Clément Gauché

January 22, 2025



Table of Contents

1 Multiple Access Protocols

- Multiple Access Protocols
- MAC Protocols in WSN
- Conclusion

Channel Allocation in WSNs

Time and Frequency-Based Allocation

- Multiple access protocols divide channels:
  - Temporally (TDMA)
  - By frequency (FDMA)
- Ensures collision-free communication.



Figure: Channel allocation strategies: time-slot based (top) and time-frequency based (bottom) [1].

Classification of MAC Protocols

Based on Channel Access Type

- MAC protocols are classified by channel access methods:
  - Contention-based: CSMA, MACA
  - Scheduled: TDMA
- Ensures efficient and reliable communication.



Figure: General classification of MAC protocols based on channel access [2].

INSA

Table of Contents

2 MAC Protocols in WSN

- Multiple Access Protocols
- MAC Protocols in WSN
- Conclusion

Sensor-MAC (S-MAC)

A Protocol for Energy Efficiency

- **Proposed in 2002** by Wei Ye et al. for static sensor networks.
- **Features:**
  - Introduced periodic sleep schedules to save energy.
  - Reduces idle listening through synchronized duty cycles.
- **Trade-off:** Energy savings increase latency due to scheduled sleep periods.

S-MAC: Key Aspects and Energy Insights

- **Channel Access Type:**
  - Contention-based mechanism (CSMA/CA).
  - Nodes coordinate using synchronized sleep/wake schedules.
- **Clock Synchronization:**
  - Periodic synchronization packets ensure nodes align their active/sleep periods.
  - Coarse precision, sufficient for static networks.



Figure: Energy savings vs. sleep delay for S-MAC [3].

S-MAC: Localization, Security, and Mobility

- **Localization Capability:**
  - No inherent localization support.
  - Localization must be implemented externally at higher layers.
- **Security Mechanisms:**
  - No built-in security.
  - Requires external solutions for encryption or authentication.
- **Mobility Support:**
  - Poor support for mobility.
  - Best suited for static environments.

Timeout-MAC (T-MAC)

Dynamic Adaptation to Traffic

- **Proposed in 2004** by Tijs van Dam and Koen Langendoen.
- **Features:**
  - Extends S-MAC with dynamic duty cycles that adjust based on traffic.
  - Reduces idle listening during low traffic.
- **Trade-off:** More energy-efficient than S-MAC but introduces additional complexity.

T-MAC: Key Aspects and Scheduling

- **Channel Access Type:**
  - Contention-based mechanism (CSMA/CA).
  - Duty cycles adapt dynamically to traffic levels.
- **Clock Synchronization:**
  - Similar to S-MAC, periodic synchronization ensures alignment of active periods.



Figure: Scheduling differences between S-MAC and T-MAC [4].

T-MAC: Localization, Security, and Mobility

- **Localization Capability:**
  - Lacks inherent localization support.
  - External systems must be used for localization.
- **Security Mechanisms:**
  - No built-in security features.
  - Requires external encryption or authentication layers.
- **Mobility Support:**
  - Poor support for mobility.
  - Best suited for static networks.

Berkeley-MAC (B-MAC)

Low-Power and Flexible Protocol

- **Proposed in 2004** by Joseph Polastre et al.
- **Features:**
  - Introduced Low-Power Listening (LPL) to reduce idle listening.
  - Flexible and adaptable to diverse WSN scenarios.
- **Trade-off:** Highly energy-efficient but may not handle dense networks optimally.

B-MAC: Key Aspects and Energy Insights

- **Channel Access Type:**
  - Contention-based mechanism with Low-Power Listening (LPL).
  - Nodes periodically sample the channel to detect activity.
- **Clock Synchronization:**
  - Operates asynchronously; no global synchronization required.



Figure: Energy consumption comparison: S-MAC vs. B-MAC [5].

B-MAC: Localization, Security, and Mobility

- **Localization Capability:**
  - No built-in localization features.
  - External localization systems can be integrated.
- **Security Mechanisms:**
  - No built-in security mechanisms.
  - Requires external solutions for secure communication.
- **Mobility Support:**
  - Moderate support for slow-moving nodes.
  - Not designed for high-mobility environments.

INSA

Zebra-MAC (Z-MAC)

Hybrid Protocol for Dynamic Networks

- **Proposed in 2005** by Injong Rhee et al.
- **Features:**
  - Combines CSMA for low contention and TDMA for high contention.
  - Balances throughput and energy efficiency by adapting to traffic.
- **Trade-off:** Requires global synchronization, which adds overhead.

Z-MAC: Channel Access and Synchronization

- **Channel Access Type:**
  - Hybrid mechanism:
    - CSMA for low contention (e.g., sparse networks).
    - TDMA for high contention (e.g., dense networks).
- **Clock Synchronization:**
  - Requires global clock synchronization to align TDMA slots.
  - Periodic synchronization messages ensure precise timing.



Figure: Comparison of Z-MAC and B-MAC under high contention [6].

Z-MAC: Localization, Security, and Mobility

- **Localization Capability:**
  - Does not include localization features.
  - Synchronization framework could support external localization systems.
- **Security Mechanisms:**
  - No inherent security mechanisms.
  - Requires external layers for encryption and authentication.
- **Mobility Support:**
  - Limited support for mobility.
  - Requires reconfiguration and resynchronization for moving nodes.

INSA

Geographic Adaptive Fidelity (GAF)

Energy Conservation Through Localization

- **Proposed in 2001** by Ya Xu et al.
- **Features:**
  - Divides the network into virtual grids.
  - Activates one node per grid cell to handle communication.
- **Trade-off:** Relies on localization mechanisms like GPS for grid formation.

GAF: Channel Access and Synchronization

- **Channel Access Type:**
  - Localization-based mechanism.
  - Activates only one node per grid cell to reduce energy consumption.
- **Clock Synchronization:**
  - Synchronization required within each grid cell.
  - No global synchronization needed across the entire network.



Figure: Virtual grid network in GAF [7].

GAF: Localization, Security, and Mobility

- **Localization Capability:**
  - Built-in localization capability using virtual grids.
  - Nodes determine their grid cell based on geographic location (e.g., GPS).
- **Security Mechanisms:**
  - Lacks built-in security features.
  - Requires external solutions for secure communication.
- **Mobility Support:**
  - Excellent support for mobility.
  - Automatically assigns new active nodes as devices move across grid cells.

Comparison Table

2 MAC Protocols in WSN

Protocol	Channel Access	Sync	Localization	Security	Mobility
S-MAC	CSMA/CA	Yes	No	No	Poor
T-MAC	CSMA/CA	Yes	No	No	Poor
B-MAC	CSMA (LPL)	No	No	No	Moderate
Z-MAC	Hybrid (TDMA+CSMA)	Yes	No	No	Limited
GAF	Localization-based	Yes	Yes	No	Good

Table: Comparison of MAC Protocols

Table of Contents

3 Conclusion

- Multiple Access Protocols
- MAC Protocols in WSN
- Conclusion

Selecting the optimal MAC Protocol

3 Conclusion

- **No Perfect Solution**:
  - Trade-offs are inevitable between energy efficiency, latency, and reliability.
  - Example: S-MAC prioritizes energy efficiency, but latency increases.
- **According to specific needs**:
  - **Energy Efficiency**: Key for long-term deployments (e.g., S-MAC, B-MAC).
  - **Low Latency**: Crucial for real-time systems (e.g., T-MAC, Z-MAC).
  - **Scalability**: Needed for dense networks (e.g., Z-MAC, hybrid protocols).
  - **Mobility Support**: Required for dynamic environments (e.g., GAF).
- **Optimize Energy, Performance, and Scalability**:
  - Protocols like Z-MAC strike a balance with hybrid approaches.
  - Simulate protocols under realistic conditions (e.g., using NS-3 or Contiki).

Conclusion

- No MAC protocol is perfect: trade-offs depend on application needs.
- Recommendations:
  - S-MAC: Energy-efficient, static networks.
  - T-MAC: Dynamic traffic scenarios.
  - B-MAC: Flexible and asynchronous.
  - Z-MAC: Hybrid, high contention support.
  - GAF: Suitable for localization and mobile environments.

Bibliography

References (1/2)

Panos Alevizos, Efthymios Vlachos, and Aggelos Bletsas.
Inference-Based Distributed Channel Allocation in Wireless Sensor Networks.
March 2017.

Mahdi Dibaei and Ali Ghaffari.
Full-duplex medium access control protocols in wireless networks: a survey.
Wireless Networks, 26(4):2825–2843, May 2020.

Wei Ye, John Heidemann, and Deborah Estrin.
An Energy-Efficient MAC Protocol for Wireless Sensor Networks.

Yu-Chia Chang and Jang-Ping Sheu.
An Energy Conservation MAC Protocol in Wireless Sensor Networks.
Wireless Personal Communications, 48:261–276, January 2009.

Joseph Polastre, Jason Hill, and David Culler.

INSA

Q&A

Thank you for listening!
Your feedback will be highly appreciated!