XPoster — Three-Round Review Workflow and Correction Record

Independent specification reviews against the user understanding, merge decisions, Python workflow and idle handshake plan

REVIEW METHOD: Each round treats the then-current unified plan as if newly supplied by the user. The reviewer compares it independently against the named source documents, records concrete mismatches or ambiguities, corrects the working plan, and only then starts the next round. The reviews concern the DOCUMENT, not live X API or Windows execution.

1. Reference documents and review rules

Primary acceptance authority: GPT_Understanding.txt. Mandatory comparison sources: Person1Person2MergeIdea(2).txt; MergeConvoAndMissingDetails.txt; LocalTwitterPoster_ProgressV2(1).txt; XPoster — Idle Handshake Work Plan.txt; XPoster_Python_Workflow_Function_Design_COMPLETE(1).pdf; and the Person 1/Person 2 specifications. DebugLogReadMe.txt and LocalTwitterPosterDesignV2.txt were also checked for exact contract fidelity.

Review gate	What is checked
Source precedence	Latest user decisions override older draft examples; no obsolete assumptions.
Functional completeness	Normal/Repost, archive-before-Python, GUI, history, OAuth2, Python, handshake.
Protocol correctness	Eight events, JSONL, DEBUG, RequestId, byte progress, terminal semantics.
Engineering safety	Runspace, UTF-8, timeout, state machine, unknown result, no auto retry.
Document quality	English only, no dates/timestamps, matching Word/PDF, legible tables and diagrams.

2. Review 1 — source fidelity and completeness

INDEPENDENT INPUT: First consolidated draft, reviewed as a new submission against GPT_Understanding.txt, Person 1/Person 2 merge notes, ProgressV2 and the specialist Python/handshake plans.

Finding	Correction applied to working plan
Older Person 2 design still assumed OAuth 1.0a and its API_KEY format.	Replaced with selected OAuth2 User Context and the six chosen X_Keys.txt fields; retained live verification gate.
Older source examples emitted Percent in Python PROGRESS.	Locked BytesUploaded and BytesTotal as the Python fields; PS1 computes percentage; no Python Percent.
Person 2 lacked permanent Debug/Output and Repost preload.	Restored both, using the approved GUI/state names; Repost is review-only and manually posted.
Person 2 appended status-oriented history rows.	Specified exactly eight columns, one archive row per attempt, blank PostURL/Timestamp until success.
Some source examples saved history only after X success.	Made ExportPostRecord a mandatory pre-Python transaction; remote failure preserves local record.
The Python plan used structured DEBUG, while Person 2 used stderr diagnostics.	Structured DEBUG Source=PYTHON on stdout; raw/unexpected stderr only; existing logger API.

ADDITIONAL DRAFT CORRECTION: In the first submitted unified draft, the Python function sequence loaded config before reading the request. Compared with the specialist Python plan, this delayed RequestId extraction. The corrected plan now reads stdin and extracts RequestId before loading/validating configuration.

REVIEW 1 RESULT: Source-level conflicts resolved in the consolidated plan. No production code or live API test performed.

3. Review 2 — operational and failure-path consistency

INDEPENDENT INPUT: Corrected Review-1 specification, reread as a new submission against the full handshake and Python function/workflow contracts, with special attention to race conditions and truthfulness.

Finding	Correction applied to working plan
A byte-transfer completion can be mistaken for completed remote media processing.	Separated PROGRESS BytesUploaded=BytesTotal from MEDIA_COMPLETE; processing status remains explicit.
A repeated heartbeat PROGRESS could falsely imply additional bytes uploaded.	Allowed DEBUG/status liveness rather than fabricated byte progress.
A health check may still be active when the user presses Post.	Added single-flight rule, suspension, safe cleanup and no competing health operations during posting.
The 10-second timer might be confused with Person 2's 100 ms GUI event pump.	Separated their responsibilities explicitly; posting transport and health timer are independent.
A health check against an API root may return HTTP 404 despite reachability.	Required a verified authenticated read-only endpoint; HTTP reachability is not proof of authenticated health.
Unknown final post outcome might invite a duplicate manual or automatic retry.	Required manual X reconciliation and explicit user confirmation before another attempt; no automatic resend.
Python/PS1 failures might leak credentials in diagnostic output.	Added safe error mapping and secret scans across stdout, stderr, GUI and log.

ADDITIONAL DRAFT CORRECTIONS: The corrected plan now uses PostRecordPath/TXT-path identity to update the same eight-column history row, requires try/finally-style recovery when ExportPostRecord fails before Python starts, tags PS1-origin handshake launch failures [PS1], and calls out the 10-second check may have rate-limit/cost impact.

REVIEW 2 RESULT: Posting/handshake concurrency, processing status, error recovery and diagnostics made explicit.

4. Review 3 — developer handoff and document consistency

INDEPENDENT INPUT: Corrected Review-2 specification, reread as a new submission against GPT_Understanding.txt, both merge documents, ProgressV2, the Python workflow, and the handshake plan. This pass focuses on executable handoff without hidden assumptions.

Finding	Correction applied to final plan
The exact existing DebugLog.ps1 function signature could be obscured by an invented wrapper.	Locked dot-source, Initialize-DebugLog -Version 1 -PerRun, Write-DebugLine and Get-DebugLogPath.
CSV cannot intrinsically carry a rich hyperlink label independently of Excel.	Kept eight visible columns; identified Excel formula/escaping and round-trip path resolution as a verification gate.
An illustrative Repost JSON might be misread as an implemented Excel launch method.	Marked Repost JSON as an application boundary and Excel template/invocation as deferred.
Person 2 timeouts and media limits could be mistaken for user-approved facts.	Labeled timeout numbers as engineering defaults and API constraints as VERIFY BEFORE LIVE USE.
Earlier Stage 1 communication proof might be mistaken for an authenticated demo post.	Separated HTTPS reachability from OAuth2/authenticated demo-post release gate.
A review document might imply Python mock tests prove PowerShell/live X success.	Retained Person 2's reported mock 22/22 only as historical evidence; required re-run on revised contract and target machine.
Documentation may accidentally include timestamps or mixed-language text.	Removed document dates and sample time-based RequestIds; retained the functional history column named Timestamp.

ADDITIONAL VISUAL CORRECTIONS: The rendered first version substituted serif fonts for the intended code/normal text and placed a short trailing paragraph on a nearly empty last page. Font names were changed to installed Carlito/Liberation Mono, run-level monospace formatting was made explicit, and spacing was tightened before final rendering.

REVIEW 3 RESULT: Final specification is suitable as a design handoff, subject to explicitly marked external verification and the separate coding-approval process.

5. Verification of deliverables

The Word plan and PDF plan are generated from one content model to prevent textual divergence. The same applies to this report. Rendered PDF/Word pages and text are checked for truncation, English-only content, absence of document timestamps/dates, exact event vocabulary, exact configuration keys, and the mandatory archive/handshake workflows.

Final requirement	Disposition
One unified plan, not a document bundle	Included.
PDF and editable Word, matching content	Generated from one source.
Person 1 requirements plus Person 2 safeguards	Merged with precedence.
Complete Python workflow and eight-event protocol	Included.
Idle handshake every 10 seconds, silent success, failure warning	Included.
Three independent reviews with recorded corrections	This report.
No dates/timestamps in deliverables	Document metadata and sample IDs kept date-free; functional Timestamp column remains.
No claim of live API or PowerShell execution	Explicitly excluded.

6. Remaining verification gates — not document defects

Live OAuth2 authorization and refresh, X v2 media endpoint permissions and current constraints, real upload byte accounting, read-only health-check endpoint/rate limits, PowerShell 5.1 process/GUI integration, and safe Excel hyperlink/Repost round-trip must be proven during implementation. They are deliberately not represented as completed tests.