


Bachelor's thesis defense

Nikolaj Dybdahl Rathcke



Background

- Inexpensive sequencing data
- Centroid-based clustering
- What does *klust* solve?



t: Threshold similarity



Centroid



Member sequence



Distance metric

- Sequence alignment is expensive
- k -mer is cheap to compute
- The Manhattan distance
- Windows ensures that string of different length are still comparable
- K-DIST

k -mer	AA	AC	AG	AT	CA	CC	CG	CT	GA	GC	GG	GT	TA	TC	TG	TT
s1				2			1	1					1	2		
s2				2			1	1					2	2		1



K-DIST example with $k = 2$

Manhattan distance: 4

A	T	C	T	A	T	C	G		
T	T	A	T	C	T	A	T	C	G



K-DIST example with $k = 2$

Manhattan distance: 2

A	T	C	T	A	T	C	G		
T	T	A	T	C	T	A	T	C	G



K-DIST example with $k = 2$


Manhattan distance: 0

	A	T	C	T	A	T	C	G	
T	T	A	T	C	T	A	T	C	G



Clustering algorithm

- Greedy algorithm improves time complexity



Clustering algorithm

- Greedy algorithm improves time complexity
- Intersection criterion to quickly dismiss sequences that are not likely to belong to a cluster

Intersection criterion

$$|K(s) \cap K(c)| \geq |K(c)| \cdot id$$

<i>k-mer</i>	AA	AC	AG	AT	CA	CC	CG	CT	GA	GC	GG	GT	TA	TC	TG	TT
s1				2			1	1					1	2		
s2				2			1	1					2	2		1



Clustering algorithm

- Greedy algorithm improves time complexity
- Intersection criterion to quickly dismiss sequences that are not likely to belong to a cluster

Intersection criterion

$$|K(s) \cap K(c)| \geq |K(c)| \cdot id$$

<i>k-mer</i>	AA	AC	AG	AT	CA	CC	CG	CT	GA	GC	GG	GT	TA	TC	TG	TT
K(s1)				1			1	1					1	1		
K(s2)				1			1	1					1	1		1



Clustering algorithm

- Greedy algorithm improves time complexity
- Intersection criteria to quickly dismiss sequences that are not likely to belong to a cluster
- Ordering centroids can improve performance



Clustering algorithm

- Greedy algorithm improves time complexity
- Intersection criteria to quickly dismiss sequences that are not likely to belong to a cluster
- Ordering centroids can improve performance
- The centroid structure




Clustering algorithm

- Greedy algorithm improves time complexity
- Intersection criteria to quickly dismiss sequences that are not likely to belong to a cluster
- Ordering centroids can improve performance
- The centroid structure
- K-CLUST



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id$

$\text{Distance}(s, c.\text{link}) \geq id$

Update centroid list



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id$

$\text{Distance}(s, c.\text{link}) \geq id$

Update centroid list



K-CLUST




Intersection criteria

$\text{Distance}(s, c) \geq id$

$\text{Distance}(s, c.\text{link}) \geq id$

Update centroid list

K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list



K-CLUST




Intersection criteria

$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

K-CLUST




Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

K-CLUST



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria


$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1

K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.link) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$


$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list

Close match set
Rejects = 1



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id$


$\text{Distance}(s, c.\text{link}) \geq id$

Update centroid list


Close match set
Rejects = 1



K-CLUST



K-CLUST



Intersection criteria

$\text{Distance}(s, c) \geq id?$

$\text{Distance}(s, c.\text{link}) \geq id?$

Update centroid list




K-CLUST

Intersection criteria

$\text{Distance}(s, c) \geq \text{id?}$

$\text{Distance}(s, c.\text{link}) \geq \text{id?}$

Update centroid list



s has a link to the centroid it was close to matching




Results

- Evaluation of K-CLUST with synthetic data
- Evaluation of klust on real data



Multi-dimensional scaling of clustering output from SILVA

Clustering on 40 very different sequences with 9 copies of each that has been altered.



Comparison of `klust` and `USEARCH` on RDP

Clustering algorithm	Time (sec.)	Throughput (seqs./sec.)	Clusters	Cluster sizes	Max memory
K-CLUST, $k = 5$, $id = 0.85$, $m = 8$, incr. sort	5420.8	557.10	220 982	Max. 100 832 Avg. 13.67 Min. 1	≈ 2031 MB
K-CLUST, $k = 5$, $id = 0.9$, $m = 8$, incr. sort	11 948.7	252.74	344 122	Max. 55 992 Avg. 8.78 Min. 1	≈ 2031 MB
USEARCH, $id = 0.95$, decr. sort <code>-cluster_smallmem</code>	6874.0	439.20	261 880	Max. 65 654 Avg. 11.50 Min. 1	≈ 1433 MB
USEARCH, $id = 0.97$, decr. sort <code>-cluster_smallmem</code>	11 980.0	252.00	471 982	Max. 56 279 Avg. 6.40 Min. 1	≈ 2560 MB



Future work

- Link optimization effectively using max rejects
- Optimizing distance metric to better recognize mutations
- A better merge strategy for a solution using parallelization

