

Question **1**

Correct

Marked out of  
3.00

🚩 Flag question

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.

The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size \* size. Print a Print W for white spaces and B for black spaces.

Input:

2  
3  
5

Output:

WBW  
BWB  
WBW  
WBWBW  
BWBWB  
WBWBW  
BWBWB  
WBWBW

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,size,i,j,k;
5     scanf("%d",&n);
6     for(k=0;k<n;k++)
7     {
8         scanf("%d",&size);
9         for(i=0;i<size;i++)
10        {
11            for(j=0;j<size;j++)
12            {
13                if((i+j)%2==0)
14                    printf("W");
15                else
16                    printf("B");
17            }
18            printf("\n");
19        }
20    }
21 }
```


	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

Question **2**

Correct

Marked out of  
5.00

 [Flag question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2

2 W

3 B

Output:

WB

BW

BWB

WBW

BWB

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,size,i,j,k;
5     char a;
6     scanf("%d",&n);
7     for(k=0;k<n;k++)
8     {
9         scanf("%d %c",&size,&a);
10        for(i=0;i<size;i++)
11        {
12            for(j=0;j<size;j++)
13            {
14                if((i+j)%2==0)
15                {
16                    printf("%c",a);
17                }
18                else
19                {
20                    (a=='W')?printf("B"):
21                    printf("W");
22                }
23            }
24            printf("\n");
25        }
26    }
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓



Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n,v,p3,c,in,i,i1,i2,t,ti;
5     scanf("%d",&t);
6     for(ti=0;ti<t;ti++)
7     {
8         v=0;
9         scanf("%d",&n);
10        printf("Case #%d\n",ti+1);
11        for(i=0;i<n;i++)
12        {
13            c=0;
14            if(i>0)
15            {
16                for(i1=0;i1<i;i1++)
17                    printf("**");
18            }
19            for(i1=i;i1<n;i1++)
20            {
21                if(i>0)
22                    c++;
23                printf("%d0",++v);
24            }
25            if(i==0)
26            {
27                p3=v+(v*(v-1))+1;
28                in=p3;
29            }
30            in=in-c;
31            p3=in;
32            for(i2=i;i2<n;i2++)
33            {
34                printf("%d",p3++);
35                if(i2!=n-1)
36                    printf("0");
37            }printf("\n");
38        }
39    }
40 }
41
```

	Input	Expected	Got
✓	3	Case #1	Case #1
	3	10203010011012	102030100110
	4	**4050809	**4050809
	5	****607	****607
		Case #2	Case #2
		1020304017018019020	102030401701
		**50607014015016	**5060701401
		****809012013	****80901201
		*****10011	*****10011
		Case #3	Case #3
		102030405026027028029030	102030405026
		**6070809022023024025	**6070809022
		****10011012019020021	****10011012
		*****13014017018	*****130140
		*****15016	*****1501

Passed all tests! ✓