


Q-Explain the difference between centralized and distributed AAA deployment models by describing how each would work in a scenario where multiple Flipkart warehouses need secure network access.

Point	Centralized AAA	Distributed AAA
AAA Server Location	One or a few AAA servers are located at a central data center/cloud.	Each warehouse has its own local AAA server or authentication service.
Authentication	Ahmedabad, Mumbai, and Bangalore warehouses send authentication requests to the central AAA server.	Each warehouse can authenticate its users locally.
Management	User accounts and security policies can be managed from one central location.	Each warehouse may manage its own local users and policies.
Internet/WAN Dependency	A WAN connection to the central AAA server is normally required for authentication.	Local authentication can continue even if the WAN connection to another location is unavailable.
Example	An employee in the Ahmedabad warehouse logs in → request travels to the central AAA server → credentials are verified → access is granted.	An employee in Ahmedabad logs in → the local AAA server verifies the credentials → access is granted locally.

1. Centralized AAA

Flow:




For example, when a Flipkart employee in Mumbai connects to the warehouse Wi-Fi, the access point/network device sends the authentication request to the **central AAA server**. The central server verifies the employee and returns the appropriate access permissions.

Main idea: One central system controls authentication, authorization, and accounting for all warehouses.

2. Distributed AAA

Flow:



For example, an employee in the Bangalore warehouse connects to Wi-Fi. The request is handled by the **Bangalore local AAA server**, without needing to contact a central AAA server for every authentication.

Main idea: AAA services are placed closer to each warehouse and can operate more independently.