


Step 1: Open Your Packet Tracer File

Open your completed network topology.

Example:



Make sure:

- ☒ All cables are connected.
- ☒ Interfaces are green.
- ☒ IP addresses are configured.
- ☒ Default gateway is set on each PC (if using a router).

Step 2: Check the IP Address of Every PC

Click on **PC0**

Go to

Desktop



IP Configuration

Note the IP Address.

Example:

Device	IP Address
PC0	192.168.1.2
PC1	192.168.1.3
PC2	192.168.2.2
PC3	192.168.2.3
Router G0/0	192.168.1.1

Device	IP Address
Router G0/1	192.168.2.1

Your addresses may be different.

Step 3: Open the Command Prompt

Click **PC0**

Go to

Desktop



Command Prompt

Step 4: Ping Another PC

Suppose PC1's IP is

192.168.1.3

Type:

ping 192.168.1.3

Press **Enter**.

If successful, you'll see:

Reply from 192.168.1.3

Reply from 192.168.1.3

Reply from 192.168.1.3

Reply from 192.168.1.3

or

Success rate is 100 percent (4/4)

This means PC0 can communicate with PC1.

Step 5: Ping the Router

If the router's interface IP is:

```
192.168.1.1
```

Type:

```
ping 192.168.1.1
```

If successful:

```
Reply from 192.168.1.1
```

This confirms PC0 can reach the router.

Step 6: Ping PCs on Another Network

If PC2's IP is

```
192.168.2.2
```

Type:

```
ping 192.168.2.2
```

If routing is configured correctly, you should see:

```
Reply from 192.168.2.2
```

If you get

```
Destination host unreachable
```

or

```
Request timed out
```

there may be a routing, IP addressing, interface, or default gateway issue.

Step 7: Repeat on Every PC

Now test from each PC to every other PC and to the router.

Example checklist:

From PC0

```
ping PC1  
ping PC2  
ping PC3  
ping Router
```

From PC1

```
ping PC0  
ping PC2  
ping PC3  
ping Router
```

From PC2

```
ping PC0  
ping PC1  
ping PC3  
ping Router
```

From PC3

```
ping PC0  
ping PC1  
ping PC2  
ping Router
```

Example Commands

If your IPs are:

```
PC0 = 10.0.0.2  
PC1 = 10.0.0.3  
PC2 = 20.0.0.2  
PC3 = 20.0.0.3
```

```
Router G0/0 = 10.0.0.1  
Router G0/1 = 20.0.0.1
```

On **PC0**, type:

```
ping 10.0.0.3  
ping 20.0.0.2  
ping 20.0.0.3  
ping 10.0.0.1
```

On **PC2**, type:

```
ping 20.0.0.3  
ping 10.0.0.2  
ping 10.0.0.3  
ping 20.0.0.1
```