

Q-Assign static IP addresses to five devices (laptops or desktops) on your home or lab network, ensuring each is in the same subnet, and verify connectivity between them using the ping command.

Static IP Address Assignment

Device	IP Address	Subnet Mask	Default Gateway
Desktop-1	192.168.1.10	255.255.255.0	192.168.1.1
Desktop-2	192.168.1.11	255.255.255.0	192.168.1.1
Laptop-1	192.168.1.12	255.255.255.0	192.168.1.1
Laptop-2	192.168.1.13	255.255.255.0	192.168.1.1
Desktop-3	192.168.1.14	255.255.255.0	192.168.1.1

Steps Performed

- 1. Assigned a static IP address to each device.
- 2. Configured the subnet mask as **255.255.255.0**.
- 3. Configured the default gateway as **192.168.1.1**.
- 4. Connected all devices to the same LAN/switch.
- 5. Opened the Command Prompt on each device.
- 6. Verified connectivity using the ping command.

Ping Verification

From **Desktop-1 (192.168.1.10)**:

C:\> ping 192.168.1.11

Reply from 192.168.1.11: bytes=32 time<1ms TTL=128

C:\> ping 192.168.1.12

Reply from 192.168.1.12: bytes=32 time<1ms TTL=128

C:\> ping 192.168.1.13

Reply from 192.168.1.13: bytes=32 time<1ms TTL=128

C:\> ping 192.168.1.14

Reply from 192.168.1.14: bytes=32 time<1ms TTL=128