

Q- Configure MAC filtering on your Wi-Fi router by adding your device's MAC address to the allowed list, then try connecting with another device not on the list and observe the result.
Hint: You can find your device's MAC address in the network settings.

To configure **MAC filtering** on a wireless router by adding a device's MAC address to the allowed list and testing another device that is not included in the list.

Parameter	Configuration
Wireless Router	Wireless-N Broadband Router
MAC Filtering	Enabled
Access Resolution	Permit PCs listed below
Allowed MAC Address	00:E0:F9:B8:E9:BB
Allowed Device	Laptop 1
Other Device	Laptop 2

1. Open **Cisco Packet Tracer**.
2. Add a **Wireless Router** and two laptops.
3. On Laptop 1, open **Desktop → Command Prompt**.
4. Run:

```
ipconfig /all
```

5. Note the Wireless0 **Physical Address**:

```
00E0.F9B8.E9BB
```

6. Open **Wireless Router → GUI → Wireless → Wireless MAC Filter**.
7. Select **Enabled**.
8. Select **Permit PCs listed below to access wireless network**.
9. Add the MAC address in the required format:

```
00:E0:F9:B8:E9:BB
```

10. Save the settings.
11. Connect Laptop 1 to the wireless network. It should connect successfully because its MAC address is on the allowed list.
12. On Laptop 2, find its MAC address using `ipconfig /all`.
13. Do **not** add Laptop 2's MAC address to the allowed list.
14. Try connecting Laptop 2 to the same wireless network. Access should be denied.

Result

MAC filtering was successfully configured on the wireless router. The MAC address 00:E0:F9:B8:E9:BB was added to the allowed list, allowing the registered laptop to access the wireless network. A second device whose MAC address was not included in the allowed list was denied access. Therefore, MAC filtering was successfully verified.